



V: NAVD88 (feet)

[illegible]

SITE ANALYSIS

- | | |
|-------------------------------------|------------------------------|
| 1. Gross tract area | 75,178 SF |
| 2. Area of dwelling | 4,784 SF |
| 3. Wooded area | NOT EST. |
| 4. Floodplain area | NOT EST. |
| 5. Net lot area | 75,184 SF |
| 6. TOTAL AREA DISTURBED | 41,632 SF |
| 7. SWM REQUIRED — Sec. 32-174(a)(3) | YES — DISTURBED AREA EXCEEDS |

G garage slab · B basement · FF finished
topographic survey before construction.

Peak flows are summed lot catchments; Q in cfs. WQv is the required water-quality volume

1. Pre-construction meeting
2. Obtain necessary permits
3. Notify Miss Utility at 811 at least 48 hours prior to any excavation
4. Install stabilized construction entrance and perimeter sediment control
5. Rough grade the lot
6. Construct dwelling
7. Install water, sewer and storm services and the driveway
8. Fine grade and stabilize all disturbed areas
9. Remove sediment control once the inspector gives written permission

1. CONTRACTOR SHALL CONTACT MISS UTILITY AT 811 A MINIMUM OF 48 HOURS PRIOR TO ANY EXCAVATION. FIELD VERIFY LOCATION AND DEPTH.

2. ALL EXISTING AND PROPOSED UTILITIES SHOWN PER PGC CODE SEE: 30-106.

3. EXISTING GRADE SHOWN SOLID; EXISTING GRADE SHOWN DASHED.

4. ROUGH EARTHWORK GRASSES AND UTILITIES EXISTENCES SHOWN TO MATCH FOOTPRINT.

5. BOUNDARY SHOWN IS THE RECORDED PLAT OF SUBDIVISION — INDIAN COUNTRY EAST — BLOCK "E" AND PARTS OF BLOCKS D & F PLAT DATED 1976 JUNE 17, 1976 APRIL 27, 1976 MAY 1976 BY PRINCE GEORGES COUNTY, MARYLAND TAX MAP #13, BLOCK F, GRID EA PLAT DATED 6 JUNE 1967, APPROVED 22 JUNE 1967 BY THE PRINCE GEORGES COUNTY BOARD OF PUBLIC WORKS AND COMMISSION, PRINCE GEORGES COUNTY PLANNING BOARD, M-C-N-P-R-C RECORD FILE 51378 FOR THE CITY OF ANNAPOLIS, ANNE ARUNDEL COUNTY, MARYLAND SURVEYOR NO. 384. TOTAL SUBDIVISION AREA 20.981 ACRES. PLAT LEGEND: FOR PUBLIC SERVICE AND WATER SYSTEMS ONLY — EXISTING GRADES ARE SHOWN WITH DASHED LINES. THE BOUNDARY SURVEY NO FIELD TOPOGRAPHY IS INCLUDED. EXISTING GRADE IS COUNTY LANDSCAPE CONTAINING:

— TREES

— CURBS AND GUTTER, DRIVEWAY AND SIDEWALK IN LINE AND GRADE.

- PROPERTY BOUNDARY
- BRL — BUILDING RESTRICTION LINE
- PROPOSED STRUCTURE
- EXISTING CONTOUR — 2 FT INTERVAL, NAVD88
- PROPOSED CONTOUR — 2 FT INTERVAL
- STREET CENTRELINE
- PROPOSED PAVEMENT — DRIVEWAY / WALK
- EASEMENT
- SANITARY LATERAL (SHC) — HEAVIEST
- WATER SERVICE (WHC)
- STORM DRAIN — TRUNK, RCP
- STORM — HOUSE CONNECTION TO TRUNK
- DRAINAGE SWALE — INVERT AND GRADED SECTION
- ESD — STORMWATER PRACTICE

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

SEAL	SIGNATURE _____	DATE _____
	LICENSE NO. _____	EXPIRATION DATE _____

REVISIONS
— none —

SYSTEM AT THE LOW POINT: 1.7260 AC, Q10 3.57 CFS, Q100 4.71 CFS.
MAX VELOCITY 2.51 FPS AT Q100 — WITHIN THE 5 FPS PERMISSIBLE FOR ESTABLISHED GRASS. 0.5 FT FREEBOARD THROUGHOUT.
THE SWALE DISCHARGES TO THE RECORDED 54/55 STORM DRAIN EASEMENT, ALONGSIDE THE 42" RCP CL IV EXTENDING THE FORT FOOTE ROAD CULVERT INLET.
THAT MAIN IS INVERTED: 0.417 FT, 1.5 FT MIN COVER OVER THE CROWN — FINISHED GRADE OVER IT SHALL BE NO LOWER THAN INVERT + 5.67 FT. FILL WHERE EXISTING GROUND IS LOWER
SWALE GRADES AND BURNS TO BE SET FROM THE FIELD-RUN TOPOGRAPHIC SURVEY ESTABLISH DSD BEFORE THE CONTRIBUTING AREA IS STABILIZED.

