

PORTER SUBDIVISION | LOTS 1 & 2

1005 & 1009 ROLLINS AVENUE, PRINCE GEORGE'S COUNTY, MARYLAND



PROJECT AND DRAWING BASIS

Two detached dwellings. Boundary control: recorded Porter Subdivision plat, PM 231 / 50. Existing contours: 2-foot interval, NAVD88. Proposed dwelling footprints: 46 ft x 26 ft, including the optional one-car garage.

Recorded areas: Lot 1 9,598 SF; Lot 2 8,008 SF; net lots 17,606 SF; public dedication 4,219 SF; gross tract 21,825 SF.

Tax Map 73, Grid B3; former Parcel 326, Preliminary Plan 4-06111; Record File 5-09121. Zoning: RSF-65 (R-55 at plat recording).

MEASURED DWELLING CLEARANCES

LOT	FRONT	SIDES	REAR
Lot 1	31.00 ft	8.40 / 10.60 ft	62.86 ft
Lot 2	31.00 ft	8.26 / 11.65 ft	Triangular lot

Design lines: front 30 ft; sides 8 ft; Lot 1 rear 20 ft. Lot 2 uses the applicant-directed triangular-lot side-yard treatment. The table reports actual geometry and does not represent an agency determination.

LOT COVERAGE

LOT	DWELLING	FOOTPRINT / LOT
Lot 1	1,196 SF	12.46%
Lot 2	1,196 SF	14.94%

35% maximum shown in the project zoning criteria. Ratios above are dwelling footprint only. Site paving is accounted for separately in the drainage calculations.

UTILITY CONNECTIONS

Both lots: water and sanitary connections toward the existing 8-inch mains in Modupeola Way, through the 20-foot WSSC corridor on Lot 13. Private utility segment runs from the Lot 1 / 12 / 13 corner toward the Lot 1 / 2 / 12 corner.

WSSC connection reference: C-004. Utility routing is preliminary; junctions, fittings, separation, depths and main tie-ins require coordinated WSSC design. Private easement limits are governed by the recorded instrument.

LEGEND

- Recorded lot line
- Building restriction line
- Utility easement
- W - Water house connection
- S - Sanitary house connection

DW-1 / DW-2 identify reserved stormwater locations. The staff report describes infiltration drywells under Concept 41230-2006-00; final approved sizing and outlet details are required before construction.

BOUNDARY CALLS OF RECORD - PM 231 / 50

LINE	BEARING	DISTANCE
B1	N 79-29-14 E	176.36 ft
B2	S 10-30-46 E	65.00 ft
B3	N 79-29-14 E	118.96 ft
B4	N 51-58-25 W	86.72 ft
B5	S 10-30-46 E	134.64 ft
B6	N 51-58-25 W	179.66 ft

B3 is the common Lot 1 / Lot 2 boundary. Bearings are stated in the direction lettered on the recorded plat. PUE: 10 ft along each Rollins frontage; public dedication: 20 ft.