

KEALEE

ATTACHED HOUSING YIELD STUDY — PRELIMINARY, NOT A SITE PLAN

THE PARCELS ARE ZONED RE. THIS STUDY APPLIES THE CGO TABLE AS THE REZONING THE OWNER WOULD SEEK; NOTHING HERE IS PERMITTED UNTIL THE COUNCIL AND THE APPROVED TCP'S WOODLAND AND CONSERVATION (3.31 AC) IS NOT RESERVED. A NEW TCP2 IS PART OF THE REZONING AND THE SEC. 25-121 REQUIREMENT IS MET BY AFFORESTATION, FEE-IN-LIEU OR OFF-SITE BANKING.

Aragona Village Blocks EE and DD (Schooner Court, 16 approved SFD lots) — rezoned CGO, converted to townhouses, two-over-tvos and duplexes

Zone CGO - certified intensity table Sec. 27-4203 - generated 2026-09-17

PARCELS (PGAtlas Address/Property — owner of record, assessment)

Acct 4007985 - BRANDYWINE BUILDERS LLC - 0.806 ac assessed / 0.807 ac GIS - plat 05230085 - L 26757 F002
Acct 4007993 - BRANDYWINE BUILDERS LLC - 0.693 ac assessed / 0.693 ac GIS - plat 05230085 - L 26757 F002
Acct 4008009 - BRANDYWINE BUILDERS LLC - 0.689 ac assessed / 0.689 ac GIS - plat 05230085 - L 26757 F002
Acct 4008082 - BRANDYWINE BUILDERS LLC - 0.689 ac assessed / 0.689 ac GIS - plat 05230086 - L 26757 F002
Acct 4008090 - BRANDYWINE BUILDERS LLC - 0.921 ac assessed / 0.921 ac GIS - plat 05230086 - L 26757 F002
Acct 4007977 - BRANDYWINE BUILDERS LLC - 1.05 ac assessed / 1.058 ac GIS - plat 05230086 - L 26757 F002
Acct 4007969 - BRANDYWINE BUILDERS LLC - 1.57 ac assessed / 1.571 ac GIS - plat 05230085 - L 26757 F002
Acct 4007961 - BRANDYWINE BUILDERS LLC - 1.13 ac assessed / 1.129 ac GIS - plat 05230085 - L 26757 F002
Acct 4007944 - BRANDYWINE BUILDERS LLC - 0.692 ac assessed / 0.690 ac GIS - plat 05230085 - L 26757 F002
Acct 4008074 - BRANDYWINE BUILDERS LLC - 0.702 ac assessed / 0.703 ac GIS - plat 05230086 - L 26757 F002
Acct 4008066 - BRANDYWINE BUILDERS LLC - 0.697 ac assessed / 0.695 ac GIS - plat 05230086 - L 26757 F002
Acct 4008058 - BRANDYWINE BUILDERS LLC - 0.922 ac assessed / 0.919 ac GIS - plat 05230086 - L 26757 F002
Acct 4008041 - BRANDYWINE BUILDERS LLC - 0.919 ac assessed / 0.914 ac GIS - plat 05230086 - L 26757 F002
Acct 4008033 - BRANDYWINE BUILDERS LLC - 0.919 ac assessed / 0.921 ac GIS - plat 05230086 - L 26757 F002
Acct 4008025 - BRANDYWINE BUILDERS LLC - 0.919 ac assessed / 0.920 ac GIS - plat 05230086 - L 26757 F002
Acct 4008017 - BRANDYWINE BUILDERS LLC - 0.990 ac assessed / 0.992 ac GIS - plat 05230086 - L 26757 F002

Tract 623.303 sf (14.309 ac). Boundary is the county parcel bayer — not a survey

WHAT CANNOT BE BUILT ON (county layers, clipped to the tract)

Woodland conservation (approved TCP areas) 0.00 ac - slopes >25% in bodes 0.00 ac (graded banks 0.80 ac, regraded) - 15-25% 2.02 ac (built with grading) - stream buffer 0.00 ac - floodplain 0.00 ac - wetlands 0.00 ac
Developable 623.303 sf (14.309 ac)
The Primary Management Area, the woodland conservation threshold and any expanded buffers are set by an approved Natural Resources Inventory and TCP; not by these layers. A 50-ft stream buffer and slopes over 25% are the minimum that would be taken; the NRI may take more.

CGO STANDARDS BY DWELLING TYPE (Sec. 27-4203)

Townhouse: 20 du/ac net - lot "e 20 ft wide - coverage "d 60% - yards 100/15 ft - height "d 50 ft
Two-family (duplex): 40 du/ac net - lot "e 20 ft wide - coverage "d 60% - yards 100/15 ft - height "d 50 ft
Two-over-two (stacked, 2 units per bay): 48 du/ac net - lot "e 50 ft wide - coverage "d 70% - yards 100/15 ft - height "d 66 ft
Mixed use (retail below, dwellings above): 48 du/ac net - lot "e 50 ft wide - coverage "d 70% - yards 100/15 ft - height "d 66 ft

YIELD — THIS LAYOUT

Townhouse: 50 bays / 108 du - 19.33 du/ac on 3.519 net ac (cap 20) - lot coverage 44.4% (cap 65%) - parking 136 at 20du ASSUMED — 1-car front-load garage + 1 driveway space on the lot
Two-family (duplex): 29 bays / 29 du - 12.89 du/ac on 2.249 net ac (cap 40) - lot coverage 44.4% (cap 65%) - parking 58 at 20du ASSUMED — 2-car front-load garage + 2 driveway spaces on each lot
Two-over-two (stacked, 2 units per bay): 51 bays / 102 du - 29.08 du/ac on 3.507 net ac (cap 48) - lot coverage 48% (cap 70%) - parking 153 at 1.5du ASSUMED — a 2-car front-load garage per bay (one space per unit) + 1 driveway space + surface bays along the street
Parking: 29 surface spaces drawn (dashed) + 456 in garages and driveways = 485 against 347 required at the assumed ratios.

TOTAL 199 DWELLING UNITS in 148 bays - 13.91 du/ac gross on the 14.309-ac tract

CEILINGs if the whole developable ground were one type (x 0.8 for streets, parking, open space):

Townhouse: 228 du -
Two-family (duplex): 457 du -
Two-over-two (stacked, 2 units per bay): 549 du

STORMWATER MANAGEMENT (ESD, MDE Ch. 5)

Impervious 285,864 sf (45.9%), Rv 0.4628, ESDv 24,037 cf at P-E 1.0 in 1" 30,046 sf of micro-bioretenion. Reserved for stormwater: 30,209 sf -
30,209 sf is reserved for ESD practices (1 micro-bioretenion area) in the ground the rows left, drawn) against the 30,046 sf footprint at P-E 1.0 in; the higher P-E the soils may require (Table 5.3) is met by bioswales along the private streets and the DPE concept.
Micro-bioretenion in every surface parking lot island and a bioswale along each private street; credited under ESD; nothng disconnection is not available over parking. Design per the DPE stormwater concept approval that precedes the CGO.

UNIT ASSUMPTIONS

Townhouse: 20 x 90 ft lot, 20 x 40 ft footprint, 1 du per bay, sticks of "d 6
Two-family (duplex): 30 x 90 ft lot, 30 x 40 ft footprint, 1 du per bay, sticks of "d 2
Two-over-two (stacked, 2 units per bay): 24 x 100 ft lot, 24 x 48 ft footprint, 2 du per bay, sticks of "d 8
Mixed use (retail below, dwellings above): 100 x 200 ft lot, 100 x 70 ft footprint, 22 du per bay, 7,000 sf retail, 5 storeys "H 62 ft
Private streets in 40-ft strips (26-ft pavement, walk-off side), each being off GUNPOWDER — the existing public right-of-way — with no new access to any other road. Visitor parking, open space and the Landscape Manual 4.7 buffer to the RE lots are DSP work not drawn here.

DESIGN STANDARDS APPLIED (Subtitle 24 Subdivision Regulations, Subtitle 27, DPE, IFG)

Sec. 24-121(a)(13) every lot front and takes access from one street only; (a)(1) corner lots truncated at platting; (a)(10) no unnecessary street — the approved rights-of-way is kept and the town front on it.
Sec. 24-121(a)(2) new streets are continuous, tie off the existing street at right angles; (a)(5) public secondary streets 50 ft / primary 60 ft of right-of-way — these are private streets, so Sec. 24-128(a)(7) governs: "e 22-ft pavement (26 ft drawn); alleys "e 18 ft, a 10-ft public utility easement contiguous to the right-of-way (24-128(a)(12), rightmost by the HOA/condominium with Fire Chief approval of emergency access.
Turnarounds: a dead end over 150 ft ends in a 45-ft-radius bulb (60-ft pavement) — IFG D103.4 as applied by Subtitle 11, 0 is drawn.
Sec. 27-4203 (CGO) yards: front 10 ft, side 8 ft (end units, party walls within a stick); rear 15 ft — drawn: build line 20 ft (the driveway apron for the front-load garage governs over the 10-ft minimum); 10-ft breaks between sticks of "d 8 (8 ft end yards), rear 30 ft on 90 ft lot width; coverage, height per the certified table above.
Pedestrian access: a 5-ft sidewalk runs along the front of every building at the street front (Sec. 23-130), on the lot in the front yard, crossed by the driveways; every building front faces a street and its walk. No street is laid on the property line — a 25-ft landscape strip is kept between any street and the tract boundary (Landscape Manual Sec. 4.7 sets the buffer yard at DSP).
Vehicular access: every twohouses, duplex and two-over-two lot fronts a street the least public right-of-way or a private street; and has its own driveway to a front-load garage — 1-car for the 20-ft townhouse, 2-car for the 30-ft duplex and the 24-ft two-over-two bay; no lot is divided and none takes access from an adjoining lot (Sec. 24-128(a)).
Table 24-4203(c) regulated stream buffer 100 ft outside a Transient Overland Control slopes over 25%, 100-year floodplain and riparian taken out of the developable ground (county layers); the NRI/TCP2 governs at preliminary plan.
Sec. 24-121(a)(15) a DPE-approved stormwater concept precedes the preliminary plan — ESD to the MEP (MDE Manual Ch. 5) micro-bioretenion in the reserved areas drawn; bioswales along each private street; (a)(14) Subtitle 25, woodland conservation by TCP2.
Sec. 23-136: curb gutter and 5-ft sidewalk on the street side of every lot (lot frontages "d 100 ft); DPE grading checklist: lawns "e 2.5%, swales 2-4%, banks "d 3:1 (residential); slopes steeper than 4:1 set back 10-20 ft from buildings.
Landscape Manual Sec. 4.7 butterfly against the adjoining RE lots and Sec. 4-6 street trees along every street; Sec. 25-128 tree canopy on the gross tract — DSP work, the widths are not drawn here.
Sec. 27-4203 parking the rules used (2.0du/townhouse and duplex on the lot, 1.5du/two-over-two) are ASSUMED — the certified tables carried by this engine do not include the parking schedule; visitor parking at 0.5du is customary and not drawn.

APPROVALS

CGO townhouse, two-family and multifamily (two-over-two) dwellings are listed uses with their own intensity standards in the certified Sec. 27-4203 table; a Detailed Site Plan is the approval path for residential in the commercial zones (confirm the use table entry for each type — the use table is not carried by this engine).
Sec. 27-5300 parking, Sec. 27-6400 landscaping (Landscape Manual 4.7 buffers against the RE lots) and Sec. 25-121 woodland conservation. Sec. 24 subdivision (a preliminary plan of subdivision creates fee-simple townhouse and duplex lots; two-over-two are condominium or fee-simple with a DSP), stormwater concept (DPE), WSSC hydraulic planning analysis.
This is a yield study prepared by the Kealee site-plan engine from county GIS and the certified zoning table. It is not a Detailed Site Plan, not a survey and not a determination of what the Planning Board will approve.

