# Лабораторная работа №3

## Системы контроля версий. Git

Давид Майкл Фрэнсис

# Содержание I

1. Информация
2. Вводная часть
3. Выполнение работы

Раздел 1

# Информация

# Докладчик

- Давид Майкл Фрэнсис
- Студент направления «Математика и компьютерные науки»
- Российский университет дружбы народов
- https://ushie47.github.io/blog

Раздел 2

# Вводная часть

# Актуальность

- Системы контроля версий — неотъемлемый инструмент разработки ПО.
- Позволяют отслеживать историю изменений и работать совместно.
- Git лежит в основе большинства современных рабочих процессов разработки и работы с GitHub.

# Цель работы

Изучить идеологию и применение средств контроля версий, освоить умения по работе с Git.

# Задание

1. Установить Git и GitHub CLI (gh).
2. Настроить пользовательские данные и кодировку вывода Git.
3. Создать SSH-ключ для аутентификации.
4. Создать PGP-ключ и настроить подпись коммитов.
5. Добавить PGP-ключ в учётную запись GitHub.
6. Настроить структуру рабочего каталога курса.

Раздел 3

# Выполнение работы

# Установка Git и GitHub CLI

Я установил Git и GitHub CLI с помощью менеджера пакетов `dnf`.

```
and without modifying the system state.
midavid@vbox:~$ sudo -i
[sudo] password for midavid:
root@vbox:~# dnf install git
Updating and loading repositories:
 google-chrome                          100% |   4.4 KiB/s |   1.3 KiB |  00m00s
 Copr repo for PyCharm owned by phracek 100% |   2.8 KiB/s |   2.1 KiB |  00m01s
 RPM Fusion for Fedora 41 - Nonfree - S 100% |  13.0 KiB/s |   8.7 KiB |  00m01s
 RPM Fusion for Fedora 41 - Nonfree - N 100% |  34.3 KiB/s |   9.1 KiB |  00m00s
 Fedora 41 - x86_64 - Updates           100% |  55.7 KiB/s |  25.1 KiB |  00m00s
 google-chrome                          100% |   8.4 KiB/s |   3.2 KiB |  00m00s
 RPM Fusion for Fedora 41 - Nonfree - N 100% |  31.4 KiB/s |  18.2 KiB |  00m01s
 Fedora 41 - x86_64 - Updates           100% |   2.6 MiB/s |   7.2 MiB |  00m03s
Repositories loaded.
Package "git-2.48.1-1.fc41.x86_64" is already installed.

Nothing to do.
root@vbox:~# git config --global Ushie47 "Michael david"
error: key does not contain a section: Ushie47
```

# Настройка Git и создание SSH-ключа

Я указал имя и почту для коммитов, настроил вывод сообщений в UTF-8, включил проверку и подпись коммитов и создал SSH-ключ.

```
Complete!
root@vbox:~# git config --global user.name "Michael David"
root@vbox:~# git config --global user.email "ukanadaushie@gmail.com"
root@vbox:~# git config --global core.quotepath false
root@vbox:~# git config --global init.defaultBranch master
root@vbox:~# git config --global core.autocrif input
root@vbox:~# git config --global core.safecrlf warn
root@vbox:~# ssh-keygen -t rsa -b 4096
Generating public/private rsa key pair.
Enter file in which to save the key (/root/.ssh/id_rsa):
Enter passphrase for "/root/.ssh/id_rsa" (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /root/.ssh/id_rsa
Your public key has been saved in /root/.ssh/id_rsa.pub
The key fingerprint is:
SHA256:PqD2qYvtkCIW5BI0DaVHiAJ4pbZmr8RB/YVlouyTDIE root@vbox
The key's randomart image is:
+---[RSA 4096]----+
|==*+. . o        |
```

# Генерация PGP-ключа

Я сгенерировал PGP-ключ командой `gpg --full-generate-key`.

```
root@vbox:~# gpg --full-generate-key
gpg (GnuPG) 2.4.5; Copyright (C) 2024 g10 Code GmbH
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.

Please select what kind of key you want:
   (1) RSA and RSA
   (2) DSA and Elgamal
   (3) DSA (sign only)
   (4) RSA (sign only)
   (9) ECC (sign and encrypt) *default*
  (10) ECC (sign only)
  (14) Existing key from card
Your selection? 1
RSA keys may be between 1024 and 4096 bits long.
What keysize do you want? (3072) 4096
Requested keysize is 4096 bits
Please specify how long the key should be valid.
```

# Добавление PGP-ключа в GitHub (шаг 1)

Я добавил сгенерированный ключ в учётную запись GitHub через настройки профиля.

```
We need to generate a lot of random bytes. It is a good idea to perform
some other action (type on the keyboard, move the mouse, utilize the
disks) during the prime generation; this gives the random number
generator a better chance to gain enough entropy.
We need to generate a lot of random bytes. It is a good idea to perform
some other action (type on the keyboard, move the mouse, utilize the
disks) during the prime generation; this gives the random number
generator a better chance to gain enough entropy.
gpg: /root/.gnupg/trustdb.gpg: trustdb created
gpg: directory '/root/.gnupg/openpgp-revocs.d' created
gpg: revocation certificate stored as '/root/.gnupg/openpgp-revocs.d/0E9F96A906BAF43
16C1D8D28E27DFA4588FD67F8.rev'
public and secret key created and signed.

pub   rsa4096 2025-03-02 [SC]
      0E9F96A906BAF4316C1D8D28E27DFA4588FD67F8
uid                      Michael <omotole47@gmai.com>
sub   rsa4096 2025-03-02 [E]

root@vbox:~# gpg --list-secret-keys --keyid-format LONG
gpg: checking the trustdb
```


# Добавление PGP-ключа в GitHub (шаг 2)

```
pub   rsa4096 2025-03-02 [SC]
      0E9F96A906BAF4316C1D8D28E27DFA4588FD67F8
uid                      Michael <omotole47@gmai.com>
sub   rsa4096 2025-03-02 [E]

root@vbox:~# gpg --list-secret-keys --keyid-format LONG
gpg: checking the trustdb
gpg: marginals needed: 3  completes needed: 1  trust model: pgp
gpg: depth: 0  valid:   1  signed:   0  trust: 0-, 0q, 0n, 0m, 0f, 1u
[keyboxd]
---------
sec   rsa4096/E27DFA4588FD67F8 2025-03-02 [SC]
      0E9F96A906BAF4316C1D8D28E27DFA4588FD67F8
uid                 [ultimate] Michael <omotole47@gmai.com>
ssb   rsa4096/29A1F451E7B997DF 2025-03-02 [E]

root@vbox:~# gpg --armor --export <PGP  Fingerprint> | xclip -sel clip
-bash: syntax error near unexpected token `|'
root@vbox:~# sudo apt install xclip
sudo: apt: command not found
root@vbox:~# gpggg --armor --export E27DFA4588FD67F8
bash: gpggg: command not found...
```

# Добавление PGP-ключа в GitHub (шаг 3)



# Автоматическая подпись коммитов

Я настроил Git на автоматическую подпись коммитов сгенерированным PGP-ключом:
“‘bash git config –global user.signingkey git config –global commit.gpgsign true git config –global gpg.program $(which gpg2)