

Release 1.2.0 — Deployment Runbook (Manual Coolify Steps)

This release ships in **green, deployable increments** pushed to `main`. After Coolify redeploys `main`, perform the manual step(s) for each increment below. Increments are additive and non-destructive; existing sites keep working and do **not** need to reconnect.

How to open the API container shell: In Coolify → your `marqira-api` application → **Terminal** (a.k.a. Console / Exec). You should get a shell inside the running container. All `php artisan ...` commands below run there.

Increment 1 — Platform roles, ownership, revocation & duplicate prevention

Commit: `492a6ce`

Risk: Low. Migrations are additive (new nullable columns + one partial unique index) and reversible. No data is deleted.

What changed (operationally)

- New `users.platform_role` (`owner` / `subscriber`) and `users.is_active`.
- Existing organization **owners are auto-promoted** to platform Owner during migration, so current admins keep full visibility. `ozman.best@gmail.com` is always promoted if present.
- New `sites.owner_user_id`, `sites.domain_normalized`, `sites.revoked_at`, `sites.revoked_by`. Ownership is backfilled from the enrollment token that created each site (where known).
- A **partial unique index** enforces one active site per (organization, normalized domain). Before the index is created the migration **soft-revokes** any pre-existing active duplicates, keeping the most recently-seen row (nothing is deleted).

Manual steps after redeploy

1. (Recommended) Preview duplicate cleanup — safe, read-only:

```
php artisan marqira:deduplicate-sites --dry-run
```

This lists every domain that has more than one active site and which rows would be soft-revoked. It writes nothing. Review the output; if a wrong row would be kept, resolve it in the dashboard first.

2. Run migrations:

```
php artisan migrate --force
```

Expected new migrations:

- `2024_01_02_000001_add_platform_role_to_users`
- `2024_01_02_000002_add_owner_and_revocation_to_sites`

- 2024_01_02_000003_add_sites_domain_unique_index
- 2024_01_02_000004_create_account_invitations_table

The `...add_sites_domain_unique_index` migration performs the safe soft-revoke of any remaining active duplicates automatically before adding the index, so it is safe even if you skipped step 1.

1. Verify the primary Owner:

```
php artisan tinker --execute="echo \App\Models\User::where('email','ozman.best@gmail.com')->value('platform_role');"
```

Should print `owner`. If that account does not exist yet, create it with

```
php artisan marqira:create-admin (it is created as an Owner).
```

- ### 2. (Optional) Re-run the dedup command without `--dry-run` only if you later discover duplicates that were enrolled before this release and were not caught by the migration:

```
php artisan marqira:deduplicate-sites
```

Rollback

If needed, `php artisan migrate:rollback` reverses these four migrations (drops the added columns/index/table). No site rows are removed by rolling back, but any sites soft-revoked during dedup will remain revoked — reactivate them from the dashboard if required.

No config/env changes required

This increment introduces **no** new environment variables. Email/SMTP settings are introduced in a later increment (offline alerting) and are documented then.

Increment 2 — Connector lifecycle: persistent pairing, cron self-heal & self-disconnect on revocation

Plugin version **1.2.0** (display name **MarQira Pulse**; folder/slug/prefix unchanged at `marqira-connector`). This increment pairs the WordPress connector with the revocation support shipped in Increment 1.

What changed (operationally)

- **Self-disconnect on revocation.** When a site is revoked from the dashboard, the API already answers its next heartbeat with `HTTP 403` `{"error":"site_revoked","site_revoked":true}` (Increment 1). The 1.2.0 connector now detects this and **stops its heartbeat cron and clears its stored credentials**, so a revoked site goes quiet immediately instead of retrying a rejected beat every couple of minutes. Reconnecting requires a fresh enrollment code.
- **Plain 403s are safe.** A 403 that is not a revocation signal (e.g. a transient WAF or permission block) is logged as an ordinary failure and does **not** wipe credentials — a healthy site is never silently disconnected.
- **Persistent pairing across updates (confirmed).** Credentials are stored in the `marqira_site_credentials` option and preserved on deactivate/upgrade;

only uninstall removes them. Combined with the existing cron self-heal, updated sites keep monitoring with **no reconnection**.

- **“Updates available” now works out of the box.** The API config `marqira.plugin.latest_version` now defaults to `1.2.0` (env `MARQIRA_PLUGIN_LATEST_VERSION`), so the dashboard flags any site still running an older connector.

Manual steps after redeploy

1. **API:** No migrations. **Optional but recommended** — set (or confirm) the env var so the “Updates available” card reflects the shipped connector:
`MARQIRA_PLUGIN_LATEST_VERSION=1.2.0`
 If the variable is left **blank**, Laravel treats it as empty and the card shows 0. If the variable is **absent**, the new `1.2.0` config default applies. After changing env in Coolify, redeploy (or run `php artisan config:cache`) so the value is picked up.
2. **Connector plugin:** Publish the updated `marqira-connector` folder (v1.2.0) to customers as a normal plugin update (same folder/slug). **No customer reconnection is required.** Existing enrolled sites keep their credentials and simply gain the self-disconnect behavior.

Verifying revocation end-to-end (optional)

1. Revoke a test site from the dashboard (Increment 1 `DELETE` / disconnect).
2. Within one heartbeat interval (~2 min test cadence) the site’s next beat receives `403 site_revoked`; the connector clears credentials and unschedules its cron. In **Settings → MarQira Connector → Recent Activity** you will see a `site_revoked` log entry.

Rollback

- **API:** revert the `marqira.plugin.latest_version` default (or unset the env var). No migrations were added, so there is nothing to roll back on the DB.
- **Connector:** re-publishing the previous 1.1.3 plugin folder restores the old behavior; enrolled sites are unaffected either way (credentials persist).

No destructive changes

No database migrations, no schema changes, and no forced reconnection. Existing sites continue heartbeating exactly as before, plus the new revocation handling.

Increment 3 — Offline monitoring with repeated & recovery email alerts

Commit: `cb416cd`

Risk: Low. One additive, reversible migration (three new nullable/default columns on `sites`). No data is deleted. New outbound email — **requires SMTP env + a running queue worker** (see manual steps).

What changed (operationally)

- **Server-driven offline detection with alerts.** The existing `marqira:check-stale-sites` scheduler (runs every 5 min) now, in addition to

marking a stale site `offline`, **emails the site owner** (and the optional platform alert address) that the site is down.

- **Repeated alerts while down.** While a site stays offline, a reminder email is re-sent every `MARQIRA_OFFLINE_ALERT_REPEAT_MINUTES` (default 60). Set to `0` to send only the single initial alert.
- **Recovery alert.** When an offline site sends its next heartbeat, the API emails a “back online” recovery notice (only if at least one offline alert was sent during the outage) and resets the offline tracking.
- **No false alarms.** Revoked sites are never alerted (their connector was told to disconnect). A freshly enrolled site that has never sent a heartbeat is marked offline for status accuracy but does **not** trigger an email.
- **Emails are queued** (Redis queue) so neither the scheduler nor the heartbeat request blocks on SMTP.

New columns on `sites` (migration `2024_01_03_000001`)

- `offline_since` (nullable timestamp) — start of the current offline episode.
- `last_offline_alert_at` (nullable timestamp) — when the last alert was sent.
- `offline_alert_count` (unsigned int, default 0) — alerts sent this episode.

Manual steps after redeploy

1. **Set SMTP + alert env vars** in the Coolify `marqira-api` environment UI (see `apps/api/.env.example` for the full block). At minimum:

```
MAIL_MAILER=smtp
MAIL_HOST=smtp.hostinger.com
MAIL_PORT=465
MAIL_SCHEME=smtps
MAIL_USERNAME=noreply@marqira.com
MAIL_PASSWORD=          # ← paste the real mailbox password HERE in Coolify only
MAIL_FROM_ADDRESS=noreply@marqira.com
MAIL_FROM_NAME="MarQira Pulse"
MARQIRA_ALERTS_ENABLED=true
MARQIRA_ALERT_EMAIL=ozman.best@gmail.com
MARQIRA_OFFLINE_ALERT_REPEAT_MINUTES=60
```

Security: never commit the real `MAIL_PASSWORD`. It lives only in the Coolify env UI. The repo keeps it blank.

2. **Run the migration** in the API container Terminal:

```
php artisan migrate --force
```

3. **Ensure a queue worker is running.** Alert emails are queued, so they will **not** send unless a worker consumes the Redis queue. In Coolify add (or confirm) a long-running process / extra container running:

```
php artisan queue:work redis --tries=3 --sleep=3
```

Without a worker, alerts silently accumulate in the queue and no email is delivered. (If you prefer no worker, you may switch `QUEUE_CONNECTION=sync`, but that makes the scheduler/heartbeat block on SMTP — not recommended.)

4. **Rebuild config cache** so the new env is picked up:

```
php artisan config:cache
```

5. **(Optional) confirm the scheduler is active.** The offline check relies on Laravel’s scheduler running every minute (`php artisan schedule:run` via cron

or the Coolify scheduler container). This was already required for `marqira:check-stale-sites` ; no change here.

Verifying alerts end-to-end (optional)

1. Temporarily set `MARQIRA_OFFLINE_ALERT_REPEAT_MINUTES=2` and lower `MARQIRA_OFFLINE_THRESHOLD` behavior via the heartbeat config if you want a fast test, then `php artisan config:cache` .
2. Stop a test site's heartbeat (deactivate its connector). Within the stale threshold the scheduler marks it offline and you receive the **offline** email; a **repeat** arrives every 2 minutes.
3. Reactivate the connector. On its next heartbeat you receive the **recovery** email and the dashboard shows the site online again.
4. Restore the production repeat interval and re-cache config.

Rollback

- **DB:** `php artisan migrate:rollback` removes the three new columns.
- **Alerts:** set `MARQIRA_ALERTS_ENABLED=false` (and `config:cache`) to disable all alert emails instantly without a redeploy. Offline status detection continues to work.