

8/24/22
10/22



1. FULL FORM THREAD SHALL BE SUCH THAT SPECIFIED THREAD MINOR DIAMETER IS MAINTAINED TO 1.4 MAX FROM UNDERSIDE OF SHOULDER.
2. RECESS DATA:

GO GAGE PENETRATION DEPTH	1.27
NO GO PENETRATION DEPTH	0.64
DRIVER SIZE	T20
3. RECOMMENDED PANEL RANGE FOR THERMAL EXPANSION JOINTS TO BE 1.7-2.2MM.
4. 2.5 MAX TO THREAD RUNOUT REFERENCE 2.0 TO BOTTOM OF HEADER POINT ANGLE BEFORE ROLLING THREAD.
5. WASHER SHALL BE RETAINED ON SCREW SHANK AND ROTATE FREELY BY APPLYING 1.1 Nm MAXIMUM WITHOUT IMPINGING ON THE UNDERHEAD FILLET BEFORE AND DURING TIGHTENING OF THE ASSEMBLY.
6. WASHER COMPRESSION AT 50% DEFLECTION TO BE 180-320 N.

[illegible]

ESTIMATED WEIGHT: 0.004 kg

PART INFORMATION PAGE FOR ITEM NUMBER : FC00AAS10594
TITLE BLOCK INFORMATION

Item Number	FC00AAS10594
Item Revision	001
PCL	A
CN	
Item Name	SC.TAP&WA/TRUSS.HD CONE.WASH.REC
Item Description	
Chrysler Part Number	06510198AA
Fiat Codep Number	53380330
Shown-on Part	
Status	FA_STEPS,CAD_Released
Owner	SMITH LOUISE (t47271s)
Engineer	
Designer	
Checker	

ASF
CONTROLLED
WHEN RED
8/24/22
ZQZ

ENGINEERING STANDARDS APPLIED

Item	Standard No.	Designation	Standard Title
1	CEP-045		MANDATORY AND DISCRETIONARY ENGINEERING STANDARDS
2	CS-11000	(1)	TRADEMARK IDENTIFICATION ON PARTS
3	PS-4480	(1)	IDENTIFICATION & BAR CODING OF PARTS
4	PF-SAFETY<S>		PRODUCT SAFETY - USE OF THE SAFETY FLAG / SAFETY S
5	PS-7099		GENERAL SPECIFICATIONS - FASTENERS AND FITTINGS
6	*MS-4515<S>		CARBON STEEL TAPPING SCREWS
7	MS.90028<S>	MS-389(RC 27-39) WASHER	CARBON, ALLOY AND MICROALLOY STEEL BAR, BILLET, BL
8	*PS-10180		DECORATIVE CATHODIC BLACK FINISH
9	PS.20001		"TORX" - 6-LOBE INTERNAL RECESS - INSPECTION PRACT
10	01307		STEEL BOLTS AND NUTS - Representation, designation

SPECIAL CHARACTERISTICS BLOCK	
APPEARANCE	N
EMISSIONS	N
SAFETY	Y
OTUP	N

GENERAL ENGINEERING NOTES (OPTIONAL)

Initial release: ODM 6042-05297

PART CHANGE BLOCK

CN PCL	Originator	CN Decision	TC Release	TC Official	CN Description	Comments
Date	Date	Rev	Date			