

Technical drawing of a bolt showing front and side views with dimensions and notes.

Front View Dimensions:

- Overall diameter: $\varnothing 14.00$
- Inner diameter: $\varnothing 13.30$
- Distance from center to edge of hexagon: 10.00
- Distance from center to edge of hexagon (minimum): 9.76
- Minimum height: 10.93 MIN

Side View Dimensions:

- Overall length: 25.00
- Distance from head to start of thread: 4.47
- Distance from head to start of thread (minimum): 4.13
- Head diameter: $\varnothing 14.00$
- Head thickness: 0.60
- Head thickness (minimum): 0.35
- Distance from head to start of thread: 2.10
- Distance from head to start of thread (minimum): 1.84
- Distance from head to start of thread: 0.40
- Distance from head to start of thread (minimum): 0.25
- Distance from head to start of thread: 3.00
- Distance from head to start of thread (minimum): 2.00
- Distance from head to start of thread: 3.40
- Distance from head to start of thread (minimum): 2.60
- Thread diameter: $\varnothing 4.50$
- Thread diameter (minimum): $\varnothing 4.35$
- Thread specification: M6 X 1.0-6g THREAD
- Thread pitch: ONE THREAD PITCH MAX
- Surface note: IRREGULAR SURFACE PERMISSIBLE
- Reference: SEE NOTE

Notes:

- USE AND SHAPE OF INDENTATION OPTIONAL

5 FLUTES EQUALLY SPACED TO EXTEND THRU THE FIRST BUT NOT BEYOND THE SECOND FULL FORMED THREAD. DEPTH OF FLUTE SHALL BE FROM 60% TO 100% OF THE FULL FORMED THREAD HEIGHT.

10	11	12
ESTIMATED WEIGHT:		0.0097 Kg

PART INFORMATION PAGE FOR ITEM NUMBER : FC00AAW26849**TITLE BLOCK INFORMATION**

Item Number FC00AAW26849
Item Revision 002
PCL A
CN
Item Name SC&WA/HEX.HD CONE.WASH.PNT.CUTTE
Item Description M6.0X1.00X25.0
Chrysler Part Number 06512393AA
Fiat Codep Number 53416583
Shown-on Part 06512393AA
Status FA_STEP5,CAD_Released
Owner O
Engineer ALL ,FASTENERS (T5850XX)
Designer
Checker

06512393AA
ASF CONTROLLED WHEN RED
ASF Engineering Approved 5/14/24
2 Pages

ENGINEERING STANDARDS APPLIED

Item	Standard No.	Designation	Standard Title
1	CS-11000	(1)	TRADEMARK IDENTIFICATION ON PARTS - 01446_22_00053
2	CS-9800		GENERAL REQUIREMENTS OF MATERIAL STANDARDS AND FCA
3	PS-9227		CAD/CAM DATA EXCHANGE POLICY
4	PS-10052		INFORMATION SECURITY
5	CS.00080		FCA CAD STANDARD - GLOBAL REQUIREMENTS
6	PS-4480	(1)	IDENTIFICATION & BAR CODING OF PARTS
7	CS-9003		SUPPLIER REQUIREMENTS FOR VEHICLE AND SERVICE PART
8	PF-8500		REQUIREMENTS FOR VERIFICATION, VALIDATION AND CONT
9	CEP-045		MANDATORY AND DISCRETIONARY ENGINEERING STANDARDS
10	CS.00022		GENERAL REQUIREMENTS FOR RELEASED DRAWINGS
11	PS-7099		GENERAL SPECIFICATIONS - FASTENERS AND FITTINGS
12	PF-SAFETY<S>		PRODUCT SAFETY - USE OF THE SAFETY FLAG / SAFETY S
13	MS.50077<S>	MS-6149 9.8A	EXTERNALLY THREADED FASTENERS FOR NORMAL USE (HARM
14	PS.50031	8 BLACK ST	ZINC NICKEL ALLOY ELECTRODEPOSITED COATINGS
15	01307		STEEL BOLTS AND NUTS - Representation, designation

SPECIAL CHARACTERISTICS BLOCK

APPEARANCE	N	DIAMONDS	N
EMISSIONS	N	HOMOLOGATION	N
SAFETY	Y	TRACEABILITY	N
OTUP	N		

GENERAL ENGINEERING NOTES (OPTIONAL)

INITIAL RELEASE: REV 001 ERASE PIP PRECID WORKFLOW PERFORMED.
ADDED ST DESIGNATION TO PS.50031 8 BLACK

PART CHANGE BLOCK

CN	PCL	Originator	CN Decision Date	TC Rev	TC Official Release Date	CN Description	Comments
		A		002	2016-06-15		