

PAINTING POSSIBILITIES



Grasim Industries Ltd. (Birla Paints Div.)
P.O Birlagram, Nagda-456 331, Ujjain,
Madhya Pradesh, India.



Scan to know more
about how we can
help you select.

BIG IN YOUR LIFE



CEMENT



FASHION



METALS



PAINTS



REAL ESTATE



CARBON BLACK



TEXTILES



FINANCIAL SERVICES

BIRLA
opus
PRIME



ABOUT ADITYA BIRLA GROUP

- 165 year old legacy based on trust, credibility and purpose
- 5,00,000 crore* INR turnover
- 40 countries presence
- 20+ diverse industries
- 1,87,000 employees
- No. 1 position in multiple industries and domains in both global and Indian marketplace



UltraTech
Cement



Grasim
Industries



Hindalco
Industries



Aditya Birla
Fashion & Retail



Aditya Birla
Capital



Aditya Birla
AMC



Vodafone-
idea JV



Century textiles
and Industries

ABOUT BIRLA OPUS PRIME

We do more than just painting,
we help clients tell their own story.
That's why we've spent **INR 10,000 Cr**
in investment with a production capacity
of **1.3 billion** litres per annum
across 6 automated plants and
supported by a team of **120+** research
experts with **1000+** years of combined experience.

-  Specialized Product Portfolio
-  Large Team of Dedicated Professionals
-  Personalized Engagements
-  Excellent Services

WIDE PRODUCT PORTFOLIO

EXTERIOR EMULSIONS



INTERIOR EMULSIONS



ENAMELS



EXTERIOR TEXTURES



WATERPROOFING



EXTERIOR EMULSIONS



BIRLA
opus
PRIME





Product Code 916108
EXTERIORS – E8
Water Thinnable Primer

Birla Opus Prime E8 Exterior Water Thinnable Primer is designed to provide an excellent whiteness and high opacity, having a strong adhesion to exterior surfaces ensuring a dignified topcoat finish.



PRODUCT FEATURES



EXCELLENT WHITENESS

Imparts a polished and vibrant appearance when applied to surfaces.



HIGH OPACITY

Delivers good surface hiding ensuring a uniform finish.



HIGH ADHESION

Provides good inter-coat bonding between substrate and top-coat.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the completely cured surface using roller:

80–100 sq.ft/L for 1 coat
or 7.43 – 9.29 sq.m/L for 1 coat ****

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE



WHITE

DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Alldry Salt Seal prior to the topcoat application. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure to ensure complete surface clean-up.



3. Cracks Filling

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, structural audit by expert has to be conducted and prescribed solution to be implemented before application.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exteriors: If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.



PAINTING STEPS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



3. Topcoat Application

Apply 2–3 coats of Birla Opus Prime E30 Exterior Emulsion Paint with a gap of 4–6 hours after each coat for optimal coverage. Add an extra coat of topcoat for horizontal surfaces.



2. Primer Application

For freshly plastered surfaces or repainting, apply a single coat of Birla Opus Prime E8 Exterior Water Thinnable Primer/equivalent Birla White Primer by diluting 1 litre of primer with 1 litre of water and allow it to dry for 4–6 hours under adequate sunlight.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	4 to 6 hours*
Paint Type	Water based
VOC	Low VOC**
Stability of Thinned Paint	24 hours in an air tight container

*Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions. High humidity and/or low temperature will further increase drying time.

**Based on internal lab results (as per test method – ASTM D6886:2018)

PRECAUTIONS

- Avoid application when the ambient temperature is below 10°C or exceeds 45°C, or if there's a possibility of the temperature dropping to these levels within 4 hours of application.
- Do not excessively thin or extend the brush. Avoid application if there is a possibility of dew formation overnight on the freshly painted substrate.
- Thoroughly stir and strain the diluted paint through a fine sieve before using.
- Ensure existing cracks are filled before applying the topcoat, as paint will not cover them.
- For surfaces with heavy algal infestation, proper cleaning is essential. If a bleaching solution is used to disinfect algae, ensure thorough cleaning of the solution with water.
- Do not leave a primer coat or only one coat of topcoat exposed during the monsoon. Ensure to complete application process before the onset of monsoon.
- Especially in the pre-monsoon season, apply paint on horizontal surfaces first and then vertical ones. This helps reduce streak marks caused by potential algal growth.
- For optimal performance, ensure the surface is dry, and the moisture meter reads in the green zone (below 15). If it is in the red zone, identify and address the source of water before painting.
- The pH of wall should be below 12.
- Avoid using chlorinated water for dilution.
- Thinned paint should be used within 24 hours of dilution. It is recommended to thin only the necessary amount and store it in a sealed container. Unused material to be stored in a sealed container.

Version No. E8-1001/11/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved





Product Code 916110
EXTERIORS – E10
Water Thinnable Primer

Birla Opus Prime E10 Exterior Water Thinnable Primer is designed to provide an exceptional whiteness and opacity, having a strong adhesion to exterior surfaces ensuring a flawless topcoat finish.



PRODUCT FEATURES



OUTSTANDING WHITENESS

Provides a clean and vibrant appearance when applied to surfaces.



EXCELLENT OPACITY

Provides excellent surface hiding and uniform finish, completely concealing the underlying substrate.



EXCELLENT ADHESION

Ensures a strong and durable bonding of topcoat to the substrates.



RESISTANCE TO CHALKING

Prevents chalking when applied on the completely cured plaster creating a uniform surface for topcoat application.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the completely cured surface using roller:

80-100 sq.ft/L for 1 coat
or 7.43 – 9.29 sq.m/L for 1 coat ****

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE



WHITE

DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Alldry Salt Seal prior to the topcoat application. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure to ensure complete surface clean-up.



3. Cracks Filling

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, structural audit by expert has to be conducted and prescribed solution to be implemented before application.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exteriors:

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.



PAINTS

PAINTING STEPS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2. Primer Application

For freshly plastered surfaces or repainting, apply a single coat of Birla Opus Prime E10 Exterior Water Thinnable Primer/equivalent Birla White Primer by diluting 1 litre of primer with 1 litre of water and allow it to dry for 4-6 hours under adequate sunlight.



3. Topcoat Application

Apply 2-3 coats of Birla Opus Prime Exterior top coat with a gap of 4-6 hours after each coat for optimal coverage. Add an extra coat of topcoat for horizontal surfaces.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	4 to 6 hours*
Paint Type	Water based
VOC	Low VOC
Stability of Thinned Paint	24 hours in an air tight container

*May vary according to temperature & humidity

PRECAUTIONS

- Avoid application when the ambient temperature is below 10°C or exceeds 45°C, or if there's a possibility of the temperature dropping to these levels within 4 hours of application.
- Do not excessively thin or extend the brush. Avoid application if there is a possibility of dew formation overnight on the freshly painted substrate.
- Thoroughly stir and strain the diluted paint through a fine sieve before using.
- Ensure existing cracks are filled before applying the topcoat, as paint will not cover them.
- For surfaces with heavy algal infestation, proper cleaning is essential. If a bleaching solution is used to disinfect algae, ensure thorough cleaning of the solution with water.
- Do not leave a primer coat or only one coat of topcoat exposed during the monsoon. Ensure to complete application process before the onset of monsoon.
- Especially in the pre-monsoon season, apply paint on horizontal surfaces first and then vertical ones. This helps reduce streak marks caused by potential algal growth.
- For optimal performance, ensure the surface is dry, and the moisture meter reads in the green zone (below 15). If it is in the red zone, identify and address the source of water before painting.
- The pH of wall should be below 12.
- Avoid using chlorinated water for dilution.
- Thinned paint should be used within 24 hours of dilution. It is recommended to thin only the necessary amount and store it in a sealed container. Unused material to be stored in a sealed container.

Version No. E10-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved



PAINTS



Product Code 916030
EXTERIORS – E30
Emulsion Paint

Birla Opus Prime E30 Exteriors Emulsion Paint is a modified acrylic emulsion paint with Peel Safe Technology* designed for dry to moderately humid geographies. This formulation ensures excellent scrub and peel resistance for long lasting performance.



PRODUCT FEATURES



HIGH PEEL RESISTANCE

Resistance to peeling of paint surface ensuring durability.



EXCELLENT SCRUB RESISTANCE

Outstanding resistance to wear and tear, when subjected to scrubbing or cleaning.



EXCELLENT WHITENESS

Best in class whiteness and brightness providing pure and vibrant colour to the surface.



EXCELLENT FINISH

Provides excellent finish to the substrate enhancing the overall look.



WARRANTY*

Long-lasting assurance against film flaking and peeling.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using roller:

55-60 sq.ft/L for 2 coats **
or 5.11-5.57 sq.m/L for 2 coats**

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

1600+ #

#Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.



FINISH

MATT



DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Alldry Salt Seal prior to the topcoat application. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure to ensure complete surface clean-up.



3. Cracks Filling

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, structural audit by expert has to be conducted and prescribed solution to be implemented before application.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exteriors

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.



PAINTS



PAINTING STEPS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2. Primer Application

Apply a single coat of Birla Opus Prime E10 Exterior Water Thinnable Primer/ equivalent Birla White Primer by diluting 1 litre of primer with 1 litre of water and allow it to dry for 4-6 hours under adequate sunlight.



3. Topcoat Application

Dilute 1 litre of E30 Exterior Emulsion Paint with a 600-700 ml of water and apply 2-3 coats for optimal coverage. Allow 4-6 hour gap between each coat to ensure proper hiding. Add an extra coat of topcoat for horizontal surfaces.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	4 to 6 hours*
Paint Type	Water based
VOC	Low VOC
Stability of Thinned Paint	24 hours in an air tight container
Sheen Level	3-5 at 60 (degree) GH for white shade

*May vary according to temperature & humidity

PRECAUTIONS

- Avoid application when the ambient temperature is below 10°C or exceeds 45°C, or if there's a possibility of the temperature dropping to these levels within 4 hours of application.
- Do not excessively thin or extend the brush. Avoid application if there is a possibility of dew formation overnight on the freshly painted substrate.
- Thoroughly stir and strain the diluted paint through a fine sieve before using.
- Ensure existing cracks are filled before applying the topcoat, as paint will not cover them.
- For surfaces with heavy algal infestation, proper cleaning is essential. If a bleaching solution is used to disinfect algae, ensure thorough cleaning of the solution with water.
- Do not leave a primer coat or only one coat of topcoat exposed during the monsoon. Ensure to complete application process before the onset of monsoon.
- Especially in the pre-monsoon season, apply paint on horizontal surfaces first and then vertical ones. This helps reduce streak marks caused by potential algal growth.
- For optimal performance, ensure the surface is dry, and the moisture meter reads in the green zone (below 15). If it is in the red zone, identify and address the source of water before painting.
- The pH of wall should be below 12.
- Avoid using chlorinated water for dilution.
- Thinned paint should be used within 24 hours of dilution. It is recommended to thin only the necessary amount and store it in a sealed container. Unused material to be stored in a sealed container.

Version No. E30-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



PAINTS



Product Code 916050
EXTERIORS - E50
Premium Emulsion

Birla Opus Prime E50 Exteriors Premium Emulsion is modified acrylic emulsion paint known for its exceptional dirt pick-up resistance and all weather protection. This formulation ensures ultra-clean exterior walls while providing excellent resistance against algal growth.

BIRLA
opus
PRIME

BIRLA
opus
PRIME

PRODUCT FEATURES



HIGH DIRT PICK-UP RESISTANCE

Exceptional ability to resist or repel the accumulation of dirt, making the surface look cleaner.



RESISTANCE TO ALGAL GROWTH

Effective prevention of algal growth, ensuring sustained resistance providing overall protection from the dark patches on the wall.



EXCELLENT SCRUB RESISTANCE

Exceptional durability against wear and tear, and resistance to damage when subjected to scrubbing or cleaning.



HIGH PEEL RESISTANCE

Prevention of paint surface peeling, ensuring its longevity.



WARRANTY*

Long-lasting assurance for film integrity and algal resistance.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using roller:

55-60 sq.ft/L for 2 coats **
or 5.11-5.57 sq.m/L for 2 coats**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

1950+*

*Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.

FINISH

SOFT SHEEN



DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Alldry Salt Seal prior to the topcoat application. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure to ensure complete surface clean-up.



3. Cracks Filling

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, structural audit by expert has to be conducted and prescribed solution to be implemented before application.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exteriors:

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.



ADITYA BIRLA

PAINTS

PAINTING STEPS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2a. Primer Application

Apply a single coat of Birla Opus Prime E10 Exterior Water Thinnable Primer/equivalent Birla White Primer by diluting 1 litre of primer with 1 litre of water and allow it to dry for 4-6 hours under adequate sunlight.

OR



2b. Waterproof Coating Application

If you wish to apply a Birla Opus waterproof coating/equivalent Birla White waterproofing product, please follow the application procedure as per the PIS of the waterproof coating used.



3. Topcoat Application

Dilute 1 litre of E50 Exterior Premium Emulsion Paint with a 300-400ml of water and apply 2-3 coats for optimal coverage. Allow 4-6 hour gap between each coat to ensure proper hiding. Add an extra coat of topcoat for horizontal surfaces.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution: Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Drying Time	4 to 6 hours*
Sheen Level	4-7 at 60 (degree) GH for white shade
Paint Type	Water based
Stability of Thinned Paint	24 hours in an air tight container
VOC	Low VOC
Shelf Life	36 months from the date of manufacturing

*May vary according to temperature & humidity

PRECAUTIONS

- Avoid application when the ambient temperature is below 10°C or exceeds 45°C, or if there's a possibility of the temperature dropping to these levels within 4 hours of application.
- Do not excessively thin or extend the brush. Avoid application if there is a possibility of dew formation overnight on the freshly painted substrate.
- Thoroughly stir and strain the diluted paint through a fine sieve before using.
- Ensure existing cracks are filled before applying the topcoat, as paint will not cover them.
- For surfaces with heavy algal infestation, proper cleaning is essential. If a bleaching solution is used to disinfect algae, ensure thorough cleaning of the solution with water.
- Do not leave a primer coat or only one coat of topcoat exposed during the monsoon. Ensure to complete application process before the onset of monsoon.
- Especially in the pre-monsoon season, apply paint on horizontal surfaces first and then vertical ones. This helps reduce streak marks caused by potential algal growth.
- For optimal performance, ensure the surface is dry, and the moisture meter reads in the green zone (below 15). If it is in the red zone, identify and address the source of water before painting.
- The pH of wall should be below 12.
- Avoid using chlorinated water for dilution.
- Thinned paint should be used within 24 hours of dilution. It is recommended to thin only the necessary amount and store it in a sealed container. Unused material to be stored in a sealed container.

Version No. E50-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



ADITYA BIRLA

PAINTS



Product Code 916070
EXTERIORS – E70
Luxury Emulsion

Birla Opus Prime E70 Exteriors Luxury Emulsion is a pure acrylic emulsion paint distinguished for its Color-Protect Technology*. It provides outstanding protection against color fading and features an excellent solar-reflective index, contributing to surface temperature reduction.



PRODUCT FEATURES



COLOR-FADE RESISTANCE

Withstand adverse effects like exposure to sunlight, rain; maintaining its vibrant and original look for an extended period.



EXCELLENT SOLAR REFLECTIVE INDEX

Excellent capability to remain cooler when exposed to sunlight.



HIGH DIRT PICK-UP RESISTANCE

Outstanding capability to deter the build-up of dirt, preventing it from sticking to the surface.



RESISTANCE TO ALGAL GROWTH

Efficiently inhibiting algal growth, and preserving the integrity of surfaces over time.



WARRANTY*

Enduring assurance for film integrity, algal resistance and long-lasting color retention.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using roller:

55-60 sq.ft/L for 2 coats **
or 5.11-5.57 sq.m/L for 2 coats**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

1950+*

*Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.

FINISH

RICH SHEEN



DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Alldry Salt Seal prior to the topcoat application. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure to ensure complete surface clean-up.



3. Cracks Filling

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, structural audit by expert has to be conducted and prescribed solution to be implemented before application.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exteriors:

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.



PAINTING STEPS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2a. Primer Application

Apply a single coat of Birla Opus Prime E10 Exterior Water Thinnable Primer/ equivalent Birla White Primer by diluting 1 litre of primer with 1 litre of water and allow it to dry for 4-6 hours under adequate sunlight.

OR



2b. Waterproof Coating Application

If you wish to apply a Birla Opus waterproof coating/ equivalent Birla White waterproofing product, please follow the application procedure as per the PIS of the waterproof coating used.



3. Topcoat Application

Dilute 1 litre of E70 Exterior Luxury Emulsion Paint with a 300-400ml of water and apply 2-3 coats for optimal coverage. Allow 4-6 hour gap between each coat to ensure proper hiding. Add an extra coat of topcoat for horizontal surfaces.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

PRECAUTIONS

- Avoid application when the ambient temperature is below 10°C or exceeds 45°C, or if there's a possibility of the temperature dropping to these levels within 4 hours of application.
- Do not excessively thin or extend the brush. Avoid application if there is a possibility of dew formation overnight on the freshly painted substrate.
- Thoroughly stir and strain the diluted paint through a fine sieve before using.
- Ensure existing cracks are filled before applying the topcoat, as paint will not cover them.
- For surfaces with heavy algal infestation, proper cleaning is essential. If a bleaching solution is used to disinfect algae, ensure thorough cleaning of the solution with water.
- Do not leave a primer coat or only one coat of topcoat exposed during the monsoon. Ensure to complete application process before the onset of monsoon.
- Especially in the pre-monsoon season, apply paint on horizontal surfaces first and then vertical ones. This helps reduce streak marks caused by potential algal growth.
- For optimal performance, ensure the surface is dry, and the moisture meter reads in the green zone (below 15). If it is in the red zone, identify and address the source of water before painting.
- The pH of wall should be below 12.
- Avoid using chlorinated water for dilution.
- Thinned paint should be used within 24 hours of dilution. It is recommended to thin only the necessary amount and store it in a sealed container. Unused material to be stored in a sealed container.

TECHNICAL DATA

Drying Time	4 to 6 hours*
Sheen Level	12-16 at 60 (degree) GH for white shade
Paint Type	Water based
Stability of Thinned Paint	24 hours in an air tight container
VOC	Low VOC
Shelf Life	36 months from the date of manufacturing

*May vary according to temperature & humidity

Version No. E70-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved





Product Code 916090

EXTERIORS – E90

Ultra Luxury Emulsion

Birla Opus Prime E90 Exteriors Ultra Luxury Emulsion is an acrylic emulsion paint with Advanced PCPU technology (Advanced Poly-carbonated Poly-urethane technology), which is a strategic integration of photo crosslinking, silica reinforcement and polyurethane matrix that enhances elongation, tensile strength and dust resistance. It also provides ultimate all-weather protection, offering 12-year warranty.



PRODUCT FEATURES



ADVANCED PC-PU TECHNOLOGY

Advanced Polycarbonate-Polyurethane technology offers outstanding durability with all-weather protection.



COLOR FADE RESISTANCE

Outstanding resistance to weather conditions like UV rays, exposure to sunlight and rain; maintaining its vibrant and original appearance.



OUTSTANDING DIRT PICK-UP RESISTANCE

Outstanding ability to prevent dirt accumulation, ensuring it does not adhere to the surface.



RESISTANCE TO ALGAL GROWTH

Fortified with special additives to prevent growth of algae and fungus ensuring better hygiene and blemish-free walls.



WARRANTY*

Long-lasting assurance for film integrity, resistance to algae, and vibrant color retention.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using roller:

**55-60 sq.ft/L for 2 coats **
or 5.11-5.57 sq.m/L for 2 coats****

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

1950+*

*Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.

FINISH

RICH SHEEN



DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Alldry Salt Seal prior to the topcoat application. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure to ensure complete surface clean-up.



3. Cracks Filling

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, structural audit by expert has to be conducted and prescribed solution to be implemented before application.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exteriors:

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2a. Primer Application

Apply a single coat of Birla Opus Prime E10 Exterior Water Thinnable Primer/Equivalent Birla White Primer by diluting 1 litre of primer with 1 litre of water and allow it to dry for 4-6 hours under adequate sunlight.

OR



2b. Waterproof Coating Application

If you wish to apply a Birla Opus waterproof coating/Equivalent Birla White waterproofing product, please follow the application procedure as per the PIS of the waterproof coating used.



3. Topcoat Application

Apply Birla Opus Texture (Optional). Dilute 1 litre of E90 Exterior Ultra Luxury Emulsion with a 300-400ml of water and apply 2-3 coats for optimal coverage. Allow 4-6 hour gap between each coat to ensure proper hiding. Add an extra coat of topcoat for horizontal surfaces.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Drying Time	4 to 6 hours*
Sheen Level	12-18 at 60 (degree) GH for white shade
Paint Type	Water based
Stability of Thinned Paint	24 hours in an air tight container
VOC	Low VOC**
Shelf Life	36 months from the date of manufacturing

*Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions. High humidity and/or low temperature will further increase drying time.

**Based on internal lab results (as per test method – ASTM D6886:2018)

PRECAUTIONS

- Avoid application when the ambient temperature is below 10°C or exceeds 45°C, or if there's a possibility of the temperature dropping to these levels within 4 hours of application.
- Do not excessively thin or extend the brush. Avoid application if there is a possibility of dew formation overnight on the freshly painted substrate.
- Thoroughly stir and strain the diluted paint through a fine sieve before using.
- Ensure existing cracks are filled before applying the topcoat, as paint will not cover them.
- For surfaces with heavy algal infestation, proper cleaning is essential. If a bleaching solution is used to disinfect algae, ensure thorough cleaning of the solution with water.
- Do not leave a primer coat or only one coat of topcoat exposed during the monsoon.
- Painting is to be avoided if there is a possibility of rain within 4 days of application. Especially in the pre-monsoon season, apply paint on horizontal surfaces first and then vertical ones. This helps reduce streak marks caused by potential algal growth.
- For optimal performance, ensure the surface is dry, and the moisture meter reads in the green zone (below 15). If it is in the red zone, identify and address the source of water before painting.
- The pH of wall should be below 12.
- Avoid using chlorinated water for dilution.
- Thinned paint should be used within 24 hours of dilution. It is recommended to thin only the necessary amount and store it in a sealed container. Unused material to be stored in a sealed container.

Version No. E90-1001/11/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved



INTERIOR EMULSIONS



I6



I10



N10

BIRLA
opus
PRIME



I30



D20



I50



Product Code 910106
INTERIORS – I6
Water Thinnable Cement Primer

Birla Opus Prime I6 Interior Water Thinnable Cement Wall Primer is an acrylic-based value primer designed for interior walls. It provides excellent whiteness, improved adhesion, and easy applicability ensuring long standing beautiful interiors.



PRODUCT FEATURES



EXCELLENT WHITENESS

A perfect foundation for your paint, enhancing the overall aesthetic appeal.



IMPROVES ADHESION

Ensures high bonding between substrate and paint film.



EASY APPLICATION

Easy painting allowing smooth and seamless strokes of roller and brush with minimal effort.



GOOD HIDING

Good opacity of primer guarantees your wall looks good without ugly spots.



ALKALI RESISTANT

Enhanced protection against alkaline substrate for better topcoat durability.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller:

180–200 sq.ft/L
for 1 coat**

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE



WHITE

DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

New masonry surfaces must be allowed to cure completely for 28 days ensuring they are water cured on daily basis.



3. Filling of Cracks

To address cracks measuring up to 5mm, use Birla Opus crack fill solutions. For larger cracks, it is recommended to audit it with a structural engineer and get it repaired before painting.



2. Cleaning

Surface should be free from any loose paint dust, or grease. Growth of fungus, algae or moss should be removed by wire brushing and water. When the underlying surface exhibits chalkiness, please use water curing for some time and then apply a layer of Birla Opus Alldry Salt Seal Primer before proceeding to painting steps.



4. Covering of holes and dents

In case of holes and dents use cement putty or a mix of white cement and fine sand in the ratio 1:3.

Special Instructions for Interior:

For interior surfaces or substrates that are subjected to continuous seepage or dampness, please check the source of leakage or seepage, and ensure the same is rectified before application.



ADITYA BIRLA

PAINTS

PAINTING STEPS



1. Primer Application

For both freshly plastered or repainting surface, apply one coat of Birla Opus Prime I6 Interior Water Thinnable Cement Wall Primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



2. Putty Application

Smoothen the surface by filling dents and undulations with thin coat of Birla Opus One Acrylic/ Birla White Cement Putty. Allow it to dry for 4–6 hours. Apply two coats of putty to achieve uniform painting surface. Apply third coat of putty if required. Sand with sandpaper and wipe it.



3. Primer Application

Apply one coat of Birla Opus Prime I6 Interior Water Thinnable Cement Wall Primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



4. Topcoat Application

Apply 2–3 coats of Birla Opus Prime Interior Topcoat with a gap of 4–6 hours after each coat. Add extra topcoat for dark shades. A gap of 4 to 6 hours to be given after each coat for drying.

POST PAINTING CARE

1

Ensure dusting at regular intervals.

2

While cleaning, wipe gently without intense pressure.

3

Give 2 weeks of drying time post application of paint before wet wiping the wall.

PRECAUTIONS

- Do not apply when ambient temperature might drop to a level below 10°C within 4 hours of application.
- Do not apply when ambient temperature might increase to a level above 45°C within 4 hours of application.
- Do not apply if relative humidity is more than 90%.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- For surfaces having heavy fungal infestation, proper cleaning is mandated.
- Keep the material in closed condition when not in use.
- Diluted primer should be used within 24 hours of dilution. Accordingly, it is recommended to thin down only the necessary amount of paint. Post 24 hours, thinned primer may be susceptible for microbial attack.
- Do not apply to wet or visibly damp surfaces.

SAFETY FEATURES

- Kindly refer to the MSDS, which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or mud.
- No added Lead, Mercury, or Chromium compounds.
- Left-over paint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drums.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	Surface dry time 30 minutes*
Recoating time	4–6 hours*
Drying time to touch	4–6 hours between recoats*
Shelf life of thinned paint	To be used within 24 hours

*May vary according to temperature & humidity

Version No. I6-1001/11/2024 *T&C Apply. For more details visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.



ADITYA BIRLA

PAINTS



Product Code 910110
INTERIORS – I10
Water Thinnable Wall Primer

Birla Opus Prime I10 Interior Water Thinnable Wall Primer is an acrylic-based primer designed for interior walls. It provides outstanding opacity, robust adhesion and contributes to the creation of smooth and long-lasting wall surfaces.



PRODUCT FEATURES



EXCELLENT OPACITY

Excellent opacity of primer guarantees a flawless finish with fewer coats.



STRONG ADHESION

Exceptional adhesion to protect against flaking and peeling of paints.



EASY BRUSHABILITY

Easy painting allowing smooth and seamless strokes of roller with minimal effort.



HIGH ALKALI RESISTANCE

Robust protection against alkaline surfaces, ensuring long-lasting durability for your topcoats.



EXCELLENT WHITENESS

A pristine foundation for your paint, enhancing the overall aesthetic appeal.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller:

180-200 sq.ft/L for 1 coat
or 16.72-18.58 sq.m/L for 1 coat****

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE



WHITE

DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

New masonry surfaces must be allowed to cure completely for 28 days ensuring they are water cured on daily basis.



3. Filling of Cracks

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, it is recommended to audit it with a structural engineer and get it repaired before painting.



2. Cleaning

Surface should be free from any loose paint dust, or grease. Growth of fungus, algae or moss should be removed by wire brushing and water. When the underlying surface exhibits chalkiness, please use water curing for some time and then apply a layer of Birla Opus Penetrating primer before proceeding to painting steps.



4. Covering of holes and dents

In case of holes and dents use cement putty or a mix of white cement and fine sand in the ratio 1:3.

Special Instructions for Interior:

For interior surfaces or substrates that are subjected to continuous seepage or dampness, please check the source of leakage or seepage and ensure the same is rectified before application.



PAINTS

PAINTING STEPS



1. Primer Application

For both freshly plastered or repainting surface, apply one coat of Birla Opus Prime I10 Interior Water Thinnable wall primer by/equivalent Birla White interior primer thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



2. Putty Application

Smoothen the surface by filling dents and undulations with thin coat of Birla Opus One Acrylic putty/equivalent Birla White putty. Allow it to dry for 4-6 hours. Apply two coats of putty to achieve uniform painting surface. Apply third coat of putty if required. Sand with sandpaper and wipe it.



3. Primer Application

Apply one coat of Birla Opus Prime I10 Interior Water Thinnable wall primer /equivalent Birla White interior primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



4. Topcoat Application

Apply 2-3 coats of Birla Opus Prime Interior Topcoat with a gap of 4-6 hours after each coat. Add extra topcoat for dark shades. A gap of 4 to 6 hours to be given after each coat for drying.

POST PAINTING CARE

1

Ensure dusting at regular intervals.

2

While cleaning, wipe gently without intense pressure.

3

Give 2 weeks of drying time post application of paint before wet wiping the wall.

PRECAUTIONS

- Do not apply when ambient temperature might drop to a level below 10°C within 4 hours of application.
- Do not apply when ambient temperature might increase to a level above 45°C within 4 hours of application.
- Do not apply if relative humidity is more than 90%.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- For surfaces having heavy fungal infestation, proper cleaning is mandated.
- Keep the material in closed condition when not in use.
- Diluted Primer should be used within 24 hours of dilution. Accordingly, it is recommended to thin down only the necessary amount of paint. Post 24 hours, thinned primer may be susceptible for microbial attack.
- Do not apply to wet or visibly damp surfaces.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	Surface dry time 30 minutes*
Recoating time	4-6 hours*
Drying time to touch	4-6 hours between recoats*
Shelf life of thinned paint	To be used within 24 hours

*May vary according to temperature & humidity

Version No. I10-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



PAINTS



Product Code 910210
INTERIORS – N10
Solvent Thinnable Wall Primer

Birla Opus Prime N10 Interior Solvent Thinnable Wall Primer is an alkyd based solvent primer designed to offer outstanding adhesion and durability.



PRODUCT FEATURES



EXCELLENT OPACITY

Excellent opacity of paint which ensures flawless finish with fewer coats.



STRONG ADHESION

Exceptional adhesion to protect against cracking and peeling of paints.



EASY BRUSHABILITY

Smooth and seamless roller strokes are achieved with ease.



EXCELLENT WHITENESS

Infusing your walls with a radiant and crisp quality paint, enhancing their overall appearance.



EXCELLENT FLOW & LEVELLING

Effortless application of paint for a uniform foundation giving a smooth topcoat finish.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller:

180–200 sq.ft/L for 1 coat
or 16.72–18.58 sq.m/L for 1 coat****

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE



WHITE

DIRECTION FOR USE

PRE PAINTING STEPS / SURFACE PREPARATION



1. Plaster

New masonry surfaces must be allowed to cure completely for 28 days before painting. Ensure surface is free from any leakage, seepage, and efflorescence.



2. Cleaning

For repainting, remove loose paint, dust/dirt particles and laitance with sandpaper no. 180. Wipe clean. Algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use professional assistance to limit further dampness.



3. Filling of cracks

For filling cracks up to 5mm use Birla Opus crack fill solutions. For cracks above 5mm, it is recommended for cement: river sand (1:4 ratio) plastering. If the cracks are more, it is recommended to audit it with a structural engineer and get it repaired before painting.



4. Covering Holes and dents

In case of dents and holes use cement putty or a mix of white cement and fine sand in the ratio 1:3.

Special Instructions for Interior:

For Interior surfaces or substrates that are subjected to continuous seepage or dampness, please check the source of leakage or seepage and ensure the same is rectified before application.



1. Primer Application

Dilute 1 litre of Birla Opus Prime N10 Interiors Solvent Thinnable Wall Primer with 80–100ml of Mineral Turpentine Oil and apply one coat by brushing / rolling. Allow to dry for 6–8 hours.



2. Putty Application

Use Birla Opus One Acrylic putty/equivalent Birla White putty to fill undulations of masonry surfaces. Ensure 4–6 hours of drying time. Apply second coat of putty if required. Sand the surface with emery paper no. 180, followed by no. 320



3. Primer Application

Dilute 1 litre of Birla Opus Prime N10 Interiors Solvent Thinnable Wall Primer with 80–100ml of Mineral Turpentine Oil and apply one coat by brushing / rolling. Allow to dry for 6–8 hours.



4. Topcoat Application

Apply suitable Birla Opus Prime Interior topcoat as per recommended procedure in the respective product data sheet.

For spray application, dilute 1 litre of Birla Opus Prime N10 Interiors Solvent Thinnable Wall Primer with 100–150ml of Mineral Turpentine Oil.

PRECAUTIONS

- Do not apply at relative humidity greater than 85%.
- Do not apply when ambient temperature is less than 10°C or above 40°C.
- For surfaces having heavy algal infestation, cleaning with bleaching solution is advised.
- Keep the material in closed condition when not in use.
- Ensure adequate ventilation under all application conditions.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- Highly flammable product, do not store the products near electrical installations and flammable sources.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.

TECHNICAL DATA

Binder	Alkyd
Drying time	30 min surface dry*
Recoating time	6–8 hours*
Flash Point	Above 30 °C
Stability of thinned paint	To be used within 24 hours
Shelf Life	18 months

*May vary according to temperature & humidity

Version No. N10-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved





Product Code 910020
INTERIORS – D20
Acrylic Distemper

Birla Opus Prime D20 Interior Acrylic Distemper offers a rich and beautiful look to the walls. It is an acrylic-based distemper that boasts high washability with a diverse palette of colors.



PRODUCT FEATURES



RICH LOOK & FINISH

Uniform distribution contributing to a professional and polished look.



WIDE RANGE OF COLOURS

Wide spectrum of shades and colours to suit every project need.



HIGH WASHABILITY

Advanced washability formula for pristine surfaces and effortless maintenance.



EXCELLENT WHITENESS

Infusing your walls with an excellent white quality paint enhancing their overall appearance.



WARRANTY*

Long lasting assurance on film integrity and colour retention.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush/roller:

70-90 sq.ft/kg/2 coats
or 6.50-8.36 sq.m/kg/2 coats****

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOUR AVAILABLE

1000+ #



#Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.

FINISH



MATT

DIRECTION FOR USE

PRE PAINTING STEPS / SURFACE PREPARATION



1. Strip all old / previously applied unadhering paint / papdi, flaking particles, plaster, dirt, dust, grease, wax, fungus or any other microbial growth by putty knife and / or sanding with emery paper No. 180 and wipe off.



3. In case of water leakage / seepage, special treatment of water proofing is required.



2. In heavy fungus or microbial growth affected area, special treatment of biowash is required.



4. Ensure surface is clean & completely dry before starting the painting procedures.

PAINTING STEPS



1. Apply one coat of Birla Opus Prime Interior Wall Primer (Water thinnable/Solvent thinnable)/equivalent Birla White interior primer. Allow it to dry for 4-6 hours in case of water thinnable primer & 6-8 hours for solvent thinnable primer.



3. Apply one coat of Birla Opus Prime Interior Wall Primer (Water thinnable/Solvent thinnable)/equivalent Birla White interior primer. Allow it to dry for 4-6 hours in case of water thinnable primer & 6-8 hours for solvent thinnable primer.



2. Apply 1-2 coats of Birla Opus One Acrylic Putty/equivalent Birla White Putty to fill dents, minor cracks and to smoothen & level the surface. Allow it to dry 4-6 hours. Sand with emery paper no. 180/320 & wipe off loose powder.



4. Dilute 1kg Birla Opus Prime D20 Acrylic Distemper with 600-650ml of clean water and apply 2-3 coats by using brush & roller or by roller at an interval between 4-6 hours between each coat.

POST PAINTING CARE

1

Paint film generally require 2 weeks to develop adequate strength.

2

A clean and well-maintained living space will aid in long lasting finish.

TECHNICAL DATA

Drying time	Surface dry time 30-45 min*
Recoating time	4-6 hours*
Thinning	60-65% by clean water
Flash point	Not applicable. Non-flammable water based product
Usage time (to be used post dilution)	Within 24 hours*
Shelf life	36 Months

*Varies on climatic conditions.

SAFETY FEATURES

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not add extra water.
- Tint using Birla Opus machine colourants only.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after Birla Opus colorant addition as well as before use.
- Store the container in ventilated locations and away from sources of ignition and fire.
- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution: Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

Version No. D20-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content - all rights reserved





Product Code 910030
INTERIORS – I30
Emulsion Paint

Birla Opus Prime I30 Interior Emulsion Paint is an acrylic-based emulsion. This paint not only delivers a smooth finish but also imparts vibrant and vivid colors, supported by a warranty of upto 4 years.*



PRODUCT FEATURES



EXCEPTIONAL BRIGHTNESS

Infusing your walls with a radiant and crisp quality paint enhancing their overall appearance.



EXCELLENT SMOOTHNESS

Impeccable smooth finish delivering a professional quality result.



HIGH OPACITY

Excellent opacity of paint which ensures flawless finish with fewer coats.



EASY BRUSHABILITY

Effortlessly smooth and seamless roller strokes are achieved with ease.



WARRANTY*

4 years warranty on color retention, **3 years** warranty on film flaking and peeling.*

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller:

120-140 sq.ft/L for 2 coats**
or 11.15-13.01 sq.m/L for 2 coats**

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

1600+*

#Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.*

FINISH

MATT



DIRECTIONS FOR USE

Recommended usage – On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

New masonry surfaces must be allowed to cure completely for 28 days ensuring they are water cured on daily basis.



3. Filling of Cracks

To address cracks measuring up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. For larger cracks, it is recommended to audit it with a structural engineer and get it repaired before painting.



2. Cleaning

Surface should be free from any loose paint dust, or grease. Growth of fungus, algae or moss should be removed by wire brushing and water. When the underlying surface exhibits chalkiness, please use water curing for some time and then apply a layer of Birla Opus Penetrating primer before proceeding to painting steps.



4. Covering of holes and dents

In case of holes and dents use cement putty or a mix of white cement and fine sand in the ratio 1:3.

Special Instructions for Interior:

For interior surfaces or substrates that are subjected to continuous seepage or dampness, please check the source of leakage or seepage and ensure the same is rectified before application.



ADITYA BIRLA

PAINTS



PAINTING STEPS



1. Primer Application

For both freshly plastered or repainting surface, apply one coat of Prime I10 Interior Water Thinnable wall primer/ equivalent Birla White interior primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



3. Primer Application

Apply one coat of Birla Opus Prime I10 Interior Water Thinnable wall primer/ equivalent Birla White interior primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4



2. Putty Application

Smoothen the surface by filling dents and undulations with thin coat of Birla Opus One Acrylic putty/ equivalent Birla White putty. Allow it to dry for 4-6 hours. Apply two coats of putty for uniform wall. Apply third coat of putty if required. Sand with sandpaper and wipe it.



4. Topcoat Application

Dilute 1 litre of Birla Opus Prime I30 Emulsion Paint with 500-600 ml of water and apply 2-3 coats of topcoat to ensure good hiding. A gap of 4-6 hours to be given after each coat.

POST PAINTING CARE

1

Ensure dusting at regular intervals.

2

While cleaning, wipe gently without intense pressure.

3

Give 2 weeks of drying time post application of paint before wet wiping the wall.

PRECAUTIONS

- Do not apply when ambient temperature might drop to a level below 10°C within 4 hours of application.
- Do not apply when ambient temperature might increase to a level above 45°C within 4 hours of application.
- Do not apply if relative humidity is more than 90%.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- For surfaces having heavy fungal infestation, proper cleaning is mandated.
- Keep the material in closed condition when not in use.
- Diluted Primer should be used within 24 hours of dilution. Accordingly, it is recommended to thin down only the necessary amount of paint. Post 24 hours, thinned primer may be susceptible for microbial attack.
- Do not apply to wet or visibly damp surfaces.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	Surface dry time 30 minutes*
Recoating time	4-6 hours*
Shelf life of thinned paint	To be used within 24 hours

*May vary according to temperature & humidity

Version No. I30-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



ADITYA BIRLA

PAINTS



Product Code 910050
INTERIORS - 150
Premium Emulsion Paint

Birla Opus Prime 150 Interior Premium Emulsion Paint is crafted for interior walls. This high-quality, scrub-resistant interior emulsion ensures both exceptional performance and longevity for your interior surfaces.



PRODUCT FEATURES



EXCELLENT SCRUB RESISTANCE

Exceptional durability against wear and tear ensuring film integrity and long-lasting protection of the walls.



HIGH FUNGAL RESISTANCE

Resists mildew & black fungal/mold growth on surfaces to maintain healthy and aesthetic appearance of the walls.



SPATTER RESISTANCE

Reduce material wastage and simple post-painting cleaning for a more efficient paint application process.



SMOOTHNESS

Achieve a premium, flawless smooth finish and add a touch of sophistication.



WARRANTY*

Long-lasting durability with 5 years assurance against color fading, film flaking and peeling.
*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller:

130-150 sq.ft/L for 2 coats
or 12.08-13.94 sq.m/L for 2 coats****

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

1600+*

#Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.

FINISH

MATT



DIRECTIONS FOR USE

Recommended usage - On fresh or repainted masonry walls

PRE PAINTING STEPS



1. Plaster

New masonry surfaces must be allowed to cure completely for 28 days ensuring they are water cured on daily basis.



3. Filling of Cracks

To address cracks measuring up to 5mm, use Birla Opus crack fill solutions. For larger cracks, it is recommended to audit it with a structural engineer and get it repaired before painting.



2. Cleaning

Surface should be free from any loose paint dust, or grease. Growth of fungus, algae or moss should be removed by wire brushing and water. When the underlying surface exhibits chalkiness, please use water curing for some time and then apply a layer of Birla Opus Penetrating primer before proceeding to painting steps.



4. Covering of holes and dents

In case of holes and dents use cement Putty or a mix of white cement and fine sand in the ratio 1:3.

Special Instructions for Interior:

For interior surfaces or substrates that are subjected to continuous seepage or dampness, please check the source of leakage or seepage and ensure the same is rectified before application.



PAINTS

PAINTING STEPS



1. Primer Application

For both freshly plastered or repainting surface, apply one coat Birla Opus Prime 110 Interior Water Thinnable wall primer/ equivalent Birla White interior primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



2. Putty Application

Smoothen the surface by filling dents and undulations with thin coat of Birla Opus One Acrylic putty/ equivalent Birla White putty. Allow it to dry for 4-6 hours. Apply two coats of putty for uniform wall. Apply third coat of putty if required. Sand with



3. Primer Application

Apply one coat of Birla Opus Prime 110 Interior Water Thinnable wall primer/ equivalent Birla White interior primer by thinning 1 litre of primer with 1 litre of water and allow it to dry for minimum 4 hours.



4. Topcoat Application

Dilute 1 litre of Birla Opus Prime 150 Emulsion Paint with 600-650 ml of water and apply 2-3 coats of topcoat to ensure good hiding. A gap of 4-6 hours to be given after each coat.

POST PAINTING CARE

1

Ensure dusting at regular intervals.

2

While cleaning, wipe gently without intense pressure.

3

Give 2 weeks of drying time post application of paint before wet wiping the wall.

PRECAUTIONS

- Do not apply when ambient temperature might drop to a level below 10°C within 4 hours of application.
- Do not apply when ambient temperature might increase to a level above 45°C within 4 hours of application.
- Do not apply if relative humidity is more than 90%.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- For surfaces having heavy fungal infestation, proper cleaning is mandated.
- Keep the material in closed condition when not in use.
- Diluted Primer should be used within 24 hours of dilution. Accordingly, it is recommended to thin down only the necessary amount of paint. Post 24 hours, thinned primer may be susceptible for microbial attack.
- Do not apply to wet or visibly damp surfaces.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Shelf Life	36 months from the date of manufacturing
Drying time	Surface dry time 30 minutes*
Recoating time	4-6 hours*
Shelf life of thinned paint	To be used within 24 hours

*May vary according to temperature & humidity

Version No. I50-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



PAINTS

ENAMELS





Product Code 921932

Enamels – N52

Premium Gloss Solvent Coating



Birla Opus Prime N52 Enamel Premium Gloss Solvent Coating is an IS 2932 compliant* synthetic enamel. It offers long-lasting gloss, making it an ideal choice for high-quality finishes.

PRODUCT FEATURES



IS 2932 COMPLIANT*

Adheres to the standards outlined by IS 2932.



OUTSTANDING GLOSS

Unmatched brilliance in gloss, providing a flawless finish that leaves a lasting impression.



EXCELLENT OPACITY

Ensures a flawless finish with fewer coats due to its excellent paint opacity.



ALKALI RESISTANT

Protects gloss against alkaline attacks.



EASY BRUSHABILITY

Effortless application which ensures smooth consistency and seamless coverage with every stroke.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller:

90–100 sq. ft/L for 2 coats.

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOUR AVAILABLE

7# Factory Made Shades



#Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.*

FINISH



DIRECTION FOR USE

PRE PAINTING STEPS / SURFACE PREPARATION



Metals

De-grease with suitable solvent (if required). Sand with emery paper no. 180 to remove rust and loose particles. Wipe clean.



Wood

Sand along the grains with emery paper no. 320 to make the surface smooth and uniform. Wipe clean.



Masonry

Remove loose paint, dust/dirt particles and sand with emery paper no. 180. Wipe clean.



PAINTING STEPS

1. Primer Application

Metals

Apply Birla Opus Calista Sparkle RO Primer by brushing as per the recommended application process. Ensure 6–8 hours of drying time. Sand the primer coat with emery paper no. 180. Wipe Clean.

Wood

Apply Birla Opus Calista Sparkle Wood primer – White/Pink as per the recommended application process. Ensure 10–12 hours of drying time. Sand the primer coat with emery paper no. 320. Wipe Clean.

Masonry

Apply Birla Opus Prime N10 Solvent Thinnable Wall Primer as per the recommended application process. Ensure 6–8 hours of drying time. Sand the primer coat with emery paper no. 180. Wipe Clean.

2. Filling of Cracks / Undulations

Metals: Use Birla Opus Knifing Paste Filler to fill undulations on metal substrates.

Wood and Masonry: Use Birla Opus One Acrylic Wall Putty to fill undulations of wooden / masonry surfaces. Ensure 4–6 hours of drying time and sand with emery paper no. 180, followed by emery paper no. 320.

After filling of crack / undulations as above, apply another coat of metal / wood primer / wall primer. Allow it to dry completely.

3. Application of Topcoat

Dilute 1 litre of Birla Opus Prime N52 Enamel Premium Gloss Solvent Coating with 80–100ml of Mineral Turpentine Oil and apply two coats by brushing. Allow 10–12 hours of drying between coats. For spray application, dilute 1 litre of Birla Opus Prime N52 Enamel Premium Gloss Solvent Coating with 150–200ml of Mineral Turpentine Oil.

PRECAUTIONS

- Do not apply at relative humidity greater than 85%.
- Do not apply when ambient temperature is less than 10°C or above 40°C.
- For surfaces having heavy algal infestation, cleaning with bleaching solution is advised.
- Keep the material in closed condition when not in use.
- Ensure adequate ventilation under all application conditions.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- Highly flammable product, do not store the products near electrical installations and flammable sources.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Drying Time	Max 4 hours surface dry*
Drying time	Max 12 hours hard dry*
Drying Time	Max 24 hours tack free*
Gloss Level	Min 80 on 60° GH
Flash Point IS 101 / Part 1 Sec 6	More than 30 °C
Stability of thinned paint	To be used within 24 hours
Shelf Life	36 months

*May vary according to temperature & humidity

Version No. N52-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved





Product Code 921933
Enamels – N53
Premium Gloss Solvent Coating



Birla Opus Prime N53 Enamel Premium Gloss Solvent Coating is an IS 2933 compliant* synthetic enamel, delivering enduring brilliance and excellent opacity for a flawless, vibrant finish.

PRODUCT FEATURES



IS 2933 COMPLIANT*

Adheres to the standards outlined by IS 2933.



EXCELLENT GLOSS

Unmatched brilliance in gloss for flawless finish that leaves a lasting impression.



EXCELLENT OPACITY

Ensures a flawless finish with fewer coats due to its excellent paint opacity.



ALKALI RESISTANT

Protects gloss against alkaline attacks.



EASE OF APPLICATION

Effortless application which ensures smooth consistency and seamless coverage with every stroke.

PRODUCT DETAILS

AVAILABLE PACKS



COVERAGE

Only on the correctly prepared surface using brush and roller for –

90–100 sq. ft/L for 2 coats**
or 8.36–9.29 sq.m/L for 2 coats**

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOUR AVAILABLE

6 # Factory
Made Shades



#Shades may vary depending on the wall and light conditions. Please consult your nearest authorized dealer to confirm on the shade availability.*

FINISH



DIRECTIONS FOR USE

PRE PAINTING STEPS / SURFACE PREPARATION



Metals

De-grease with suitable solvent (if required). Sand with emery paper no. 180 to remove rust and loose particles. Wipe clean.



Wood

Sand along the grains with emery paper no. 320 to make the surface smooth and uniform. Wipe clean.



Masonry

Remove loose paint, dust/dirt particles and sand with emery paper no. 180. Wipe clean.



PAINTING STEPS

1. Primer Application

Metals

Apply Birla Opus Calista Sparkle RO Primer by brushing as per the recommended application process. Ensure 6–8 hours of drying time. Sand the primer coat with emery paper no. 180. Wipe Clean.

Wood

Apply Birla Opus Calista Sparkle Wood primer – White/Pink as per the recommended application process. Ensure 10–12 hours of drying time. Sand the primer coat with emery paper no. 320. Wipe Clean.

Masonry

Apply Birla Opus Prime N10 Solvent Thinnable Wall Primer as per the recommended application process. Ensure 6–8 hours of drying time. Sand the primer coat with emery paper no. 180. Wipe Clean.

2. Filling of Cracks / Undulations

Metals: Use Birla Opus Knifing Paste Filler to fill undulations on metal substrates.
Wood and Masonry: Use Birla Opus Acrylic Wall Putty to fill undulations of wooden / masonry surfaces. Ensure 4–6 hours of drying time and sand with emery paper no. 180, followed by no. 320. After filling of crack / undulations as above, apply another coat of metal / wood primer / wall primer. Allow it to dry completely.

3. Application of Topcoat

Dilute 1 litre of Birla Opus Prime N53 Enamel Premium Gloss Solvent Coating with 80–100ml of Mineral Turpentine Oil and apply two coats by brushing. Allow 16–18 hours of drying between coats. For spray application, dilute 1 litre of Birla Opus Prime N53 Enamel Premium Gloss Solvent Coating with 150–200ml of Mineral Turpentine Oil.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C.
- Do not apply at relative humidity greater than 85%.
- For surfaces having heavy algal infestation, cleaning with bleaching solution is advised.
- Keep the material closed when not in use.
- Ensure adequate ventilation under all application conditions.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- Highly flammable product, do not store the products near electrical installations and flammable sources.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL DATA

Drying Time	Max 8 hours surface dry*
Drying time	Max 18 hours hard dry*
Drying Time	Max 24 hours tack free*
Gloss Level	Min 80 on 60° GH
Flash Point IS 101 / Part 1 Sec 6	More than 30 °C
Stability of thinned paint	To be used within 24 hours
Shelf Life	36 months

*May vary according to temperature & humidity

Version No. N53-1003/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved



WATERPROOFING



B30



B70

BIRLA
opus
PRIME



B90



C2K



C2K+



Product Code 918130

WATERPROOFING – B30

Waterproof Coating

Birla Opus Prime B30 Waterproof Coating is an acrylic waterproof coating designed for application on both horizontal and vertical walls. It provides excellent crack-bridging and water-resistant properties, reinforcing the protection of exterior surfaces.



PRODUCT FEATURES



HYDROSTATIC PRESSURE

Safeguards against positive hydrostatic pressure of up to **5 Bar***.



EXCELLENT CRACK BRIDGING ABILITY

Highly elastomeric coating provides crack bridging of upto 1 mm on horizontal surfaces and upto 0.5mm on vertical surfaces*.



EXCELLENT ADHESION

Forms a robust bond between the coating film and the substrate enhancing longevity, stability, and overall performance.



EXCELLENT FLEXIBILITY

Offers elongation upto 170% on horizontal surfaces and upto 100% on vertical surfaces* preventing cracks.



WARRANTY*

Up to 5-year waterproofing system warranty on horizontal and vertical applications.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COLOURS AVAILABLE

WHITE

SHELF LIFE



36 months from the date of manufacture

DIRECTIONS FOR USE

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Birla Opus Alldry Salt Seal prior to the topcoat application.



3. Crack filling

To fill cracks up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. Bigger cracks, damaged or hollow portions, etc. must be repaired with a polymer-modified mortar.



4. Covering of holes and dents

For addressing small dents and holes, utilise cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exterior

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.

*Based on lab tests





PAINTING APPLICATION PROCESS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2. Waterproof Coating Application

Dilute 1 litre of B30 Exterior Waterproof Coating with 100-120 ml of water and apply one coat. Allow it to dry for 4-6 hours. Apply another coat of undiluted B30 Exterior Waterproof Coating and dry for 4-6 hours.



3. Topcoat Application

Horizontal Surfaces: Apply additional coat of undiluted B30 Waterproof Coating in perpendicular direction. Allow it to dry for 4-6 hours.

Vertical Surfaces: Apply Texture (optional) and 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat.

POST PAINTING CARE

1

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

2

Thoroughly clean horizontal surfaces to enhance durability.

3

Ensure there is no stagnant water at any point on any surface.

PRECAUTIONS

- Ensure DFT of 110-120 microns for vertical surfaces and 300-330 microns for horizontal surfaces
- For extremely rough surfaces: Application by brush is recommended to ensure all the grooves are covered well.
- Coating will not cover existing cracks, proper care to be taken to ensure the cracks are filled first and then coating is applied.
- The surface should be in Surface Saturated Dry (SSD) before application of coating.
- Do not apply when the ambient temperature is less than 10°C or above 45°C or if the temperature might drop to this level within 4 hours of application.
- For surfaces with heavy algal infestation, proper cleaning is mandated. If a bleaching solution is used to disinfect the algae, ensure proper cleaning of the bleaching solution with water.

TECHNICAL INFORMATION

Appearance	Viscous liquid
Color	White
% Elongation	Upto 170% on horizontal surfaces and upto 100% on vertical surfaces
Tensile Strength	Upto 2.5mpa
Resistance to Positive hydrostatic pressure	Up to 5 bar passes pressure
Specific Gravity	1.3 +- 0.04 g/cc
Solids by wt. %	54-60

SAFETY ASPECTS

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

Version No. B30-1002/05/2024

For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved





Product Code 918170

WATERPROOFING - B70

Luxury Waterproof Coating

Birla Opus Prime B70 Luxury Waterproof Coating is an elastomeric coating that provides excellent waterproofing properties, high durability, and resistance to water penetration for wall & terrace surfaces. The elastic cross-linking mechanism of the polymer along with the acrylic fibres gives additional reinforcement to the film.

BIRLA
opus
PRIME

BIRLA
opus
PRIME

PRODUCT FEATURES



HYDROSTATIC PRESSURE

Shields against positive hydrostatic pressure of up to **10 Bar*** thus preventing water penetration into the film.



EXCEPTIONAL CRACK BRIDGING ABILITY

Highly elastomeric coating provides crack bridging of up to 2 mm*.



SURFACE TEMPERATURE REDUCTION

Provides excellent surface temperature reduction up to **10° C***.



ANTI-CARBONATION

Coating acts as an effective barrier against carbon dioxide thus protecting the rebars against corrosion.



WARRANTY*

11 years warranty on vertical applications and 10 years warranty on horizontal applications*.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COLOURS AVAILABLE

WHITE

SHELF LIFE



36 months
from the date
of manufacture

DIRECTIONS FOR USE

Recommended usage – To be applied on RCC or plaster using brush or roller. It can be used on building roofs, terraces, parapet, sunshades and exterior vertical walls. It can be also be applied on IPS, sound brick bat coba or cementitious waterproofing.

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



3. Crack filling

To fill cracks up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. Bigger cracks, damaged or hollow portions, etc. must be repaired with a polymer-modified mortar.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Birla Opus AllDry Salt Seal prior to the topcoat application.



4. Covering of holes and dents

For addressing small dents and holes, utilize cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exterior:

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.

*Based on lab tests



PAINTING APPLICATION PROCESS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2. Waterproof Coating Application

Dilute 1 litre of B70 Exterior Waterproof Coating with 300-350 ml of water and apply one coat. Allow it to dry for 4-6 hours. Apply another coat of undiluted B70 Exterior Waterproof Coating and dry for 4-6 hours.



3. Topcoat Application

Horizontal Surfaces: Apply additional coat of undiluted B70 Waterproof Coating in perpendicular direction. Allow it to dry for 4-6 hours.

Vertical Surfaces: Apply Texture (optional) and 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat.

POST PAINTING CARE

1

Conduct ponding test by filling water up to 5 cm height for 24 hours post 7 days air curing to ensure leak-free terrace.

2

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

3

Thoroughly clean horizontal surfaces to enhance durability.

4

Ensure there is no stagnant water at any point on any surface.

SAFETY ASPECTS

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution: Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Appearance	Viscous liquid
Color	White
Anti Carbonation, R Value (EN 1062 Part6:2002- Method A)	460
Tensile Strength	Upto 2.7 mpa
Crack Bridging Ability	Up to 2 mm
Solar reflectance index*	Greater than 100
% Elongation	Up to 250
Resistance to Positive hydrostatic pressure	Passes up to 10 bar
Specific Gravity	1.24 +- 0.04 g/cc
Solids by wt, %	54-60

*Surface temperature reduction: Temperature recorded from 1 pm to 3 pm with the help of IR gun. Degree of surface temperature reduction will vary depending upon the surface & weather conditions.

PRECAUTIONS

- Ensure DFT of 160-180 microns for vertical surfaces and 500-550 microns for horizontal surfaces
- Ensure end to end application on parapet walls along with terrace and inside drainage pipes upto 6 inches.
- Glass fibre mesh (45 gsm) is recommended at areas with high movements or irregular substrate or to bridge cracks, joints and seams on the substrate. It must be sandwiched between 1st and 2nd coat and placed on surface when 1st coat is still wet.
- Do not apply when ambient temperature is less than 10°C or above 45°C.
- Do not apply on wet or visibly damp surfaces or when humidity > 80%.
- Do not apply if rain is expected within 48 hours from the day of application.
- For surfaces having heavy algal infestation, cleaning with bleaching solution is advised.
- Ensure that the terrace surface has adequate slope to avoid water accumulation.
- All corners, gaps, joints, repair areas and outlets shall be coated with extra coat.
- The surface should be in Surface Saturated Dry (SSD) before application of coating.
- The product is designed only for foot traffic and not vehicular or movement of machinery or equipment.

Version No. B70-1002/05/2024

For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved





Product Code 918190

WATERPROOFING – B90

Ultra Luxury Waterproof Coating

Birla Opus Prime B90 Ultra Luxury Waterproof Coating is a specialized waterproofing formulation comprising of tough acrylic and PU hybrid polymers. The incorporation of a unique elastomeric structure, combined with acrylic fibres, enhances the film's strength and provides cooler exterior surfaces.



PRODUCT FEATURES



HYDROSTATIC PRESSURE

Protects against positive hydrostatic pressure of upto **12 Bar*** thus preventing infiltration of water into the film.



OUTSTANDING CRACK BRIDGING ABILITY

Highly elastomeric PU hybrid polymer provides crack-bridging of upto **3 mm***.



SURFACE TEMPERATURE REDUCTION

Provides outstanding surface temperature reduction upto **12°C***.



ANTI-CARBONATION

Coating serves as a robust barrier against carbon dioxide thereby safeguarding the rebars from corrosion.



WARRANTY*

14 years warranty on vertical applications and 12 years warranty on horizontal applications*.

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS



COLOURS AVAILABLE

WHITE

SHELF LIFE



36 months from the date of manufacture

DIRECTIONS FOR USE

Recommended usage – To be applied on RCC or plaster using brush or roller. It can be used on building roofs, terraces, parapet, sunshades and exterior vertical walls. It can be also be applied on IPS, sound brick bat coba or cementitious waterproofing.

PRE PAINTING STEPS



1. Plaster

It is essential to let new masonry surfaces fully cure. The suggested curing duration is 28 days, during which daily water curing is recommended for optimal results.



3. Crack filling

To fill cracks up to 5mm in width and 3mm in depth, use Birla Opus crack fill solutions. Bigger cracks, damaged or hollow portions, etc. must be repaired with a polymer-modified mortar.



2. Cleaning

Ensure the surface is devoid of loose paint, dust, or grease. Eliminate any fungus, algae, or moss growth through wire brushing and water. In case of chalkiness on the underlying surface, perform water curing and subsequently apply a coat of Birla Opus AllDry Salt Seal prior to the topcoat application.



4. Covering of holes and dents

For addressing small dents and holes, utilize cement wall putty or a blend of white cement and fine sand in a 1:3 ratio.

Special Instructions for Exterior:

If exterior surfaces face persistent seepage or dampness, investigate and arrest the source of leakage or seepage, let the surface dry and then apply Birla Opus Prime waterproof coatings. Ensure we provide slope to horizontal surfaces and proper drain to avoid any stagnant water accumulation.

*Based on lab tests



PAINTS

PAINTING APPLICATION PROCESS



1. Surface Preparation

Newly plastered surfaces must undergo complete curing. Ensure thorough filling of any spot with putty, crack filler, etc. and achieve a uniform surface across the entire wall.



2. Waterproof Coating Application

Dilute 1 litre of B90 Exterior Waterproof Coating with 300-350 ml of water and apply one coat. Allow it to dry for 4-6 hours. Apply another coat of undiluted B90 Exterior Waterproof Coating and dry for 4-6 hours.



3. Topcoat Application

Horizontal Surfaces: Apply additional coat of undiluted B90 Waterproof Coating in perpendicular direction. Allow it to dry for 4-6 hours.

Vertical Surfaces: Apply Texture (optional) and 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat.

POST PAINTING CARE

1

Conduct ponding test by filling water up to 5 cm height for 24 hours post 7 days air curing to ensure leak-free terrace.

2

For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months.

3

Thoroughly clean horizontal surfaces to enhance durability.

4

Ensure there is no stagnant water at any point on any surface.

SAFETY ASPECTS

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution: Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Appearance	Viscous liquid
Color	White
Tensile strength	Upto 3.2 mpa
Crack Bridging Ability	Upto 3 mm
Solar reflectance index*	Greater than 100
% Elongation	Upto 300
Resistance to Positive hydrostatic pressure	Passes up to 12 bar
Specific Gravity	1.15 +/- 0.04 g/cc
Solids by wt, %	50-56

*Surface temperature reduction: Temperature recorded from 1 pm to 3 pm with the help of IR gun. Degree of surface temperature reduction will vary depending upon the surface & weather conditions.

PRECAUTIONS

- Ensure DFT of 160-180 microns for vertical surfaces and 500-550 microns for horizontal surfaces
- Ensure end to end application on parapet walls along with terrace and inside drainage pipes upto 6 inches.
- Glass fibre mesh (45 gsm) is recommended at areas with high movements or irregular substrate or to bridge cracks, joints and seams on the substrate. It must be sandwiched between 1st and 2nd coat and placed on surface when 1st coat is still wet.
- Do not apply when ambient temperature is less than 10°C or above 45°C.
- Do not apply on wet or visibly damp surfaces or when humidity > 80%.
- Do not apply if rain is expected within 48 hours from the day of application.
- For surfaces having heavy algal infestation, cleaning with bleaching solution is advised.
- Ensure that the terrace surface has adequate slope to avoid water accumulation.
- All corners, gaps, joints, repair areas and outlets shall be coated with extra coat.
- The surface should be in Surface Saturated Dry (SSD) before application of coating.
- The product is designed only for foot traffic and not vehicular or movement of machinery or equipment.

Version No. B90-1002/05/2024

For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content - all rights reserved



PAINTS



WATERPROOFING – C2K

Cementitious 2K Coating

Birla Opus Prime C2K is a two-component acrylic cementitious, polymer modified elastomeric waterproof coating. It is composed of cement with properly graded sand and selected additives as one part & an acrylic emulsion as a binder in its second part. It is applied for protection & waterproofing of concrete and masonry substrates.

PRODUCT FEATURES



POTABLE WATER SAFE*

Product conforms to overall migration test specifications as per USFDA-175.300 conducted by CFTRI for intended use for contact with potable water.



ANTI-EFFLORESCENCE

Mitigates the salt formation on the surface maintaining the integrity and overall finish.



CRACK BRIDGING ABILITY

Highly elastomeric coating provides crack bridging of up to 1.2 mm.



WARRANTY*

Up to 7 years waterproofing warranty*

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS

15kg



COVERAGE

Estimated forced coverage:

7 – 8 sq.ft/kg for 2 coats**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

GREY

SHELF LIFE



12 months from the date of manufacture

AREAS OF APPLICATION



Old & New Concrete, Plaster & Masonry surfaces



Wet Areas – Bathrooms, Kitchens, Balconies



RCC roofs, Small terraces, chhajjas & sinks



Concrete Water Tanks

SURFACE PREPARATION



1. The surface under treatment must be strong and cleaned thoroughly for any loose particles or laitance etc. before application. Oil or grease on the surface must be removed by suitable degreasing agent and then washed out with jet water (about 160 bar water pressure). Any plumbing or sanitation work must be completed before taking up the application.



3. Any minor cracks must be filled with Birla Opus AllDry Crack Master Paste. For larger cracks or repairs, use Birla Opus repair solutions.



2. Any previously applied putty or POP must be removed before application. The surface must be cleaned to expose the plaster surface for application.



4. In case of efflorescence or loose plaster, expose the surface up to the brick level. Use Birla Opus AllDry Repair Master with mortar for replastering the surface.

ANGLE FILLET/CORNER TREATMENT

- Moisten the RCC surface, apply a 1:1 bonding coat of Birla Opus AllDry Repair Master and Cement.
- Create a 50x50 mm angle fillet using PMM (1:5:15 ratio) with Birla Opus AllDry Repair Master, fresh cement, and graded quartz sand. Moist cure for 3–4 days.
- Apply a coat of Birla Opus Prime C2K followed by laying of 45 GSM glass fiber over angle fillet when the coating is still wet. Then apply the second coat to fully embed the glass fiber mesh, ensuring it's free from creases and air pockets.

PIPE OUTLET/BORE PACKING TREATMENT

- Ensure gaps around PVC, GI pipes are packed with Birla Opus AllDry Repair Master.
- Fill the gap around the pipe penetration points with non-shrink grout. Apply a coat of Birla Opus Prime C2K waterproofing coating around the pipe penetration point. Ensure no gaps are left uncoated.

MIXING & APPLICATION

- Birla Opus Prime C2K liquid component must be shaken thoroughly before mixing.
- In a mixing vessel, slowly add the powder component into the liquid (1 part liquid : 2 part powder) with continuous stirring. In case of bulk volume, use mechanical mixer. Continue to stir until a homogenous, lump free mix is achieved. Allow the mix to stand for 3 – 5 mins to release entrapped air during mixing.
- Apply 1st coat of the mixed slurry using brush on SSD (saturated surface dry) surface. Make sure that the application is done correctly in areas where the surface shows minor abnormalities or undulations. Add an extra 1–2 feet of mixed slurry to all sides of the affected area.
- After 4 – 6 hours, apply 2nd coat in the direction perpendicular to the 1st coat.
- Leave the coating to air cure for 2 – 3 days. Then apply plaster or screed.
- Prepare 1:3 Screed mixture (50 kg of cement to be mixed 150 kg sand). Screed thickness should be a minimum of 15 mm to 30 mm. It needs 48 hrs of air curing followed by minimum 4 days of water curing.
- Apply 2 coats of Product on all over shower area. Sprinkle coarse quartz sand while second coat is still wet. This will provide better adhesion for subsequent tile adhesive materials.

SAFETY ASPECTS

- Kindly refer to the MSDS for Birla Opus Prime C2K which gives detailed information on safety measures.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with as mentioned above in "Mixing & Application" steps.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and as mentioned above in "Mixing & Application" steps.
- No added Lead, Mercury or Chromium compounds.

PRECAUTIONS & LIMITATIONS

- Always add powder to liquid. Do not add water into the mixture.
- In case of patch application, extend the application atleast 2 feet beyond the affected area to cover the surrounding regions effectively.
- Do not conduct ponding test till the coating is cured for 7 days.
- Ensure that the freshly plastered surface or new masonry surface is completely cured for at least 28 days. In case of replastering, plaster must be cured for at least 7 days.
- Application is not to be done in rainy/high humid (> 80% relative humidity) season or in extreme cold temperatures (less than 10°C) or if the temperature might drop to this level within 4 hours of application.
- Mixed product should be used within 4 hours of dilution. It is recommended to mix only the necessary amount and consume it fully.
- Ensure that terrace surface has adequate slope to avoid water accumulation.
- All corners, gaps, joints, roof leak repair area and outlets shall be coated with extra coat.
- Keep the material closed when not in use.
- The Product when applied on horizontal exterior surfaces need to be covered with screed, as mentioned above in "Mixing & Application" steps.

TECHNICAL INFORMATION

Properties	Observations / Results	Specification
Mixing ratio (Liquid : Powder)	1:2	---
Surface dry time	40 – 50 mins	ASTM C 1640
Recoat time	4 – 6 hours	ASTM C 1640
Pot Life@27°C	Min 45 mins	---
Dry Film Thickness	1 mm	ASTM D 1005
% Elongation at break	up to 100	ASTM D 2370
Tensile strength	0.9 N/mm ²	ASTM D 2370
Positive Hydrostatic Pressure	up to 5 bar	EN12390-8
Negative Hydrostatic Pressure	up to 4 bar	ASTM D 7088
Crack Bridging ability	Upto 1.2 mm	EN 1062-7(A)
Pull off adhesion strength	Upto 1 mpa	ASTM D 7234
Food grade certification	POTABLE WATER SAFE*	(As per US FDA – 175.300)



WATERPROOFING – C2K+

Premium Cementitious 2K Coating

Birla Opus Prime C2K+ is a two-component high performance acrylic cementitious, polymer modified elastomeric, waterproofing & protective coating. It is composed of high quality cement with properly graded sand, selected additives as one part & an acrylic emulsion as a binder in its second part. It is applied for protection & waterproofing of water retaining structures like swimming pools etc. It has strong bonding to the substrate & excellent resistance to hydrostatic pressure.

PRODUCT FEATURES



POTABLE WATER SAFE*

Product conforms to overall migration test specifications as per USFDA-175.300 conducted by CFTRI for intended use for contact with potable water.



EXCELLENT ELONGATION

Offers elongation up to 200% for vertical surfaces preventing cracks.



EXCEPTIONAL CRACK BRIDGING ABILITY

Highly elastomeric coating provides crack bridging of up to 2mm.



WARRANTY*

Up to 10 years waterproofing warranty*

*T&C apply. For more details, please refer to the product warranty document.

PRODUCT DETAILS

AVAILABLE PACKS

12kg



COVERAGE

Estimated forced coverage:

5.4 – 6.4 sq.ft/kg for 2 coats**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

GREY

SHELF LIFE



12 months from the date of manufacture

AREAS OF APPLICATION



Old & New Concrete, Plaster & Masonry surfaces that is subjected to damage due to moisture.



Sunken Areas – Swimming pools, reservoirs, water Tanks.



RCC Roof, Terraces, Lift pits & Basement walls.



Wet Areas – Toilets, Bathrooms & Balconies

SURFACE PREPARATION



1. The surface under treatment must be strong and cleaned thoroughly for any loose particles or laitance etc. before application. Oil or grease on the surface must be removed by suitable degreasing agent and then washed out with jet water (about 160 bar water pressure). Any plumbing or sanitation work must be completed before taking up the application.



2. Any previously applied putty or POP must be removed before application. The surface must be cleaned to expose the plaster surface for application.



3. Any minor cracks must be filled with Birla Opus AllDry Crack Master Paste. For larger cracks or repairs, use Birla Opus repair solutions.



4. In case of efflorescence or loose plaster, expose the surface up to the brick level. Use Birla Opus AllDry Repair Master with mortar for replastering the surface.

ANGLE FILLET/CORNER TREATMENT

- Moisten the RCC surface, apply a 1:1 bonding coat of Birla Opus AllDry Repair Master and Cement.
- Create a 50x50 mm angle fillet using PMM (1:5:15 ratio) with Birla Opus AllDry Repair Master, fresh cement, and graded quartz sand. Moist cure for 3–4 days.
- Apply a coat of Birla Opus Prime C2K+ followed by laying of 45 GSM glass fiber over angle fillet when the coating is still wet. Then apply the second coat to fully embed the glass fiber mesh, ensuring it's free from creases and air pockets.

PIPE OUTLET/BORE PACKING TREATMENT

- Ensure gaps around PVC, GI pipes are packed with Birla Opus AllDry Repair Master.
- Fill the gap around the pipe penetration points with non-shrink grout. Apply a coat of Birla Opus Prime C2K+ waterproofing coating around the pipe penetration point. Ensure no gaps are left uncoated.

MIXING & APPLICATION

- Birla Opus Prime C2K+ liquid component must be shaken thoroughly before mixing.
- In a mixing vessel, slowly add the powder component into the liquid (40 parts Liquid : 60 parts Powder)) with continuous stirring. In case of bulk volume, use mechanical mixer. Continue to stir until a homogenous, lump free mix is achieved. Allow the mix to stand for 3 – 5 mins to release entrapped air during mixing.
- Apply 1st coat of the mixed slurry using brush on SSD (saturated surface dry) surface. Make sure that the application is done correctly in areas where the surface shows minor abnormalities or undulations. Add an extra 1-2 feet of mixed slurry to all sides of the affected area.
- After 4 – 6 hours, apply 2nd coat in the direction perpendicular to the 1st coat.
- Leave the coating to air cure for 2 – 3 days. Then apply plaster or screed.
- Prepare 1:3 Screed mixture (50 kg of cement to be mixed 150 kg sand). Screed thickness should be a minimum of 15 mm to 30 mm. It needs 48 hrs of air curing followed by minimum 4 days of water curing.
- Apply 2 coats of Product on all over shower area. Sprinkle coarse quartz sand while second coat is still wet. This will provide better adhesion for subsequent tile adhesive materials.

SAFETY ASPECTS

- Kindly refer to the MSDS for Birla Opus Prime C2K+ which gives detailed information on safety measures.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with as mentioned above in "Mixing & Application" steps.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and as mentioned above in "Mixing & Application" steps.
- No added Lead, Mercury or Chromium compounds.

PRECAUTIONS & LIMITATIONS

- Always add powder to liquid. Do not add water into the mixture.
- Do not conduct ponding test till the coating is cured for 7 days.
- Ensure that the freshly plastered surface or new masonry surface is completely cured for at least 28 days. In case of replastering, plaster must be cured for at least 7 days
- Application is not to be done in rainy/high humid (> 80% relative humidity) season or in extreme cold temperatures (less than 10°C) or if the temperature might drop to this level within 4 hours of application.
- Mixed product should be used within 4 hours of dilution. It is recommended to mix only the necessary amount and consume it fully.
- Ensure that terrace surface has adequate slope to avoid water accumulation.
- All corners, gaps, joints, roof leak repair area and outlets shall be coated with extra coat.
- Keep the material closed when not in use.
- The Product when applied on horizontal exterior surfaces need to be covered with screed. as mentioned above in "Mixing & Application" steps.

TECHNICAL INFORMATION

Properties	Observations / Results	Specification
Mixing ratio (Liquid : Powder)	60:40	---
Surface dry time	50 mins	ASTM C 1640
Recoat time	4 – 6 hours	ASTM C 1640
Pot Life@27°C	30–40 mins	---
Dry Film Thickness	1 mm	ASTM D 1005
% Elongation at break	up to 200	ASTM D 2370
Tensile strength	1.03 N/mm ²	ASTM D 2370
Positive Hydrostatic Pressure	up to 5 bar	EN12390–8
Negative Hydrostatic Pressure	up to 4 bar	ASTM D 7088
Crack Bridging ability	Upto 2 mm	EN 1062–7(A)
Pull off adhesion strength	Upto 1.2 mpa	ASTM D 7234
Food grade certification	POTABLE WATER SAFE*	(As per US FDA – 175.300)

EXTERIOR TEXTURES





Product Code: 916005

EXTERIOR TEXTURES – T15

Scratch Wall Finish 1.5mm

Birla Opus Prime T15 Exterior Scratch Wall Finish Texture is a 1.5mm water repellent texture with excellent plaster protection. It is designed to provide distinctive design patterns that elevate the aesthetics of exterior surfaces.

BIRLA
opus
PRIME

BIRLA
opus
PRIME

PRODUCT FEATURES



EXCELLENT WATER REPELLENCY

Ensuring that your exterior walls remain shielded from harsh climatic conditions due to its excellent water repellent property.



EXCELLENT PLASTER PROTECTION

Excellent protection to the structure by providing a barrier coat against climatic conditions.



OUTSTANDING NAIL HARDNESS PROPERTIES

Outstanding durability due to the hardness of the film preserving its beauty and integrity for years to come.

PRODUCT DETAILS

AVAILABLE PACKS



25kg

COVERAGE

Estimated Coverage

3.5-4 sq. ft/kg for 1 coat**
or 0.33-0.37 sq.m/kg for 1 coat**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

2000+*

(*When applied with Birla Opus Prime Exterior Emulsions)



SHELF LIFE



12 months
from the date
of manufacture

PATTERNS




DIRECTIONS FOR USE

APPLICATION TOOLS

Regular
Fiber Trowel



Putty
Blade



SURFACE PREPARATION



1. Clean and Dry Surface

Clean and dry the surface. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure, to ensure complete surface cleanup. On algal/fungal affected areas, post jet wash, ensure cleaning with 10% bleaching powder solution followed by thorough cleaning with potable water.



2. Cracks Filling

Fill cracks using Birla Opus crack fill solutions. Ensure that the painting surface is uniform.



PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C or if the temperature might drop to this level within 4 hours of application.
- To avoid water or dew condensation, the temperature of the substrate should be a minimum of 3° C above the dew point of the air temperature and relative humidity measured in the vicinity of the substrate.
- For best performance, ensure that the surface is dry. On the moisture meter it should be in the green zone (below 15). In case it is in the red zone, find out the source of the water and address it before painting.
- The pH of the wall must be below 12.
- Ensure no rain within 7 days of texture application. Incomplete drying may lead to softening of texture and debonding from the substrate.
- Dilution is up to 200 ml only for 25 Kg bag. Over-dilution of texture may lead to sagging of the texture.
- Do not apply on chalky / lime washed substrate / powdery substrate or when the wall is wet (except sprinkling during summer).
- Do not apply when humidity is greater than 80%. It may cause prolonged drying time of texture/paint and moisture condensation on the walls.
- For better performance, ensure the substrate is cured for 4 weeks under normal atmospheric conditions. (30°C; 50-60% RH) with continuous water curing.
- During summer, whenever the substrate temperature goes more than 45° C, a sprinkling of water on the substrate may be required before texture application for better ease of application. But ensure that no excess pouring of water on to the surface, which might lead to sagging of texture.
- A primer coat, texture, or only one coat of topcoat should not be kept exposed in monsoon. Complete application before monsoon to be ensured.
- Apply 2 coats of topcoat within 7-8 days of texture application.
- Mix the material in the bag before use.

PAINTING STEPS



01

Apply Birla Opus Prime Exterior Water Thinnable Primer/equivalent Birla White Primer or Exterior Waterproof Coating /equivalent Birla White waterproofing product as prescribed in the application guidelines.



02

Apply one coat of undiluted Birla Opus Prime Exterior T15 Scratch Texture with fiber trowel. Maintain uniform thickness of about 1.5 mm. If required, dilute 25 kg of texture with maximum of 200 ml of water to achieve a better consistency for application.



03

Ensure pattern creation completion prior to drying of the surface. Sprinkling of water on the texture film may be required to create patterns during summers.



04

Apply 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat

POST PAINTING CARE



For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months. Thoroughly clean horizontal surfaces to enhance durability. Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure. Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Drying time	Overnight
Flash point IS101/1987 Part 1, Sec 6	Water based
Stability of thinned paint	NA

Version No. T15-1001/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content - all rights reserved





Product Code: 916006

EXTERIOR TEXTURES – T20

Scratch Wall Finish 2mm

Birla Opus Prime T20 Exterior Scratch Wall Finish Texture is a 2.0mm water repellent texture offering prominent design patterns that enrich the looks of exterior surfaces. It also offers outstanding plaster protection properties.



PRODUCT FEATURES



EXCELLENT WATER REPELLENCY

Ensuring that your exterior walls remain shielded from harsh climatic conditions due to its excellent water repellent property.



EXCELLENT PLASTER PROTECTION

Excellent protection to the structure by providing a barrier coat against climatic conditions.



OUTSTANDING NAIL HARDNESS PROPERTIES

Outstanding durability due to the hardness of the film preserving its beauty and integrity for years to come.

PRODUCT DETAILS

AVAILABLE PACKS



25kg

COVERAGE

Estimated Coverage

2.5–3 sq. ft/kg for 1 coat**
or 0.23–0.28 sq.m/kg for 1 coat**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

2000+*

(*When applied with Birla Opus Prime Exterior Emulsions)



SHELF LIFE



12 months
from the date
of manufacture

PATTERNS




DIRECTIONS FOR USE

APPLICATION TOOLS

Regular
Fiber Trowel



Putty
Blade



SURFACE PREPARATION



1. Clean and Dry Surface

Clean and dry the surface. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure, to ensure complete surface cleanup. On algal/fungal affected areas, post jet wash, ensure cleaning with 10% bleaching powder solution followed by thorough cleaning with potable water.



2. Cracks Filling

Fill cracks using Birla Opus crack fill solutions. Ensure that the painting surface is uniform.



ADITYA BIRLA

PAINTS



PAINTING STEPS



01

Apply Birla Opus Prime Exterior Water Thinnable Primer/ equivalent Birla White Primer or Exterior Waterproof Coating /equivalent Birla White waterproofing product as prescribed in the application guidelines.



02

Apply one coat of undiluted Birla Opus Prime Exterior T20 Scratch Texture with fiber trowel. Maintain uniform thickness of about 2 mm. If required, dilute 25 kg of texture with a maximum of 200 ml of water to achieve a better consistency for application.



03

Ensure pattern creation completion prior to drying of the surface. Sprinkling of water on the texture film may be required to create patterns during summers.



04

Apply 2–3 coats of Birla Opus Prime Exterior topcoat with a gap of 4–6 hours after each coat

POST PAINTING CARE



For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months. Thoroughly clean horizontal surfaces to enhance durability. Ensure there is no stagnant water at any point on any surface.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C or if the temperature might drop to this level within 4 hours of application.
- To avoid water or dew condensation, the temperature of the substrate should be a minimum of 3° C above the dew point of the air temperature and relative humidity measured in the vicinity of the substrate.
- For best performance, ensure that the surface is dry. On the moisture meter it should be in the green zone (below 15). In case it is in the red zone, find out the source of the water and address it before painting.
- The pH of the wall must be below 12.
- Ensure no rain within 7 days of texture application. Incomplete drying may lead to softening of texture and debonding from the substrate.
- Dilute the material up to 200 ml for 25 Kg bag, only when it is necessary to get better consistency.
- Do not apply on chalky / lime washed substrate / powdery substrate or when the wall is wet (except sprinkling during summer).
- Do not apply when humidity is greater than 80%. It may cause prolonged drying time of texture/paint and moisture condensation on the walls.
- For better performance, ensure the substrate is cured for 4 weeks under normal atmospheric conditions(30°C; 50–60% RH) with continuous water curing.
- During summer, whenever the substrate temperature goes more than 45° C, sprinkling of water on the substrate may be required before texture application for better ease of application. But ensure no excess pouring of water on to the surface, which might lead to sagging of texture.
- A primer coat, texture, or only one coat of topcoat should not be kept exposed in monsoon. Complete application before monsoon to be ensured.
- Apply 2 coats of topcoat within 7–8 days of texture application.
- Mix the material in the bag before use.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Drying time	Overnight
Flash point IS101/1987 Part 1, Sec 6	Water based
Stability of thinned paint	NA

Version No. T20-1001/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved



ADITYA BIRLA

PAINTS



Product Code: 916009

EXTERIOR TEXTURES – T30

Scratch Wall Finish 3mm

Birla Opus Prime T30 Exterior Scratch Wall Finish Texture is a 3mm water repellent texture specially designed to add essence to the aesthetics of exterior surfaces. It also offers best-in-class plaster protection.

BIRLA
opus
PRIME

PRODUCT FEATURES



EXCELLENT WATER REPELLENCY

Ensuring that your exterior walls remain shielded from harsh climatic conditions due to its excellent water repellent property.



EXCELLENT PLASTER PROTECTION

Excellent protection to the structure by providing a barrier coat against climatic conditions.



OUTSTANDING NAIL HARDNESS PROPERTIES

Outstanding durability due to the hardness of the film preserving its beauty and integrity for years to come.

PRODUCT DETAILS

AVAILABLE PACKS



25kg

COVERAGE

Estimated Coverage

1.8-2 sq. ft/kg for 1 coat**
or 0.17-0.19 sq.m/kg for 1 coat**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

2000+*

(*When applied with Birla Opus Prime Exterior Emulsions)



SHELF LIFE



12 months
from the date
of manufacture

PATTERNS




DIRECTIONS FOR USE

APPLICATION TOOLS

Regular
Fiber Trowel



Putty
Blade



SURFACE PREPARATION



1. Clean and dry the surface

Clean and dry the surface. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure, to ensure complete surface cleanup. On algal/fungal affected areas, post jet wash, ensure cleaning with 10% bleaching powder solution followed by thorough cleaning with potable water.



2. Cracks Filling

Fill cracks using Birla Opus crack fill solutions. Ensure that the painting surface is uniform.



BIRLA
opus
PRIME

PAINTING STEPS



01 Apply Birla Opus Prime - Exterior Water Thinnable Primer / equivalent Birla White Primer or Exterior Waterproof Coating / equivalent Birla White waterproofing products as prescribed in the application guidelines.



02 Apply one coat of undiluted Birla Opus Prime Exterior T30 Scratch Texture with fiber trowel. Maintain uniform thickness of about 3 mm. If required, dilute 25 kg of texture with a maximum of 200 ml of water to achieve a better consistency for application.



03 Ensure Pattern creation completion prior to drying of the surface. It may be required to sprinkle water on the Texture film to create patterns during summers.



04 Apply 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat.

POST PAINTING CARE



For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months. Thoroughly clean horizontal surfaces to enhance durability. Ensure there is no stagnant water at any point on any surface.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C or if the temperature might drop to this level within 4 hours of application.
- To avoid water or dew condensation, the temperature of the substrate should be a minimum of 3° C above the dew point of the air temperature and relative humidity measured in the vicinity of the substrate.
- For best performance, ensure that the surface is dry. On the moisture meter it should be in the green zone (below 15). In case it is in the red zone, find out the source of the water and address it before painting.
- The pH of the wall must be below 12.
- Ensure no rain within 7 days of texture application. Incomplete drying may lead to softening of texture and debonding from the substrate.
- Dilute the material up to 200 ml for 25 Kg bag, only when it is necessary to get better consistency.
- Do not apply on chalky / lime washed substrate / powdery substrate or when the wall is wet (except sprinkling during summer).
- Do not apply when humidity is greater than 80%. It may cause prolonged drying time of texture/paint and moisture condensation on the walls.
- For better performance, ensure the substrate is cured for 4 weeks under normal atmospheric conditions (30°C; 50-60% RH) with continuous water curing.
- During summer, whenever the substrate temperature goes more than 45° C, sprinkling of water on the substrate may be required before texture application for better ease of application. But ensure no excess pouring of water on to the surface, which might lead to sagging of texture.
- A primer coat, texture, or only one coat of topcoat should not be kept exposed in monsoon. Complete application before monsoon to be ensured.
- Apply 2 coats of topcoat within 7-8 days of texture application.
- Mix the material in the bag before use.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Drying time	Overnight
Flash point IS101/1987 Part 1, Sec 6	Water based
Stability of thinned paint	NA

Version No. T30-1001/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved





Product Code: 916007

EXTERIOR TEXTURES – TD3

Dholpur Wall Finish

Birla Opus Prime TD3 Exterior Dholpur Wall Finish Texture provides exceptional looks to the walls along with providing excellent plaster protection.



PRODUCT FEATURES



EXCELLENT WATER REPELLENCY

Ensuring that your exterior walls remain shielded from harsh climatic conditions due to its excellent water repellent property.



EXCELLENT PLASTER PROTECTION

Excellent protection to the structure by providing a barrier coat against climatic conditions.



OUTSTANDING NAIL HARDNESS PROPERTIES

Outstanding durability due to the hardness of the film preserving its beauty and integrity for years to come.

PRODUCT DETAILS

AVAILABLE PACKS



25kg

COVERAGE

Estimated Coverage

2-2.5 sq.ft/kg for 2 coats**
or 0.19-0.23 sq.m/kg for 2 coats**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

2000+*

(*When applied with Birla Opus Prime Exterior Emulsions)



SHELF LIFE



12 months
from the date
of manufacture

PATTERNS



Brick



Stone



Brushing
Effect


DIRECTIONS FOR USE

APPLICATION TOOLS

Stainless-Steel
or
Regular
Steel Trowel



Putty
Blade



SURFACE PREPARATION



1. Clean and dry the surface

Clean and dry the surface. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure, to ensure complete surface cleanup. On algal/fungal affected areas, post jet wash, ensure cleaning with 10% bleaching powder solution followed by thorough cleaning with potable water.



2. Cracks Filling

Fill cracks using Birla Opus crack fill solutions. Ensure that the painting surface is uniform.



ADITYA BIRLA
PAINTS

PAINTING STEPS



01

Apply Birla Opus Prime - Exterior Water Thinnable Primer/equivalent Birla White Primer or Exterior Waterproof Coating/equivalent Birla White waterproofing product as prescribed in the application guidelines



02

Apply one coat of Birla Opus Prime Exterior TD3 Dholpur Texture with a stainless-steel or a regular steel trowel. Maintain uniform thickness of upto 1 mm. Allow it to dry overnight in ambient conditions. If required, dilute 25 kg of texture with a maximum of 200 ml of water to achieve a better consistency for application.



03

After the first coat is dried, use masking tape (if applicable) to create the design template and then apply second coat as per the design requirement.



04

Ensure design creation completion prior to drying of the surface. Ensure masking tapes are removed immediately after the second coat application.



05

Allow the texture to dry overnight before top-coat application. Apply 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat.

POST PAINTING CARE



For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months. Thoroughly clean horizontal surfaces to enhance durability. Ensure there is no stagnant water at any point on any surface.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C or if the temperature might drop to this level within 4 hours of application.
- To avoid water or dew condensation, the temperature of the substrate should be a minimum of 3° C above the dew point of the air temperature and relative humidity measured in the vicinity of the substrate.
- For best performance, ensure that the surface is dry. On the moisture meter it should be in the green zone (below 15). In case it is in the red zone, find out the source of the water and address it before painting.
- The pH of the wall must be below 12.
- Ensure no rain within 7 days of texture application. Incomplete drying may lead to softening of texture and debonding from the substrate.
- Dilute the material up to 200 ml for 25 Kg bag, only when it is necessary to get better consistency.
- Do not apply on chalky / lime washed substrate / powdery substrate or when the wall is wet (except sprinkling during summer).
- Do not apply when humidity is greater than 80%. It may cause prolonged drying time of texture/paint and moisture condensation on the walls.
- For better performance, ensure the substrate is cured for 4 weeks under normal atmospheric conditions (30°C; 50-60% RH) with continuous water curing.
- During summer, whenever the substrate temperature goes more than 45° C, sprinkling of water on the substrate may be required before texture application for better ease of application. But ensure no excess pouring of water on to the surface, which might lead to sagging of texture.
- A primer coat, texture, or only one coat of topcoat should not be kept exposed in monsoon. Complete application before monsoon to be ensured.
- Apply 2 coats of topcoat within 7-8 days of texture application.
- Mix the material in the bag before use.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Drying time	Overnight
Flash point IS101/1987 Part 1, Sec 6	Water based
Stability of thinned paint	NA

Version No. TD3-1001/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



ADITYA BIRLA
PAINTS



Product Code: 916008

EXTERIOR TEXTURES – TR3

Roller Wall Finish

Birla Opus Prime TR3 Exterior Roller Wall Finish Texture offers exclusive patterns to provide outstanding looks to the exterior surfaces. It also protects the plaster from external weather conditions.



PRODUCT FEATURES



EXCELLENT WATER REPELLENCY

Ensuring that your exterior walls remain shielded from harsh climatic conditions due to its excellent water repellent property.



EXCELLENT PLASTER PROTECTION

Excellent protection to the structure by providing a barrier coat against climatic conditions.



OUTSTANDING NAIL HARDNESS PROPERTIES

Outstanding durability due to the hardness of the film preserving its beauty and integrity for years to come.

PRODUCT DETAILS

AVAILABLE PACKS



25kg

COVERAGE

Estimated Coverage

10–12 sq.ft/kg for 1 coat**
or 0.93–1.1 sq.m/kg for 1 coat**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

2000+*

(*When applied with Birla Opus Prime Exterior Emulsions)



SHELF LIFE



12 months
from the date
of manufacture

PATTERNS

- Cane Weave
- Honeycomb
- Diagonal
- Ripples
- Spring Time


DIRECTIONS FOR USE

APPLICATION TOOLS

Honeycomb
or
Embossed Roller



Putty
Blade



SURFACE PREPARATION



1. Clean and dry the surface

Clean and dry the surface. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure, to ensure complete surface cleanup. On algal/fungal affected areas, post jet wash, ensure cleaning with 10% bleaching powder solution followed by thorough cleaning with potable water.



2. Cracks Filling

Fill cracks using Birla Opus crack fill solutions. Ensure that the painting surface is uniform.



PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C or if the temperature might drop to this level within 4 hours of application.
- To avoid water or dew condensation, the temperature of the substrate should be a minimum of 3° C above the dew point of the air temperature and relative humidity measured in the vicinity of the substrate.
- For best performance, ensure that the surface is dry. On the moisture meter it should be in the green zone (below 15). In case it is in the red zone, find out the source of the water and address it before painting.
- The pH of the wall must be below 12.
- Ensure no rain within 7 days of texture application. Incomplete drying may lead to softening of texture and debonding from the substrate.
- Dilute the material up to 200 ml for 25 Kg bag, only when it is necessary to get better consistency.
- Do not apply on chalky / lime washed substrate / powdery substrate or when the wall is wet (except sprinkling during summer).
- Do not apply when humidity is greater than 80%. It may cause prolonged drying time of texture/paint and moisture condensation on the walls.
- For better performance, ensure the substrate is cured for 4 weeks under normal atmospheric conditions(30°C; 50–60% RH) with continuous water curing.
- During summer, whenever the substrate temperature goes more than 45° C, sprinkling of water on the substrate may be required before texture application for better ease of application. But ensure no excess pouring of water on to the surface, which might lead to sagging of texture.
- A primer coat, texture, or only one coat of topcoat should not be kept exposed in monsoon. Complete application before monsoon to be ensured.
- Apply 2 coats of topcoat within 7–8 days of texture application.
- Mix the material in the bag before use.

PAINTING STEPS



01

Apply Birla Opus Prime - Exterior Water Thinnable Primer/equivalent Birla White Primer or Exterior Waterproof Coating/equivalent Birla White waterproofing product as prescribed in the application guidelines.



02

Apply one coat of undiluted Birla Opus Prime TR3 Exterior Roller Wall Finish Texture with honeycomb or embossed rubber roller. Maintain uniform thickness of about 1 mm. If required, dilute 25 kg of texture with a maximum of 200 ml of water to achieve a better consistency for application.



03

Ensure Pattern creation completion prior to drying of the surface. It may be required to sprinkle water on the Texture film to create patterns during summers.



04

Apply 2–3 coats of Birla Opus Prime Exterior topcoat with a gap of 4–6 hours after each coat.

POST PAINTING CARE



For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months. Thoroughly clean horizontal surfaces to enhance durability. Ensure there is no stagnant water at any point on any surface.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Drying time	Overnight
Flash point IS101/1987 Part 1, Sec 6	Water based
Stability of thinned paint	NA

Version No. TR3-1001/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content –all rights reserved





Product Code: 916010

EXTERIOR TEXTURES – TS3

Spray Wall Finish

Birla Opus Prime TS3 Exterior Spray Wall Finish Texture is an acrylic-based exterior texture with excellent plaster protection properties, formulated to enhance the aesthetics of exterior surfaces.

BIRLA
opus
PRIME

PRODUCT FEATURES



EXCELLENT WATER REPELLENCY

Ensuring that your exterior walls remain shielded from harsh climatic conditions due to its excellent water repellent property.



EXCELLENT PLASTER PROTECTION

Excellent protection to the structure by providing a barrier coat against climatic conditions.



OUTSTANDING NAIL HARDNESS PROPERTIES

Outstanding durability due to the hardness of the film preserving its beauty and integrity for years to come.

PRODUCT DETAILS

AVAILABLE PACKS



30kg

COVERAGE

Estimated Coverage


7-9 sq. ft/kg for 1 coat**
or 0.65-0.84 sq.m/kg for 1 coat**

**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. One should ensure coverage is not higher than the one prescribed above for optimal performance.

COLOURS AVAILABLE

2000+*

(*When applied with Birla Opus Prime Exterior Emulsions)




SHELF LIFE



12 months
from the date
of manufacture

PATTERNS



Headcut



Bubble Pattern

DIRECTIONS FOR USE

APPLICATION TOOLS

Hopper Gun with
nozzle size: 4-8 mm

Pressure: 4 – 6 bar



Plastic roller



SURFACE PREPARATION



1. Clean and dry the surface

Clean and dry the surface. For best performance, it is recommended to use a jet pressure washer of minimum 160 bar pressure, to ensure complete surface cleanup. On algal/fungal affected areas, post jet wash, ensure cleaning with 10% bleaching powder solution followed by thorough cleaning with potable water.



2. Cracks Filling

Fill cracks using Birla Opus crack fill solutions. Ensure that the painting surface is uniform.



ADITYA BIRLA

PAINTS

BIRLA
opus
PRIME

PAINTING STEPS



01

Apply Birla Opus Prime - Exterior Water Thinnable Primer/equivalent Birla White Primer or Exterior Waterproof Coating/equivalent Birla White waterproofing product as prescribed in the application guidelines.



03

For Head-cut pattern, follow the same process as mentioned in the above step and then flatten the bubbles slightly with a plastic roller soaked in turpentine oil. Apply gently as excessive pressure would flatten the entire texture.



05

Apply 2-3 coats of Birla Opus Prime Exterior topcoat with a gap of 4-6 hours after each coat.



02

For Bubble pattern, apply one coat of undiluted Birla Opus Prime Exterior TS3 Spray Texture with a hopper gun. Maintain a uniform pressure of 4-6 bar. If required, dilute 30 kg of texture with a maximum of 500 ml of water to achieve a better consistency for application.



04

Allow the texture to dry overnight before top-coat application.

POST PAINTING CARE



For the best paint performance, regularly wash and clean surfaces to remove dust, stagnant materials, and any algae or fungus growth, preferably every six months. Thoroughly clean horizontal surfaces to enhance durability. Ensure there is no stagnant water at any point on any surface.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C or if the temperature might drop to this level within 4 hours of application.
- To avoid water or dew condensation, the temperature of the substrate should be a minimum of 3° C above the dew point of the air temperature and relative humidity measured in the vicinity of the substrate.
- For best performance, ensure that the surface is dry. On the moisture meter it should be in the green zone (below 15). In case it is in the red zone, find out the source of the water and address it before painting.
- The pH of the wall must be below 12.
- Ensure no rain within 7 days of texture application. Incomplete drying may lead to softening of texture and debonding from the substrate.
- Dilute the material up to 500 ml for 30 kg pail, only when it is necessary to get better consistency.
- Do not apply on chalky / lime washed substrate / powdery substrate or when the wall is wet (except sprinkling during summer).
- Do not apply when humidity is greater than 80%. It may cause prolonged drying time of texture/paint and moisture condensation on the walls.
- For better performance, ensure the substrate is cured for 4 weeks under normal atmospheric conditions (30°C; 50-60% RH) with continuous water curing.
- During summer, whenever the substrate temperature goes more than 45° C, sprinkling of water on the substrate may be required before texture application for better ease of application. But ensure no excess pouring of water on to the surface, which might lead to sagging of texture.
- A primer coat, texture, or only one coat of topcoat should not be kept exposed in monsoon. Complete application before monsoon to be ensured.
- Apply 2 coats of topcoat within 7-8 days of texture application.
- Mix the material in the bag before use.

SAFETY FEATURES

- For detailed safety instructions on paint handling, refer to the Material Safety Data Sheet (MSDS) which is available upon request.
- The container should be stored in upright position in a cool and dry place which is shaded from sunlight. Ensure the lid is tightly closed when not in use.
- Avoid contact with food items and keep away from children.
- Caution : Swallowing may cause harm. Seek immediate medical attention if it occurs.
- Use eye protection while applying. If eye contact occurs, rinse thoroughly and seek medical guidance.
- If skin comes into contact, wash immediately with soap and abundant water. If irritation persists, seek medical attention.
- Avoid inhaling vapor or spray. Use a nose pad during sanding and surface preparation to avoid dust exposure.
- Dispose off unused paint responsibly. Avoid pouring it into drains or water bodies.
- If spill occurs, use sand or soil to contain it.
- No added lead, mercury or chromium compounds.

TECHNICAL INFORMATION

Drying time	Overnight
Flash point IS101/1987 Part 1, Sec 6	Water based
Stability of thinned paint	NA

Version No. TS3-1001/05/2024. For more details, kindly contact customer care at 18001201234 or visit www.birlaopusprime.com. Kindly note that this datasheet supersedes all preceding versions.

© Copyrighted content -all rights reserved



ADITYA BIRLA

PAINTS

PRIME SERVICES



More Success. Less Stress.

PRIME PALETTE

- Colour Consultancy
- Colour Match Services
- Colour Selection Tools
- ProView – Visualization service

PRIME PRIVILEGE

- Dedicated Sampler Packs
- Bid Assist Tools
- Best-in-Class Warranty

PRIME CONNECT

- Customized Engagement Programs
- Dedicated Social Media Handles
- Exclusive Institutional Website
- Customer Centric Apps

NOTES



.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

