



NXTBLOCTM

AUTOCLAVED AERATED CONCRETE BLOCKS



ABOUT

NXTBLOC

Bigbloc Construction Limited is a leading manufacturer and supplier of AAC (Autoclaved Aerated Concrete) Blocks. We are a professionally managed company listed on NSE & BSE. We manufacture both Fly-ash and Sand based AAC blocks under the brand name of NXTBLOC, Block Jointing Mortar under NXTFIX brand and Ready-Mix Plaster under brand name of NXT-PLAST.

We are in this industry since 2009 & the largest player in western india and one of the largest in the country with a vision to becoming a pan India player very shortly. Also, we are currently having supply presence in entire western india across the states of Maharashtra, Gujarat, Rajasthan and Madhya Pradesh.

We have Head Office at Surat and Branch Offices at Ahmedabad and Mumbai. Currently we have three manufacturing units and those are strategically located. One at Umargam of Valsad district in Gujarat state, Second at Kapadwanj, near Ahmedabad city and third at Wada, Maharashtra. Our current total production capacity is 13 lakh cubic metre per year.

NXTBLOC are manufactured as per the instruction provided by IS code 2185 part III and that offers Green Products and Solutions with an ultimate aim of helping the Real Estate & Infrastructure Industry to build green and sustainable constructions.

Being the oldest player in AAC Blocks industry, our supply chain is associated with the major Builders, Contractors, Industrial Clients & Governments Departments. Major builders like Lodha Group, Godrej Properties, Runwal Group, K Raheja, B.G. Shirke, L & T, Oberoi Group, Adani Group, Savvy Group, Kavyaratna Group, Reliance Industries Ltd, Nilamber Group, PSP Projects, Sunteck, Capacite infraprojects, & many more are our regular customers.


Timely delivery is one of our major concerns. The supply chain is backed by company owned fleet and registered transporters. The company manages its own 65 trucks, including small and big size.




TYPES OF AAC BLOCKS

Fly Ash AAC Blocks

Superior green solution with lighter weight and best in compressive strength. Porous structure of it allows for superior fire resistance. It is an eco-friendly replacement for conventional red clay brick in all aspects governed by IS Norms



Fly Ash



Cement



Lime




Gypsum




Aeration Agent

Sand-based AAC Blocks


A Lightweight, Smooth finish, High-insulating, Durable building product, which is produced in a wide range of sizes and strengths. Compared to the red bricks AAC blocks are three times lighter. The blocks governed by IS Norms



Sand



Cement



Lime



Gypsum



Aeration Agent

AAC Blocks and Fly Ash AAC Blocks allows



Nails can be put with normal hammer



Small groves and chases for services can be cut with a manual chasing tool.



Block can be drilled to provide electrical socket



Take copping above 1.2 mtr height



Sound
Proof



Pest
Protection



High
Strength



Fire
Resistant



Energy
Efficient



Water
Barrier



Floor Space
Area



Thermal
Insulation



Earth
Quake
Resistance



Cost
Saving



Light
Weight

FEATURES & ADVANTAGES

NXTBLOCTM

AUTOCLAVED AERATED CONCRETE BLOCKS

PRODUCTS CHARACTERISTICS & TECHNICAL SPECIFICATION

Sr. No.	PARAMETER	AAC BLOCK	CLAY BRICK
1	Size (L x H x T)	600 x 200 x (50 to 300) 625 x 240 x (50 to 300) 650 x 240 x (50 to 300)	230 x 100 x 75 mm
2	Size Tolerance	3 mm (+/-)	05 to 15 mm (+/-)
3	Compressive Strength	as per IS:2185 - Part 3	as per IS:1077
4	Dry Density	550 - 650 Kg/Cum (oven dry)	1950 Kg/Cum
5	Fire Resistance	02 to 06 hours (depending upon thickness)	02 hours
6	Sound Insulation Index	45 db for 200 mm thick wall	50 db for 230 mm thick wall
7	Thermal Conductivity	0.16 - 0.18 (w / m-K)	0.81 (w / m-K)

COMPARISON & TRADITIONAL METHOD

1	Structural Cost	Steel saving up to 15% to 20%	No such saving
2	Cement Mortar For Plaster & Masonry	Required less due to flat, even surfaces & minimum number of joints	Required more due to irregular surface & more number of joints
3	Breakage & Utilization	Negligible breakage therefore 100% utilization	Average 10 to 15% breakage
4	Construction Speed	Speedy construction due to it's big size, light weight & ease to cut in any size or shape	Comparatively slower
5	Labour Out Put	Approximately double of conventional brick	Comparatively low
6	Quality	Uniform & consistent	Normally varies
7	Carpet Area	More due to less thickness of walling material	Comparatively low
8	Storage	Readily available at any season in a short notice so no storage required	Particularly in monsoon, stock at site is compulsory
9	Water Required	Required less in wetting & curing, hence saving in electricity bill & labour cost.	Need more curing resulted to higher amount of electricity bill & labour cost.
10	Energy Saving	Approximately 30% reduction in air-conditioned load	No such saving

LOGISTICS DATA

Sr. No.	TRUCK CAPACITY	MATERIAL
1	12 Ton	14-15 CBM
2	25 Ton	33-36 CBM
3	30 Ton	40-43 CBM
4	35 Ton	45-50 CBM



ABOUT



NXTFIX mortar is a semi premix high quality mortar for jointing and bonding of AAC blocks. NXTFIX mortar semi premix consists of cement, graded sand and specialised polymers which combine to give superior strength, water retention and stability. It replaces the conventional method and material of jointing mortar which requires a 12-18 mm thickness with a revolutionary 2-3 mm joint thickness. NXTFIX mortar only requires addition of water before application to prepare the product for use, reducing the hassle of measuring and maintaining various individual elements to create a conventional mortar



HIGH BOND STRENGTH

Special polymer imparts high adhesive strength increasing overall masonry strength & load bearing capacity.



ECONOMICAL

Quantity of NXTFIX required is 3 times lesser than conventional mortar



Semi Premix

NXTFIX Mortar are semi-premix solutions which only require the addition of water prepare for application



NO CURING REQUIRED

Due to water retention polymers, curing is not essential after application



NEGLIGIBLE SEEPAGE

Due to texture Chemical bond and properties of NXTFIX mortar, seepage water penetration through joints is negligible.



EASY APPLICATION

Reducing the hassle of mixing various raw materials, saves the wastage and ensures the higher flow ability and water retention properties.

PRODUCTS CHARACTERISTICS & TECHNICAL SPECIFICATION

PARAMETERS	VALUES
Physical Nature	Powder and Grey in Colour
Water Demand	25 - 35%
Spread on surface	Excellent (in comparison to conventional mortar due to the consistency in texture and smoothness in application)
Hard Dry	Approx. 24 Hours (further depending on the temperature and humidity conditions)
Surface Area Covered by 40Kg bag	115 Sq. Ft to 120 Sq. Ft. (for 4" thick blocks)
Splitting Tensile Strength	$\geq 0.4 \text{ N/mm}^2$ (as per ASTM - C1660)
Ingredients	Graded Sand, Pozzolanic material, Binder, Performance additives
Packaging	40 kg Bags
Storage	Keep in dry place free from moisture and water. Do not leave the bags open.

COMPARISON & TRADITIONAL METHOD

PARAMETERS	TRADITIONAL	NXTFIX
Joint Thickness	10 mm - 18 mm	3 mm+
Drying Time	Slow	Rapid
Setting time	Slow	Rapid
Height of build	Restricted	No Restriction
Precision	Less	More
Air tightness	Less	More
Strength	Joints are weak points	Joints are stronger
Shrinkage	Yes	No
Stability	Less Stable	More Stable
Material storage	More	Less
Aesthetics	Uneven, with variations	Even and better laying



ABOUT NXTPLAST

READY MIX PLASTER

NXTPLAST Ready Mix Plaster is a ready mix cement plaster with high quality polymer additives to substitute for the traditional site mix wall plaster process. The solution consists of processed sand which is graded and distributed as per particle size and proportionately mixed, cement and water soluble polymers which act as additives. The application method requires mixing of water before application and the mix is ready for plastering. NXTPLAST Ready Mix Plaster can be used for both external and internal plastering.

NXTPLAST Ready Mix Plaster can be applied on:

- AAC Block Walls
- Fly Ash Block Walls
- Concrete Block Walls
- Clay Brick Walls
- Stone Walls
- Concrete Surfaces

PLASTER COATS

Internal: 10-15 mm single coat is recommended for internal plaster covering.

External: Two coats are recommended to cover the external side of walls i.e. Base coat of 8-12 mm and Finish coat of 8-12 mm to get a total thickness of around 18-20 mm, Further depending upon site conditions. After the Base coat minimum of 2 to 3 days curing must be done before the application of the final coat.

COMPARISON

PERFORMANCE PARAMETERS	JOB-SITE PLASTER	NXTPLAST
DE-BONDING LOSSES	High	Negligible
SMOOTHNESS	Not so smooth	Smooth and hard surface provides aesthetic base of plaster to work upon.
CRACK FORMATION	Due to on site mixing practice, chances of crack formation is more.	NXTPLAST produced at automated dry mix plant. Chances of crack formation is very negligible subjected to proper curing and application.
WATER: CEMENT RATIO	Due to presence of moisture in sand it is not possible to determine exact quantity of water to be mixed.	Due to dry sand used, water cement ratio is easily maintained and full strength of plaster is obtained.
GRADING OF SAND	No grading	NXTPLAST has graded sand which results in compactness of plaster.
CEMENT: SAND RATIO	Mistake may occur at job site mix	Sand cement ratio is maintained as NXTPLAST is made in automated plant.
POLYMER MODIFICATION	Polymer modification difficult as it involves multiple polymers and doses.	Polymers already added, results in overall durability.



FEATURES & BENEFITS

NXTPLAST



High Strength

High compressive and tensile strength increases masonry strength and load-bearing capacity.



Easy Application

The material is pre-mixed and only water has to be added on site. This makes the process of plastering much easier and quicker.



Minimum Cracks

Shrinkage cracks are minimised as premix plaster raw materials are tested and accurately mixed with specific particle size and quantity.



Higher Coverage

Due to lower density and high volume, it covers 15-20 sq.ft./bag with a thickness of 10-12mm.



Storage

Easy to maintain stock as equal size packaging in bag form is provided.



Finish

Surface finish after application is excellent and equal due to best particle size grading, hence maximizing wall plaster performance.



Economical

It provides smooth finish walls even in a single coat. Hence saves time and cost required for putty coating.



Availability

Unlike the uncertain availability of raw river sand, premix bags are available round the year.



Minimum Wastage

The wastage caused in the conventional site mix process while sand sieving and mixing material is totally avoided.



Premixed

No site mix and blending of powder is required. Only water is to be added.



Consistency

Due to the manufacturing process and accurate particle size distribution, the premix bags are of consistent quality.

PRODUCTS CHARACTERISTICS & TECHNICAL SPECIFICATION

Parameters	Values
Appearance	Greyish Granular Powder
Coverage	17 to 20 square feet / 40 Kg bag @ 10-12 mm thickness
Thickness of Single Layer	6-12 mm
Pot Life	Approx 1-2 hours @ 27° C
Water Demand	17-20% of Mix (can vary on climatic conditions)
Bulk Density	1.2-1.6 Kg/litre unit
Compressive Strength (MPa)	More than 4 in 28 days

Ingredients: Graded River Sand, OPC 53 Cement, Fly Ash, Hydrated Lime, Performance additives & Glass Fibre.

Safety Precaution

- This product is non-toxic and nonhazardous.
- Use of gloves, dust-mask and goggles is recommended.
- In case of contact with skin/eyes, wash with plenty of clean water.
- In situation of prolonged irritation, professional medical aid should be sought.

"The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not covered by this document are used, customers must request specific additional information and/or carry out a representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document."

BY NXTBLOC

ZMARTBUILD by NXTBLOC Wall Panel are lightweight, steel reinforced, groove & tongue panels that can be easily installed by your normal on-site installers. They are suitable to be used as both external & internal walls. ZMARTBUILD by NXTBLOC Wall Panel are steel reinforced (start from) 75 mm thick and are available in lengths of 1.50 m to 4.0 m of width of 600 mm.

Non-combustible: up to four-hour fire rating.

Outstanding thermal and acoustic insulation qualities increase levels of comfort and save on energy cooling costs.

Product Specification

Specification	Report	Unit ₃
Dry Density	550-650	Kg / m ₃
Working Density	750-850	Kg / m ₃
Wind Load	Up to 180	Kg / m ₃
Compressive Strength	> 40	Kg / m
Water Absorption	<33%	by volume

Testing	Report	Unit
Fire Resistance	Up to 4.00	Hr.
Thermal Conductivity	0.115	W / mk.
STC Rating	38 - 43	dB
Tensile Strength	> 500	N / mm ²

Features & Advantages

- Light weight
- Easy Installation & Clean site
- Thermal Proof
- Soundproof
- Fire Resistance
- Environment Friendly
- Energy Saving
- Highly Durable



OUR CLIENTS



LODHA
BUILDING A BETTER LIFE



Sunteck

Raymond REALTY



adani
Realty



Gony | PROPERTIES



OR
CEPRO
REALTY



CLOUD9



SHIVALIK
BUILDING LANDMARK SINCE 1988



SHIRKE

CHAVDA
SINCE 1990



HI-TECH



Alembic
Touching Lives over 100 years



ATS
The Better way Home



The Wadhwa Group



KEC





■ CORPORATE OFFICE

908, Rajhans Montessa,
Dumas Road, Magdalla,
Surat - 395007, Gujarat.

■ REGIONAL OFFICES

609-610, A Wing,
Corporate Avenue,
Sonawala Road,
Goregaon (E) Mumbai - 400063

620, 6th Floor, Gala Empire,
Opp. TV Tower, Drive Inn Road,
Thaltej,
Ahmedabad - 380052

■ MANUFACTURING PLANTS

Survey No.:279/7, Paikie 1,2,
Manda-Khatalwada,
Khatalwada, Umargaon,
Dist.: Valsad

Survey No. 234/235/236,
Village Ramosadi, NR. Kapadwanj,
DI: Kheda, Godhara Highway,
Nadiad - 387620, Gujarat, India

Survey No. 378/373/380,
Savli Village, NR. Kapadwanj,
DI: Kheda, Godhara Highway,
Nadiad - 387620, Gujarat, India

Survey No-94, Pandhare Pada
Wada Manor Road, Savli Village,
Village-Kanchad, TaL: Wada,
Dist : Palghar, Maharashtra 421303,

