

CYBER THREAT INTELLIGENCE INCIDENT INVESTIGATION REPORT

By:

Utibe Anthony (~ Smart)

Introduction

This report presents the findings of a cyber threat intelligence investigation conducted on a suspicious IP address identified during a security incident. The investigation involved analyzing the indicator of compromise (IOC) using multiple threat intelligence platforms, mapping the observed attacker behavior to the MITRE ATT&CK framework, classifying the intelligence gathered, and preparing an analyst report with recommended containment and long-term security improvements.

The report is organized into four sections:

- Task 1: IOC Investigation and Threat Intelligence Analysis
- Task 2: MITRE ATT&CK Mapping
- Task 3: Cyber Threat Intelligence Classification
- Task 4: SOC Analyst Report and Recommendations

TASK 1: IOC Lookup and Classification:

185.220.101.47 | Network for Tor-Exit traffic | LevelBlue - Open Threat Exchange | IPv4: 185.220.101.47 - LevelBlue | 185.220.101.47/tor-exit-47-for- | + | Ask Gemini | - | 0 | x

abuseipdb.com/check/185.220.101.47?page=439

AbuseIPDB Report IP Bulk Checker Bulk Reporter Pricing Integrations Docs IP Utilities Contact More Login Sign Up

AbuseIPDB » 185.220.101.47

Check an IP Address, Domain Name, Subnet, or ASN
e.g. 105.112.104.119, microsoft.com, 5.188.10.0/24, or AS15169

185.220.101.47 was found in our database!

This IP was reported 6,580 times. Confidence of Abuse is 99%.

99%

This address is a Tor exit node. Neither the owner nor the provider are directly behind the offending action.

ISP Network for Tor-Exit traffic.

Usage Type Commercial

ASN AS60729

Amazing Themes made by Creators just like you.

Explore Themes ADS VIA CARBON

78°F Mostly cloudy 12:15 AM 6/28/2026

185.220.101.47 | Network for Tor-Exit traffic | LevelBlue - Open Threat Exchange | IPv4: 185.220.101.47 - LevelBlue | 185.220.101.47/tor-exit-47-for- | + | Ask Gemini | - | 0 | x

obx.alienvault.com/indicator/ip/185.220.101.47

Open Threat Exchange Dashboard Browse Scan Endpoints Create Pulse Submit Sample API Integration All 185.220.101.47 UTIBEANTH

IPv4 185.220.101.47 Add to Pulse

Pulses 50 Passive DNS 2 URLs 0 Files 0

Analysis Overview

Location	Germany	External Resources	Whois, VirusTotal
ASN	AS208294 cia triad security llc		
Related Pulses	OTX User-Created Pulses (50)		
Related Tags	33 Related Tags Bruteforce, Brute-Force, SSH, HoneyPot, webscanner, bruteforce, web app attack More		

Analysis Related Pulses Comments (0)

78°F Mostly cloudy 12:15 AM 6/28/2026

The malicious IP address identified during the investigation was categorized as a Tor exit node. According to AbuseIPDB, the IP is identified as a Tor Exit-47 Privacy Network and has a 99% confidence of abuse, indicating that it is a highly malicious Indicator of Compromise (IOC). Further analysis

using AlienVault OTX did not reveal any malware families or specific threat campaigns associated with the IP address. This IOC is classified as a network IOC because it is an IP address used for network communication between systems. During the incident, the compromised workstation established repeated outbound connections to this external IP address, making it a significant network-based indicator of suspicious activity.

TASK 2: MITRE ATT&CK Mapping

Tactic	Technique ID	Technique Name	Justification
Exfiltration	T1029	Scheduled Transfer	The repeated outbound connections and off-hour data transfer are consistent with a scheduled transfer designed to exfiltrate data at predetermined times.
Command and Control	T0885	Commonly Used Ports	The workstation communicated repeatedly with a suspicious external IP address over port 443, a commonly used HTTPS port. Adversaries often use common ports to blend malicious traffic with legitimate network activity. Therefore, this behavior is consistent with the MITRE ATT&CK technique Commonly Used Ports.

Execution	T1053	Scheduled Task/Job	The malicious network activity occurred outside business hours while no user was logged in, suggesting that an automated scheduled task or job could have been used to execute the activity without requiring user interaction.
-----------	-------	--------------------	---

TASK 3: Intel Type & Pyramid of Pain Analysis

The investigated IP address represents technical intelligence because it is a network-based Indicator of Compromise (IOC). Technical intelligence focuses on observable indicators such as malicious IP addresses, domain names, URLs, and file hashes that Security Operations Center (SOC) analysts use to detect, monitor, and investigate malicious activity.

The investigated IOC is a malicious IP address, which is classified under the "Easy" level of the Pyramid of Pain. This is because an attacker can easily replace or rotate a blocked IP address with another one to continue communicating with compromised systems. Although blocking a malicious IP address is an effective short-term containment measure, it has a relatively low impact on the attacker because changing IP addresses requires little effort.

Blocking the malicious IP address would be a minor inconvenience to the attacker because IP addresses are relatively easy to change. While blocking the IP may temporarily interrupt communication with the compromised system, the attacker can quickly switch to another IP address and continue their operations.

The most impactful level of the Pyramid of Pain is TTPs because attackers cannot simply replace their tactics, techniques, and procedures as easily as they can change an IP address or domain. If defenders successfully detect and disrupt an attacker's TTPs, the attacker must change how they operate, which requires significant time, effort, and resources. This makes it far more disruptive than blocking a single malicious IP address.

TASK 4: SIEM Rule and TI feed integration description

Pseudocode Correlation Rule:

IF destination_IP = <malicious IP>

AND destination_port = 443

AND Threat_Intelligence = "Malicious"

AND communication_time = "Outside Business Hours"

THEN

 Generate High-Severity Alert

 Notify SOC Analyst

 Block the destination IP

Threat Intelligence Feed Integration Description:

The Security Information and Event Management (SIEM) platform should be integrated with external threat intelligence feeds such as VirusTotal and AbuseIPDB. When an IP address observed in network traffic matches an entry in these threat intelligence feeds, the SIEM should automatically enrich the alert with reputation information, confidence scores, and threat classifications. If the IP address is identified as malicious or associated with a Tor exit node, the system should generate a high-severity alert for SOC investigation

TASK 5 Incident Summary Report

At approximately 2:14 a.m., outside normal business hours, workstation WAS-Finance-04 established repeated outbound connections to the external IP address 185.220.101.47 over port 443. The communication lasted approximately 18 minutes, during which 4.2 MB of outbound data was transferred while no user was logged into the workstation, indicating potentially unauthorized automated activity.

IOC Findings

The primary Indicator of Compromise (IOC) identified during the investigation was the external IP address 185.220.101.47. Threat intelligence analysis using AbuseIPDB and AlienVault OTX identified the IP address as a Tor Exit Node, commonly associated with anonymous network traffic. AbuseIPDB assigned the IP address an abuse confidence score of 99%, indicating a high likelihood of malicious activity. No specific threat campaign could be confidently attributed based on the available threat intelligence.

MITRE ATT&CK Mapping:

Tactic	Technique ID	Technique Name	Justification
Exfiltration	T1029	Scheduled Transfer	The repeated outbound connections and off-hour data transfer are consistent with a scheduled transfer designed to exfiltrate data

			at predetermined times.
Command and Control	T0885	Commonly used ports	The workstation communicated repeatedly with a suspicious external IP address over port 443, a commonly used HTTPS port. Adversaries often use common ports to blend malicious traffic with legitimate network activity. Therefore, this behavior is consistent with the MITRE ATT&CK technique Commonly Used Ports.
Execution	T1053	Scheduled Task/Job	The malicious network activity occurred outside business hours while no user was logged in, suggesting that an automated scheduled task or job could have been used to execute the activity without

			requiring user interaction.
--	--	--	-----------------------------

Containment Actions

1. Immediately block communication with the malicious IP address 185.220.101.47 at the firewall and other security controls to interrupt further communication with the attacker.
2. Isolate workstation WAS-Finance-04 from the network and perform forensic analysis to identify and remove any malicious processes, scheduled tasks, or malware.

Long-Term Improvement

Implement SIEM detection rules to identify repeated outbound communications to known malicious IP addresses, particularly those occurring outside normal business hours. Additionally, integrate external threat intelligence sources such as AbuseIPDB and AlienVault OTX into the organization's security monitoring platform to improve automated IOC detection and incident response.