Design Note: LLD Practice Platform


A TypeScript monolith (Express + SQLite + React). The domain layer (`src/domain`) has no framework, SQL or LLM code. Everything below describes what is in the repository.

1. MVP scope


In	Out (deliberately)
4 problems, each with 6 requirements, constraints and one change request	Auth (one demo learner)
Attempt editor: 5 structured sections, autosaved draft	Diagram editor, running learner code
Async evaluation: rules → LLM → evidence check → 1–4 per dimension	Timers, peer review, courses
Status: Submitted → Evaluating → Completed / Failed, manual retry	Multi-user scaling, real queue
Retry as v2 with the change request; history with weakest dimension	Analytics beyond the weakest dimension

2. User flow and status

Choose problem → write 5 sections (autosaved) → submit (stored, 202) → background evaluation → feedback (scores, top fix, quoted findings) → **try again as v2 with a change request** → history shows both attempts and the weakest dimension.



3. Domain model



Class	Single responsibility
`Problem`	Requirements (id, text, keywords), constraints, one change request.

Class	Single responsibility
`Attempt`	One try at a problem. `version` ≥ 2 adds the change request in `effectiveRequirements()`. Holds the draft.
`Submission`	Immutable content snapshot + status. Owns legal moves via a transition table; idempotency key = `attemptId:contentHash`.
`SubmissionContent`	What was submitted, in some format. Validates itself and maps to `EvaluationInput`.
`Evaluator`	Turns an `EvaluationContext` into `Finding[]` (rule, LLM, or later human).
`EvaluationPipeline`	Runs evaluators in order, stops on a blocking finding, verifies quotes, builds `Feedback`.
`Feedback`	Per-dimension 1–4 scores, findings, `topFix`, `partial`, `model`, `promptVersion`. One per submission.
`PracticeService`	The practice loop: start attempt, save draft, submit, retry. Knows no formats or evaluators.
`EvaluationWorker`	Claims jobs, runs the pipeline, stores feedback and the final status.
`ProgressService`	Averages each attempt's latest completed feedback; returns the weakest dimension.

The two variation points sit behind two interfaces:

```
interface SubmissionContent {
  readonly format: string;                 // "text-design" today, "class-diagram" later
  validate(): ValidationResult;            // deterministic, at submit time
  toEvaluationInput(): EvaluationInput;    // sections by role: the one shape evaluators read
  contentHash(): string;                   // part of the idempotency key
  toJSON(): unknown;                       // persisted; rebuilt via ContentFormatRegistry
}

interface Evaluator {
  readonly source: "rule" | "llm" | "human";
  readonly name: string;
  readonly provenance?: { model: string; promptVersion: string };
  evaluate(ctx: EvaluationContext): Promise<Finding[]>;
  // ctx = { input, problem, attempt, requirements, priorFindings }
}

type Finding = {
  criterion: RubricDimension; score: 1 | 2 | 3 | 4;
  evidence: string | null;   // verbatim quote; null only for rule "nothing mentions X"
  concern: string; suggestion: string;
  confidence: number;        // < 0.5 = "worth checking", does not move the score
  source: "rule" | "llm" | "human"; blocking?: boolean;
};
```

Why only Strategy and a pipeline. Patterns appear only where something varies. Submission formats and evaluators vary, so each is a Strategy. Evaluation is an ordered sequence with a short-circuit, so it is a pipeline. Submission status is a **transition table, not the State pattern**: the states have no behaviour of their own, only rules about which state may follow which. One rule sits outside the table: `retryEvaluation()` is allowed only from FAILED. A test caught that the table alone would let a retry jump a SUBMITTED submission.

4. Evaluation approach

Deterministic (`RuleEvaluator`, at submit time and first in the pipeline)	**LLM (`LlmRubricEvaluator`)**
All 5 sections present, min/max length → 400 with per-section messages	Quality of responsibilities, coupling, abstraction
Code declares no class/interface/enum → **blocking**: LLM is never called	Whether a requirement is really handled (confirms or rejects keyword hints)
Classes listed in prose but missing from code → finding with quote	How well the change request was absorbed
God class: ≥ 8 methods and ≥ 2× the median	Edge cases, states, trade-off reasoning
Requirement keywords absent → "possible gap" hint (confidence 0.35)	Concrete suggestions naming a class or method
v2+: change-request keywords absent → finding (0.6)	

Rubric. Six fixed dimensions: requirement coverage, responsibilities & cohesion, coupling & abstraction, extensibility (on v2+: absorbing the change), edge cases & state, trade-off explanation. Each has an anchor sentence for every score from 1 (missing) to 4 (strong); see `src/domain/evaluation/rubric.ts`. A dimension's score is the confidence-weighted mean of its findings with confidence ≥ 0.5. The **top fix is chosen by code**: a blocking finding first, otherwise the lowest-scored confident finding. This keeps it pointing at a verified quote rather than at free text from the LLM.

Prompt (`src/prompts/rubric-evaluator.v1.md`, versioned):

- Role: a senior engineer reviewing an LLD interview answer. "Many designs are valid; judge against requirements and anchors, never a model answer."
- Inputs are XML-tagged: `<problem>`, `<requirements>` (the change request is marked), `<rubric>`, `<rule_findings>` (hints to confirm or reject), and `<submission>` (sections tagged by role).
- Output: JSON only, 1–3 findings per dimension. Evidence is a verbatim quote of at most 200 characters. The prompt includes one worked example (hard-wired parking pricing → inject a `PricingStrategy`).
- **Injection defence:** the submission is declared to be data, and its instructions must never be followed. Delimiter tags typed by the learner are escaped, so injected text cannot leave `<submission>`.

Guards on AI output. Output is parsed and validated with zod (every dimension must be present). If that fails, one **repair retry** sends the error back; a second failure throws. `EvidenceVerifier` normalises case, whitespace and quote marks, then drops any finding whose evidence is not a substring of the submission (or is shorter than 8 characters), and the drop count is logged and shown. `model` and `promptVersion` are stored with every Feedback.

Providers. `LLM_PROVIDER=mock|anthropic|openai`, defaulting to mock when no key is set.

- The mock parses the real prompt and quotes real sentences, so mock mode exercises the whole pipeline.
- Anthropic uses the official SDK with structured output.
- *Deviation from the brief:* no `temperature: 0` for Anthropic, because current Claude models reject non-default sampling. OpenAI gets `temperature: 0`.

5. Slow or failed evaluation

- `POST /attempts/:id/submissions` validates, then stores the submission (SUBMITTED) and its job **in one transaction**, and returns **202** before any evaluation.

- **Idempotency:** `Idempotency-Key` (the UI sends `attemptId:sha256(content)`, the server's own default). A repeat returns the original with 200.
- **Worker:** an in-process loop polls the `evaluation_jobs` table every 2 s. A claim sets `lease_until`. Jobs survive restarts, and a job whose lease has expired is reclaimed.
- **LLM calls:** each call has a 60 s timeout and 2 retries with exponential backoff (1 s, 2 s). Errors that won't fix themselves (401, 400, refusal) are not retried. The lease covers the worst case: two calls with all retries.
- **Failure:** the submission becomes FAILED with a `failureReason`. The rule findings are kept as Feedback with `partial: true`. `POST /submissions/:id/retry` (FAILED only, else 409) re-queues it.
- **Polling:** the UI polls `GET /submissions/:id` every 3 s.
- **Growth:** the first component to separate is the worker (its own process on the same jobs table, then a real queue), because LLM calls are the slow, costly and bursty part.

6. Change tests (both run as code in `tests/change-tests.test.ts`)

	Added	Untouched
A: learner submits a class diagram	`FakeDiagramContent implements SubmissionContent` (maps boxes and arrows to section roles) + one `registry.register("class-diagram", …)` line	Attempt, Submission, PracticeService, pipeline, evaluators, worker, DB schema (content is stored as format + JSON)
B: rule-based or human evaluator	`FakeHumanEvaluator implements Evaluator` + one entry in the evaluator list	PracticeService, worker, Submission, Feedback; findings show `source: "human"`

7. Trade-offs and limitations

Decision	Gain	Cost
Structured text, not diagrams	Shows reasoning and code-level abstraction; cheap to build	Relationships are inferred from text
1–4 per dimension with anchors, not a 100-point score	Repeatable, tells the learner what to work on	Coarse; small improvements don't move a score
Drop findings whose quote isn't found	No invented criticism; every point is checkable	Correct but paraphrased points are lost
SQLite table as the job queue	Survives restarts, zero infrastructure	One process; polling latency up to 2 s
Transition table, not State pattern	All legal moves in one place	Retry needs one extra explicit rule
Mock evaluator by default	Runs with zero setup; tests the whole pipeline	Keyword heuristics, not real judgement

Limitations.

- Keyword coverage is crude: synonyms are missed and substrings can match, which is why it only produces low-confidence hints.
- LLM scores can still vary slightly between runs.
- There is one demo learner.
- Repositories are synchronous (better-sqlite3).
- **Next:** an eval set of real designs to calibrate the prompt, human review as a third evaluator, diagram input, and per-requirement traceability in feedback.