

**Birla Institute of Technology & Science, Pilani**  
**Computer Programming (CS F111)**  
**Second Semester 2014-2015**  
**Lab-10**

---

**Topics**

Dynamic Memory Allocation and Structure

---

**General Instructions:**

- o First create a directory with your full ID e.g. 2010A7PS111.
- o Create a sub-directory (within the above directory) named Lab\_No.
- o Create all your files within the subdirectory.

**Write a C program to maintain list of text book information for each class. The structure definition of text book and class/standard is as given below:**

<pre>struct class { int no_books; struct text_book *booklist; }; typedef struct class std;</pre>	<pre>struct text_book { char name[10]; int bid; float price; int numaut; char autlist[5][10]; };</pre>
--	--

Where, "*no\_books*" refers the number of text books for the respective class and "*booklist*" stores the set of text books information of the respective class. The variable *name*, *bid*, *price*, *numaut* and *autlist* in the structure *text\_book* refers name, identification number, price, number of author and list of authors of the text book respectively.

**Write functions to perform the following:**

**1. void read\_classInfoByRef**(std \*s,int cl\_no,int nb)

This function takes a structure variable of type class by reference(*s*), class number(*cl\_no*) and number of text books (*nb*) for the class *cl\_no* as arguments. This function reads the value of each variable in the structure class from the user.

**Note1:** Allocate memory dynamically for the variable *booklist*.

**Note2:** To access member of the structure using pointer variable *ptr*, either of following operators is used:

- ptr -> member
- (\*ptr).member

**2. void print\_classInfo**(std s,int cl\_no)

This function takes a structure variable of type class by value(*s*) and class number(*cl\_no*) as arguments. This function prints the value of each variable in the structure class.

**3. std read\_classInfoByVal**(std s,int cl\_no,int nb)

This function takes a structure variable of type standard by value(*s*), class number(*cl\_no*) and number of text books (*nb*) for the class *cl\_no* as

arguments. This function reads the value of each variable in the structure standard from the user and returns the class s.

4. void **print\_allInfo**(std \*s, int nc)

This function takes array of structure of type class and number of classes in the school (**nc**) as arguments. This function prints the text book information of all classes in the school.

**Template of Driver/Main function for calling the above mentioned functions is given below:**

```
void main()
{
    int nc,ns,i,j;
    std *s;
    printf("enter number of classes\n");
    scanf("%d",&nc);

    // Allocate memory dynamically for the variable s using malloc()

    for(i=1;i<=nc;i++)
    {
        printf("enter number of text_books for %d standard\n",i);
        scanf("%d",&ns);

        // Call the function read_classInfobyRef() or read_classInfobyVal()

    }
    for(i=1;i<=nc;i++)
    {

        // Call the function print_classInfo() appropriately

    }

    // Call the function print_allInfo()

}
```

### **Exercises:**

1. Modify the variable *autlist[5][10]* in the structure text\_book into **\*\*autlist** and rewrite the function **read\_classInfobyRef()** and **read\_classInfobyVal()** by dynamically allocating memory for two dimensional array autlist[5][10].
2. Write a function to sort books *in non-increasing order of* book id "*bid*".