Problem Chosen	2021 MCM/ICM Summary Sheet	Team Control Number
A		2123481

The XXX problem

Summary

Use this template to begin typing the first page (summary page) of your electronic report. This template uses a 12-point Times New Roman font. Submit your paper as an Adobe PDF electronic file (e.g. 1111111.pdf), typed in English, with a readable font of at least 12-point type.

Do not include the name of your school, advisor, or team members on this or any page.

Papers must be within the 25 page limit.

Be sure to change the control number and problem choice above. You may delete these instructions as you begin to type your report here.

Follow us @COMAPMath on Twitter or COMAPCHINAOFFICIAL on Weibo for the most up to date contest information.

Keywords: Matlab; Mathematical modelling.

The XXX problem

Miao Fangran, Wang Xizhi, Wang Zhuo

February 7, 2021

Summary

Use this template to begin typing the first page (summary page) of your electronic report. This template uses a 12-point Times New Roman font. Submit your paper as an Adobe PDF electronic file (e.g. 1111111.pdf), typed in English, with a readable font of at least 12-point type.

Do not include the name of your school, advisor, or team members on this or any page.

Papers must be within the 25 page limit.

Be sure to change the control number and problem choice above. You may delete these instructions as you begin to type your report here.

Follow us @COMAPMath on Twitter or COMAPCHINAOFFICIAL on Weibo for the most up to date contest information.

Keywords: Matlab; Mathematical modelling.

Contents

1 Introduction

1.1 Restatement of The Problem

1.2 Analysis of The Problem

1.3 Assumptions

2 The Buildup of The model and Calculating

From what is analyzed before, we can conclude that:

$$\frac{\partial(FR)}{\partial(ER)} = C_1 \tag{1}$$

$$\frac{\partial \ln(FR)}{\partial M} = C_2 \tag{2}$$

3 The Model Results

4 Validating the Model

5 Conclusions

6 A Summary

7 Evaluate of the Mode

8 Strengths and weaknesses

test
test
test!
test.

8.1 Strengths

- **Applies widely**
  This system can be used for many types[**?**] of airplanes, and it also solves the interference during the procedure of the boarding airplane,as described above we can get to the optimization boarding time.We also know that all the service is automate.
- **Improve the quality of the airport service**
  Balancing the cost of the cost and the benefit, it will bring in more convenient for airport and passengers.It also saves many human resources for the airline.
-

Appendices

Appendix A First appendix

In addition, your report must include a letter to the Chief Financial Officer (CFO) of the Goodgrant Foundation, Mr. Alpha Chiang, that describes the optimal investment strategy, your modeling approach and major results, and a brief discussion of your proposed concept of a return-on-investment (ROI). This letter should be no more than two pages in length.

Dear, Mr. Alpha Chiang

Sincerely yours,

Your friends

Here are simulation programmes we used in our model as follow.

Input matlab source:

```
function [t,seat,aisle]=OI6Sim(n,target,seated)
pab=rand(1,n);
for i=1:n
    if pab(i)<0.4
       aisleTime(i)=0;
    else
        aisleTime(i)=trirnd(3.2,7.1,38.7);
    end
end
```

Appendix B Second appendix

some more text **Input C++ source:**

```
//============================================================================
// Name        : Sudoku.cpp
// Author      : wzlf11
// Version     : a.0
// Copyright   : Your copyright notice
// Description : Sudoku in C++.
//============================================================================

#include <iostream>
#include <cstdlib>
#include <ctime>

using namespace std;

int table[9][9];

int main() {
```

```
    for(int i = 0; i < 9; i++){
        table[0][i] = i + 1;
    }

    srand((unsigned int)time(NULL));

    shuffle((int *)&table[0], 9);

    while(!put_line(1))
    {
        shuffle((int *)&table[0], 9);
    }

    for(int x = 0; x < 9; x++){
        for(int y = 0; y < 9; y++){
            cout << table[x][y] << " ";
        }

        cout << endl;
    }

    return 0;
}
```