


Meta-analyses in R

Cathalijn H.C. Leenaars, Ph.D.



Universiteit Utrecht



Hannover Medical School


Note

This presentation has been adapted for online posting. Example plots no longer correspond to the code on the slide before.

CC-BY 4.0

Systematic reviews

Why do Systematic Reviews (SRs) and Meta-Analyses (MAs)?



How to do an SR?



Meta-analyses

Meta-analyses in R

- Relatively simple
- Several packages: meta, metafor, rmeta, metagear, mvmeta, netmeta
- This presentation: meta, metafor and netmeta
 - Simple MA
 - Forest plot
 - Meta-regression
 - Weighted bubble plot
 - Network meta-analysis
- Not in this presentation: Importing your data

Before you start

- Load the relevant packages
- Get your data into R
- Check if the import went well
(`str`, `summary`, `dim`, `names`)
- Visualise the data to check if the structure is OK

```
1 # Load relevant packages
2 library(readxl)
3 library(meta)
4 library(metafor)
5 library(netmeta)
6
```


Simple MA function in R: metacont

- For continuous outcome data
- Comparing 2 conditions
- Fixed/ random effects
- Inverse variance weighting; SD

```
6 # simple MA with metacont function
7 ma_name <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, studlab, data=NULL,
8                     sm="MD", comb.fixed=FALSE, hakn=TRUE)
```

e → experimental; c → control

Running a meta-analysis; example output

```
> metaSWS <- metacont(n_sws, SWS, SWS_SD, n_wake, W, W_SD,  
+                      studlab = STUDY_ID, data=NAMDMA,  
+                      comb.fixed = FALSE, comb.random = TRUE,  
+                      hakn=TRUE, sm="SMD")  
> metaSWS
```

	SMD	95%-CI	%w(random)
Orosco_95	-0.6502	[-1.9427; 0.6423]	8.1
Shouse_00	-0.8912	[-2.1036; 0.3211]	8.6
Shouse_00	-1.6756	[-3.0719; -0.2794]	7.5
Shouse_01	-1.6010	[-2.7708; -0.4311]	8.8
Shouse_01	-2.4503	[-3.8347; -1.0659]	7.6
Shouse_01	-1.3045	[-2.4141; -0.1948]	9.2
Shouse_01	-2.3671	[-3.7282; -1.0059]	7.7
Park_02	-4.6418	[-7.5342; -1.7494]	2.9
Lena_05	-0.9325	[-2.1523; 0.2872]	8.5
Lena_05	-0.8889	[-2.1009; 0.3230]	8.6
Shouse_00	-3.3766	[-5.0428; -1.7104]	6.2
Shouse_00	-2.1948	[-3.5092; -0.8804]	8.0
DeSaintHilaire_00	0.2129	[-1.0325; 1.4583]	8.4

Number of studies combined: k = 13

	SMD	95%-CI	t	p-value
Random effects model	-1.5404	[-2.1902; -0.8906]	-5.17	0.0002

Quantifying heterogeneity:

$\tau^2 = 0.5214$; $H = 1.46$ [1.07; 2.00]; $I^2 = 53.3\%$ [12.3%; 75.1%]

Test of heterogeneity:

Q	d.f.	p-value
25.68	12	0.0119


Details on meta-analytical method:

Preliminary data

Creating a forest plot

```
17 #creating a forest plot
18 forest(ma_name, sortvar = Author, xlab = "Bone damage",
19        studlab = TRUE, overall = TRUE, test.overall.random = TRUE,
20        test.effect.subgroup = TRUE, leftcols = "studlab")
21
```

Example Forest Plot



General MA function in R: metagen

- Fixed/ random effects
- based on estimates (TE = Treatment Estimate)
 - MD/ SMD/ NMD → also for cross-over trials
 - Log hazard ratios
 - Risk difference
 - ...
- Inverse variance weighting; SE

```
10 #MA with metagen function
11 ma_name <- metagen(TE, seTE, studlab, data=NULL, sm="MD",
12                   comb.fixed=FALSE, hakn=TRUE)
13
14 #printing output
15 print(summary(ma_name), digits=2)
```

Meta-Regression

General MA function in R: rma


- Fixed/ random effects
- With or without moderators → meta-regression
- Inverse variance/ manual weighting

```
23 #meta-regression with rma function
24 mr_name <- rma(yi, sei, weights, mods,
25               knha=TRUE, data)
26
```

Creating the corresponding bubble plot

```
27 # creating a bubble plot
28 # create a vector with the actual weights
29 realweights <- weights (mr_name)
30 # make a bubble plot weight by precision
31 # note: if cex 2x larger, radius of bubble 2x larger, surface 4x
32 plot(objectname$columnforX,objectname$columnforY,cex=realweights,
33      pch=21, xlim=c(0,6), ylim=c(0,6),
34      xlab="Flowrate (μL/min)", ylab="Ln Adenosine (nM)")
```



Example bubble plot



Network Meta-analysis

Network meta-analysis

- Pairwise meta-analysis; compares pairs of treatments within a number of treatments for the same condition
- Transform your data (if needed)
- Fixed/ random effects
- based on estimates (TE = Treatment Estimate)
- Inverse variance weighting; SE



```
37 # Network MA
38 nm_name <-netmeta(TE, seTE, treat1, treat2, studlab, data=NULL,
39                   sm="SMD", comb.fixed=FALSE, reference.group="")
```

Resources

- Package documentation
- General R resources
- Meta-Analysis with R book (Use R!) – Schwarzer et al.