

CloudPlatform - API Reference and Integration Guide

Base URL and Authentication

Base URL: `https://api.cloudplatform.example.com/v1`

Authentication: Authenticate all requests using Authorization Bearer token header:

Authorization: Bearer YOUR_API_SECRET_KEY

Endpoint: List Projects (GET /projects)

Method: GET /projects

Query Parameters: limit (integer, default: 20, max: 100), status (active, archived)

Response Example:

```
{
  "status": "success",
  "data": [
    {
      "id": "proj_99812",
      "name": "ecommerce-backend",
      "status": "active",
      "created_at": "2026-01-15T09:00:00Z"
    }
  ]
}
```

Endpoint: Trigger Deployment (POST /projects/{project_id}/deploy)

Method: POST /projects/{project_id}/deploy

Request Body:

```
{
  "branch": "main",
  "commit_sha": "a1b2c3d4",
  "environment": "production"
}
```

Response Example:

```
{  
  "status": "success",  
  "deployment_id": "dep_456789",  
  "build_url": "https://dashboard.cloudplatform.example.com/deployments/dep_456789"  
}
```

Webhooks & Event Subscriptions

Register webhooks to receive real-time notifications for deployment events:

- Supported events: deployment.started, deployment.succeeded, deployment.failed
- Webhook payloads include HMAC-SHA256 signature in X-CloudPlatform-Signature header for verification.