SUPER FLOW

SUBMERSIBLE PUMP















design : www.maheshkeshur.com



Company Profile

Royal Manufacture is a professional and reputed organization engaged in manufacture and exporter of submersible water pumps, submersible water well pumps, submersible irrigation pumps, irrigation water pumps, stainless steel submersible pumps. V-3, V-4, V-5, V-6, V-7, V-8, V-9 Openwell submersible pumps are fast moving product of company. Since 2000 its ineptions the company has earned a name for itself on account of its world class quality. Royal Manufacture is reputed for its ethics, transparency, and etc.

Today Royal Manufacture is leading manufacturer of expert submersible pumps, submersible water pumps, irrigation pumps, Openwell pumps, monoblock pumps, Self priming pump, stainless steel submersible pumps and

pump set in India. With its credentials, experience & resources at command, Royal Manufacture hold prime & domineering position in the India pumps market. The The organization is managed by dynamic young perfessionals with zeal and commitment to customer satisfaction a and pragmatic approach to marketing.

It is the result of its dedicated efforts and quality products that the company has made a mark in its sphere of operation in a short span of time.

We have done all the manufacturing process in our factory.

All Product are tested in factory

Our Company's priority is customer satisfaction and quality services. we are the best in our quality and rotation with our customer

Our company's vision is to fulfill all need of our valuable customer. we are doing the R & D in our developed a new models and make movation in products. we are confident about we are in the list of top 3 companies in India in next 5 year

V-3 HIGH HEAD

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	0.37 kW to 1.1 kW (0.50 HP to 1.5HP)
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 100 Mtr
Maximum Flow Rate	110 LPM to 15 LPM
Nominal Outlet Size in Inches	1.0", 1.25"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 3" bore
Direction of Rotation	Counter clockwise from driving end -1 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph-Capacitor
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	**Bowl& Impeller**	: Glass Filled Engineered Polymer GF30
Motor Body Pipe	: Stainless Steel AISI 202	**Suction& NRV**	: CI FG:200
Casting Part	: CI FG:200	**Pump Shaft**	: Stainless Steel AISI 410
Thrust Bearing	: Carbon v/s Stainless Steel	**Pump Casing**	: Stainless Steel AISI 202
Motor Bush	: LTB-4	**All Hardware**	: Stainless Steel
Stamping	: Silicon Steel	**Pump Bush**	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	**Pump Sleeve**	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	**Pump Couple**	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Solar Application •Sprinkler system
- Fountains, Gardens

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Impeller and bowl are made from glass filled NORYL which gives strong resistance against sand.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- Motors are designed using multi layer PVC insulated wire to get better reliability and easy repairing at remote location.
- All parts machined on CNC to set consistent Quality performance.
- Thread type motor construction ensures service feasibility
- Can be installed with HDPE / UPVC Pipes.
- Light weight & Easy to operate in wide voltage band.
- Coupling is over self-aligning spline arrangement



V-3 HIGH HEAD

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM3-2	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	68	62	54	45	38	30	15	0	Pump Set
RM3-20510	0.5	0.37	10	1.0"	Head In Meter	10	15	20	25	30	35	40	46	9940/-
RM3-207515	0.75	0.55	15	1.0"		15	23	30	38	45	53	60	69	10930/-
RM3-2120	1.0	0.75	20	1.0"		20	30	40	50	60	70	80	91	12190/-
RM3-21525	1.5	1.10	25	1.0"		25	38	50	63	75	88	100	114	12900/-

Model Rm4	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	75	70	65	58	50	42	30	0	Pump Set
RM3-4058	0.5	0.37	8	1.0"	Head In Meter	8	12	16	20	24	28	32	37	9850/-
RM3-407512	0.75	0.55	12	1.0"		12	18	24	30	36	42	48	55	10678/-
RM3-4115	1.0	0.75	15	1.0"		15	23	30	38	45	53	60	69	11840/-
RM3-41520	1.5	1.10	20	1.0"		20	30	40	50	60	70	83	91	12760/-

Model Rm5	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	95	92	82	75	65	50	32	0	Pump Set
RM3-5056	0.5	0.37	6	1.25"	Head In Meter	6	9	12	15	18	21	24	37	9799/-
RM3-507510	0.75	0.55	10	1.25"		10	15	20	25	30	35	40	55	10625/-
RM3-5112	1.0	0.75	12	1.25"		12	18	24	30	36	42	48	69	11610/-
RM3-51515	1.5	1.10	15	1.25"		15	23	30	38	45	53	60	91	12600/-

Model Rm7	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	110	82	90	80	70	50	40	0	Pump Set
RM3-70758	0.75	0.5	8	1.25"	Head In Meter	8	12	16	20	24	28	32	37	10625/-
RM3-7110	1.0	0.75	10	1.25"		10	15	20	25	30	35	40	46	11470/-
RM3-71512	1.5	1.0	12	1.25"		12	18	24	30	36	42	48	55	12400/-
RM3-71514	1.5	1.1	14	1.25"		14	22	28	35	42	49	56	85	12600/-

V-4 PRIMIUM

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	0.5 HP to 3.0 HP SINGLE PHASE 1.0 HP to 5.0 HP THREE PHASE
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 388 Mtr
Maximum Flow Rate	455 LPM to 10 LPM
Nominal Outlet Size in Inches	1.0", 1.25", 1.5", 2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 4" bore
Direction of Rotation	Counter clockwise from driving end -1 ph Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph - Capacitor Start Capacitor Run 3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl& Impeller	: Glass Filled Engineered polymer GF30
Motor Body Pipe	: Stainless Steel AISI 202	Suction& NRV	: CI FG:200
Casting Part	: CI FG:200	Pump Shaft	: Stainless Steel AISI 410
Thrust Bearing	: Carbon/Teflon v/s Stainless Steel	Pump casing	: Stainless Steel AISI 202
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: Silicon Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive
Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Fully corrosive resistance stainless steel stator tube.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Designed for wide voltage operation
- Additional intermediate support through CI Middle and bush in higher stage pumps.



V-4 PRIMIUM

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM-1	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	54	48	41	37	27	18	0	1 Phase	3 Phase
RM-10510	0.5	0.37	10	25	Head In Meter	21	27	34	40	46	52	60	13250/-	-
RM-17515	0.75	0.56	15	25		32	41	50	60	69	78	90	15140/-	-
RM-11018	1.0	0.75	18	25		38	49	60	72	82	93	108	18020/-	-
RM-11525	1.5	1.12	25	25		53	69	84	100	114	130	150	21230/-	18350
RM-12030	2	1.49	30	25		34	82	101	120	137	155	180	23850/-	21700
RM-13035	3	2.24	35	25		75	92	117	140	160	181	210	27270/-	25150
RM-15045	5	3.7	45	25		96	123	151	180	206	233	270	-	32400

Model RM-2	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	76	71	61	48	44	31	0	1 Phase	3 Phase
RM-20507	0.5	0.37	7	25	Head In Meter	15	19	23	28	32	36	42	13040/-	-
RM-20508	0.5	0.37	8	25		8	16	24	32	36	40	48	13090/-	-
RM-27510	0.75	0.56	10	25		21	27	34	40	46	52	60	14750/-	-
RM-27512	0.75	0.56	12	25		26	33	40	48	55	62	72	14890/-	-
RM-21015	1.0	0.75	15	25		32	41	50	60	69	78	120	17790/-	15890/-
RM-21520	1.5	1.12	20	25		43	55	67	80	91	104	90	20840/-	17980/-
RM-22025	2	1.49	25	25		53	69	84	100	114	130	150	23340/-	21200/-
RM-23030	3	2.24	30	25		64	82	101	120	137	155	180	26800/-	24700/-
RM-25040	5	3.73	40	25		85	110	134	160	183	207	240	-	31450/-

Model RM-4	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	107	99	85	70	53	31	0	1 Phase	3 Phase
RM-40505	0.5	0.37	5	32	Head In Meter	11	14	17	20	23	26	30	12900/-	-
RM-47508	0.75	0.56	8	32		17	22	27	32	37	41	48	14630/-	-
RM-41010	1.0	0.75	10	32		21	27	34	40	46	52	60	17420/-	15500/-
RM-41012	1.0	0.75	12	32		26	33	40	48	55	62	72	17580/-	15640/-
RM-41515	1.5	1.12	15	32		32	41	50	60	69	78	90	20250/-	17400/-
RM-42020	2	1.49	20	32		43	55	67	80	91	104	120	22950/-	20800/-
RM-43025	3	2.24	25	32		53	69	84	100	114	130	150	26370/-	24260/-
RM-45035	5	3.73	35	32		75	96	117	140	160	181	210	-	30800/-

V-4 PRIMIUM

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM-5	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	147	128	97	92	80	68	0	1 Phase	3 Phase
RM-57506	0.75	0.56	6	38	Head In Meter	11	15	18	24	26	29	36	14620/-	-
RM-51512	1.5	1.12	12	38		26	33	40	48	55	62	72	20102/-	17260/-
RM-52015	2.0	1.49	15	38		27	37	46	60	64	73	90	22590/-	20440/-
RM-53020	3.0	2.24	20	38		37	49	61	80	85	98	120	26110/-	23995/-
RM-55030	5.0	3.73	30	38		55	73	91	120	128	146	180	-	30600/-

Model RM-7	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	190	175	151	110	95	78	0	1 Phase	3 Phase
RM-71508	1.5	1.12	8	50	Head In Meter	12	20	25	32	40	44	48	19950/-	-
RM-71510	1.5	1.12	10	50		15	21	27	40	44	46	58	20000/-	17188/-
RM-72012	2.0	1.49	12	50		22	29	37	48	52	59	72	22220/-	20080/-
RM-73015	3.0	2.24	15	50		27	37	46	60	66	73	90	25730/-	23600/-
RM-75025	5.0	3.73	25	50		46	61	76	100	109	122	150	-	30350/-

Model RM-10	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	192	179	155	130	130	105	0	1 Phase	3 Phase
RM-102010	2.0	1.49	10	50	Head In Meter	15	21	27	40	40	46	58	22100/-	19960/-
RM-103012	3.0	2.24	12	50		18	26	33	48	48	55	70	25480/-	23360/-
RM-105020	5.0	3.73	20	50		37	49	61	80	80	98	120	-	29800/-

Model RM-12	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	200	175	170	150	125	105	0	1 Phase	3 Phase
RM-121506	1.5	1.12	6	50		8	13	16	24	27	30	33	20028/-	-
RM-12310	3	2.24	10	50		15	21	27	40	40	50	55	25070/-	22950/-

Model RM-18	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE	
					LPM	336	312	250	195	162	84	0	1 Phase	3 Phase
RM-18206	2	1.5	6	50	Head In Meter	8	11	14	18	22	25	32	22160/-	-
RM-18308	3	2.2	8	50		11	15	19	24	29	33	43	27900/-	26190/-
RM-18515	5	3.7	15	50		20	27	35	45	55	62	80	-	29600/-

V-4 PRIMIUM Q-type CI

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM-20	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM									PRICE		
					LPM	455	405	370	320	275	200	150	0	1 Phase	2 Phase	3 Phase
RM-20206	2	1.5	6	65	Head In Meter	12	15	18	21	24	27	30	35	25990/-	25235/-	27085/-
RM-20306	3	2.3	6	65		12	15	18	21	24	27	30	35	29140/-	26915/-	28025/-
RM-20307	3	2.3	7	65		14	18	21	25	28	32	35	41	30120/-	27895/-	29000/-
RM-20308	3	2.3	8	65		16	20	24	28	32	36	40	47	30660/-	27990/-	29550/-
RM-20309	3	2.3	9	65		18	23	27	32	36	41	45	52	31350/-	-	-
RM-20409	4	3.0	9	65		18	23	27	32	36	41	45	52	-	-	30855/-
RM-20511	5	3.70	11	65		22	28	33	39	44	50	55	64	-	-	35715/-

V-4 NANO

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	1.0 HP to 3.0 HP SINGLE PHASE
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 388 Mtr
Maximum Flow Rate	455 LPM to 10 LPM
Nominal Outlet Size in Inches	1.0", 1.25", 1.5", 2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 4" bore
Direction of Rotation	Counter clockwise from driving end -1 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph - Capacitor Start Capacitor Run
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl& Impeller	: Glass Filled Engineered polymer GF30
Motor Body Pipe	: Stainless Steel AISI 202	Suction& NRV	: CI FG:200
Casting Part	: CI FG:200	Pump Shaft	: Stainless Steel AISI 410
Thrust Bearing	: Carbon/Teflon v/s Stainless Steel	Pump casing	: Stainless Steel AISI 202
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: Silicon Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive
Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Specially designed thread type motor construction to ensure more rigid structure with more better mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Designed for wide voltage operation
- Additional intermediate support through CI Middle and bush in higher stage pumps.



V-4 NANO

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM-1	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	47	42	36	33	24	15	0	1 Phase
RM-11018	1.0	0.75	18	25	Head In Meter	38	49	60	72	82	93	108	16950/-
RM-11524	1.5	1.12	25	25		53	69	84	100	114	130	150	19670/-
RM-12030	2	1.49	30	25		34	82	101	120	137	155	180	22130/-

Model RM-2	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	69	65	56	44	40	28	0	1 Phase
RM-21015	1.0	0.75	15	25	Head In Meter	32	41	50	60	69	78	120	16725/-
RM-21520	1.5	1.12	20	25		43	55	67	80	91	104	90	19300/-
RM-22024	2	1.49	25	25		53	69	84	100	114	130	150	21620/-
RM-23030	3	2.24	30	25		64	82	101	120	137	155	180	25180/-

Model RM-4	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	98	90	78	64	49	29	0	1 Phase
RM-41010	1.0	0.75	10	32	Head In Meter	21	27	34	40	46	52	60	16350/-
RM-41012	1.0	0.75	12	32		26	33	40	48	55	62	72	16510/-
RM-41515	1.5	1.12	15	32		32	41	50	60	69	78	90	18750/-
RM-42020	2	1.49	20	32		43	55	67	80	91	104	120	21240/-
RM-43025	3	2.24	25	32		53	69	84	100	114	130	150	24740/-

Model RM-5	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	128	112	85	80	70	60	0	1 Phase
RM-51512	1.5	1.12	12	38	Head In Meter	26	33	40	48	55	62	72	18620/-
RM-52015	2.0	1.49	15	38		27	37	46	60	64	73	90	20870/-
RM-53020	3.0	2.24	20	38		37	49	61	80	85	98	120	24480/-

Model RM-7	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	180	167	144	105	90	75	0	1 Phase
RM-71510	1.5	1.12	10	50	Head In Meter	15	21	27	40	44	46	58	18550/-
RM-72012	2.0	1.49	12	50		22	29	37	48	52	59	72	20495/-
RM-73015	3.0	2.24	15	50		27	37	46	60	66	73	90	24090/-

V-4 NANO

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM-10	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	192	179	155	130	120	105	0	1 Phase
RM-102010	2.0	1.49	10	50	Head In Meter	15	21	27	40	44	46	58	20390/-
RM-103012	3.0	2.24	12	50		18	26	33	48	52	55	70	23850/-

Model RM-12	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	204	182	174	154	133	112	0	1 Phase
RM-12310	3	2.24	10	50	Head In Meter	15	21	27	40	40	50	55	23440/-

V-4 MAGIC

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	0.5 HP to 2.0 HP SINGLE PHASE
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 388 Mtr
Maximum Flow Rate	455 LPM to 10 LPM
Nominal Outlet Size in Inches	1.0", 1.25", 1.5", 2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 4" bore
Direction of Rotation	Counter clockwise from driving end -1 ph Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph - Capacitor Start Capacitor Run 3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl& Impeller	: Glass Filled Engineered polymer GF30
Motor Body Pipe	: Stainless Steel AISI 202	Suction& NRV	: CI FG:200
Casting Part	: CI FG:200	Pump Shaft	: Stainless Steel AISI 410
Thrust Bearing	: Carbon/Teflon v/s Stainless Steel	Pump casing	: Stainless Steel AISI 202
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: CRC Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive
Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Specially designed thread type motor construction to ensure more rigid structure with more better mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Designed for wide voltage operation
- Additional intermediate support through CI Middle and bush in higher stage pumps.



V-4 MAGIC

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM-1	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	47	42	36	33	24	15	0	1 Phase
RM-10510	0.5	0.37	10	25	Head In Meter	21	27	34	40	46	52	60	11740/-
RM-17515	0.75	0.56	15	25		32	41	50	60	69	78	90	12790/-
RM-11018	1.0	0.75	18	25		38	49	60	72	82	93	108	14750/-
RM-11524	1.5	1.12	25	25		53	69	84	100	114	130	150	16575/-
RM-12030	2	1.49	30	25		34	82	101	120	137	155	180	18800/-

Model RM-2	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	69	65	56	44	40	28	0	1 Phase
RM-20508	0.5	0.37	8	25	Head In Meter	8	16	24	32	36	40	48	11600/-
RM-27510	0.75	0.56	10	25		21	27	34	40	46	52	60	12450/-
RM-27512	0.75	0.56	12	25		26	33	40	48	55	62	72	12600/-
RM-21015	1.0	0.75	15	25		32	41	50	60	69	78	120	14510/-
RM-21520	1.5	1.12	20	25		43	55	67	80	91	104	90	16140/-
RM-22024	2	1.49	25	25		53	69	84	100	114	130	150	18290/-

Model RM-4	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	98	90	78	64	49	29	0	1 Phase
RM-41010	1.0	0.75	10	32	Head In Meter	21	27	34	40	46	52	60	14160/-
RM-41012	1.0	0.75	12	32		26	33	40	48	55	62	72	14320/-
RM-41515	1.5	1.12	15	32		32	41	50	60	69	78	90	15650/-
RM-42020	2	1.49	20	32		43	55	67	80	91	104	120	17950/-

Model RM-5	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	128	112	85	80	70	60	0	1 Phase
RM-51512	1.5	1.12	12	38	Head In Meter	26	33	40	48	55	62	72	15450/-
RM-52015	2.0	1.49	15	38		27	37	46	60	64	73	90	17650/-

Model RM-7	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	180	167	144	105	90	75	0	1 Phase
RM-71510	1.5	1.12	10	50	Head In Meter	15	21	27	40	44	46	58	15420/-
RM-72012	2.0	1.49	12	50		22	29	37	48	52	59	72	17300/-

Model RM-10	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	192	179	155	130	120	105	0	1 Phase
RM-101508	1.5	1.12	8	50	Head In Meter	12	17	22	32	35	37	48	15420/-
RM-102010	2.0	1.49	10	50		15	21	27	40	44	46	58	17200/-

V-4 TURBO

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	0.5 HP to 5.0 HP SINGLE PHASE 1.0 HP to 7.5 HP THREE PHASE
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 388 Mtr
Maximum Flow Rate	455 LPM to 10 LPM
Nominal Outlet Size in Inches	1.0", 1.25", 1.5", 2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 4" bore
Direction of Rotation	Counter clockwise from driving end -1 ph Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph - Capacitor Start Capacitor Run 3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl& Impeller	: Glass Filled Engineered polymer GF30
Motor Body Pipe	: Stainless Steel AISI 202	Suction& NRV	: CI FG:200
Casting Part	: CI FG:200	Pump Shaft	: Stainless Steel AISI 410
Thrust Bearing	: Carbon/Teflon v/s Stainless Steel	Pump casing	: Stainless Steel AISI 202
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: Silicon Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive
Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Specially designed thread type motor construction to ensure more rigid structure with more better mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Designed for wide voltage operation
- Additional intermediate support through CI Middle and bush in higher stage pumps.



V-4 TURBO

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

R-1 Star (27 Feet Head) MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	Head In Meter	68	55	48	40	35	31	20	1 Phase	3 Phase
RM1S-225	2	1.5	25		75	100	113	125	138	150	175	27480/-	-
RM1S-335	3	2.2	35		105	140	157	175	192	210	222	32324/-	31246/-
RM1S-550	5	3.7	50		150	198	225	250	275	298	350	-	39350/-

ModelR-2 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	LPM	77	68	62	52	45	38	26	1 Phase	3 Phase
RM2-220	2	1.5	20	Head In Meter	60	79	90	100	110	119	140	26900/-	-
RM2-330	3	2.2	30		90	119	135	150	165	179	210	29736/-	30530/-
RM2-545	5	3.7	45		135	178	202	225	247	268	315	-	38933/-
RM2-6555	6.5	4.5	55		165	217	247	275	302	327	385	-	45090/-
RM2-7558	7.5	5.5	60		180	237	269	300	329	357	420	-	49230/-

ModelR-3 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	LPM	85	77	70	62	52	47	36	1 Phase	3 Phase
RM3-216	2	1.5	16	Head In Meter	48	64	73	80	89	97	112	26150/-	-
RM3-325	3	2.2	25		75	100	114	125	139	151	175	30658/-	29580/-
RM3-540	5	3.7	40		120	160	182	200	222	242	280	-	37720/-
RM3-6545	6.5	4.5	45		135	180	204	225	250	272	315	-	43650/-
RM3-7555	7.5	5.5	55		165	120	250	275	305	232	385	-	48415/-

V-4 TURBO

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

ModelR-4 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.P.M.								PRICE	
Model	H.P.	K.W.	STG	LPH	87	78	73	66	59	52	40	1 Phase	3 Phase
RM4-215	2	1.5	15	Head In Meter	45	60	68	75	83	90	105	25960/-	-
RM4-320	3	2.2	20		60	80	91	100	110	120	140	29736/-	28650/-
RM4-535	5	3.7	35		105	140	158	175	192	210	245	-	36824/-
RM4-6540	6.5	4.5	40		120	160	182	200	220	240	280	-	42830/-
RM4-7550	7.5	5.5	50		150	200	227	250	275	300	350	-	46800/-

ModelR-5 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.P.M.								PRICE	
Model	H.P.	K.W.	STG	LPM	112	99	91	78	70	60	33	1 Phase	3 Phase
RM5-212	2	1.5	12	Head In Meter	36	48	54	60	66	71	81	25612/-	

J-17 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.P.M.								PRICE	
Model	H.P.	K.W.	STG	165	150	140	130	120	110	100	80	1 Phase	3 Phase
RM17-212	2	1.5	12	24	30	36	42	48	54	60	66	25200/-	-
RM17-320	3	2.2	20	40	50	60	70	80	90	100	110	29890/-	28815/-
RM17-530	5	3.7	30	60	75	90	105	12	135	150	165	-	35990/-
RM17-6535	6.5	4.5	35	70	88	105	122	140	158	175	192	-	41940/-

V-4 TURBO

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

J-19 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160 DISCHARGE IN L.PM.								TURBO MODEL PRICE	
Model	H.P.	K.W.	STG	180	170	160	15	140	130	110	90	1 Phase	3 Phase
RM19-210	2	1.5	10	20	25	30	35	40	45	50	55	25030/-	-
RM19-315	3	2.2	15	30	38	45	53	60	68	75	83	28700/-	27850/-
RM19-317	3	2.2	17	34	43	51	60	68	77	85	94	29070/-	28210/-
RM19-525	5	3.7	25	50	63	75	88	100	113	125	138	-	34890/-
RM19-6530	6.5	4.5	30	60	75	90	105	120	135	150	165	-	40760/-
RM19-7535	7.5	5.5	35	70	88	105	123	140	158	175	193	-	44300/-
RM19-7540	7.5	5.5	40	80	100	120	140	160	180	200	220	-	45500/-

J-22 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160 DISCHARGE IN L.PM.								TURBO MODEL PRICE	
Model	H.P.	K.W.	STG	200	190	180	170	165	150	140	120	1 Phase	3 Phase
RM22-312	3	2.2	12	24	30	36	42	48	54	60	66	28100/-	27250/-
RM22-520	5	3.7	20	40	50	60	70	80	90	100	110	-	33615/-
RM22-6525	6.5	4.5	25	50	62	75	88	100	113	125	138	-	39437/-
RM22-7530	7.5	5.5	30	60	75	90	105	120	135	150	165	-	43225/-

RM40 MIXFLOW 16 Feet Head MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160 DISCHARGE IN L.PM.								TURBO MODEL PRICE	
Model	H.P.	K.W.	STG	465	400	375	320	280	230	160	120	1 Phase	3 Phase
RM40-26	2	1.5	6	6	12	15	18	21	23	24	27	25946/-	-
RM40-38	3	2.2	8	8	16	20	24	28	30	32	36	29675/-	28820/-
RM40-512	5	3.7	12	12	24	30	36	42	46	48	54	-	35672/-
RM40-6514	6.5	4.5	14	14	28	35	42	49	53	56	63	-	41500/-

V-4 TURBO

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

RM-35 MIXFLOW 18 Feet Head MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	425	360	325	280	240	180	120	80	1 Phase	3 Phase
RM35-28	2	1.5	8	6	12	15	18	21	23	24	27	26920/-	-
RM35-310	3	2.2	10	10	16	20	24	28	30	32	36	30635/-	29777/-
RM35-514	5	3.7	14	14	24	30	36	42	46	48	54	-	36690/-

V-4 TURBO MIX FLOW CI

SUBMERSIBLE PUMP SET

ModelR-20 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	LPM	455	405	370	320	275	200	150	0	1 Phase	3 Phase
RM-20206	2	1.5	6	Head In Meter	12	15	18	21	24	27	30	35	28246/-	-
RM-20307	3	2.3	7		14	18	21	25	28	32	35	41	32190/-	31090/-
RM-20511	5	3.70	11		22	28	33	39	44	50	55	64	-	36870/-
RM-206514	6.5	4.5	14		28	36	42	50	56	64	70	81	-	42140/-
RM-207518	7.5	5.5	18		36	46	54	64	72	82	90	105	-	47150/-

V-4 SU - 98 DAI SINGLE & THREE PHASE PUMP SET

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	0.5 HP to 5.0 HP SINGLE PHASE 1.0 HP to 7.5 HP THREE PHASE
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 388 Mtr
Maximum Flow Rate	455 LPM to 10 LPM
Nominal Outlet Size in Inches	1.0", 1.25", 1.5", 2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 4" bore
Direction of Rotation	Counter clockwise from driving end -1 ph Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph - Capacitor Start Capacitor Run 3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl& Impeller	: Glass Filled Engineered polymer GF30
Motor Body Pipe	: Stainless Steel AISI 202	Suction& NRV	: CI FG:200
Casting Part	: CI FG:200	Pump Shaft	: Stainless Steel AISI 410
Thrust Bearing	: Carbon/Teflon v/s Stainless Steel	Pump casing	: Stainless Steel AISI 202
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: Silicon Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive
Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Specially designed thread type motor construction to ensure more rigid structure with more better mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Designed for wide voltage operation
- Additional intermediate support through CI Middle and bush in higher stage pumps.



V-4 98 DAI SINGLE & THREE PHASE PUMP SET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

R-1 Star (27 Feet Head) MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG		68	55	48	40	35	31	20	1 Phase	3 Phase
RM1S-225	2	1.5	25	Head In Meter	75	100	113	125	138	150	175	25110/-	-
RM1S-335	3	2.2	35		105	140	157	175	192	210	222	29980/-	28860/-
RM1S-550	5	3.7	50		150	198	225	250	275	298	350	-	36120/-

ModelR-2 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	LPM	77	68	62	52	45	38	26	1 Phase	3 Phase
RM2-220	2	1.5	20	Head In Meter	60	79	90	100	110	119	140	24570/-	-
RM2-330	3	2.2	30		90	119	135	150	165	179	210	29290/-	28170/-
RM2-545	5	3.7	45		135	178	202	225	247	268	315	-	35730/-
RM2-6555	6.5	4.5	55		165	217	247	275	302	327	385	-	42570/-
RM2-7560	7.5	5.5	60		180	237	269	300	329	357	420	-	46140/-

ModelR-3 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	LPM	85	77	70	62	52	47	36	1 Phase	3 Phase
RM3-216	2	1.5	16	Head In Meter	48	64	73	80	89	97	112	23870/-	-
RM3-325	3	2.2	25		75	100	114	125	139	151	175	28040/-	26922/-
RM3-540	5	3.7	40		120	160	182	200	222	242	280	-	34435/-
RM3-6545	6.5	4.5	45		135	180	204	225	250	272	315	-	41130/-
RM3-7555	7.5	5.5	55		165	120	250	275	305	232	385	-	45315/-

V-4

98 DAI SINGLE & THREE PHASE PUMP SET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

ModelR-4 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.P.M.								PRICE	
Model	H.P.	K.W.	STG	LPH	87	78	73	66	59	52	40	1 Phase	3 Phase
RM4-215	2	1.5	15	Head In Meter	45	60	68	75	83	90	105	23690/-	-
RM4-320	3	2.2	20		60	80	91	100	110	120	140	27500/-	26380/-
RM4-535	5	3.7	35		105	140	158	175	192	210	245	-	33700/-
RM4-6540	6.5	4.5	40		120	160	182	200	220	240	280	-	40310/-
RM4-7550	7.5	5.5	50		150	200	227	250	275	300	350	-	44000/-

ModelR-5 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.P.M.								PRICE	
Model	H.P.	K.W.	STG	LPM	112	99	91	78	70	60	33	1 Phase	3 Phase
RM5-212	2	1.5	12	Head In Meter	36	48	54	60	66	71	81	23370/-	

J-17 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.P.M.								PRICE	
Model	H.P.	K.W.	STG	165	150	140	130	120	110	100	80	1 Phase	3 Phase
RM17-212	2	1.5	12	24	30	36	42	48	54	60	66	23010/-	-
RM17-320	3	2.2	20	40	50	60	70	80	90	100	110	27660/-	26535/-
RM17-530	5	3.7	30	60	75	90	105	12	135	150	165	-	32900/-
RM17-6535	6.5	4.5	35	70	88	105	122	140	158	175	192	-	39430/-

V-4

98 DAI SINGLE & THREE PHASE PUMP SET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

J-19 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	180	170	160	15	140	130	110	90	1 Phase	3 Phase
RM19-210	2	1.5	10	20	25	30	35	40	45	50	55	22640/-	-
RM19-315	3	2.2	15	30	38	45	53	60	68	75	83	26535/-	25415/-
RM19-317	3	2.2	17	34	43	51	60	68	77	85	94	26890/-	25765/-
RM19-525	5	3.7	25	50	63	75	88	100	113	125	138	-	31620/-
RM19-6530	6.5	4.5	30	60	75	90	105	120	135	150	165	-	38250/-
RM19-7535	7.5	5.5	35	70	88	105	123	140	158	175	193	-	41170/-
RM19-7540	7.5	5.5	40	80	100	120	140	160	180	200	220	-	42370/-

J-22 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	200	190	180	170	165	150	140	120	1 Phase	3 Phase
RM22-312	3	2.2	12	24	30	36	42	48	54	60	66	25950/-	24830/-
RM22-520	5	3.7	20	40	50	60	70	80	90	100	110	-	30625/-
RM22-6525	6.5	4.5	25	50	62	75	88	100	113	125	138	-	36930/-
RM22-7530	7.5	5.5	30	60	75	90	105	120	135	150	165	-	40100/-

V-4

98 DAI SINGLE & THREE PHASE PUMP SET MIX FLOW

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

RM40 MIXFLOW 16 Feet Head MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	465	400	375	320	280	230	160	120	1 Phase	3 Phase
RM40-26	2	1.5	6	6	12	15	18	21	23	24	27	23500/-	-
RM40-38	3	2.2	8	8	16	20	24	28	30	32	36	27600/-	26460/-
RM40-512	5	3.7	12	12	24	30	36	42	46	48	54	-	32600/-
RM40-6514	6.5	4.5	14	14	28	35	42	49	53	56	63	-	38990/-

RM40 MIXFLOW 18 Feet Head MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160								TURBO MODEL	
				DISCHARGE IN L.PM.								PRICE	
Model	H.P.	K.W.	STG	425	360	325	280	240	180	120	80	1 Phase	3 Phase
RM35-28	2	1.5	8	6	12	15	18	21	23	24	27	24425/-	-
RM35-310	3	2.2	10	10	16	20	24	28	30	32	36	28540/-	27420/-
RM35-514	5	3.7	14	14	24	30	36	42	46	48	54	-	33620/-

V-4

98 DAI SINGLE & THREE PHASE PUMP SET MIX FLOW CI

SUBMERSIBLE PUMP SET

ModelR-20 MOTOR RATING				THREE PHASE LOW VOLT MOTOR 380 V TO 220 V AND SINGLE PHASE LOW VOLT MOTOR 220 V TO 160									TURBO MODEL	
				DISCHARGE IN L.PM.									PRICE	
Model	H.P.	K.W.	STG	LPM	455	405	370	320	275	200	150	0	1 Phase	3 Phase
RM-20206	2	1.5	6	Head In Meter	12	15	18	21	24	27	30	35	26107/-	-
RM-20307	3	2.3	7		14	18	21	25	28	32	35	41	30060/-	28920/-
RM-20511	5	3.70	11		22	28	33	39	44	50	55	64	-	34140/-
RM-206514	6.5	4.5	14		28	36	42	50	56	64	70	81	-	39830/-
RM-207518	7.5	5.5	18		36	46	54	64	72	82	90	105	-	44260/-

V-5 MIX FLOW

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	3.0 HP to 5.0 HP SINGLE PHASE 3.0 HP to 7.5 HP THREE PHASE
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	6 Mtr. to 96 Mtr
Maximum Flow Rate	740 LPM to 150 LPM
Nominal Outlet Size in Inches	2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 5" bore
Direction of Rotation	Counter clockwise from driving end -1 ph Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph - Capacitor Start Capacitor Run 3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl	: CI FG:200
Motor Body Pipe	: Stainless Steel AISI 202	Impeller	: Stainless Steel AISI 410
Casting Part	: CI FG:200	Suction& NRV	: CI FG:200
Thrust Bearing	: Carbon v/s Stainless Steel	Pump Shaft	: Stainless Steel AISI 410
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: Silicon Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive
Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Thread type motor construction ensures service feasibility
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Motors are designed using multi layer PVC insulated wire to get better reliability and easy repairing at remote location.
- Designed for wide voltage operation



V-5 MIX FLOW

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Model RM5M-80	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	620	590	626	480	430	350	220	0	Pump Set
RM5M-8033	3.0	2.20	4	2.5"	Head In Meter	8	12	16	20	24	28	32	40	35570/-
RM5M-8045	4.0	3.00	5	2.5"		10	15	20	25	30	35	40	50	39610/-
RM5M-8068	6.0	4.50	8	2.5"		16	24	28	40	48	56	64	80	47120/-
RM5M-807510	7.5	5.50	10	2.5"		20	30	40	50	60	70	80	100	51500/-

Model RM5M-100	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	700	655	615	540	470	380	245	0	Pump Set
RM5M-10033	3.0	2.20	3	2.5"	Head In Meter	6	9	12	15	18	21	24	30	33750/-
RM5M-10044	4.0	3.00	4	2.5"		8	12	16	20	24	28	32	40	37800/-
RM5M-10055	5.0	3.70	5	2.5"		10	15	20	25	30	35	40	50	40100/-
RM5M-10066	6.0	4.50	6	2.5"		12	18	24	30	36	42	48	60	43640/-
RM5M-100758	7.5	5.50	8	2.5"		16	24	32	40	48	56	64	80	47730/-

Model RM5M-125	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	700	710	665	620	560	480	370	0	Pump Set
RM5M-12554	5.0	3.70	4	2.5"	Head In Meter	8	12	16	20	24	28	32	43	38290/-
RM5M-12565	6.0	4.50	5	2.5"		10	15	20	25	30	35	40	54	41830/-
RM5M-125756	7.5	5.50	6	2.5"		12	18	24	30	36	42	48	65	44240/-

V-6 PRIMIUM 50 FEET

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	2.20 kW to 22.0 kW (3.0 HP to 20.0HP)
Speed	2800 RPM
Version	Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	12 Mtr. to 434 Mtr
Maximum Flow Rate	680 LPM to 60 LPM
Nominal Outlet Size in Inches	2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 6" bore
Direction of Rotation	Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		**Pump**	
Motor Shaft	: Stainless Steel AISI 410	Bowl	: Stainless Steel AISI 304
Motor Body Pipe	: Stainless Steel AISI 202	Impeller	: Stainless Steel AISI 410
Casting Part	: CI FG:200	Suction& NRV	: CI FG:200
Thrust Bearing	: Carbon v/s Stainless Steel	Pump Shaft	: Stainless Steel AISI 410
Motor Bush	: LTB-4	Pump Tierod	: Stainless Steel AISI 304
Stamping	: Silicon Steel.	All Hardware	: Stainless Steel
Copper	: EC Grade 99.9% Copper	Pump Bush	: NBR / LTB4
Winding Wire	: Multilayer Polyester Insulated	Pump Sleeve	: Hard Chromed SS-410
Oil Seal	: NBR	Pump Couple	: SS-410

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- SS304 Grade Investment Casting Bowl and SS410 Impeller With 50 feet head.
- T-Bolt type motor construction of TURBO model ensures more mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Higher HP motors to have premium SILICON CARBIDE bearings.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Thread type motor construction ensures service feasibility
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Using GM Bush and SS/NBR bush in alternate sequence ensures higher mechanical stability of pump
- Usage of gasket per stage in higher stages pump ensures no leakage even at higher pressure.



V-6 PRIMIUM 50 FEET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

SS-50				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	40	80	90	110	135	160	190	
RM 50306	2.2	3	6		84	78	73	69	60	48	33	42410/-
RM 505010	3.7	5	10		140	130	122	115	100	80	55	53100/-
RM 506012	4.5	6	12		168	156	146	138	120	96	66	57108/-
RM 507514	5.5	7.5	14		196	182	171	161	140	112	77	64738/-
RM 507515	5.5	7.5	15		210	195	183	172	150	120	82	66422/-
RM 501020	7.5	10	20		280	260	244	230	200	160	110	85980/-
RM 5012525	9.3	12.5	25		350	325	305	287	250	200	137	98585/-
RM 501530	11	15	30		418	390	365	345	300	240	165	111100/-

SS-60				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	75	115	130	150	175	205	225	
RM 60305	2.2	3	5		75	70	66	60	52	45	35	40767/-
RM 60508	3.7	5	8		120	112	105	96	82	72	56	49820/-
RM 606010	4.5	6	10		150	140	130	120	102	90	70	53820/-
RM 607512	5.5	7.5	12		180	168	158	144	123	108	84	61360/-
RM 601015	7.5	10	15		225	210	197	180	154	107	105	77270/-
RM 601016	9.3	10	16		240	224	210	192	164	144	112	79100/-
RM 6012520	11	12.5	20		300	280	264	240	205	180	140	89870/-
RM 601524	13.1	15	24		360	336	316	288	246	216	168	100628/-
RM 6017528	15	17.5	28		405	378	356	324	277	243	190	116015/-
RM 602032	15	20	32		450	420	395	360	308	270	210	126530/-

SS-80				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	90	140	165	200	250	275	320	
RM 60304	2.2	3	4		60	56	53	48	36	28	18	39690/-
RM 60506	3.7	5	6		90	84	79	72	54	42	27	47380/-
RM 60608	4.5	6	8		120	112	105	96	72	56	36	51660/-
RM 607510	5.5	7.5	10		150	140	132	120	90	70	45	59440/-
RM 601012	7.5	10	12		180	167	158	144	108	84	54	73840/-
RM 6012515	9.3	12.5	15		225	210	198	180	135	105	68	83400/-
RM 601518	11	15	18		270	252	238	216	162	126	81	92865/-
RM 6017522	13.1	17.5	22		330	308	290	264	198	154	99	108675/-
RM 602025	15	20	25		375	350	330	300	225	175	112	117865/-

V-6 PRIMIUM 50 FEET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

SS-100				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	110	190	230	260	320	370	410	
RM 10033	2.2	3	3		45	42	37	36	30	23	15	37900/-
RM 10055	3.7	5	5		75	70	64	60	50	39	25	45590/-
RM 10066	4.5	6	6		90	84	77	72	60	46	30	48090/-
RM 100758	5.5	7.5	8		120	112	103	96	80	62	40	55780/-
RM 1001010	7.5	10	10		150	140	130	120	100	78	50	70050/-
RM 10012512	9.3	12.5	12		180	168	155	144	120	93	60	77720/-
RM 1001515	11	15	15		225	210	193	180	150	116	75	87190/-
RM 10017518	13.1	17.5	18		270	252	232	216	180	140	90	100910/-
RM 1002022	15	20	22		300	280	258	240	200	155	100	108169/-

SS-125				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	130	240	280	340	450	500	550	
RM 12554	3.7	5	4		60	56	53	48	36	28	20	44195/-
RM 12565	4.5	6	5		75	70	66	60	45	35	25	46795/-
RM 125756	5.5	7.5	6		90	84	80	72	54	42	30	52710/-
RM 125108	7.5	10	8		120	112	106	96	72	56	40	67080/-
RM 12512510	9.3	12.5	10		150	140	133	120	90	70	50	74960/-
RM 1251512	11	15	12		180	168	160	144	108	84	60	82740/-
RM 12517514	13.1	17.5	14		210	195	186	168	126	98	70	94630/-
.RM 1252016	15	20	16		240	224	212	192	144	112	80	102065/-

SS-150				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	135	320	350	400	505	550	600	
RM 15032	2.2	3	2		30	28	26	24	18	14	10	36310-
RM 15053	3.7	5	3		45	41	40	36	27	21	15	42320/-
RM 15064	4.5	6	4		60	55	53	48	43	28	20	44910/-
RM 150755	5.5	7.5	5		75	69	66	60	45	35	25	50780/-
RM 150106	7.5	10	6		105	97	92	84	63	49	35	63077/-
RM 150107	7.5	10	7		105	98	91	84	63	49	35	
RM 1501258	9.3	12.5	8		120	110	106	96	72	56	40	70970/-
RM 1501510	11	15	10		150	140	130	120	90	70	50	78750/-
RM 15017512	13.1	17.5	12		180	166	158	144	108	84	60	90550/-
RM 1502013	15	20	13		195	180	172	156	117	91	65	95960/-

V-6 PRIMIUM 50 FEET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

SS-200				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	130	375	410	510	590	690	810	
RM 20063	4.5	6	3		45	42	40	36	30	23	10	43030/-
RM 200754	5.5	7.5	4		60	56	53	48	40	30	14	48850/-
RM 200105	7.5	10	5		75	70	66	60	50	37	17	61100/-
RM 2001256	9.3	12.5	6		90	84	80	72	60	45	21	66980/-
RM 200158	11	15	8		120	112	105	96	80	60	27	74755/-
RM 2001759	13.1	17.5	9		135	126	118	108	90	66	31	84410/-
RM 2002010	15	20	10		150	140	132	120	100	74	35	89825/-

V-6 PRIMIUM JACKET

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	2.20 kW to 22.0 kW (3.0 HP to 20.0HP)
Speed	2800 RPM
Version	Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	12 Mtr. to 434 Mtr
Maximum Flow Rate	680 LPM to 60 LPM
Nominal Outlet Size in Inches	2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 6" bore
Direction of Rotation	Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		**Pump**	
Motor Shaft	: Stainless Steel AISI 410	Bowl	: CI FG:200
Motor Body Pipe	: Stainless Steel AISI 202	Impeller	: SS 304
Casting Part	: CI FG:200	Suction& NRV	: CI FG:200
Thrust Bearing	: Carbon v/s Stainless Steel	Pump Shaft	: Stainless Steel AISI 410
Motor Bush	: LTB-4	Pump Tierod	: Stainless Steel AISI 304
Stamping	: Silicon Steel.	All Hardware	: Stainless Steel
Copper	: EC Grade 99.9% Copper	Pump Bush	: NBR / LTB4
Winding Wire	: Multilayer Polyester Insulated	Pump Sleeve	: Hard Chromed SS-410
Oil Seal	: NBR	Pump Couple	: SS-410

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- CI Grade Casting Bowl and SS410 Impeller With 50 feet head.
- T-Bolt type motor construction of TURBO model ensures more mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Higher HP motors to have premium SILICON CARBIDE bearings.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Thread type motor construction ensures service feasibility
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Using GM Bush and SS/NBR bush in alternate sequence ensures higher mechanical stability of pump
- Usage of gasket per stage in higher stages pump ensures no leakage even at higher pressure.



V-6 PRIMIUM JACKET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

SS-50				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	40	80	90	110	135	160	190	
JKT 50306	2.2	3	6		84	78	73	69	60	48	33	40110/-
JKT 505010	3.7	5	10		140	130	122	115	100	80	55	49470/-
JKT 506012	4.5	6	12		168	156	146	138	120	96	66	52794/-
JKT 507514	5.5	7.5	14		196	182	171	161	140	112	77	59622/-
JKT 507515	5.5	7.5	15		210	195	183	172	150	120	82	60965/-
JKT 501020	7.5	10	20		280	260	244	230	200	160	110	78555/-
JKT 5012525	9.3	12.5	25		350	325	305	287	250	200	137	89378/-
JKT 501530	11	15	30		418	390	365	345	300	240	165	102560/-

SS-60				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	75	115	130	150	175	205	225	
JKT 60305	2.2	3	5		75	70	66	60	52	45	35	38800/-
JKT 60508	3.7	5	8		120	112	105	96	82	72	56	46850/-
JKT 606010	4.5	6	10		150	140	130	120	102	90	70	50180/-
JKT 607512	5.5	7.5	12		180	168	158	144	123	108	84	56940/-
JKT 601015	7.5	10	15		225	210	197	180	154	107	105	71625/-
JKT 601016	9.3	10	16		240	224	210	192	164	144	112	73010/-
JKT 6012520	11	12.5	20		300	280	264	240	205	180	140	82440/-
JKT 601524	13.1	15	24		360	336	316	288	246	216	168	94030/-
JKT 6017528	15	17.5	28		405	378	356	324	277	243	190	105485/-
JKT 602032	15	20	32		450	420	395	360	308	270	210	114540/-

SS-80				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	90	140	165	200	250	275	320	
JKT 60304	2.2	3	4		60	56	53	48	36	28	18	37610/-
JKT 60506	3.7	5	6		90	84	79	72	54	42	27	44400/-
JKT 60608	4.5	6	8		120	112	105	96	72	56	36	47790/-
JKT 607510	5.5	7.5	10		150	140	132	120	90	70	45	54545/-
JKT 601012	7.5	10	12		180	167	158	144	108	84	54	67820/-
JKT 6012515	9.3	12.5	15		225	210	198	180	135	105	68	75958/-
JKT 601518	11	15	18		270	252	238	216	162	126	81	86060/-
JKT 6017522	13.1	17.5	22		330	308	290	264	198	154	99	97630/-
JKT 602025	15	20	25		375	350	330	300	225	175	112	105360/-
JKT 602530	18.7	25	30		450	418	395	360	270	210	135	

V-6 PRIMIUM JACKET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

SS-100				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	110	190	230	260	320	370	410	
JKT 10033	2.2	3	3	45	42	37	36	30	23	15	36270/-
JKT 10055	3.7	5	5	75	70	64	60	50	39	25	43070/-
JKT 10066	4.5	6	6	90	84	77	72	60	46	30	45120/-
JKT 100758	5.5	7.5	8	120	112	103	96	80	62	40	51800/-
JKT 1001010	7.5	10	10	150	140	130	120	100	78	50	64990/-
JKT 10012512	9.3	12.5	12	180	168	155	144	120	93	60	71707/-
JKT 1001515	11	15	15	225	210	193	180	150	116	75	81700/-
JKT 10017518	13.1	17.5	18	270	252	232	216	180	140	90	91826/-
JKT 1002022	15	20	22	300	280	258	240	200	155	100	98099/-

HEAD IN METER

SS-125				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	130	240	280	340	450	500	550	
JKT 12554	3.7	5	4	60	56	53	48	36	28	20	41960/-
JKT 12565	4.5	6	5	75	70	66	60	45	35	25	44070/-
JKT 125756	5.5	7.5	6	90	84	80	72	54	42	30	49410/-
JKT 125108	7.5	10	8	120	112	106	96	72	56	40	62630/-
JKT 12512510	9.3	12.5	10	150	140	133	120	90	70	50	69470/-
JKT 1251512	11	15	12	180	168	160	144	108	84	60	78080/-
JKT 12517514	13.1	17.5	14	210	195	186	168	126	98	70	86876/-
JKT 1252016	15	20	16	240	224	212	192	144	112	80	93270/-

HEAD IN METER

SS-150				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	135	320	350	400	505	550	600	
JKT 15032	2.2	3	2	30	28	26	24	18	14	10	35050/-
JKT 15053	3.7	5	3	45	41	40	36	27	21	15	40570/-
JKT 15064	4.5	6	4	60	55	53	48	43	28	20	42675/-
JKT 150755	5.5	7.5	5	75	69	66	60	45	35	25	47985/-
JKT 150106	7.5	10	6	105	97	92	84	63	49	35	59680/-
JKT 150107	7.5	10	7	105	98	91	84	63	49	35	61160/-
JKT 1501258	9.3	12.5	8	120	110	106	96	72	56	40	66518/-
JKT 1501510	11	15	10	150	140	130	120	90	70	50	75060/-
JKT 15017512	13.1	17.5	12	180	166	158	144	108	84	6	83857/-
JKT 1502013	15	20	13	195	180	172	156	117	91	65	88736/-

HEAD IN METER

V-6 PRIMIUM JACKET

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

SS-200				DISCHARGE LITER / MINUTE							PRICE
Model	K.W.	H.P.	STG	HEAD IN METER	130	375	410	510	590	690	810	
JKT 20063	4.5	6	3		45	42	40	36	30	23	10	41490/-
JKT 200754	5.5	7.5	4		60	56	53	48	40	30	14	46845/-
JKT 200105	7.5	10	5		75	70	66	60	50	37	17	58575/-
JKT 2001256	9.3	12.5	6		90	84	80	72	60	45	21	64010/-
JKT 200158	11	15	8		120	112	105	96	80	60	27	72645/-
JKT 2001759	13.1	17.5	9		135	126	118	108	90	66	31	80000/-
JKT 2002010	15	20	10		150	140	132	120	100	74	35	84960/-

V-6 Q TYPE (MIX FLOW)

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	2.20 kW to 15.0 kW (3.0 HP to 20.0HP)
Speed	2800 RPM
Version	Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	6 Mtr. to 180 Mtr
Maximum Flow Rate	1625 LPM to 275 LPM
Nominal Outlet Size in Inches	2.5", 3.0", 4.0"(ONLY IN AP67M SERIES)
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 6" bore
Direction of Rotation	Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		Pump	
Motor Shaft	: Stainless Steel AISI 410	Bowl	: CI FG:200
Motor Body Pipe	: Stainless Steel AISI 202	Impeller	: Stainless Steel AISI 410
Casting Part	: CI FG:200	Suction& NRV	: CI FG:200
Thrust Bearing	: Carbon v/s Stainless Steel	Pump Shaft	: Stainless Steel AISI 410
Motor Bush	: LTB-4	All Hardware	: Stainless Steel
Stamping	: Silicon Steel.	Pump Bush	: NBR / LTB4
Copper	: EC Grade 99.9% Copper	Pump Sleeve	: Hard Chromed SS-410
Winding Wire	: Multilayer Polyester Insulated	Pump Couple	: SS-410
Oil Seal	: NBR		

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- FG:200 Grade CI Casting Bowl and SS410 Impeller With 35-40 feet head in AP6M Series and 55-60 feet head AP67M Series.
- T-Bolt type motor construction of TURBO model ensures more mechanical stability.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Higher HP motors to have premium SILICON CARBIDE bearings.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Thread type motor construction ensures service feasibility.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Using GM Bush and SS/NBR bush in alternate sequence ensures higher mechanical stability of pump.



V-6 Q TYPE (MIX FLOW)

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

CI Bowl & SS Impller. 35 To 45 Feet Head Per Stage

Head Per Stage - 35' Feet (10.6 Meter)

RM-262-08				DISCHARGE IN LPM								Price
Model No.	H.P.	K.W.	STG.	LPM	540	500	470	400	370	300	150	
RM-2620834	3	2.20	4	Head In Meter	16	20	24	28	32	36	40	37440/-
RM-2620856	5	3.70	6		24	30	36	42	48	54	60	45360/-
RM-2620868	6	4.50	8		32	50	48	56	64	72	80	49830/-
RM-262087510	7.5	5.50	10		40	50	60	70	80	90	100	57750/-
RM-262081012	10	7.50	12		48	60	72	84	96	108	120	74060/-
RM-2620812515	12.5	11	15		60	75	90	105	120	135	150	84130/-
RM-262081518	15	11.25	18		72	90	108	126	144	162	180	93970/-

Head Per Stage - 36' Feet (10.9 Meter)

RM-262-10				DISCHARGE IN LPM								Price
Model No.	H.P.	K.W.	STG.	LPM	630	580	550	500	430	380	200	
RM-2621033	3	2.20	3	Head In Meter	12	20	24	21	24	27	30	35670/-
RM-2621055	5	3.70	5		20	25	30	35	40	45	50	43550/-
RM-2621066	6	4.50	6		24	30	36	42	48	54	60	46075/-
RM-26210758	7.5	5.50	8		30	40	48	56	64	72	80	53895/-
RM-262101010	10	7.50	10		40	50	60	70	80	90	100	69975/-
RM-2621012512	12.5	11	12		48	60	72	84	96	108	120	78037/-
RM-262101515	15	11.25	15		60	75	90	105	120	135	150	88010/-
RM-2621017518	17.5	13.10	18		72	90	108	126	144	162	180	99740/-
RM-262102020	20	15	20		80	100	120	140	160	180	200	107144/-

Head Per Stage - 40' Feet (12 Meter)

RM-262-12				DISCHARGE IN LPM								Price
Model No.	H.P.	K.W.	STG.	LPM	750	700	600	540	450	350	200	
RM-2621254	5	3.70	4	Head In Meter	20	24	28	32	36	40	44	41565/-
RM-2621265	6	4.50	5		25	30	35	40	45	50	55	44260/-
RM-26212756	7.5	5.50	6		30	36	42	48	54	60	66	50050/-
RM-26212108	10	7.50	8		40	48	56	64	72	80	88	65898/-
RM-2621212510	12.5	11	10		50	60	70	80	90	100	110	73960/-
RM-262121512	15	11.25	12		60	72	84	96	108	120	132	81916/-
RM-2621217514	17.5	13.10	14		70	84	98	112	126	140	154	91625/-
RM-262122016	20	15	16		80	96	112	128	144	160	176	99077/-

V-6 Q TYPE (MIX FLOW)

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Head Per Stage - 40' Feet (12 Meter)

RM-273-15				DISCHARGE IN LPM								Price
Model No.	H.P.	K.W.	STG.	LPM	870	780	710	600	570	450	280	
RM-2731553	5	3.70	3	Head In Meter	15	18	24	24	27	30	33	40500/-
RM-2731564	6	4.50	4		20	24	28	32	36	40	44	43250/-
RM-273755	7.5	5.50	5		25	30	35	40	45	50	55	49395/-
RM-273106	10	7.50	6		30	36	42	48	54	60	66	63380/-
RM-2731258	12.5	11	8		40	48	56	64	72	80	88	71980/-
RM-2731510	15	11.25	10		50	60	70	80	90	100	110	80450/-
RM-27317512	17.5	13.10	12		60	72	84	96	108	120	132	90850/-
RM-2732013	20	15	13		65	78	91	104	117	130	143	96420/-

Head Per Stage - 42' Feet (12.8 Meter)

RM-302-20				DISCHARGE IN LPM								Price
Model No.	H.P.	K.W.	STG.	LPM	980	900	850	780	680	570	450	
RM-3022063	6	4.50	3	Head In Meter	15	18	24	24	27	30	33	41350/-
RM-30220754	7.5	5.50	4		20	24	28	32	36	40	44	47320/-
RM-30220105	10	7.50	5		25	30	35	40	45	50	55	61360/-
RM-302201256	12.5	11	6		30	36	42	48	54	60	66	67580/-
RM-30220157	15	11.25	8		88	80	72	64	56	48	40	76100/-
RM-302201759	17.5	13.10	9		45	54	63	72	81	90	99	84340/-
RM-302202010	20	15	10		50	60	70	80	90	100	110	89910/-

Head Per Stage - 45' Feet (13.7 Meter)

RM-302-25				DISCHARGE IN LPM								Price
Model No.	H.P.	K.W.	STG.	LPM	1300	1200	1100	950	880	700	550	
RM-3022553	5	3.70	2	Head In Meter	10	12	14	16	18	20	22	39030/-
RM-30225753	7.5	4.50	3		15	18	21	24	27	30	33	45850/-
RM-30225104	10	5.50	4		20	24	28	32	36	40	44	59800/-
RM-302251255	12.5	7.50	5		25	30	35	40	45	50	55	66350/-
RM-30225156	15	11	6		30	36	42	48	54	60	66	72650/-
RM-302251757	17.5	11.25	7		35	42	49	56	63	70	77	80850/-
RM-30225208	20	13.10	8		40	48	56	64	72	80	88	86880/-

V-6 DILUX

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	1.5 kW to 3.75 kW (2.0 HP to 5.00 HP)
Speed	2800 RPM
Version	Single/Two/Three Phase 220V 350V 415V, 50Hz, AC Supply
Maximum Total Head	27 Mtr. to 91 Mtr
Maximum Flow Rate	630 LPM to 80 LPM
Nominal Outlet Size in Inches	2.0", 2.5"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for 6" bore
Direction of Rotation	Electrically Reversible -1ph / 2ph / 3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor		**Pump**	
Motor Shaft	: Stainless Steel AISI 410	Bowl	: CI FG:200
Motor Body Pipe	: Stainless Steel AISI 202	Impeller	: NAYLON
Casting Part	: CI FG:200	Suction& NRV	: CI FG:200
Thrust Bearing	: Carbon v/s Stainless Steel	Pump Shaft	: Stainless Steel AISI 410
Motor Bush	: LTB-4	Pump Tierod	: Stainless Steel AISI 304
Stamping	: CRC Steel.	All Hardware	: Stainless Steel
Copper	: EC Grade 99.9% Copper	Pump Bush	: NBR / LTB4
Winding Wire	: Multilayer Polyester Insulated	Pump Sleeve	: Hard Chromed SS-410
Oil Seal	: NBR	Pump Couple	: SS-410

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Fountains, Gardens
- Sprinkler system

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- CI Grade Casting Bowl and SS410 Impeller With 50 feet head.
- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing to withstand high axial thrust load, resulting in High operating efficiency.
- Higher HP motors to have premium SILICON CARBIDE bearings.
- Specially designed gaskets are used to prevent leakage even at higher pressure.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- Thread type motor construction ensures service feasibility
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Using GM Bush and SS/NBR bush in alternate sequence ensures higher mechanical stability of pump
- Usage of gasket per stage in higher stages pump ensures no leakage even at higher pressure.



V-6 DILUX

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

Delux Model

V-6 Submersible Pump Set Suitable For 150mm (6") Borewell Outside Dia 142mm
Supply Voltage At 220V S.P. 50Hz / 350V 2.P 50 Hz Supply

Model RM 262Q — Mix Flow

Model No.	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	0	150	290	370	440	542	630	680	
RM-262Q	3	2.2	3	65	HEAD IN METER	32	27	24	21	18	12	6	-	25000/-
RM-262Q	5	3.7	4	65		42	36	32	28	24	16	8	-	27450/-
RM-262Q	5	3.7	5	65		53	45	40	35	30	20	10	-	28500/-

Model RM 100R — Radial Flow

Model No.	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	0	195	290	323	351	407	448	470	
RM-100R	3	2.2	4	65	HEAD IN METER	49	40	32	28	24	16	8	-	24300/-
RM-100R	5	3.7	6	65		73	60	48	42	36	24	12	-	27200/-

Model RM 80R — Radial Flow

Model No.	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	0	150	241	262	287	338	387	423	
RM-80R	2	1.50	4	65	HEAD IN METER	49	40	32	28	24	16	8	-	22390/-
RM-80R	3	2.2	5	65		61	50	40	35	30	20	10	-	25000/-
RM-80R	5	3.7	8	50		96	80	64	52	48	32	16	-	28600/-

Model RM 60R — Radial Flow

Model No.	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	0	117	195	232	260	314	372	410	
RM-60R	2	1.50	5	50	HEAD IN METER	59	50	40	35	30	20	10	-	23100/-
RM-60R	3	2.2	6	50		70	60	48	42	36	24	12	-	25750/-
RM-60R	5	3.7	10	50		117	100	80	70	60	40	20	-	30000/-

Model RM 40R — Radial Flow

Model No.	H.P.	K.W.	STG.	OUTLET IN MM	DISCHARGE IN LPM								PRICE
					LPM	0	80	145	178	205	265	315	360	
RM-40R	2	1.50	6	50	HEAD IN METER	66	60	48	42	36	24	12	-	23800/-
RM-40R	3	2.2	8	50		88	80	64	56	48	32	16	-	27150/-

*No Guarantee

HORIZONTAL OPENWELL

SUPER FLOW
SUBMERSIBLE PUMP

SPECIFICATION

Power Range	0.37 kW to 7.50 kW (0.50 HP to 10HP)
Speed	2800 RPM
Version	Single Phase 160V to 230V, 50Hz, AC Supply Three Phase 350V to 415V, 50Hz, AC Supply
Maximum Total Head	10 Mtr. to 54 Mtr
Maximum Flow Rate	1175 LPM to 20 LPM
Nominal Outlet Size in Inches	1.0", 1.25", 1.5", 2.0", 2.5", 3.0"
Degree of Protection	IP 58
Maximum Outer Diameter in mm	Suitable for Openwell
Direction of Rotation	Counter clockwise from driving end -1 pH Electrically Reversible -3 ph
Mini. Cooling Flow Along the motor	0.15 m/sec
Type of Duty	S1 (continues)
Method of Starting	1ph-Capacitor 3ph - Direct Online
Maximum Starts per hour	10 times

MATERIAL OF CONSTRUCTION

Motor	
Motor Shaft	: Stainless Steel AISI 410
Motor Body	: Stainless Steel AISI 202 / CI FG:200
Casting Part	: CI FG:200
Thrust Bearing	: Carbon v/s Stainless Steel, FIber
Motor Bush	: LTB-4
Stamping	: CRCA PRIME
Copper	: EC Grade 99.9% Copper
Winding Wire	: Multilayer Polyester Insulated
Oil Seal	: NBR

APPLICATION

- Domestic and municipal water supply
- Canals & Rivers.
- Solar Application
- Under Ground Water Tank

PUMP LIQUIDS

Clean, Thin ,Non-Aggresive, Non-Explosive Clear Cold, Fresh Water without Solid Particles or Abrasives

SALIENT FEATURES

- Rotors are coated with Epoxy paint for long life and corrosion free operation resulting in more durability and hygiene.
- CI part of pump is coated with CED for better corrosion – resistance, durability, alignment and smoother running.
- Specially designed extremely hardwearing water lubricated thrust bearing.
- All parts machined on CNC to set consistent Quality performance.
- Rotors are grinded & burnished to give better surface finish value which ensures long life.
- No suction and priming problem.
- No need of pump house.
- Dynamically balanced Rotating parts to ensure minimum noise and vibration-free operation.
- Motors are designed using multi layer PVC insulated wire to get better reliability and easy repairing at remote location.
- Light weight & Easy to operate in wide voltage band.
- Designed for wide voltage operation











V-7 HORIZONTAL OPENWELL SS

SUBMERSIBLE PUMP SET

SUPER FLOW SUBMERSIBLE PUMP

RM7-Openwell Aluminum				Discharge In L.P.M.	Total Head in Meters														Price (Without Panel)	
Model No.	H.P.	K.W	Outlet		10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	1 Phase	3 Phase
RM7-052525	0.5	0.37	1.0"X1.0"		135	130	120	105	**90**	75	42	-	-	-	-	-	-	-	-	6770/-	-
RM7-103225	1.0	0.75	1.0"X1.0"		200	195	192	190	**180**	165	155	143	130	112	88	75	-	-	-	9150/-	-
RM7-154040	1.5	1.10	1.5"X1.5"		-	-	-	-	**-**	180	165	155	145	130	115	100	85	65	35		
RM7-205050	2.0	1.50	2.0"X2.0"		470	450	425	405	**380**	355	325	290	140	-	-	-	-	-	-	15831/-	15831/-
RM7-306550	3.0	2.30	2.5"X2.0"		565	554	530	510	**485**	470	430	405	280	150	-	-	-	-	-	17880/-	17250/-
RM7-506550	5.0	3.70	2.5"X2.0"		780	765	755	745	**735**	725	715	690	525	485	350	230	-	-	-	19500/-	19100/-

RM7-Openwell Coper				Discharge In L.P.M.	Total Head in Meters														Price (Without Panel)	
Model No.	H.P.	K.W	Outlet		10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	1 Phase	3 Phase
RM7-052525	0.5	0.37	1.0"X1.0"		135	130	120	105	**90**	75	42	-	-	-	-	-	-	-	-	7790/-	-
RM7-103225	1.0	0.75	1.0"X1.0"		200	195	192	190	**180**	165	155	143	130	112	88	75	-	-	-	10155/-	-
RM7-154040	1.5	1.10	1.5"X1.5"		-	-	-	-	**-**	180	165	155	145	130	115	100	85	65	35	15175/-	15175/-
RM7-205050	2.0	1.50	2.0"X2.0"		470	450	425	405	**380**	355	325	290	140	-	-	-	-	-	-	17895/-	17895/-
RM7-306550	3.0	2.30	2.5"X2.0"		565	554	530	510	**485**	470	430	405	280	150	-	-	-	-	-	20180/-	19550/-
RM7-506550	5.0	3.70	2.5"X2.0"		780	765	755	745	**735**	725	715	690	525	485	350	230	-	-	-	22230/-	20860/-

V-7 HORIZONTAL OPENWELL CI

SUBMERSIBLE PUMP SET

RM7-Openwell Aluminum				Discharge In L.P.M.	Total Head in Meters														Price (Without Panel)	
Model No.	H.P.	K.W	Outlet		10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	1 Phase	3 Phase
RM7-052525	0.5	0.37	1.0"X1.0"		135	130	120	105	**90**	75	42	-	-	-	-	-	-	-	-	-	-
RM7-103225	1.0	0.75	1.0"X1.0"		200	195	192	190	**180**	165	155	143	130	112	88	75	-	-	-	-	-
RM7-154040	1.5	1.10	1.5"X1.5"		-	-	-	-	**-**	180	165	155	145	130	115	100	85	65	35	-	-
RM7-205050	2.0	1.50	2.0"X2.0"		470	450	425	405	**380**	355	325	290	140	-	-	-	-	-	-	16740/-	16740/-
RM7-306550	3.0	2.30	2.5"X2.0"		565	554	530	510	**485**	470	430	405	280	150	-	-	-	-	-	18880/-	18250/-
RM7-506550	5.0	3.70	2.5"X2.0"		780	765	755	745	**735**	725	715	690	525	485	350	230	-	-	-	20630/-	20200/-

RM7-Openwell Coper				Discharge In L.P.M.	Total Head in Meters														Price (Without Panel)	
Model No.	H.P.	K.W	Outlet		10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	1 Phase	3 Phase
RM7-052525	0.5	0.37	1.0"X1.0"		135	130	120	105	**90**	75	42	-	-	-	-	-	-	-	-	-	-
RM7-103225	1.0	0.75	1.0"X1.0"		200	195	192	190	**180**	165	155	143	130	112	88	75	-	-	-	-	-
RM7-154040	1.5	1.10	1.5"X1.5"		-	-	-	-	**-**	180	165	155	145	130	115	100	85	65	35	-	-
RM7-205050	2.0	1.50	2.0"X2.0"		470	450	425	405	**380**	355	325	290	140	-	-	-	-	-	-	18800/-	18800/-
RM7-306550	3.0	2.30	2.5"X2.0"		565	554	530	510	**485**	470	430	405	280	150	-	-	-	-	-	21185/-	20550/-
RM7-506550	5.0	3.70	2.5"X2.0"		780	765	755	745	**735**	725	715	690	525	485	350	230	-	-	-	23400/-	22960/-

V-9 HORIZONTAL OPENWELL

SUBMERSIBLE PUMP SET

SUPER FLOW ™
SUBMERSIBLE PUMP

RM9-Openwell					Total Head in Meters																				Price `	
Model No.	H.P.	K.W	Outlet	Discharge In L.P.M.	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	54	S.S. Body	C.I. Body
RM9-506550	5.0	3.70	2.5"X2.0"		800	790	780	770	750	730	700	665	625	580	530	480	420	340	-	-	-	-	-	-	-	28660/-	30900/-
RM9-506550	5.0	3.70	2.5"X2.5"		1095	1045	995	940	880	830	765	690	610	500	420	330	-	-	-	-	-	-	-	-	-	28660/-	30900/-
RM9-756550	7.5	5.50	2.5"X2.0"		825	820	815	810	805	800	795	790	785	780	775	765	735	690	655	600	530	440	360	-	-	33680/-	36580/-
RM9-756565	7.5	5.50	2.5"X2.5"		1140	1135	1130	1125	1120	1080	1030	975	910	835	740	635	505	330	130	-	-	-	-	-	-	33680/-	36580/-
RM9-1006565	10.0	7.50	2.5"X2.5"		-	-	-	-	-	-	-	-	890	865	860	855	830	805	760	710	655	590	530	445	345	44680/-	
RM9-1008080	10.0	7.50	3.0"X3.0"		-	-	-	1500	1445	1375	1300	1225	1140	1045	950	810	665	485	-	-	-	-	-	-	-	44850/-	



SUPER FLOW

SUBMERSIBLE PUMP

AN ISO 9001 : 2008 CERTIFIED COMPANY

IS : 8034 CM/L3637668 | IS : 14220 CM/L7600101706

Our Other Products

V-3, V-4, V-5, V-6, V7- V-8, V-9

Horizontal Openwell | Vertical Openwell

Mfg. & Marketed By

Royal Manufacture

Padvala, Rajkot - 360024

Customer Care : 097 822 96 822 | Email : royalmanufacture7@gmail.com

Web. **www.royalmanufacture.in**

design : www.maheshkeshur.com

design by: www.artfullbiz