Some GIT Basics

Dr. Uwe Ziegenhagen September 23, 2022

www.uweziegenhagen.de

Content

Introduction

MinGW Basics

Git

Introduction

Introduction

- "Git is a free and open source distributed version control system designed to handle everything from small to very large projects with speed and efficiency."
- Version control systems track changes to files and allow you to go back to earlier versions thus creating backups as well.
- Git is not the first or only available version control system (VCS): CVS, Bitbucket, and Subversion are wellknown
- Git was developed by the Linux creator Linus Torvalds to maintain the Linux kernel

Centralized versus Distributed VCS

- Subversion is a centralized vcs, it uses a central server. Only this server has the full history of all files
- All developers get special snapshots from this server.
- Backing up the server is essential!
- Git is a distributed vcs, so all clients (developers) have the complete repository on their machines.
- I personally used Subversion for a long time (and still use it for some projects) but mostly have migrated to Github.
- Github = a central platform where I can put my projects, but not the "central server" like with Subversion

Working with Git

In the following we will look as various use cases for working with Git

- Create new repositories¹
- Add files to the repository
- · Making changes to the repository

•


Remark: Git can be quite complex, normally you need only a few commands.

¹The project structure you manage with Git

MinGW Basics

Running Git

- You find Git 2.28 on your desktop
- When you start it you land here:



MinGW

- MinGW = Minimal GNU² for Windows
- A shell that ports many Unix/Linux tools to Windows
- This is not Git, Git is just a commandline tool that can be used within MinGW
- · It contains a few Linux tools as well
- To move in this MinGW environment you need to use Linux commands

²"GNU is not Unix" = Open-Source stuff

Basic MinGW commands

pwd In which directory are we?ls List all files and folderscd go to some specific directorymkdir create a new directory

Remarks:

- There are no drive letters in MinGW
- / is the root directory
- Windows drive letters are (invisible) directories below this root directory
- so cd /c takes you to the C:\directory

Git

Create new Repositories

Create a directory, change to that directory and init the repository. The directory may already contains some files

```
cd /e # go to the e: drive

mkdir myfirstgitrepo # create empty directory

cd myfirstgitrepo # go to the directory

git init . # create repo (with a 'master' branch)
```

git status

Use git status whenever you want to know something about the current state of the repository

```
Uwe@DESKTOP MINGW64 /e/myfirstgitrepo (master)
$ git status
On branch master

No commits yet

nothing to commit (create/copy files and use
"git add" to track)
```