

## SSTF,LOOK,C-LOOK

```
#include<stdio.h>
#include<stdlib.h>
void SSTF(){
    int RQ[100],i,n,TotalHeadMoment=0,initial,count=0;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);

    // logic for sstf disk scheduling

    /* loop will execute until all process is completed*/
    while(count!=n)
    {
        int min=1000,d,index;
        for(i=0;i<n;i++)
        {
            d=abs(RQ[i]-initial);
            if(min>d)
            {
                min=d;
                index=i;
            }
        }

        TotalHeadMoment=TotalHeadMoment+min;
        initial=RQ[index];
    }
}
```

```

        // 1000 is for max
        // you can use any number
        RQ[index]=1000;
        count++;
    }

    printf("Total head movement is %d",TotalHeadMoment);
}
void C_LOOK(){
int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    /*printf("Enter total disk size\n");
    scanf("%d",&size);*/
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for C-look disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for( j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];
                RQ[j+1]=temp;
            }
        }
    }
}

```

```

    }

}

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for( i=0;i<index;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)

```

```

    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=n-1;i>=index;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
}

void LOOK(){
int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for look disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for(j=0;j<n-i-1;j++)

```

```

    {
        if(RQ[j]>RQ[j+1])
        {
            int temp;
            temp=RQ[j];
            RQ[j]=RQ[j+1];
            RQ[j+1]=temp;
        }
    }
}

```

```

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

```

// if movement is towards high value

```

if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

```

```

for(i=index-1;i>=0;i--)
{
    TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
    initial=RQ[i];
}

```

```

    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
}

void main(){
int ch;
printf("\n 1.SSTF\t 2.LOOK\t 3.C-LOOK\t 4.EXIT\n");
while(1){
    printf("\nEnter your choice\n");
    scanf("%d",&ch);
    switch(ch){
    case 1:SSTF();
        break;
    case 2:LOOK();
        break;
    case 3:C_LOOK();
        break;

```

```

        case 4:exit(0);
        default:printf("Invalid choice\n");
    }
}
}

```

## OUTPUT:

```

1.SSTF  2.LOOK  3.C-LOOK          4.EXIT
Enter your choice
3
Enter the number of Requests
8
Enter the Requests sequence
95 180 34 119 11 123 62 64
Enter initial head position
50
Enter the head movement direction for high 1 and for low 0
1
Total head movement is 322
Enter your choice
2
Enter the number of Requests
8
Enter the Requests sequence
95 180 34 119 11 123 62 64
Enter initial head position
50
Enter the head movement direction for high 1 and for low 0
1
Total head movement is 299
Enter your choice
1
Enter the number of Requests
8
Enter the Requests sequence
95 180 34 119 11 123 62 64
Enter initial head position
50
Total head movement is 236
Enter your choice
_

```