

## ② CSS - Cascading Style sheet

1. linking html to CSS -

`<head>`  
`<link rel="stylesheet" href="style.css" />`

2. background: ;

- background color

color: ;

- text color

3. Element specificity

body {

color: black;

}

h3 {

color: red;

}

body h3 {

color: white

}

This column will be executed as it is more specific but only for h3 in body.

~~body~~ body > header > h3 {

}

This can be use

for more specificity

ID - #

4 font-family - font style  
font-weight - light or bold  
border - dashed, dotted

margin - 0px

→ To remove the margin from top

↓  
written inside the body

fonts.google.com

border : 1px

↓  
width

solid

↓  
style

black

↓  
color

styles - 3 styles - solid  
dotted  
dashed

single-side border - border-bottom : 1px solid black

Margin -  $\frac{10px}{\downarrow}$  top  
 $\frac{20px}{\downarrow}$  right  
 $\frac{30px}{\downarrow}$  bottom  
 $\frac{40px}{\downarrow}$  left

$\frac{10px}{\downarrow}$  top & bottom  
 $\frac{20px}{\downarrow}$  right & left

$\frac{10px}{\downarrow}$  all sides



display : inline ;  
float : left ;  
- on the same line  
- use for aligning

Code -

```
<html>  
<head>  
  <link href = " " > → for fonts  
  <link rel = "stylesheet" href = "project1.css" > ← for linking css to html  
  <title> Project 1 </title>  
</head>  
<body>  
  <header id = "main-header" >  
    <h1> Best News Ever! </h1>  
    <h3> We don't care if it's accurate.  
    We care that it's the BEST!  
    </h3>  
  </header>  
  <main id = "top-posts" >  
    <h1> </h1>  
    <h2> About Me </h2>  
    <p> We've spent years in the  
    news you ... accurate news. </p>  
  </section>  
  <article>  
    <h1> <a href = # > Dog kidnaps  
    clowns </a> </h1>  
    <div class = "section-image"  
    style = "background-image: url();"  
    > </div>
```

for image ←

mac </p>  
<p> In a shocking

<article>

</br> </br>

</section>

<section>

<article>

</section>

<section>

</section>

</main>

<footer style="text-align: center;" > &copy; 2011

</div>

<a href="#"> Terms of Service </a>

</div>

</footer>

</body>

</html>



# css style sheet code -

body {

background :

font-family: "Playwrite ES", cursive;

font-optical-sizing: auto;

font-weight: 400;

font-style: normal;

margin: 0px;

→ bg color

→ to cover the whole website

}

used for id.

#main - header {

border-bottom: 4px solid black;

→ line below the header

}

body h1 {

margin: 10px 20px;

→ left right

top-bottom

}

body > header > h1, h3 {

background-color: alice-blue;

→ bg color of bar for header

display: inline; → side by side

}

#top-posts {

width: 1000px;

margin: auto;

}

section {

max-width: 31%;

display: inline-block;

margin-right: 10px;

side by side - 3 sections  
space between all the sections

}  
section - image {

width: 100%;

height: 450px;

background-size: cover;

}  
for images

}

output -


Best News Ever!

We don't care if it's accurate. We care...

About me


We've spent

Pop kidnaps clowns




In a shocking

Chocolate in space



Have you

HTML5 saves the



since it's

© 2017

Terms of service



\* Only one element can have ~~so~~ similar id name whereas more than one element can have similar class name.

6 text-decoration: ; - for lines on the text  
↓  
types - dashed, dotted, none, underline, overline, solid, line through.

letter-spacing: ; - for space between letters  
-ve + for overwriting letters  
+ve - for increasing space between the letter

text-indent: ; - space before starting of a para

text-align: ;

text-shadow: 1px 1px 2px black ;

shadow to right      shadow to bottom      spread → jitha zyada hogee utna achha hai

→ Same can be used for box-shadow.

## I Pseudo-states

① hover - If we hover over an element the specified actions will be depicted.

code-

a: hover {

text-decoration: underline;

color: black;

font-weight: 1000;

}

② focus - for highlighting the items

code -

1. input : focus {

background: gray;

color: black;

outline: none;

border: 1px solid black;

}

③ active - has opacity

0 - transparent

1 - opaque

code -

section: active {

opacity: 0.1;

}

8 border-radius: 5px;

position: relative, fixed, absolute;

9 Pseudo - elements

① :: before

code -

# main-header :: before {

content: " ";

position: absolute;

display: block;

width: 10px;



height : 65px;  
background : black;  
top : 0;

}

② :: after

{ same as before }

10 z-index - stacking of the elements

11 Max-height - maximum height of an element  
Overflow - if the height of content exceeds the max height you can use overflow.

Overflow : scroll ; , hidden ;

Overflow - x : ; - for x axis

overflow - y ; ; - for y-axis

←  
stop - stop  
stop - stop