


# How many code paths?



```
std::string returnNameCheckPawsome(Pet p) {  
    /// NOTE: dogs > cats  
    if (p.type() == "Dog" || p.firstName() == "Fluffy") {  
        std::cout << p.firstName() << " " <<  
            p.lastName() << " is paw-some!" << '\n';  
    }  
    return p.firstName() + " " + p.lastName();  
}
```

3?

# Exceptions


- Exceptions are a way of handling errors when they arise in code
- Exceptions are “thrown”
- However, we can write code that lets us handle exceptions so that we can continue in our code without necessarily erroring.

# Exceptions

- Exceptions are a way of handling errors when they arise in code
- Exceptions are “thrown”
- However, we can write code that lets us continue in our code without
- We call this “catching” an exception.

```
try {  
    // code that we check for exceptions  
}  
catch([exception type] e1) { // "if"  
    // behavior when we encounter an error  
}  
catch([other exception type] e2) { // "else if"  
    // ...  
}  
catch { // the "else" statement  
    // catch-all (haha)  
}
```

# How many code paths?



```
std::string returnNameCheckPawsome(Pet p) {  
    /// NOTE: dogs > cats  
    if (p.type() == "Dog" || p.firstName() == "Fluffy") {  
        std::cout << p.firstName() << " " <<  
            p.lastName() << " is paw-some!" << '\n';  
    }  
    return p.firstName() + " " + p.lastName();  
}
```

# At least 23 code paths!

- (1): Copy constructor of Pet may throw
- (5): Constructor of temp strings may throw
- (6): Call to type, firstName(3), lastName(2) may throw
- (10): User overloaded operators may throw
- (1): Copy constructor of returned string may throw

```
std::string returnNameCheckPawsome(Pet p) {  
    /// NOTE: dogs > cats  
    if (p.type() == "Dog" || p.firstName() == "Fluffy") {  
        std::cout << p.firstName() << " " <<  
            p.lastName() << " is paw-some!" << '\n';  
    }  
    return p.firstName() + " " + p.lastName();  
}
```

# What could go wrong?

```
std::string returnNameCheckPawsome(int petId) {  
    Pet* p = new Pet(petId);  
    if (p.type() == "Dog" || p.firstName() == "Fluffy") {  
        std::cout << p.firstName() << " " <<  
            p.lastName() << " is paw-some!" << '\n';  
    }  
    std::string returnStr = p.firstName() + " " + p.lastName();  
    delete p;  
    return returnStr;  
}
```

What if this  
function threw an  
exception here?

Or here?

Or here?

Or anywhere an exception can be  
thrown?

# What could go wrong?

exception  
here  
means  
memory  
leak

```
std::string returnNameCheckPawsome(int petId) {  
    Pet* p = new Pet(petId);  
    if (p.type() == "Dog" || p.firstName() == "Fluffy") {  
        std::cout << p.firstName() << " " <<  
            p.lastName() << " is paw-some!" << '\n';  
    }  
    std::string returnStr = p.firstName() + " " + p.lastName();  
    delete p;  
    return returnStr;  
}
```

# This is not unique to just pointers!

It turns out that there are many resources that you need to release after acquiring

	Acquire	Release
Heap memory	<code>new</code>	<code>delete</code>
Files	<code>open</code>	<code>close</code>
Locks	<code>try_lock</code>	<code>unlock</code>
Sockets	<code>socket</code>	<code>close</code>



# This is not unique to just pointers!

It turns out that there are many resources that you need to release after acquiring

	Acquire	Release
Heap memory	<code>new</code>	<code>delete</code>
Files	<code>open</code>	<code>close</code>
	<code>try_lock</code>	<code>unlock</code>
	<code>socket</code>	<code>close</code>

How to we ensure that we properly release resources in the case that we have an exception?

# RAII

## RAII: Resource Acquisition is Initialization (What is this name?)

RAII was developed by this lad:



And it's a concept that is very emblematic in C++, among other languages.

### So what is RAII?

- All resources used by a class should be acquired in the constructor!
- All resources that are used by a class should be released in the destructor.

# RAII: why tho?

## RAII: Resource Acquisition is Initialization

- By abiding by the RAII policy we avoid “half-valid” states.
- No matter what, the destructor is called whenever the resource goes out of scope.
- One more thing: the resource/object is usable immediately after it is created.

# RAII compliant?

```
void printFile() {  
    ifstream input;  
    input.open("hamlet.txt");  
  
    string line;  
    while(getLine(input, line)) { // might throw an exception  
        std::cout << line << std::endl;  
    }  
  
    input.close();  
}
```


the  
**ifstream** is  
opened and  
closed in  
code, not  
constructor  
& destructor

# Neither is this!

```
void cleanDatabase(mutex& databaseLock, map<int, int>& db) {  
    databaseLock.lock();  
  
    // no other thread or machine can change database  
    // modify the database  
    // if any exception is thrown, the lock never unlocks!  
  
    database.unlock();  
}
```

If any code throws an exception in the red area, which we can call the 'critical section', the lock never unlocks!

# How can we fix this?



```
void cleanDatabase(mutex& databaseLock, map<int, int>& db) {  
    lock_guard<mutex> lg(databaseLock);  
    // no other thread or machine can change database  
    // modify the database  
    // if exception is throw, mutex is not released  
    // no explicit unlock necessary  
}
```

A lock guard is a RAII-compliant wrapper that attempts to acquire the passed in lock. It releases the the lock once it goes out of scope. Read more [here](#)

# Smart Pointers

**RAII for locks → `lock_guard`**

**RAII for memory → 🤔**

# Smart Pointers

## R.11: Avoid calling `new` and `delete` explicitly

### Reason

The pointer returned by `new` should belong to a resource handle (that can call `delete`). If the pointer returned by `new` is assigned to a plain/naked pointer, the object can be leaked.

### Note

In a large program, a naked `delete` (that is a `delete` in application code, rather than part of code devoted to resource management) is a likely bug: if you have `N` `delete`s, how can you be certain that you don't need `N+1` or `N-1`? The bug may be latent: it may emerge only during maintenance. If you have a naked `new`, you probably need a naked `delete` somewhere, so you probably have a bug.

### Enforcement

(Simple) Warn on any explicit use of `new` and `delete`. Suggest using `make_unique` instead.



# Remember this?



```
std::string returnNameCheckPawsome(int petId) {  
    Pet* p = new Pet(petId);  
    if (p.type() == "Dog" || p.firstName() == "Fluffy") {  
        std::cout << p.firstName() << " " <<  
            p.lastName() << " is paw-some!" << '\n';  
    }  
    std::string returnStr = p.firstName() + " " + p.lastName();  
    delete p;  
    return returnStr;  
}
```

# What did we do for locks?

## **RAII for locks → `lock_guard`**

- Created a new object that acquires the resource in the constructor and releases in the destructor

# What did we do for locks?

## **RAII for locks → `lock_guard`**

- Created a new object that acquires the resource in the constructor and releases in the destructor

## **RAII for memory → We can do the same 🎉**

- These “wrapper” pointers are called “smart pointers”!

# Visualizing smart pointers


**RAII for memory** → **We can do the same** 🎉

- These “wrapper” pointers are called “smart pointers”!

There are three types of RAII-compliant pointers:

- **`std::unique_ptr`**
  - Uniquely owns its resource, can't be copied
- **`std::shared_ptr`**
  - Can make copies, destructed when the underlying memory goes out of scope
- **`std::weak_ptr`**
  - A class of pointers designed to mitigate circular dependencies
    - More on these in a bit

# What does this look like?



```
void rawPtrFn() {  
    Node* n = new Node;  
    // do smth with n  
    delete n;  
}
```



```
void rawPtrFn() {  
    std::unique_ptr<Node> n(new Node);  
    // do something with n  
    // n automatically freed  
}
```

# Remember we can't copy unique pointers



```
void rawPtrFn() {  
    std::unique_ptr<Node> n(new Node);  
  
    // this is a compile-time error!  
    std::unique_ptr<Node> copy = n;  
}
```

# Why?




```
void rawPtrFn() {  
    std::unique_ptr<Node> n(new Node);  
  
    // this is a compile-time error!  
    std::unique_ptr<Node> copy = n;  
}
```

Imagine a case where the original destructor is called **after** the copy happens.

**Problem:** The copy points to deallocated memory!

# std::shared\_ptr

Shared pointers get around our issue of trying to copy **std::unique\_ptr**'s by not deallocating the underlying memory until **all** shared pointers go out of scope!





# Initializing smart pointers!



```
std::unique_ptr<T> uniquePtr{new T};
```

```
std::shared_ptr<T> sharedPtr{new T};
```

```
std::weak_ptr<T> wp = sharedPtr;
```

# Initializing smart pointers!

```
std::unique_ptr<T> uniquePtr{new T};
```

```
std::shared_ptr<T> sharedPtr{new T};
```

```
std::weak_ptr<T> wp = sharedPtr;
```

We're still explicitly  
calling **new**

no....no

# Initializing smart pointers!



```
// std::unique_ptr<T> uniquePtr{new T};  
std::unique_ptr<T> uniquePtr = std::make_unique<T>();  
  
// std::shared_ptr<T> sharedPtr{new T};  
std::shared_ptr<T> sharedPtr = std::make_shared<T>();  
  
std::weak_ptr<T> wp = sharedPtr;
```

# Initializing smart pointers!

**Always use `std::make_unique<T>` and `std::make_shared<T>`**

Why?

1. The most important reason: if we don't then we're going to allocate memory twice, once for the pointer itself, and once for the **new T**
2. We should also be consistent — if you use **make\_unique** also use **make\_shared**!

# **std::weak\_ptr**

Weak pointers are a way to avoid circular dependencies in our code so that we don't leak any memory.

# std::weak\_ptr bad example

```
#include <iostream>
#include <memory>

class B;

class A {
public:
    std::shared_ptr<B> ptr_to_b;
    ~A() {
        std::cout << "All of A's resources deallocated" << std::endl;
    }
};

class B {
public:
    std::shared_ptr<A> ptr_to_a;
    ~B() {
        std::cout << "All of B's resources deallocated" << std::endl;
    }
};

int main() {
    std::shared_ptr<A> shared_ptr_to_a = std::make_shared<A>();
    std::shared_ptr<B> shared_ptr_to_b = std::make_shared<B>();
    a->ptr_to_b = shared_ptr_to_b;
    b->ptr_to_a = shared_ptr_to_a;
    return 0;
}
```

Both instance **a** of class **A** and instance **b** class **B** are keeping a share pointer to each other.

Therefore, they will never properly deallocate

# std::weak\_ptr good example

```
#include <iostream>
#include <memory>

class B;

class A {
public:
    std::shared_ptr<B> ptr_to_b;
    ~A() {
        std::cout << "All of A's resources deallocated" << std::endl;
    }
};

class B {
public:
    std::weak_ptr<A> ptr_to_a;
    ~B() {
        std::cout << "All of B's resources deallocated" << std::endl;
    }
};

int main() {
    std::shared_ptr<A> shared_ptr_to_a = std::make_shared<A>();
    std::shared_ptr<A> shared_ptr_to_b = std::make_shared<B>();
    a->ptr_to_b = shared_ptr_to_b;
    b->ptr_to_a = shared_ptr_to_a;
    return 0;
}
```

Here, in class B we are no longer storing **a** as a `shared_ptr` so it does not increase the reference count of **a**.

Therefore **a** can gracefully be deallocated, and therefore so can **b**

# Compilation Crash Course

When we write C++ code, it needs to be translated into a form our computer understands it

## Source Code

```
std::cout << "Hello World" << std::endl;  
std::cout << "Welcome to " << std::endl;  
for (char ch : "CS106L")  
{  
    std::cout << ch << std::endl;  
}
```

## Compiler

## Machine Code

```
10110101  
01011010  
10011101  
10110001
```

```
$ g++ main.cpp -o main
```

```
$ ./main
```

# g++ is the compiler, outputs binary to main


# This actually runs our program



# Compilation Crash Course

When we write C++ code, it needs to be translated into a form our computer understands it

```
$ g++ main.cpp -o main    # g++ is the compiler, outputs binary to main  
$ ./main                 # This actually runs our program
```



This is the compiler  
command

# Compilation Crash Course

When we write C++ code, it needs to be translated into a form our computer understands it

```
$ g++ main.cpp -o main    # g++ is the compiler, outputs binary to main  
$ ./main                 # This actually runs our program
```




This is the source file

# Compilation Crash Course

When we write C++ code, it needs to be translated into a form our computer understands it

```
$ g++ main.cpp -o main # g++ is the compiler, outputs binary to main
$ ./main               # This actually runs our program
```



This means that you're going to give a specific name to your executable

# Compilation Crash Course

When we write C++ code, it needs to be translated into a form our computer understands it

```
$ g++ main.cpp -o main # g++ is the compiler, outputs binary to main
$ ./main               # This actually runs our program
```

In this case it's main

# Makefiles and make

make is a “build system” program that helps you compile!

- You can specify what compiler you want to use
- In order to use **make** you need to have a **Makefile**

What does a **Makefile** look like? Let's take a look!

```
# Compiler
CXX = g++

# Compiler flags
CXXFLAGS = -std=c++20

# Source files and target
SRCS = ../main.cpp $(wildcard ../src/*.cpp)
TARGET = main

# Default target
all: $(TARGET)

# Build the executable
$(TARGET): $(SRCS)
    $(CXX) $(CXXFLAGS) $(SRCS) -o $(TARGET)

# Target to enable virtual inheritance
virtual: CXXFLAGS += -DVIRTUAL_INHERITANCE
virtual: $(TARGET)

# Clean up
clean:
    rm -f $(TARGET)
```

```
# Compiler
CXX = g++

# Compiler flags
CXXFLAGS = -std=c++20
```

Flags

```
# Source files and target
SRCS = ../main.cpp $(wildcard ../src/*.cpp)
TARGET = main
```

```
# Default target
all: $(TARGET)
```

```
# Build the executable
```

```
$(TARGET): $(SRCS)
    $(CXX) $(CXXFLAGS) $(SRCS) -o $(TARGET)
```

Targets

Rules

```
# Clean up
clean:
    rm -f $(TARGET)
```


The target, in our case `main` depends on the rules which are really just the source files!

# CMake

**CMake** is a build system generator.

So you can use **CMake** to generate Makefiles

Is like a higher level abstraction for Makefiles



***CMake***



# CMakeLists.txt

```
cmake_minimum_required(VERSION 3.10)

project(cs106l_inheritance)

set(CMAKE_CXX_STANDARD 20)

include_directories(include)

add_definitions(-DVIRTUAL_INHERITANCE)

file(GLOB SRC_FILES "src/*.cpp")

add_executable(main main.cpp ${SRC_FILES})
```

This is the cmake file for our assignment – it looks more like a programming language!