```
/*
Components
Arduino Uno R3
Shift Register 74HC595N
Wires
8 LEDs
8 220 ohm Resisters
Breadboard
*/
int latchPin = 8;//Pin 12
int clockPin = 12;//Pin 11
int dataPin = 11;//Pin 14
int x=0;
void setup() {
 Serial.begin(9600);
  pinMode(latchPin, OUTPUT);
  pinMode(clockPin, OUTPUT);
 pinMode(dataPin, OUTPUT);
}
void loop(){
    digitalWrite(latchPin,LOW);
    for(x=0;x<=255;x++){
                                               //Increments variable x from 0 to
255
        shiftOut(dataPin, clockPin, MSBFIRST,x); //Performs Bit shift operation
        digitalWrite(latchPin,HIGH);
        delay(1000);
    }
}
```

```
/*
Components
Arduino Uno R3
Shift Register 74HC595N
Wires
8 LEDs
8 220 ohm Resisters
Breadboard
*/
int latchPin = 8;//Pin 12
int clockPin = 12;//Pin 11
int dataPin = 11;//Pin 14
int x=0;
void setup() {
  Serial.begin(9600);
  pinMode(latchPin, OUTPUT);
  pinMode(clockPin, OUTPUT);
  pinMode(dataPin, OUTPUT);
}
void loop(){
  while (!Serial.available()) {}
  digitalWrite(latchPin,LOW);
  x=Serial.parseInt();
                               //Receives Input from Serial Monitor
    if(x>0 && x<256){
      Serial.print("Received : ");
      Serial.println(x);
      shiftOut(dataPin, clockPin, MSBFIRST,x); //Performs bit shift operation
    if(x>=256\&&x!=0){
      x=0;
      shiftOut(dataPin, clockPin, MSBFIRST,x);
      Serial.println("Invalid Number");
      Serial.println("Reset");
    }
  digitalWrite(latchPin,HIGH);
  delay(1000);
}
```