

20/10/2025

# Procédure

## Switch

### Table des matières

Configuration du switch ..... 1

Valentin TRILLAUD  
HPK

## Configuration du switch

## Configurer les VLAN :

| VLAN | Name               | Status    | Ports                                                                            |
|------|--------------------|-----------|----------------------------------------------------------------------------------|
| 1    | default            | active    | Fa0/15, Fa0/16, Fa0/17, Fa0/18<br>Fa0/19, Fa0/20, Fa0/21, Fa0/22<br>Gi0/1, Gi0/2 |
| 10   | VLAN0010           | active    |                                                                                  |
| 111  | Informatique       | active    | Fa0/1, Fa0/2                                                                     |
| 112  | Direction          | active    | Fa0/3, Fa0/4                                                                     |
| 113  | Developpement      | active    | Fa0/5, Fa0/6                                                                     |
| 114  | Commercial         | active    | Fa0/7, Fa0/8                                                                     |
| 115  | RH/Compta          | active    | Fa0/9, Fa0/10                                                                    |
| 116  | Support            | active    | Fa0/11, Fa0/12                                                                   |
| 117  | Visiteurs          | active    | Fa0/13, Fa0/14                                                                   |
| 211  | WAN                | active    | Fa0/23                                                                           |
| 411  | LAN                | active    | Fa0/24                                                                           |
| 1002 | fddi-default       | act/unsup |                                                                                  |
| 1003 | token-ring-default | act/unsup |                                                                                  |
| 1004 | fddinet-default    | act/unsup |                                                                                  |
| 1005 | trnet-default      | act/unsup |                                                                                  |

### Mettre les interfaces en mode access et G0/0 en trunk :

[illegible]

```
interface FastEthernet0/23
  switchport access vlan 211
  switchport mode access
!
interface FastEthernet0/24
  switchport access vlan 411
  switchport mode access
!
interface GigabitEthernet0/1
  switchport mode trunk
!
interface GigabitEthernet0/2
!
interface Vlan1
  no ip address
!
interface Vlan111
  no ip address
!
ip http server
ip http secure-server
!
!
line con 0
line vty 5 15
!
end
```