42U -Floor Standing Rack

BoostRack Cabinets are feature-rich rack enclosures optimized for easy installation, managing cables, integrating power distribution, and maximizing airflow. These racks are multi-functional rack enclosures designed to meet current IT market trends and applications ranging from high density computing and networking to broadcast and audio-video.

Standard

Comply with ANSI/EIARS-310-D,DIN41491;PART1,IEC297-2,DIN41494;PART7,GB.T3047.2-92 Standard.Compatible with metric ETSI and 19 inchintermational standard



Features

Material: Cold Rolled Steel
Modern stylish appearance and elegant exterior
19" standard assembly width
Detachable Composite Structure
Vertical cabinet can move backwards and forwards and adjust up and down to mount instrument
Fan heat dissipation device
Equipped with castor and adjustment feet
Degrease, acid picking, rust prevention and parkerizing pure water cleaning, static electricity plastic for the surface
High strength toughened glass or perforated front door
Maximum Static Loading Capacity:800KGS(With adjustable feet)
Color: Light Gray or Black

Standard Attached Accessories

With Screw and Nut
With 4pcs castor and adjustement feet
With 2 fans for 600×600MM for cabinets
With 4 fans for 600×800/900/1000MM for cabinets

Packing

Whole package or flat package
(Whole package: The cabinet have been assembled.The whole cabinet are packed into one export carton.
Flat package: The cabinet is disassembled and pakced into 2 or 3 export cartons.)

Other Optional Accessories:

1. Sliding shelf
2. 19" PDU
3.Fixed shelf
4.Others according to Customer's requirements

Main parts for floor cabinet

No.	Specification	Qty.	Unit	Material	Surface Finish	Remark
1	Top Cover	1	PCS	SPCC Cold rolled steel 1.2	Powder coated	/
2	Bottom panel	1	PCS	SPCC Cold rolled steel 1.2	Powder coated	/
3	Mounting Profile	4	PCS	SPCC Cold rolled steel 2.0	Powder coated	/
4	Mounting angle	6	PCS	SPCC Cold rolled steel 1.2	Powder coated	4pcs of lower 32U
5	Toughened glass or mesh front door	1	PCS	SPCC 1.2/Toughened glass5.0	Powder coated	High Density vented door/ sheet steel door/ double section high density vented door optional
6	Frame	2	PCS	SPCC Cold rolled steel 1.2	Powder coated	/
7	Fan unit	1	PCS	SPCC Cold rolled steel 1.2	Powder coated	/
8	Fan	4	PCS	120*120*38mm	/	2pcs for over 600 width and 600 depth
9	Side panel	2	PCS	SPCC Cold rolled steel 1.0	Powder coated	/
10	rear door	1	PCS	SPCC Cold rolled steel 1.2	Powder coated	/
11	Handle lock for front door	1	PCS	/	Galvanization	with 2keys
12	Small round lock for rear door	1	PCS	/	Galvanization	with 2keys
13	M6 Screw and Square Nuts	20	SET	steel	Zinc coated	/
14	M10 Adjustable feet	4	PCS	steel	Zinc coated	/
15	Wheels	4	PCS	/	/	/

Size	Width	Depth	Part No.
42U	600 mm	600 mm	2178-G/2177-M
42U	600 mm	800 mm	2068-G/2066-M

Size	Width	Depth	Part No.
42U	600 mm	1000 mm	206810-G/114801-M
42U	600 mm	1200 mm	206812-G

Structure drawing

The Cabinet Installation Diagram

1. Front Glass Door
2. Side Door
3. Top Cover
4. Top Cover Board
5. Back Door
6. Frame
7. Mounting Angle
8. Bottom Cover
9. Mounting Profile
10. Fixed Shelf
11. Fan Tray
12. M8*12 Inside Hexagonal Screw
13. Adjustable Feet
14. Castors
15. Bottom Cover Board
16. M8 Flange Nut
17. M4*8 Self-Tapping Screw
18. M6*12 & Washer
19. M6 Cage & Nuts
20. L Type Side Door Baffle
21. Cages for Grounding

