25U - Floor Standing/Hanging Rack

BoostRack Cabinets are feature-rich rack enclosures optimized for easy installation, managing cables, integrating power distribution, and maximizing airflow. These racks are multi-functional rack enclosures designed to meet current IT market trends and applications ranging from high density computing and networking to broadcast and audio-video.


Dimensions

Type	19 inch standard
Size	25U
Width	600 mm
Height	1220 mm
Depth	600 mm
Gross Weight	38 KG (Including the packaging)
Net Weight	40 KG



Cabinet Features

- 19" mounting angles
- Front glass door with lock and handle
- Rear lattice metal
- Both the doors can be mounted to be opening from either side
- Lock on the front door with handle and rear door with duplicate keys
- Removable side panels
- Adjustable jacking feet
- Two fans tray with cable for connection
- Extra cage nuts provided(30 Pieces)
- Earthing screws



Technical Specifications

- All steel construction
- Frame made of 1.2 mm thick SPCC
- Fixed shelves made of 1.2 mm thick SPCC (Optional)
- Mounting angles made of 2.0 mm thick steel
- Strong structure of individually fabricated components
- Manufactured using CNC machine
- Surface Finish: Matt Black Epoxy Powder Coated Paint (RAL 9005)

Power Distribution and cooling fan

- Max Current: 13 Amps
- Max Output Power: 3250 Watts
- Rated voltage: 200 -250 Volts 50-60 HZ
- Six Outlet UK Type
- Cooling Fan : Lower noise, Less than 48db, Air flow 50-110 CBM/H

Ordering Information

Size	Width	Depth	Part No.
25U	600 mm	600 mm	1194 Glass Door
25U	600 mm	600 mm	1195 Perforated Door
25U	600 mm	500 mm	2226 Glass door