

```

1: unit PayeeNames;
2:
3: {$mode objfpc}{$H+}
4:
5: //=====
6: //
7: // Unit : PayeeNames.pas
8: //
9: // Description :
10: //
11: // Called By : AppInit : ShowInit
12: //
13: // Calls : Settings
14: //
15: // Ver. : 1.0.0
16: //
17: // Date : 20 Mar 2015
18: //
19: //=====
20:
21: interface
22:
23: uses
24:   Classes, SysUtils, db, dbf, FileUtil, Forms, Controls, Graphics, Dialogs,
25:   // Application units
26:   Settings;
27:
28:
29: type
30:
31:   { TfrmPayeeNames }
32:
33:   TfrmPayeeNames = class(TForm)
34:     dbfPayeeNamesTable: TDbf;
35:     dsPayeeNamesTable: TDataSource;
36:     procedure FormShow(Sender: TObject);
37:   private
38:     { private declarations }
39:     var
40:       strDefaultPayeeNamesFileName : string;
41:   public
42:     { public declarations }
43:     function CreateDefaultPayeeNames : boolean;
44:   end;
45:
46: var
47:   frmPayeeNames: TfrmPayeeNames;
48:
49: implementation
50:
51: {$R *.lfm}
52:
53: const
54:
55:   cstrPayeeNamesFileName = 'PayeeNames.dat';
56:
57: var
58:
59:   PayeeNamesFile : TextFile;
60:

```

```
61: //=====
62: //          SUPPORT ROUTINES
63: //=====
64:
65: //=====
66: //          FUNCTIONAL ROUTINES
67: //=====
68:
69: //=====
70: function TfrmPayeeNames.CreateDefaultPayeeNames : boolean;
71: // This routine creates and saves a Textfile consisting of a minimum default list of
72: // Payee Names to be used as base for the Payee Names Table of a new
73: // Logbook. It is called when the application is first installed and whenever a new
74: // Setting.cfg file is created.
75: //
76: begin
77:
78:     // Open the PayeeNames File for Writing
79:     strDefaultPayeeNamesFileName := frmSettings.strDataPath +
80:                                     cstrPayeeNamesFileName;
81:     AssignFile (PayeeNamesFile, strDefaultPayeeNamesFileName);
82:     Rewrite(PayeeNamesFile);
83:     Writeln(PayeeNamesFile, '[PayeeNames Ver. 1.0.0]');
84:     Writeln(PayeeNamesFile, 'Other');
85:
86:     // Close the File
87:     CloseFile (PayeeNamesFile);
88:
89: end; // function CreateDefaultPayeeNames : boolean;
90:
91: //=====
92: //          MENU ROUTINES
93: //=====
94:
95: ///=====
96: //          TOOLBAR ROUTINES
97: //=====
98:
99: //=====
100: //          STATUSBAR ROUTINES
101: //=====
102:
103: //=====
104: //          FILE ROUTINES
105: //=====
106:
107: //=====
108: //          DATABASE ROUTINES
109: //=====
110:
111: //=====
112: //          FUNCTIONAL ROUTINES
113: //=====
114:
115: //=====
116: //          COMMAND BUTTON ROUTINES
117: //=====
118:
119: //=====
120: //          CONTROL ROUTINES
```

```
121: //=====
122:
123: //=====
124: //  OnChange Routines
125: //=====
126:
127: //=====
128: //  OnClick Routines
129: //=====
130:
131: //=====
132: //  OnKeypress Routines
133: //=====
134:
135: //=====
136: //          FORM ROUTINES
137: //=====
138: procedure TfrmPayeeNames.FormShow(Sender: TObject);
139: begin
140:   strDefaultPayeeNamesFileName := frmSettings.strDataPath +
141:                                     cstrPayeeNamesFileName;
142:   showmessage(strDefaultPayeeNamesFileName);
143: end; // procedure TfrmPayeeNames.FormShow
144:
145: //=====
146:
147:
148: end. // unit PayeeNames
149:
150:
```