

Microsoft Windows [Version 10.0.26100.3323]

(c) Microsoft Corporation. All rights reserved.

C:\Users\Lenovo>mysql -u root -p

Enter password: ****

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 34

Server version: 8.0.41 MySQL Community Server - GPL

Copyright (c) 2000, 2025, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> use customer;

Database changed

mysql> show tables;

+-----+

| Tables_in_customer |

+-----+

| cust |

| customer |

+-----+

2 rows in set (0.01 sec)

```
mysql> select*from cust desc;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'desc' at line 1

```
mysql> selct*from customer;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'selct*from customer' at line 1

```
mysql> use customer;
```

Database changed

```
mysql> select*from customer;
```

```
+-----+-----+-----+-----+-----+
| id | Name   | Age | Address | Salary |
+-----+-----+-----+-----+-----+
|  1 | Ramesh | 32  | Ahmedabad | 2000 |
|  2 | Khilan | 25  | Delhi    | 1500 |
|  3 | Kaushik | 23  | Kota     | 2000 |
|  4 | Chaitali | 25  | Mumbai   | 6500 |
|  5 | Hardik | 27  | Bhopal   | 8500 |
|  6 | Komal  | 22  | Hyderabad | 4500 |
|  7 | Muffy  | 24  | Indore   | 10000 |
+-----+-----+-----+-----+-----+
```

7 rows in set (0.01 sec)

```
mysql> use cust;
```

ERROR 1049 (42000): Unknown database 'cust'

```
mysql> show tables;
```

```
+-----+
| Tables_in_customer |
+-----+
```

```
| cust      |
| customer  |
```

```
+-----+
```

2 rows in set (0.00 sec)

```
mysql> Create table orders(oid int,date DATETIME,CUSTOMER_ID INT primary key,Amount
int);
```

Query OK, 0 rows affected (0.12 sec)

```
mysql> INSERT INTO ORDERS (OID, DATE, CUSTOMER_ID, AMOUNT) VALUES
```

```
-> (102, '2009-10-08 00:00:00', 3, 3000),
```

```
-> (100, '2009-10-08 00:00:00', 3, 1500),
```

```
-> (101, '2009-11-20 00:00:00', 2, 1560),
```

```
-> (103, '2008-05-20 00:00:00', 4, 2060);
```

ERROR 1062 (23000): Duplicate entry '3' for key 'orders.PRIMARY'

```
mysql> Create table orders(oid int primary key,date DATETIME,CUSTOMER_ID I
NT,Amount int);
```

ERROR 1050 (42S01): Table 'orders' already exists

```
mysql> drop table cust;
```

Query OK, 0 rows affected (0.03 sec)

```
mysql> drop table orders;
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> show tables;
```

```
+-----+
```

```
| Tables_in_customer |
```

```
+-----+
```

```
| customer      |
```

```
+-----+
```

1 row in set (0.00 sec)

```
mysql> CREATE TABLE ORDERS (OID INT Primary key,DATE DATETIME,CUSTOMER_ID IN  
T,AMOUNT int);
```

Query OK, 0 rows affected (0.06 sec)

```
mysql> insert into orders(OID, DATE, CUSTOMER_ID, AMOUNT) values(102, '2009-  
10-08 00:00:00', 3, 3000),(100, '2009-10-08 00:00:00', 3, 1500),(101, '2009-  
11-20 00:00:00', 2, 1560),(103, '2008-05-20 00:00:00', 4, 2060);
```

Query OK, 4 rows affected (0.01 sec)

Records: 4 Duplicates: 0 Warnings: 0

```
mysql> select*from orders;
```

```
+----+-----+-----+-----+
```

```
| OID | DATE          | CUSTOMER_ID | AMOUNT |
```

```
+----+-----+-----+-----+
```

```
| 100 | 2009-10-08 00:00:00 |      3 | 1500 |
```

```
| 101 | 2009-11-20 00:00:00 |      2 | 1560 |
```

```
| 102 | 2009-10-08 00:00:00 |      3 | 3000 |
```

```
| 103 | 2008-05-20 00:00:00 |      4 | 2060 |
```

```
+----+-----+-----+-----+
```

4 rows in set (0.00 sec)

```
mysql> select id,name,age,amount from customer,orders where customer.id=orde  
rs.customer_id;
```

```
+----+-----+-----+-----+
```

id	name	age	amount
----	------	-----	--------

2	Khilan	25	1560
---	--------	----	------

3	Kaushik	23	3000
---	---------	----	------

3	Kaushik	23	1500
---	---------	----	------

4	Chaitali	25	2060
---	----------	----	------

4	Chaitali	25	2060
---	----------	----	------

4	Chaitali	25	2060
---	----------	----	------

4 rows in set (0.00 sec)

```
mysql> select id,name,amount,date from customer inner join orders on custome
```

```
r.id=orders.customer_id;
```

id	name	amount	date
----	------	--------	------

2	Khilan	1560	2009-11-20 00:00:00
---	--------	------	---------------------

3	Kaushik	3000	2009-10-08 00:00:00
---	---------	------	---------------------

3	Kaushik	1500	2009-10-08 00:00:00
---	---------	------	---------------------

4	Chaitali	2060	2008-05-20 00:00:00
---	----------	------	---------------------

4	Chaitali	2060	2008-05-20 00:00:00
---	----------	------	---------------------

4	Chaitali	2060	2008-05-20 00:00:00
---	----------	------	---------------------

4	Chaitali	2060	2008-05-20 00:00:00
---	----------	------	---------------------

4 rows in set (0.00 sec)

```
mysql> select id,name,amount,date from customer left join orders on customer
```

```
.id=orders.customer_id;
```

id	name	amount	date
----	------	--------	------

1	Ramesh	NULL	NULL
---	--------	------	------

2	Khilan	1560	2009-11-20 00:00:00
---	--------	------	---------------------

2	Khilan	1560	2009-11-20 00:00:00
---	--------	------	---------------------

2	Khilan	1560	2009-11-20 00:00:00
---	--------	------	---------------------

	3	Kaushik		3000		2009-10-08 00:00:00	
	3	Kaushik		1500		2009-10-08 00:00:00	
	4	Chaitali		2060		2008-05-20 00:00:00	
	5	Hardik		NULL		NULL	
	6	Komal		NULL		NULL	
	7	Muffy		NULL		NULL	
+-----+-----+-----+-----+							

8 rows in set (0.00 sec)

```
mysql> select id,name,amount,date from customer right join orders on custome
r.id=orders.customer_id;
```

+-----+-----+-----+-----+							
id	name	amount	date				
+-----+-----+-----+-----+							
	3	Kaushik		1500		2009-10-08 00:00:00	
	2	Khilan		1560		2009-11-20 00:00:00	
	3	Kaushik		3000		2009-10-08 00:00:00	
	4	Chaitali		2060		2008-05-20 00:00:00	
+-----+-----+-----+-----+							

4 rows in set (0.00 sec)

```
mysql> select id,name,amount,date from customer full join orders on customer
.id=orders.customer_id;
```

ERROR 1054 (42S22): Unknown column 'customer.id' in 'on clause'

```
mysql> select id,name,amount,date from customer full join orders on
customer.id=orders.customer_id;
```

ERROR 1054 (42S22): Unknown column 'customer.id' in 'on clause'

```
mysql> select id,name,amount,date from customer left join orders on customer
```

.id=orders.customer_id

-> union all

-> select id,name,amount,date from customer right join orders on custome

r.id=orders.customer_id;

id	name	amount	date
1	Ramesh	NULL	NULL
2	Khilan	1560	2009-11-20 00:00:00
3	Kaushik	3000	2009-10-08 00:00:00
3	Kaushik	1500	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00
5	Hardik	NULL	NULL
6	Komal	NULL	NULL
7	Muffy	NULL	NULL
3	Kaushik	1500	2009-10-08 00:00:00
2	Khilan	1560	2009-11-20 00:00:00
3	Kaushik	3000	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00

12 rows in set (0.00 sec)

mysql> select id,name,amount,date from customer right join orders on
customer.id=orders.customer_id;

id	name	amount	date
3	Kaushik	1500	2009-10-08 00:00:00

	2		Khilan		1560		2009-11-20 00:00:00	
	3		Kaushik		3000		2009-10-08 00:00:00	
	4		Chaitali		2060		2008-05-20 00:00:00	

```
+-----+-----+-----+-----+
```

4 rows in set (0.00 sec)

```
mysql> select id,name,amount,date from customer right join orders on
customer.id=orders.customer_id
```

-> intersect

```
-> select id,name,amount,date from customer left join orders on customer
.id=orders.customer_id;
```

```
+-----+-----+-----+-----+
```

	id		name		amount		date	
--	----	--	------	--	--------	--	------	--

```
+-----+-----+-----+-----+
```

	3		Kaushik		1500		2009-10-08 00:00:00	
	2		Khilan		1560		2009-11-20 00:00:00	
	3		Kaushik		3000		2009-10-08 00:00:00	
	4		Chaitali		2060		2008-05-20 00:00:00	

```
+-----+-----+-----+-----+
```

4 rows in set (0.01 sec)

```
mysql> select id,name,amount,date from customer left join orders on
customer.id=orders.customer_id
```

-> except

```
-> select id,name,amount,date from customer right join orders on custome
r.id=orders.customer_id;
```

```
+-----+-----+-----+-----+
```

	id		name		amount		date	
--	----	--	------	--	--------	--	------	--

```
+-----+-----+-----+-----+
```

	1	Ramesh		NULL		NULL	
	5	Hardik		NULL		NULL	
	6	Komal		NULL		NULL	
	7	Muffy		NULL		NULL	

+-----+-----+-----+-----+

4 rows in set (0.00 sec)

mysql>

mysql> select id,name,age,address,salary

-> from customer

-> where salary is not null;

+-----+-----+-----+-----+

id	name	age	address	salary	
----	------	-----	---------	--------	--

+-----+-----+-----+-----+

	1	Ramesh		32	Ahmedabad		2000	
--	---	--------	--	----	-----------	--	------	--

	2	Khilan		25	Delhi		1500	
--	---	--------	--	----	-------	--	------	--

	3	Kaushik		23	Kota		2000	
--	---	---------	--	----	------	--	------	--

	4	Chaitali		25	Mumbai		6500	
--	---	----------	--	----	--------	--	------	--

	5	Hardik		27	Bhopal		8500	
--	---	--------	--	----	--------	--	------	--

	6	Komal		22	Hyderabad		4500	
--	---	-------	--	----	-----------	--	------	--

	7	Muffy		24	Indore		10000	
--	---	-------	--	----	--------	--	-------	--

+-----+-----+-----+-----+

7 rows in set (0.00 sec)

mysql> select id,name,age,address,salary

-> from customer

-> where salary is null;

Empty set (0.00 sec)