

pCT_TOOLS DOCUMENTATION:

THE FOLLOWING DOCUMENTATION DESCRIBES EACH BASH FUNCTION/SCRIPT AND OUTLINES THEIR OPTIONS AND USAGE.

BASH SCRIPTS:

DESCRIPTION OF BASH SCRIPTS SUPPLIED IN pCT_TOOLS REPOSITORY AND THEIR USAGE

.bash_profile

Description: – Generic bash profile pCT users can use for shell sessions on Kodiak/Tardis. This sources the load_pct_functions.sh script and loads its bash functions, variables, and aliases/shortcuts so (1) these can be used to perform the host dependent and session setup tasks during user login and (2) they are made available to the pCT user during their shell session

load_pct_functions.sh

Description: – Loads the bash functions, variables, and aliases/shortcuts useful to pCT users on Kodiak/Tardis. This is then sourced by the .bash_profile (provided separately) so (1) these can be used to perform the host dependent and session setup tasks during user login and (2) they are made available to the pCT user during their shell session

link_raw_data.sh

USAGE: `USAGE: [-h][-p <data path>][-i <angle interval>]`

Description: – Generates soft data links to raw data files (/ion/pCT_data/raw_data/<run_date>) for a particular run date and organizes these in the /ion/pCT_data/organized_data directory by phantom name according to the standardized naming/organizational scheme

Options:

Option Details:

-h

print help to terminal

-p

path to source raw data (DEFAULT: current working directory)

-i

set angle interval [°] between data files (DEFAULT: 4 [°])

link_projection_data.sh

USAGE: [-h][-EGT][-g][-p <data path>][-i <angle interval>]

Description: – Generates soft data links to preprocessed data files (/ion/pCT_data/preprocessed_data/<run_date>) for a particular run date and organizes these in the /ion/pCT_data/organized_data directory by phantom name according to the standardized naming/organizational scheme

Options:

Option Details:

- h** print help to terminal
- p** path to source preprocessed data (DEFAULT: current working directory)
- i** set angle interval [°] between data files (DEFAULT: 4 [°])
- E** Experimental data flag (DEFAULT)
- G** GEANT4 data flag
- T** TOPAS data flag

stage_preprocessed_data.sh

USAGE: [-h][-v][-O][-p <readme/data path>] [-f <readme.txt filename>]

Description: – Used to stage preprocessed data with naming/organization appropriate for immediate sharing by specifying location of preprocessed_data and corresponding readme.txt file from which the phantom name, run #/tag(s), and projection angle can be parsed

Options:

Option Details:

- h** print help to terminal
- v** verbose flag: terminal output 'on' (DEFAULT: \$verbose_flag)
- d** date of preprocessing (DEFAULT: \$preprocessed_date (today))
- p** path to data and readme.txt text file (DEFAULT: \$preprocessed_path)
- f** filename of readme.txt text file (DEFAULT: \$filename)
- O** specifies old date format MMDDYYYY is used (DEFAULT: 'YY-MM-DD' format)

rename-files.sh

USAGE: [-h][\$1 <angle interval>]

Description: – Rename preprocessed data files in current folder, changing each file with .dat.root.reco.root.bin extension to projection.xxx.bin for each angle xxx

Options:

Option Details:

-h

print help to terminal

-i

angle interval between preprocessed data files (DEFAULT: 4 [°])

BASH FUNCTIONS:

DESCRIPTION OF BASH FUNCTIONS SUPPLIED IN PCT_TOOLS REPOSITORY AND THEIR USAGE

add_rcode_repo

USAGE: [-h][-u <username>][-a <git account>][-r <git repo>]

Description: – add GitHub repository to a user's code directory on Tardis

Options:

Option Details:

-h

print help to terminal

-u

username (DEFAULT: \$username)

-a

git account (DEFAULT: \$account)

-r

git repository (DEFAULT: \$repo)

set_rcode

USAGE: [-h][-G][-g][-a <git account>][-r <git repo>][-b <git branch>] [-u <username>]

Description: – add GitHub repository to a user's code directory on Tardis

Options:

Option Details:

- h** print help to terminal
- a** git account (DEFAULT: \$account)
- r** git repository (DEFAULT: \$repo)
- b** git branch (DEFAULT: \$branch)
- u** username, if applicable (DEFAULT: \$username)
- G** reconstruction group username flag (DEFAULT: \$username)
- g** global git code repositories flag (DEFAULT: user git code directories)

nvccgen

USAGE: [-h][\$1][\$2]

Description: – compile pCT_Reconstruction code with argument #1/#2 used to set architecture/code

Options:

Option Details:

- h** print help to terminal
- \$1** NVCC architecture specification # (35 used in compute_35)
- \$2** NVCC code specification # (i.e. 35 used in sm_35)

runrecon

USAGE: [-h][\$1][\$2]

Description: – compile and run pCT_Reconstruction code with argument #1/#2 used to set architecture/code

Options:

Option Details:

- h** print help to terminal
- \$1** NVCC architecture specification # (35 used in compute_35)
- \$2** NVCC code specification # (i.e. 35 used in sm_35)

construct_recon_path

USAGE: [-h][-EGT][-IO][-o <object name>] [-r <run date>][-n <run # + tag(s)>] [-d <preprocessed date>][-D <reconstruction date>]

Description: – construct input or output data path for appropriately organized reconstruction data

Options:

Option Details:

-h	print help to terminal
-v	verbose console output on (DEFAULT: 'off')
-o	object name (REQUIRED)
-r	run date (REQUIRED)
-n	run # + tag(s) (REQUIRED)
-d	preprocessed date (DEFAULT: today)
-D	reconstruction date, if applicable (DEFAULT: today)
-E	Experimental data flag (DEFAULT)
-G	GEANT4 data flag
-T	TOPAS data flag
-I	input data flag
-O	output data flag

construct_preprocessing_path

USAGE: [-h][-EGT][-IO][-o <object name>] [-r <run date>][-n <run # + tag(s)>] [-d <preprocessed date>]

Description: – construct input or output data path for appropriately organized preprocessed data

Options:

Option Details:

-h	print help to terminal
-v	verbose console output on (DEFAULT: 'off')
-o	object name (REQUIRED)
-r	run date (REQUIRED)
-n	run # + tag(s) (REQUIRED)
-d	preprocessed date (DEFAULT: today)
-E	Experimental data flag (DEFAULT)
-G	GEANT4 data flag
-T	TOPAS data flag
-I	input data flag
-O	output data flag

organize_data

USAGE: [-h] [-MC] [-EGT] [-IO] [-t <destination>] [-o <object name>]
 [-r <run date>] [-n <run #/tag(s)>] [-d <preprocessed date>]
 [-D <reconstruction date>]

Description: – construct input or output data path for appropriately organized reconstruction data

Options:

Option Details:

-h	print help to terminal
-v	verbose console output on (DEFAULT: 'off')
-M	move data (DEFAULT: copy)
-C	copy data (DEFAULT: copy)
-p	path to data (DEFAULT: current working directory)
-t	write output hierarchy to (DEFAULT: current working directory)
-o	object name (REQUIRED)
-r	run date (REQUIRED)
-n	run # + tag(s) (REQUIRED)
-d	preprocessed date (DEFAULT: today)
-D	reconstruction date, if applicable (DEFAULT: today)
-E	Experimental data flag (DEFAULT)
-G	GEANT4 data flag
-T	TOPAS data flag
-I	input data flag
-O	output data flag

stage_preprocessed_data.sh

USAGE: [-h][-v][-O][-p <readme/data path>] [-f <readme.txt filename>]

Description: – Used to stage preprocessed data with naming/organization appropriate for immediate sharing by specifying location of `preprocessed_data` and corresponding `readme.txt` file from which the phantom name, run #/tag(s), and projection angle can be parsed

Options:

Option Details:

- `-h` print help to terminal
- `-v` verbose flag: terminal output 'on' (DEFAULT: `$verbose_flag`)
- `-d` date of preprocessing (DEFAULT: `$preprocessed_date` (today))
- `-p` path to data and `readme.txt` text file (DEFAULT: `$preprocessed_path`)
- `-f` filename of `readme.txt` text file (DEFAULT: `$filename`)
- `-O` specifies old date format MMDDYYYY is used (DEFAULT: 'YY-MM-DD' format)