



PILOT BRIEFING

Algiers Houarri - DAAG

NOT TO BE USED FOR REAL-WORLD

General information

The Maghreb vACC team is thrilled to warmly welcome you and provide professional air traffic control services as fly from Algiers.

Houari Boumediene Airport is located about 17km southeast of Algiers city centre. It is the busiest airport in Algeria and serves as the country's primary international gateway.

The airport serves as the primary hub of Air-Algerie, offering connections across Europe, Africa and the Middle East.

Our team is fully committed to delivering exceptional ATC services and making your flight memorable. Whether you're a seasoned pilot or new to the event, we are here to support you every step of the way.

Scenery

Scenery usage is strongly recommended. Here is the selection of scenery that we suggest you use when flying into or out of Casablanca!

Simulator	Freeware	Payware
MFS2020 & MSFS2024	-	ORBX
Prepar3D	-	PrealSoft
X-Plane	-	TDG

AIRAC

To prevent problems with inaccurate data, please make sure you have the most recent AIRAC cycle installed before your next flight. AIRAC for Microsoft Flight Simulator and Prepar3D: www.aero.sors.fr

Charts

It is important to have the latest version of the charts when flying. Through the Algerian eAIP, you can get a set of charts for Algiers Houari International airport.

These charts and the eAIP are directly accessible **here: vats.im/mag_da-charts**

Airfield data

Name: Algiers Houari

ICAO code: DAAG

IATA code: ALR

Coordinates: 36°41'27" N, 3°12'55" E

Radio Communication language: English (French)

Algiers Houari International Airport (DAAG) is the main international airport serving the capital city of Algeria, Algiers. Located approximately 17km southeast of Algiers city centre, DAAG is a modern airport with two runways, Runway 27/09 and Runway 23/05.

RWY	TORA	ADSA	TODA	LDA
05	3,500 m	3,500 m	3,500 m	3,500 m
23	3,500 m	3,500 m	3,500 m	3,500 m
09	3,500 m	3,500 m	3,500 m	3,500 m
27	3,500 m	3,700 m	3,500 m	3,500 m

Frequencies

Identifier	Callsign	Frequency
DAAG_DEL	Algiers Delivery	125.575 MHz
DAAG_GND	Algiers Ground	121.800MHz
DAAG_TWR	Algiers Tower	118.700 MHz
DAAG_APP	Algiers Approach	121.400 MHz

Start-up and pushback

Slots

Your CTOT (Calculated Take-off time) is determined by your **TOBT** (Target off-block time) and the average taxi time (around 8-10 minutes in Algiers, including pushback and taxiing).

The **TOBT** is when the pilot should be ready to start up/push back. It should be **5 minutes before** your TOBT.

When you are on the ground prior to requesting start-up or pushback you are expected to file your TOBT at **<https://vats.im/vdgs>**.

call ground (or delivery during high traffic) within 5 minute window before the TSAT.

This is the controller's assurance that you will be cleared to move within the next few minutes (**+/- 5 minutes** of TSAT). Typically, this approval coincides with pushback clearance. If cleared, the pushback process has to start **no later than 1 minute** and taxi **no later than 30 seconds after clearance**.

If pushback clearance is **not** received, **hold position until instructed**; this may be due to traffic crossing behind. Engine start occurs during pushback, even with start-up approval. **Only start engines at the gate if positioned at a taxi-out stand.**

5 MIN BEFORE TSAT — — — — — — — — —



DAH204F, aircraft ready, request start-up.



DAH04F, start-up approved.

Enroute clearance

Expect clearance during taxi with Ground controller after receiving taxi instructions.

Clearance requests should be kept short. **Please avoid unnecessarily long clearance requests** to reduce frequency congestions.



Ground, DAH204F, request enroute clearance, information D.



Cleared destination, after departure runway heading crossing 1500ft direct PECES climb FL360 DAH204F.



DAH204F, Ground, cleared destination, after departure runway heading crossing 1500ft direct PECES climb FL360.

Taxi

During taxi expect a long taxi due to many taxiways and if you wish to have progressive taxi than make a request to the controller.

Arrival Procedure

With Algiers Control

Tunis Control will not assign a STAR. Instead, you can expect direct routings, which will generally indicate the likely arrival flow.

- A direct to ZEM suggests you should expect the ILS approach for the approach.
- A direct to ALR which suggests you should expect the ILS approach via ALR VOR.

Please note that when approaching Algiers–Houari International Airport from the north, you may be required to commence your descent prior to establishing contact with Algiers Control.

With Algiers Approach

Upon initial contact, Algiers Approach will advise you of the expected approach and may assign a corresponding transition, depending on traffic and operational requirements otherwise might advise you to expect vectors for the approach.

Tower

Tower will provide standard separation and may issue traffic information on other arriving aircraft if visual separation is required.

Do not vacate the runway via another runway unless specifically instructed by the controller.

Tower will then issue your initial taxi instruction and handoff to ground.



Feedback

Feedback from pilots is always welcomed. Please leave all feedback for our controllers at vats.im/mag

Social media

Keep informed about Maghreb vACC's latest updates and events by following us on social media. Don't forget to share your experience with us at:

