

VATSIM
Malaysia



WMKK Pilot's Briefing

25 March 2026

Issue 1 (Revision 0)



Document Description

This document is published for the purpose of briefing to pilots about procedures used in Kuala Lumpur International Airport (WMKK). This Guideline shall be adhered to by all pilots flying in and out of WMKK.

This document shall be maintained, revised, updated or cancelled by Malaysia vACC Staff Team or any organisation that supersedes, replaces or assumes Malaysia vACC Staff Team responsibilities. Any suggestions for modification or amendment to this manual shall be addressed to Malaysia vACC Staff for review.

This document is only used for VATSIM purposes. **DO NOT** use this document for Real World flying whatsoever. VATSIM Malaysia vACC and its affiliate shall **NOT** be held responsible and accountable for the usage of this document in all Real-World Flying Activities.

This document shall be put into effect beginning **25 March 2026** and all previous SOPs or documents resembling the content put forth in this document shall be rendered void.

Prepared by:

Approved by:



Revisions

Revision	Effective Date	Changes	Amended by
1.0	18 September 2024	Initial Release Version	MI



Table of Contents

Table of Contents

1. Kuala Lumpur International Airport	4
2. General Information.....	4
2.1 Charts/Scenery, Runway Information, ATCs Position Callsign & Frequencies	4
2.2 Parking Positions	7
3. Departing from KLIA	10
3.1 SID Assignment	10
3.2 Initial Climb.....	11
3.3 ATC Clearance	11
3.4 Pushback	11
3.5 Taxi.....	11
3.6 Takeoff	12
4. Arriving to KLIA	12
4.1 STAR Assignment	12
4.2 Descent Planning	12
4.3 Runway Assignment.....	13
4.4 Approach	13
4.5 Landing.....	14
4.6 Taxi.....	14
5. Special Pilot Briefing for Hajj OPS 2026.....	15

1. Kuala Lumpur International Airport

Kuala Lumpur International Airport (KLIA) (IATA: KUL, ICAO: WMKK) is the main international airport serving Kuala Lumpur, the capital of Malaysia. It is located in the Sepang District of Selangor, approximately 45 km (28 mi) south of downtown Kuala Lumpur and serves the city's greater conurbation.

KLIA is the largest and busiest airport in Malaysia. In 2023, it handled 47,224,000 passengers, 980,040 tonnes of cargo and 819,026 aircraft movements. It is the world's 35th-busiest airport by total passenger traffic.

2. General Information

Since AIRAC 2209, there have been **major changes** within the Lumpur FIR airspace. It is recommended to use the **current AIRAC** when flying in or out of WMKK.

If you are on an older AIRAC, please advise the controller at first contact.

2.1 Charts/Scenery, Runway Information, ATCs Position Callsign & Frequencies

2.1.1 Charts for KLIA are available at <https://chartfox.org/WMKK> (VATSIM sign-in required) or <https://vatmy.org/charts/>

2.1.2 Available airport sceneries are listed down in the table below:

Simulator	Freeware	Payware
MSFS	The Secret Studios Freeware/Demo Version	The Secret Studios
X-Plane 11	Xplane.org	Cloudsurf Asia Simulation
P3D	AVSIM Library	A_A Sceneries
FSX	AVSIM Library	A_A Sceneries

2.1.3 Runway Information WMKK

RWYs	True Bearing
14L	146.01
14R	
15	
32R	326.01
32L	
33	


2.1.4 ATCs Position, Callsign & Frequencies

Position	Callsign	Frequencies	Remarks
WMKK_DEL	Lumpur Delivery	126.000	Responsible giving clearance for all IFR traffic
WMKK_GND	Lumpur Ground	121.800	Covers ground movement traffic both Terminal 1, Cargo & Terminal 2 when no other GND is online.
WMKK_A_GND	Lumpur Ground	122.850	Covers ground movement in Terminal 1 including Cargo area only.
WMKK_B_GND	Lumpur Ground	122.550	Covers ground movement traffic in Terminal 2 area only.
WMKK_TWR	Lumpur Tower	118.800	Covers all three RWYs 14L/32R, 14R/32L, 15/33 when no other TWR is online.
WMKK_1_TWR	Lumpur Tower	118.500	Covers RWYs 14R/32L only
WMKK_3_TWR	Lumpur Tower	119.800	Covers RWYs 15/33 only



WMKK_APP	Lumpur Radar	124.200	Covers both Arrival & Departure traffic inside the TMA zone when no other TMA controller online, and vertical limit is up to FL245.
WMKK_DEP	Lumpur Departure	135.250	Responsible to control Departure traffic outbound from WMKK up to 10000ft
WMFC_CTR	Lumpur Radar	132.800	Covers the whole FIRs of Kuala Lumpur FIR (WMFC)

2.2.1 There are three main parts of the apron, Terminal 1, Terminal 2 and the Cargo apron.





2.2.2 Terminal 1

Terminal 1 has two buildings: Main Terminal Building (MTB) and Satellite Terminal Building (STB).

MTB is used by **Malaysia Airlines and Batik Air Malaysia**, usually by **domestic flights** utilising **narrow-body** aircraft. However, international flights can operate from this terminal as well. **A and B** bays are located here.

STB is used by **Malaysia Airlines and Batik Air Malaysia wide-body** aircraft flying **international routes** and other **full-service carriers** such as Singapore Airlines, Cathay Pacific, Thai Airways etc. **C bays** are located here.

The Bunga Raya Complex is located west of Terminal 1. It is used by VVIP flights only.

2.2.3 Terminal 2

Terminal 2 is used exclusively by **low cost carriers**, mainly **AirAsia**.

Terminal 2 also has two buildings: Main Terminal Building (MTB) and Satellite Terminal Building (STB).

MTB is used for **domestic flights (J and K bays)** by AirAsia. It is worth noting that the K bays may also be used by AirAsia for international flights.

STB is used primarily by **international flights (P and Q bays)** by AirAsia, other AirAsia Group airlines (AirAsia Indonesia, AirAsia Thailand, AirAsia Philippines etc.) and other low cost carriers (Scoot, Jetstar Asia etc.). The southern apron of STB is used by low cost carriers which utilises widebody aircraft. (AirAsia X).

2.2.4 Cargo

Cargo carriers operate from the cargo apron which consists of the F bays.

3. Departing from KLIA

3.1 SID Assignment

Refer to the table below for the SIDs that ATC will usually assign. **Note that if your first waypoint is not listed here, it means you are on an old AIRAC and you must advise ATC at first contact.**

Waypoint	32R	33	14R	15	Remarks
ATIMU	1D	1F	1B	1C	
BIKDU				3C	via Y501 heading northbound towards Bangkok FIR
IBUKU					
KIMAT		3F		1C	via VPK heading eastbound towards Singapore FIR
MITOS		1F			via M630 heading to southeast towards Jakarta FIR
PIBOS					3C
PUGER				1C	
RUSBU					via A464 to WSSS (max level FL250)
SALAX					
Pilots with none of the first waypoints listed above shall be given a Standard Radar Departure (SRD).					

RWYs & SIDs: RWY14L 1A | RWY14R 1B | RWY15 1C/3C | RWY32R 1D | RWY32L 1E | RWY33 1F/3F

3.2 Initial Climb

Initial climbs in WMKK are **runway dependent**. The table below shows the initial climb altitudes for each departure runway.

Runway	14L/32R	14R/32L	15/33
Initial Climb (ft)	5000	6000	4000

3.3 ATC Clearance

When requesting ATC clearance with Lumpur Delivery, include your callsign, bay number, requested cruising flight level and ATIS information letter.

Pilot: Lumpur Delivery, MAS123, bay A3, request ATC clearance to Singapore, FL250, information A.

3.4 Pushback

Before requesting pushback, please make sure you have set your assigned squawk code as per your ATC clearance and set your transponder to Mode C.

Lumpur Ground will issue pushback instructions with direction of push in reference to the compass cardinal directions. **(Push and start approved facing EAST/WEST)** or alternatively facing the exit points of the apron **(Push and start approved, Exit T6/T5)**.

Note that on **Terminal 2**, aircraft will be pushed back onto the **white lines** instead of onto the taxiways (only for K even, J even, P odd and Q odd).

3.5 Taxi

To avoid delays for other users, **start taxiing as soon as possible after receiving your taxi clearance** from Lumpur Ground. Always **hold short** before the **parallel taxiways** (B, D, Q or Z), unless specifically cleared otherwise by ATC and wait for handoff to Lumpur Tower.

Standard Routes

During high levels of traffic, Lumpur Ground may instruct you to taxi via the published standard taxi routes. You may refer to the taxi charts for the standard routes.

Intersection Departures

Lumpur Ground has no authority to assign intersection departures for all runways. **Lumpur Tower will by default assign full length departures. If you are able for an intersection departure, advise Lumpur Tower on first contact.**

3.6 Takeoff

When Lumpur Tower instructs you to **line-up and wait behind a departing/arriving** traffic, it is **your responsibility** to ensure that the departing/arriving aircraft has **cleared the runway threshold** before lining up.

After taking off, Lumpur Tower will not give you instructions for frequency switch to Lumpur Radar. All departing aircraft shall switch to and establish contact with Lumpur Radar as soon as practicable before passing 2000ft.

4. Arriving to KLIA

4.1 STAR Assignment

STARs into KLIA are assigned based on your final waypoint of your flight plan route. When Lumpur Radar is **online**, you will be assigned to one of the four **Point-Merge System (PMS)** STARs. More information about PMS can be found here [Point merge | EUROCONTROL](#). The four PMS STARs are **1G, 1H, 1J and 1K**.

At the hours of **1600z-2100z**, **3K and 3J STARs** are to be used providing there is **low-levels of traffic**. You can also expect the **RNP X approach** when using these STARs.

4.2 Descent Planning

As part of Air Traffic Flow Management measures to regulate arrivals into KLIA. The following height restrictions shall be observed:

WAYPOINT	PUGER	NIREN	KAKAK	PULIP	SAROX	GUPTA	SALAX
RESTRICTION	<u>FL310</u>	<u>FL270</u>	<u>FL270</u>	<u>FL250</u>	<u>FL230</u>	<u>FL230</u>	<u>FL220</u>

4.3 Runway Assignment

KLIA's weather is mostly calm throughout the year. Therefore, during the first half of the year runways 32/33 shall be the duty runways and runways 14/15 shall be the duty runways during the second half (this is still **subject to winds** at KLIA).

For runways 32/33, flights bound for **Terminal 1** will be assigned runway **32L**, and flights for **Terminal 2** can be assigned either runways **32R** or **33**.

For runways 14/15, flights bound for **Terminal 1** will be assigned runway **14L**, and flights for **Terminal 2** will be assigned runway **15**.

To maximise the flow of traffic into KLIA during high traffic events, arriving traffic may be assigned to land on a runway commonly used for departures.

4.4 Approach

IT IS IMPORTANT TO SET THE CORRECT INITIAL APPROACH (TRANSITION) IN YOUR FMC.

The approach into KLIA will usually be an ILS approach. Other approaches are available upon request.

Speed Restrictions

Pilots shall adopt the following speeds when notified that the STAR is cancelled:

- Under radar vectors:
 1. 250 KIAS on passing 10000 ft;
 2. 220 KIAS on turning base;
 3. 185 KIAS on turning to intercept the localizer;
 4. 160 KIAS from 10NM until 5NM to touchdown.
- Own navigation to intercept the final approach track (**when given a direct for track shortening**):
 1. 250 KIAS on passing 10000 ft;
 2. 220 KIAS 20 track miles from touchdown;



3. 185 KIAS 15 track miles from touchdown;
4. 160 KIAS from 10NM until 5NM to touchdown.

High Speed Descent

Subject to **traffic level**, ATC may provide **track shortening** to clear you into the **final approach faster**. ATC will give you a direct to a new waypoint or provide radar vectors. ATC may as well use the phraseology "**HIGH SPEED APPROVED**". You may descend with a speed of **270 KTS or greater below 10000 ft**. But do **make sure** you are **slowed down** for the final approach.

4.5 Landing

Flights landing on **32L** bound for **Terminal 2** shall expect a long **landing rollout** to vacate left via **P4**.

Keep in mind that your aircraft needs to be past the appropriate runway holding point in its entirety before you are considered clear of the runway.

After vacating, join the appropriate parallel taxiways at not more than 15 knots (A, C, P or Z) and wait for further instructions. Do not stop on the runway exits/holding points after vacating.

4.6 Taxi

To avoid delay for other users, **start taxiing as soon as possible after receiving your taxi clearance** from Lumpur Tower especially if you are still in near proximity to the runway exits. You will be handoff to Lumpur Ground once you have exited the parallel taxiway.

Standard Routes

During high-levels of traffic, Lumpur Ground may instruct you to taxi via standard route. You may refer to the taxi charts for the standard routes.

5. Special Pilot Briefing for Hajj OPS 2026 Event

Event Route: PUGER R461 ISVUR P756 OKABU M300 MDI W46 CIA T6 POMAN P570 LADIB P751 BOLUR T208 ASPUX L425 GOBRO AMBIT L425 BOSUT

RWYs Configuration:

RWYs	Configuration
14L	[use for DEP event traffic ONLY] Event traffic bound to OEJN park at Terminal 1 & Cargo area expect <u>PUGER1A</u> Departure.
14R	[use DEP & ARR for non-event traffic ONLY] - Non-event departure traffic from Terminal 1, Cargo & Terminal 2 tracking RUSBU1B/SALAX1B/MITOS1B/KIMAT1B/PIBOS1B/BIKDU1B expect departure RWY14R. - Arrival from SAROX/GUPTA/PULIP/KAKAK/NIREN expect 1G arrival EGURI transition ILS RWY14R.
15	[DEP for Event/Non-Event & ARR for non-event traffic ONLY] - Event traffic bound to OEJN park at Terminal 2 area expect <u>PUGER1F</u> Departure. - Non-event traffic park at Terminal 2 expect tracking via RUSBU1F/SALAX1F/MITOS1F departure - Arrival from SALAX/GUPTA expect 1H arrival MESUP transition ILS RWY15

Clearance:

All event traffic to request clearance from WMKK_DEL on 121.600 or subject to ATIS information. **Event traffic** will be given the clearance priority to accommodate their booking slots time and CTOTs. All event traffic bound to **OEJN** expect departures via PUGER1A RWY14L & via PUGER1F RWY15 depending where your aircraft park at. Event traffic to request ATCs clearance 15-20 before CTOT for better traffic flows and planning. **CPDLC** will not be available in WMKK. Expect clearance via VOICE or TEXT.

For non-event traffic bound for PUGER expect to follow PUGER1A RWY14L or PUGER1F RWY15. Non-event traffic to follow RWY configuration to make sure all event traffic flows goes smoothly.

Ground:

Event traffic will be given the priority for pushback & start-up and also following their CTOT. Event traffic to request taxi 10-11 minutes prior your CTOT plan. After requesting taxi event traffic depart from RWY14L will be instructed to hold short of a **specific taxiways such as taxiways B** and to be transferred to TWR before continue their movement to RWY holding points.

Tower:

WMKK_TWR will be responsible to assigned runway intersection length, expect full length. All event departure traffic will be separated 3-4 minutes based on wake turbulence. Once instructed for takeoff PIC should set APP/DEP frequency on stby.



***THIS PAGE INTENTIONALLY LEFT BLANK
END OF DOCUMENT***