

1:07

Vo 4.60 5G+  
NR KB/s



GNUSimBOB5 - BOB5 Microprocessor Simulator

File Reset Assembler Debug Help

Registers

| Register | Value | Flag |
|----------|-------|------|
| A        | 00    | S 1  |
| BC       | 1E 00 |      |
| DE       | 00 00 | Z 0  |
| HL       | 00 00 |      |
| PSW      | 00 00 | AC 0 |
| PC       | 40 1B | P 1  |
| SP       | FF FF |      |
| Int Reg  | 00    | C 1  |

Decimal - Hex Conversion

| Decimal | Hex |
|---------|-----|
| 0       | 0   |

I/O Ports

| Port | Value |
|------|-------|
| 0    | 00    |

Memory

| Address | Value |
|---------|-------|
| 0       | 00    |

Load me at

```
1 LDA 8500
2 MOV A,A
3 LDA 8500
4 MVI C,06
5
6 LOOP: CMP B
7 JG LOOP
8 ADD B
9 INR C
10 JNZ LOOP
11 STA 8503
12 DCR C
13 MOV A,C
14 MVI A,0
15 LOOP1: STA 8502
16 RST 1
```

Start: 8500

| Address (Hex) | Address | Data |
|---------------|---------|------|
| 2134          | 8500    | 2    |
| 2135          | 8501    | 30   |
| 2136          | 8502    | 11   |
| 2137          | 8503    | 2    |
| 2138          | 8504    | 0    |
| 2139          | 8505    | 0    |
| 213A          | 8506    | 0    |
| 213B          | 8507    | 0    |
| 213C          | 8508    | 0    |
| 213D          | 8509    | 0    |
| 213E          | 8510    | 0    |
| 213F          | 8511    | 0    |
| 2140          | 8512    | 0    |
| 2141          | 8513    | 0    |

Line No. Assembler Message

```
0 Program assembled successfully
```

Simulator: Idle