

1:07

Vo 5.30 5G+
NR KB/s



GNUsim8085 - 8085 Microprocessor Simulator

File Reset Assembler Debug Help

Registers: A 00, BC 06 00, DE 00 02, HL 00 03, PSW 00 00, PC 42 14, SP FF FF, Int-Reg 00. Flags: S 0, Z 1, AC 0, P 1, C 0.

Load me at: 1. LEAD 2050, 2. RORG, 3. LEAD 2052, 4. MPT 0, 5. MOV A, R, 6. RSH L, 7. RSH 2054, 8. MOV A, D, 9. RSH W, 10. RSH 2055, 11. RET, 12., 13.

Decimal - Hex Conversion: Decimal 0, Hex 0. Buttons: To Hex, To Dec.

I/O Ports: 0, +, -, 00. Update Port Value.

Memory: 0, +, -, 00. Update Memory.

Start 2050 OK

Address (Hex)	Address	Data
0802	2050	2
0803	2051	0
0804	2052	3
0805	2053	0
0806	2054	1
0807	2055	1
0808	2056	0
0809	2057	0
080A	2058	0
080B	2059	0
080C	2060	0
080D	2061	0
080E	2062	0
080F	2063	0

Line No Assembler Message
0 Program assembled successfully

Simulator: idle