

1) create a customer table to store following columns, customer id as primary key
customer id, name, mobile set<int>,email tuple(text,text),purchaseveh
map<text,int>,hobbies list<text>

→

```
cqlsh:iacs0923> create table customer1(cid int primary key,cname text,mobile set<int>,email tuple<text,text>,  
... purchaseveh map<text,int>,hobbies list<text>);
```

cid | cname | email | hobbies | mobile | purchaseveh

-----+-----+-----+-----+-----+-----

(0 rows)

2) insert 5 records with customer id 11,12,13,14,15

→

```
insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh)  
values(11,'Amrut','amrut@gmail.com'),['swimming'],{3333},{'cheese':1});
```

```
insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh)  
values(12,'Ganesh','ganesh@gmail.com'),['Painting'],{6666},{'Milk':3});
```

```
insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh)  
values(13,'Vikram','vikram@gmail.com'),['swimming'],{4444},{'butter':2});
```

```
insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh)  
values(14,'Kalpesh','kalpesh@gmail.com'),['Painting'],{5555},{'C.Milk':4});
```

```
insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh)  
values(15,'Anuj','anuj@gmail.com'),['GYM'],{2222},{'bread':5});
```

cid | cname | email | hobbies | mobile | purchaseveh

-----+-----+-----+-----+-----+-----

13 | Vikram | ('vikram@gmail.com', None) | ['swimming'] | {4444} | {'butter': 2}

11 | Amrut | ('amrut@gmail.com', None) | ['swimming'] | {3333} | {'cheese': 1}

15 | Anuj | ('anuj@gmail.com', None) | ['GYM'] | {2222} | {'bread': 5}

14 | Kalpesh | ('kalpesh@gmail.com', None) | ['Painting'] | {5555} | {'C.Milk': 4}

12 | Ganesh | ('ganesh@gmail.com', None) | ['Painting'] | {6666} | {'Milk': 3}

(5 rows)

3) add hobbies design, drawing for custid=12

→

```
cqlsh:iacsd0923> update customer1 set hobbies=hobbies+['designing'] where cid=12;
```

```
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)		['swimming']	{4444} {'butter': 2}
11	Amrut	('amrut@gmail.com', None)		['swimming']	{3333} {'cheese': 1}
15	Anuj	('anuj@gmail.com', None)		['GYM']	{2222} {'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)		['Painting']	{5555} {'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'designing']	{6666}	{'Milk': 3}

```
cqlsh:iacsd0923> update customer1 set hobbies=hobbies+['drawing'] where cid=12;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)		['swimming']	{4444} {'butter': 2}
11	Amrut	('amrut@gmail.com', None)		['swimming']	{3333} {'cheese': 1}
15	Anuj	('anuj@gmail.com', None)		['GYM']	{2222} {'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)		['Painting']	{5555} {'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'designing', 'drawing']	{6666}	{'Milk': 3}

(5 rows)

4) remove hobbies design for custid=12

→

```
cqlsh:iacsd0923> update customer1 set hobbies=hobbies-['designing'] where cid=12;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'butter': 2}
11	Amrut	('amrut@gmail.com', None)	['swimming']	{3333}	{'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting']	{5555}	{'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{'Milk': 3}

(5 rows)

5)update name of customer with id 11

→

```
cqlsh:iacsd0923> update customer1 set cname='Amrut Amble Patil' where cid=11;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'butter': 2}
11	Amrut Amble Patil	('amrut@gmail.com', None)	['swimming']	{3333}	{'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting']	{5555}	{'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{'Milk': 3}

(5 rows)

6)modify emails of customer 13

→

```
cqlsh:iacsd0923> update customer1 set email=('patil@gmail.com') where cid=11;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting']	{5555}	{'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{'Milk': 3}

(5 rows)

7)add and delete one of the purchase vehicle

→

```
cqlsh:iacsd0923> update customer1 set purchaseveh=purchaseveh+{'BMW':80, 'AUDI':75} where cid=13;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{ 'AUDI': 75, 'BMW': 80, 'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{ 'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{ 'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting']	{5555}	{ 'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{ 'Milk': 3}

(5 rows)

```
cqlsh:iacsd0923> update customer1 set purchaseveh=purchaseveh-{'BMW'} where cid=13;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{ 'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{ 'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{ 'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting']	{5555}	{ 'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{ 'Milk': 3}

(5 rows)

8)add and delete one of the hobbies for customer 14

→

```
cqlsh:iacsd0923> update customer1 set hobbies=hobbies+['reading','gym'] where cid=14;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{ 'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{ 'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{ 'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting', 'reading', 'gym']	{5555}	{ 'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{ 'Milk': 3}

(5 rows)

```
cqlsh:iacsd0923> update customer1 set hobbies=hobbies-['gym'] where cid=14;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{ 'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{ 'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{ 'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting', 'reading']	{5555}	{ 'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{ 'Milk': 3}

(5 rows)

9) change the quantity of vehicle activa from customer id 15

->

```
cqlsh:iacsd0923> update customer1 set purchaseveh= purchaseveh+{'Activa':10} where cid=14;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting', 'reading']	{5555}	{'Activa': 10, 'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{'Milk': 3}

(5 rows)

```
cqlsh:iacsd0923> update customer1 set purchaseveh['Activa']=100 where cid=14;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	('patil@gmail.com', None)	['swimming']	{3333}	{'cheese': 1}
15	Anuj	('anuj@gmail.com', None)	['GYM']	{2222}	{'bread': 5}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting', 'reading']	{5555}	{'Activa': 100, 'C.Milk': 4}
12	Ganesh	('ganesh@gmail.com', None)	['Painting', 'drawing']	{6666}	{'Milk': 3}

(5 rows)

Q2) create a batch to add 2 records in customer table, delete record for customer 13

and delete only email from customer 11

and update emails for customer 12

→

```
cqlsh:iacsd0923> insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh) values(16,'Shivam',('shivam@gmail.com'),['Painting'],{1515},{'C.Milk':4});
cqlsh:iacsd0923> insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh) values(17,'Ajinkya',('nanu@gmail.com'),['Painting'],{1999},{'C.Milk':4});
cqlsh:iacsd0923> delete from customer1 where cid=15;
cqlsh:iacsd0923> delete email from customer1 where cid=11;
cqlsh:iacsd0923> update customer1 set email=email+('waman@gmail.com') where cid=12
... ;
InvalidRequest: Error from server: code=2200 [Invalid query] message="Invalid operation (email = email + ('waman@gmail.com')) for non counter column email"
cqlsh:iacsd0923> update customer1 set email=('waman@gmail.com') where cid=12;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
16	Shivam	('shivam@gmail.com', None)	['Painting']	{1515}	{'C.Milk': 4}
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	null	['swimming']	{3333}	{'cheese': 1}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting', 'reading']	{5555}	{'Activa': 100, 'C.Milk': 4}
17	Ajinkya	('nanu@gmail.com', None)	['Painting']	{1999}	{'C.Milk': 4}
12	Ganesh	('waman@gmail.com', None)	['Painting', 'drawing']	{6666}	{'Milk': 3}

(6 rows)

OR

```
cqlsh:iacsd0923> begin batch
... insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh) values(18,'prajwal',('prajwal@gmail.com'),['Painting'],{2999},{choko:4});
... insert into customer1(cid,cname,email,hobbies,mobile,purchaseveh) values(19,'praveer',('praveer@gmail.com'),['Painting'],{2999},{choko:4});
... delete from customer1 where cid=17;
... delete email from customer1 where cid=12;
... update customer1 set email=('ganu@gmail.com') where cid=12;
... apply batch;
cqlsh:iacsd0923> select * from customer1;
```

cid	cname	email	hobbies	mobile	purchaseveh
16	Shivam	('shivam@gmail.com', None)	['Painting']	{1515}	{'C.Milk': 4}
13	Vikram	('vikram@gmail.com', None)	['swimming']	{4444}	{'AUDI': 75, 'butter': 2}
11	Amrut Amble Patil	null	['swimming']	{3333}	{'cheese': 1}
19	praveer	('praveer@gmail.com', None)	['Painting']	{2999}	{'choko': 4}
18	prajwal	('prajwal@gmail.com', None)	['Painting']	{2999}	{'choko': 4}
14	Kalpesh	('kalpesh@gmail.com', None)	['Painting', 'reading']	{5555}	{'Activa': 100, 'C.Milk': 4}
12	Ganesh	null	['Painting', 'drawing']	{6666}	{'Milk': 3}

(7 rows)

Q3) create type department to store deptno, dname

a.

change the type department to add dloc in it.

create table emp to store eid, ename, sal, projects List<text>, dept department
add 5 records in the table

→

```
cqlsh:vikram> create type department(deptno int,dname text);
```

```
cqlsh:vikram> alter type department add dloc text;
```

```
cqlsh:vikram> create table emp(eid int primary key,ename text,sal int,project list<text>,dept department);
```

```
cqlsh:vikram> select * from emp;
```

```
eid | dept | ename | project | sal
-----+-----+-----+-----+-----
(0 rows)
```

```
cqlsh:vikram> insert into
```

```
emp(eid,dept,ename,project,sal)values(11,{deptno:11,dname:'vikram'},'biradar',['A','B','C','D'],8);
```

```
cqlsh:vikram> insert into emp(eid,dept,ename,project,sal) values(12,{deptno:12,dname:'kalpesh'},'patil',['A','B','C','D'],9);
```

```
cqlsh:vikram> insert into emp(eid,dept,ename,project,sal) values(13,{deptno:13,dname:'amrut'},'patil',['A','B','C','D'],8);
cqlsh:vikram> insert into emp(eid,dept,ename,project,sal)
values(14,{deptno:14,dname:'ganesh'},'waman',['A','B','C','D'],7);
cqlsh:vikram> insert into emp(eid,dept,ename,project,sal) values(15,{deptno:15,dname:'anuj'},'thavre',['A','B','C','D'],8);
cqlsh:vikram> select * from emp;
```

eid	dept	ename	project	sal
13	{deptno: 13, dname: 'amrut', dloc: null}	patil	['A', 'B', 'C', 'D']	8
11	{deptno: 11, dname: 'vikram', dloc: null}	biradar	['A', 'B', 'C', 'D']	8
15	{deptno: 15, dname: 'anuj', dloc: null}	thavre	['A', 'B', 'C', 'D']	8
14	{deptno: 14, dname: 'ganesh', dloc: null}	waman	['A', 'B', 'C', 'D']	7
12	{deptno: 12, dname: 'kalpesh', dloc: null}	patil	['A', 'B', 'C', 'D']	9

(5 rows)

b. create index on ename column

```
cqlsh:vikram> create index idxname on emp(ename);
cqlsh:vikram> select * from emp;
```

eid	dept	ename	project	sal
13	{deptno: 13, dname: 'amrut', dloc: null}	patil	['A', 'B', 'C', 'D']	8
11	{deptno: 11, dname: 'vikram', dloc: null}	biradar	['A', 'B', 'C', 'D']	8
15	{deptno: 15, dname: 'anuj', dloc: null}	thavre	['A', 'B', 'C', 'D']	8
14	{deptno: 14, dname: 'ganesh', dloc: null}	waman	['A', 'B', 'C', 'D']	7
12	{deptno: 12, dname: 'kalpesh', dloc: null}	patil	['A', 'B', 'C', 'D']	9

(5 rows)