

# Purchase Inquiry — API Reference

## Horizon Enterprise IMS

**Module:** Purchase Inquiry ( `/purchase-inquiry` )

**Frontend:** React 19 SPA

**Backend:** ASP.NET ASMX Web Service

**Document date:** 2026-06-08

**Audience:** Backend team · QA team

## Screen

Horizon Enterprise  
BUSINESS SUITE

HOME

Dashboard

MODULES

Invoices

Purchase Inquiry

Purchase Order

v2.4.0

← Back

Purchase Inquiry

Fill in the header fields, then use Item Grid or Suppliers tabs.

Q Global Search...

Admin

Supervisor

A

Purchase Inquiry Detail

8 header fields

|              |                      |               |                 |            |           |
|--------------|----------------------|---------------|-----------------|------------|-----------|
| INQUIRY NO.  | Enter Inquiry No.... | DATE          | 08-06-2026      | DIVISION   | Select... |
| INQUIRY TYPE | Select...            | EXPECTED DATE | dd-mm-yyyy      | DEPARTMENT | Select... |
| BASED ON     | Direct               | REMARK        | Enter Remark... |            |           |

Item Grid

Suppliers

Term And Conditions

+ Add New

Select Item

Approved

All x

Delete

| ITEMCODE                                          | ITEMNAME | HSN | TRAN QTY | TRAN UNIT | UNIT CONV | BASE QTY | BASE UNIT | REMARKS |
|---------------------------------------------------|----------|-----|----------|-----------|-----------|----------|-----------|---------|
| No items yet. Click Add New or Select Item above. |          |     |          |           |           |          |           |         |

Showing 0 – 0 of 0 records

Rows: 10 1

> Indent Details

(Select one Item row above to load its Indent records)

0

Add

## Base URLs

| Alias                                        | URL                                                                     |
|----------------------------------------------|-------------------------------------------------------------------------|
| <b>Primary</b> ( <code>API_BASE_URL</code> ) | <code>http://122.179.135.100:8095/IMS_LIVE/webservice/WsIMS.asmx</code> |

REST Gateway ( `API_BASE_URL_IMS` )

`http://122.179.135.100:8095/IMS_LIVE`

All GET calls go to the primary base URL. Indent summary and Save go to the REST gateway.

## Shared Request Defaults

| Constant                                | Value                           |
|-----------------------------------------|---------------------------------|
| <code>DEFAULT_LOGIN_ID</code>           | <code>1</code>                  |
| <code>DEFAULT_COMPANY_ID</code>         | <code>1</code>                  |
| <code>PI_CONFIG.DIVISION_YEAR_ID</code> | <code>2</code>                  |
| <code>PI_CONFIG.CONFIG_YEAR_ID</code>   | <code>2</code>                  |
| <code>PI_CONFIG.FORM_TAG</code>         | <code>"INQ"</code>              |
| <code>PI_CONFIG.TRAN_BOOK</code>        | <code>"PURINQUIRY"</code>       |
| <code>PI_CONFIG.RB_MASTER</code>        | <code>"RB_PurInquiryMst"</code> |
| <code>PI_CONFIG.RB_DETAIL</code>        | <code>"RB_PurInquiryDet"</code> |

## API Load Sequence

```
PAGE MOUNT (all in parallel)
├─ fetchHeaderMeta()
│   └─ [4.1] FN_Fetch_Data → Fn_Fetch_RBDetailByRBCode (RB_PurInquiryMst) → RBID
│       └─ in parallel:
│           └─ [4.2] GetDetailColData (header RBID) → headerColumns
│               └─ [4.3] FN_Fetch_Data → Fn_tbl_FetchUserWsDivision → divisionOptions
│                   └─ [4.4] FN_Fetch_Data → Pr_Fetch_DepartmentData_IMS → departmentOptions
└─ fetchDetailMeta()
    └─ [4.5] FN_Fetch_Data → Fn_Fetch_RBDetailByRBCode (RB_PurInquiryDet) → RBID
        └─ [4.6] GetDetailColData (detail RBID) → allColumns + eventColumns

ON DIVISION CHANGE
└─ [4.8] FN_Fetch_Data → fn_tbl_ddl_Pur_Configuration → inquiryTypeOptions

ON DIVISION + CONFIG ID SET (BasedOn = Indent wise)
└─ [4.9] FN_Fetch_Data → Fn_Tbl_FetchPurchaseItemDetailTransWs4Web → indentOptions

ON "Add New" / fetchGridColumns()
└─ [4.7] GetFilterDetail (per dropdown col, parallel) → grid column dropdowns

ON "Select Item"
└─ [4.10] FN_Fetch_Data → Fn_Fetch_RBDetailByRBCode (item picker RB) → RBID
    └─ [4.11] GetDetailColData (item picker RBID) → modal columns
        └─ [4.12] FN_Fetch_Data → Fn_Tbl_FetchPurchaseItemDetailTransWs4Web → modal rows

ON INSERT (indent-wise)
└─ [4.13] POST /API/Values → Fn_tbl_FetchIndentSummaryItem4Inquiry → parent rows

ON "Select Supplier"
```

```

└─ [4.14] FN_Fetch_Data → Fn_tbl_FetchCustomerSupplierTranWs4Web → supplier list

ON SAVE
└─ [4.15] POST /API/TranFormSave/Post_RB_PurInquiryMst_Save

```

## API 4.1 — Fetch Header RB Metadata

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** On page mount inside `fetchHeaderMeta()`

**Component:** `PurchaseInquiryPage` → `usePurchaseInquiry.fetchHeaderMeta()`

### Request

```

GET http://122.179.135.100:8095/IMS_LIVE/webservice/WsIMS.aspx/FN_Fetch_Data
?ObjType=2
&ObjName=Fn_Fetch_RBDetailByRBCode
&JSon=[{"prmRBCode":"RB_PurInquiryMst"}]
&p_ErrCode=-1
&p_ErrMsg=

```

| Parameter              | Type                | Value                                           | Notes                             |
|------------------------|---------------------|-------------------------------------------------|-----------------------------------|
| <code>ObjType</code>   | number              | <code>2</code>                                  | SP execution mode                 |
| <code>ObjName</code>   | string              | <code>Fn_Fetch_RBDetailByRBCode</code>          | <code>PI_CONFIG.SP_RB_META</code> |
| <code>JSon</code>      | string (JSON array) | <code>[{"prmRBCode":"RB_PurInquiryMst"}]</code> | RB board code                     |
| <code>p_ErrCode</code> | number              | <code>-1</code>                                 | Output error sentinel             |
| <code>p_ErrMsg</code>  | string              | <code>""</code>                                 | Output error message              |

### Response

```

{
  "Table": [
    {
      "RBID": 45,
      "SaveProcName": "Pr_Save_PurInquiryMst"
    }
  ]
}

```

| Field                     | Type   | Used for                                                                                            |
|---------------------------|--------|-----------------------------------------------------------------------------------------------------|
| <code>RBID</code>         | number | Passed as <code>prmMasterID</code> to all subsequent <code>GetDetailColData</code> calls for master |
| <code>SaveProcName</code> | string | Stored in <code>localStorage["piHeaderMeta"]</code> — used in the save payload                      |

**Why:** Resolves the numeric RBID from the string RB board code so header column definitions can be fetched.

## API 4.2 — Fetch Header Column Definitions

**Endpoint:** `GET /GetDetailColData`

**When called:** Immediately after 4.1 resolves, in parallel with 4.3 and 4.4

**Component:** `usePurchaseInquiry.fetchHeaderMeta()`

### Request

```
GET .../GetDetailColData?prmMasterID=45&prmLoginID=1
```

| Parameter                | Type   | Value                          |
|--------------------------|--------|--------------------------------|
| <code>prmMasterID</code> | number | <code>RBID</code> from API 4.1 |
| <code>prmLoginID</code>  | number | <code>1</code>                 |

### Response

```
{
  "Links": [
    {
      "ColName": "TranCode",
      "DisplayName": "Inquiry No.",
      "ColCtrlType": 1,
      "ColDataType": "varchar(50)",
      "IsVisible": true,
      "IsEditAllow": false,
      "IsFreezeReq": 1,
      "ObjDetID": 201
    },
    {
      "ColName": "DivisionID",
      "DisplayName": "Division",
      "ColCtrlType": 4,
      "ColDataType": "numeric(18,0)",
      "IsVisible": true,
      "IsEditAllow": true,
      "IsFreezeReq": 0,
      "ObjDetID": 202
    }
  ]
}
```

| Field                    | Type   | Used for                                                                                                                                      |
|--------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <code>ColName</code>     | string | Field key — matched against <code>PI_HEADER_FILTERS</code>                                                                                    |
| <code>DisplayName</code> | string | Field label in the header panel                                                                                                               |
| <code>ColCtrlType</code> | number | <code>1</code> =TextBox, <code>2</code> =Date, <code>4</code> =Dropdown, <code>9</code> =Textarea                                             |
| <code>ColDataType</code> | string | Row seed default: <code>numeric</code> → <code>0</code> , <code>varchar</code> → <code>" "</code> , <code>datetime</code> → <code>null</code> |

|                          |          |                                                                             |
|--------------------------|----------|-----------------------------------------------------------------------------|
| <code>IsVisible</code>   | bool/int | Hidden columns excluded from panel                                          |
| <code>IsEditAllow</code> | bool/int | Whether field is editable                                                   |
| <code>IsFreezeReq</code> | bool/int | Pinned/frozen column flag                                                   |
| <code>ObjDetID</code>    | number   | Used as <code>prmFilterParameterName</code> in <code>GetFilterDetail</code> |

**Why:** Provides header field definitions — used to sync `FilterColName` and `DisplayName` with `PI_HEADER_FILTERS`.

## API 4.3 — Fetch Division Options

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** In parallel with 4.2 during `fetchHeaderMeta()`

**Component:** `usePurchaseInquiry.fetchHeaderMeta()`

### Request

```
GET .../FN_Fetch_Data
?ObjType=2
&ObjName=Fn_tbl_FetchUserWsDivision
&JSON=[{"prmUserID":1,"prmCompanyID":1,"prmYearID":2}]
&p_ErrCode=-1
&p_ErrMsg=
```

| JSon Field                | Type   | Value                                         |
|---------------------------|--------|-----------------------------------------------|
| <code>prmUserID</code>    | number | <code>1 ( DEFAULT_LOGIN_ID )</code>           |
| <code>prmCompanyID</code> | number | <code>1 ( DEFAULT_COMPANY_ID )</code>         |
| <code>prmYearID</code>    | number | <code>2 ( PI_CONFIG.DIVISION_YEAR_ID )</code> |

### Response

```
{
  "Table": [
    { "DivisionID": 1, "DivisionName": "Head Office" },
    { "DivisionID": 3, "DivisionName": "Mumbai Branch" }
  ]
}
```

| Field                     | Type   | Used for              |
|---------------------------|--------|-----------------------|
| <code>DivisionID</code>   | number | Dropdown option value |
| <code>DivisionName</code> | string | Dropdown option label |

**Why:** Populates the Division dropdown in the PI header filter panel.

---

## API 4.4 — Fetch Department Options

---

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** In parallel with 4.2 and 4.3 during `fetchHeaderMeta()`

**Component:** `usePurchaseInquiry.fetchHeaderMeta()`

### Request

```
GET ../FN_Fetch_Data
?ObjType=1
&ObjName=Pr_Fetch_DepartmentData_IMS
&JSon=[{"PrmDeptID":0}]
&p_ErrCode=-1
&p_ErrMsg=
```

| JSon Field             | Type   | Value          | Notes                                  |
|------------------------|--------|----------------|----------------------------------------|
| <code>PrmDeptID</code> | number | <code>0</code> | <code>0</code> = fetch all departments |

### Response

```
{
  "Table": [
    { "DepartmentID": 1, "DepartmentName": "Purchase" },
    { "DepartmentID": 2, "DepartmentName": "Stores" }
  ]
}
```

| Field                       | Type   | Used for              |
|-----------------------------|--------|-----------------------|
| <code>DepartmentID</code>   | number | Dropdown option value |
| <code>DepartmentName</code> | string | Dropdown option label |

**Why:** Populates the Department dropdown in the PI header filter panel.

---

## API 4.5 — Fetch Detail RB Metadata

---

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** On page mount via `fetchDetailMeta()`, concurrently with `fetchHeaderMeta()`

**Component:** `PurchaseInquiryPage` → `usePurchaseInquiry.fetchDetailMeta()`

## Request

```
GET .../FN_Fetch_Data
?ObjType=2
&ObjName=Fn_Fetch_RBDetailByRBCode
&JSon=[{"prmRBCode":"RB_PurInquiryDet"}]
&p_ErrCode=-1
&p_ErrMsg=
```

## Response

```
{
  "Table": [
    {
      "RBID": 46,
      "SaveProcName": "Pr_Save_PurInquiryDet"
    }
  ]
}
```

| Field        | Type   | Used for                                                                              |
|--------------|--------|---------------------------------------------------------------------------------------|
| RBID         | number | Passed as <code>prmMasterID</code> to <code>GetDetailColData</code> for the item grid |
| SaveProcName | string | Stored in <code>localStorage["piEntryMeta"]</code> — used in save payload             |

**Why:** Resolves the detail RBID for item grid column definitions and save proc name.

## API 4.6 — Fetch Detail Column Definitions

**Endpoint:** `GET /GetDetailColData`

**When called:** Immediately after 4.5 resolves

**Component:** `usePurchaseInquiry.fetchDetailMeta()` → `loadRbDetailGridMeta()`

## Request

```
GET .../GetDetailColData?prmMasterID=46&prmLoginID=1
```

## Response — same shape as API 4.2

Key columns typically returned:

```
{
  "Links": [
    { "ColName": "ItemID",      "ColCtrlType": 4, "IsEventReq": 1, "ColDataType": "numeric(18,0)", "ObjDetID": 301 },
    { "ColName": "ItemCode",   "ColCtrlType": 1, "IsEventReq": 1, "ColDataType": "varchar(50)",   "ObjDetID": 302 },
    { "ColName": "TranQty",     "ColCtrlType": 1, "IsEventReq": 1, "ColDataType": "numeric(18,3)", "ObjDetID": 303 },
    { "ColName": "BaseQty",     "ColCtrlType": 1, "IsEventReq": 1, "ColDataType": "numeric(18,3)", "ObjDetID": 304 },
    { "ColName": "UnitConvRate", "ColCtrlType": 1, "IsEventReq": 1, "ColDataType": "numeric(18,6)", "ObjDetID": 305 },
    { "ColName": "TranRate",    "ColCtrlType": 1, "IsEventReq": 1, "ColDataType": "numeric(18,3)", "ObjDetID": 306 },
    { "ColName": "TranUnit",    "ColCtrlType": 4, "IsEventReq": 1, "ColDataType": "numeric(18,0)", "ObjDetID": 307 }
  ]
}
```

| Field                                             | Used for                                                                                      |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------|
| <code>ColName</code> + <code>ColDataType</code>   | Extracted to form <code>allColumns</code> — used to seed blank row defaults                   |
| <code>IsEventReq</code> / <code>IsEventCol</code> | <code>1</code> = tabbing this cell fires a server event; builds <code>eventColumns</code> Set |
| <code>ObjDetID</code>                             | Key for <code>GetFilterDetail</code> dropdown fetch per column                                |

Fallback `eventColumns` if none flagged: `['ItemID','ItemCode','TranQty','BaseQty','UnitConvRate','TranRate','TranUnit']`

**Why:** Defines all item grid columns and establishes which columns trigger server-side calculation on Tab.

## API 4.7 — Fetch Item Grid Dropdown Options

**Endpoint:** `GET /GetFilterDetail`

**When called:** On `fetchGridColumns(divisionID)` — called on page load when `allColumns` populates, or on first "Add New"

**Component:** `usePurchaseInquiry.fetchGridColumns()` → `fetchDropdownOptions()` in `gridUtils.js`

One call per column where `ColCtrlType === 4`, all in parallel.

### Request

```
GET .../GetFilterDetail
?prmMasterID=46
&prmFilterParameterName=307
&prmCboMode=C
&prmFuncCode=RB_PurInquiryDet
&prmDivisionID=3
&prmLoginID=1
```

| Parameter                  | Type   | Value                           | Notes                                      |
|----------------------------|--------|---------------------------------|--------------------------------------------|
| <code>prmCboMode</code>    | string | <code>"C"</code>                | Column mode — <code>CBO_MODE.COLUMN</code> |
| <code>prmFuncCode</code>   | string | <code>"RB_PurInquiryDet"</code> | <code>PI_CONFIG.RB_DETAIL</code>           |
| <code>prmDivisionID</code> | number | currently selected DivisionID   | Scopes dropdown data to division           |



## Response

```
{
  "Links": [
    {
      "FilterCtrlValueCol": "UnitID",
      "FilterCtrlDisplayCol": "UnitName",
      "UnitID": 1,
      "UnitName": "Kg"
    },
    {
      "FilterCtrlValueCol": "UnitID",
      "FilterCtrlDisplayCol": "UnitName",
      "UnitID": 2,
      "UnitName": "Pcs"
    }
  ]
}
```

| Field                             | Type   | Used for                                                                                                                                                  |
|-----------------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>FilterCtrlValueCol</code>   | string | Points to the key field for the option <b>value</b>                                                                                                       |
| <code>FilterCtrlDisplayCol</code> | string | Points to the key field for the option <b>label</b>                                                                                                       |
| (data fields)                     | any    | Actual option data — key names determined by <code>FilterCtrlValueCol</code> / <code>FilterCtrlDisplayCol</code> . Fallback: <code>IDNumber → Name</code> |

**Why:** Populates dropdown options for editable dropdown cells in the item entry grid.

## API 4.8 — Fetch Inquiry Types (Cascade: Division changes)

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** When user changes the Division dropdown — `handleFilterChange('DivisionID', val)`

**Component:** `PurchaseInquiryPage.handleFilterChange()` → `usePurchaseInquiry.fetchInquiryTypes (divisionId)`

## Request

```
GET .../FN_Fetch_Data
?ObjType=2
&ObjName=fn_tbl_ddl_Pur_Configuration
&JSon=[{
  "PrmCompanyId":1,
  "PrmDivisionId":3,
  "PrmYearId":2,
  "PrmUserId":1,
  "PrmFormTag":"INQ",
  "PrmRefType":""
}]
&p_ErrCode=-1
&p_ErrMsg=
```

| JSon Field | Type | Value | Notes |
|------------|------|-------|-------|
|------------|------|-------|-------|

|               |        |                     |                                                    |
|---------------|--------|---------------------|----------------------------------------------------|
| PrmCompanyId  | number | 1                   | DEFAULT_COMPANY_ID                                 |
| PrmDivisionId | number | selected DivisionID | Changes on each Division pick                      |
| PrmYearId     | number | 2                   | PI_CONFIG.CONFIG_YEAR_ID                           |
| PrmUserId     | number | 1                   | DEFAULT_LOGIN_ID                                   |
| PrmFormTag    | string | "INQ"               | PI_CONFIG.FORM_TAG — filters to inquiry types only |
| PrmRefType    | string | ""                  | Empty                                              |

## Response

```
{
  "Table": [
    { "ConfigurationId": 5, "Name": "Standard Inquiry" },
    { "ConfigurationId": 6, "Name": "Urgent Inquiry" }
  ]
}
```

| Field           | Type   | Used for              |
|-----------------|--------|-----------------------|
| ConfigurationId | number | Dropdown option value |
| Name            | string | Dropdown option label |

**Why:** Cascade — refreshes Inquiry Type dropdown options whenever Division changes. Clears to empty if Division is 0.

## API 4.9 — Fetch Indents

**Endpoint:** GET /FN\_Fetch\_Data

**When called:** When Division + ConfigID are both set (and either changes) with BasedOn = Indent wise

**Component:** usePurchaseInquiry.fetchIndents({ divisionId, configId, tranDate, supplierId, frmOption })

## Request

```
GET ../FN_Fetch_Data
?ObjType=2
&ObjName=Fn_Tbl_FetchPurchaseItemDetailTransWs4Web
&JSon=[{
  "prmDivisionID":3,
  "prmYearID":2,
  "prmLoginID":1,
  "prmTranDate":"08-Jun-2026",
  "prmConfigID":5,
  "prmSupplierID":0,
  "prmTranBook":"PURINQUIRY",
  "prmFrmOption":0
}]
&p_ErrCode=-1
&p_ErrMsg=
```

| JSon Field                 | Type   | Value                      | Notes                                                               |
|----------------------------|--------|----------------------------|---------------------------------------------------------------------|
| <code>prmYearID</code>     | number | <code>2</code>             | <code>PI_CONFIG.CONFIG_YEAR_ID</code>                               |
| <code>prmLoginID</code>    | number | <code>1</code>             | <code>DEFAULT_LOGIN_ID</code>                                       |
| <code>prmTranDate</code>   | string | <code>"08-Jun-2026"</code> | <code>dd-Mon-yyyy</code> format via <code>formatPiTranDate()</code> |
| <code>prmConfigID</code>   | number | selected ConfigurationId   | Inquiry Type                                                        |
| <code>prmSupplierID</code> | number | <code>0</code>             | From header; default <code>0</code>                                 |
| <code>prmTranBook</code>   | string | <code>"PURINQUIRY"</code>  | <code>PI_CONFIG.TRAN_BOOK</code>                                    |
| <code>prmFrmOption</code>  | number | <code>0</code>             | <code>PI_CONFIG.INDENT_FRM_OPTION</code>                            |

## Response

```
{
  "Table": [
    {
      "IndentID": 201,
      "IndentNo": "IND/2026/001",
      "IndentDate": "2026-05-20T00:00:00",
      "ItemName": "Stainless Steel Pipe",
      "IndentQty": 100,
      "TranQty": 0,
      "Unit": "Kg"
    }
  ]
}
```

| Field                 | Type   | Used for                                            |
|-----------------------|--------|-----------------------------------------------------|
| <code>IndentID</code> | number | Dropdown value key                                  |
| <code>IndentNo</code> | string | Dropdown label                                      |
| (all fields)          | any    | Full row stored in <code>indentOptions</code> state |

**Why:** Provides the list of available indents when the PI is indent-based ( `BasedOnID = "2"` ).

## API 4.10 — Fetch Item Picker RB Metadata

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** User clicks "Select Item" button

**Component:** `PurchaseInquiryPage.handleSelectedItem()`

## Request

```
GET .../FN_Fetch_Data
?ObjType=2
```

```
&ObjName=Fn_Fetch_RBDetailByRBCode
&JSon=[{"prmRBCode":"RB_PurInqSelOnlyItem"}]
&p_ErrCode=-1
&p_ErrMsg=
```

| JSon Field | Value                  | Notes                                                |
|------------|------------------------|------------------------------------------------------|
| prmRBCode  | "RB_PurInqSelOnlyItem" | PI_CONFIG.RB_ITEM_PICKER_DIRECT when BasedOnID = "0" |
| prmRBCode  | "RB_PurInqSelIndtItem" | PI_CONFIG.RB_ITEM_PICKER_INDENT when BasedOnID = "2" |

## Response — same shape as API 4.1

`RBID` used for the subsequent column fetch (4.11).

**Why:** Resolves the RBID for the item picker modal — RB code differs based on whether Direct or Indent-wise flow.

## API 4.11 — Fetch Item Picker Column Definitions

**Endpoint:** `GET /GetDetailColData`

**When called:** Immediately after 4.10 resolves

**Component:** `PurchaseInquiryPage.handleSelectedItem()`

### Request

```
GET .../GetDetailColData?prmMasterID=<pickerRBID>&prmLoginID=1
```

## Response — same shape as API 4.2

Columns built with `filterable: false, allEditable: false` (read-only modal grid).

**Why:** Defines the columns shown in the item picker modal.

## API 4.12 — Fetch Item Picker Rows

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** After columns are resolved in `handleSelectedItem()`

**Component:** `PurchaseInquiryPage.handleSelectedItem()`

### Request

```

GET .../FN_Fetch_Data
?ObjType=2
&ObjName=Fn_Tbl_FetchPurchaseItemDetailTransWs4Web
&JSon=[{
  "prmDivisionID":3,
  "prmYearID":2,
  "prmLoginID":1,
  "prmTranDate":"08-Jun-2026",
  "prmConfigID":5,
  "prmSupplierID":0,
  "prmTranBook":"PURINQUIRY",
  "prmFrmOption":0
}]
&p_ErrCode=-1
&p_ErrMsg=

```

| JSon Field                 | Type   | Value             | Notes                                 |
|----------------------------|--------|-------------------|---------------------------------------|
| <code>prmDivisionID</code> | number | from header       | Guard: alert if 0                     |
| <code>prmYearID</code>     | number | 2                 | <code>PI_CONFIG.CONFIG_YEAR_ID</code> |
| <code>prmTranDate</code>   | string | "dd-Mon-yyyy"     | Formatted from header TranDate        |
| <code>prmConfigID</code>   | number | selected ConfigID | 0 if not set                          |
| <code>prmSupplierID</code> | number | from header       | 0 if not set                          |
| <code>prmFrmOption</code>  | number | 0 or 2            | <code>BasedOnID</code> cast to number |

## Response

```

{
  "Table": [
    {
      "ItemID": 501,
      "ItemCode": "SS-PIPE-001",
      "ItemName": "Stainless Steel Pipe",
      "IndentQty": 100,
      "Unit": "Kg",
      "IndentNo": "IND/2026/001",
      "IndentDate": "2026-05-20T00:00:00",
      "ChildFKey": 501
    }
  ]
}

```

Rows displayed in the item picker modal. Selected rows mapped onto blank grid rows via `mapPickerToItemRow()`.

**Why:** Provides the selectable item list for the PI item picker modal (Direct or Indent-wise).

## API 4.13 — Fetch Indent Summary (REST Gateway)

**Endpoint:** `POST /API/Values`

**When called:** After user selects indent-wise items and clicks Insert — `handleInsertItems()` when `BasedOnID === "2"`

**Component:** `PurchaseInquiryPage.handleInsertItems()`

**Request**

```
POST http://122.179.135.100:8095/IMS_LIVE/API/Values
Content-Type: application/json
```

```
{
  "ObjType": 2,
  "ObjName": "Fn_tbl_FetchIndentSummaryItem4Inquiry",
  "JSon": [
    {
      "prmJSon": [
        { "ItemID": 501, "IndentNo": "IND/2026/001", "IndentQty": 100 },
        { "ItemID": 502, "IndentNo": "IND/2026/002", "IndentQty": 50 }
      ]
    }
  ],
  "p_ErrCode": -1,
  "p_ErrMsg": ""
}
```

| Field   | Type   | Value                                 | Notes                                          |
|---------|--------|---------------------------------------|------------------------------------------------|
| ObjName | string | Fn_tbl_FetchIndentSummaryItem4Inquiry | PI_CONFIG.SP_INDENT_SUMMARY                    |
| JSon    | array  | [{ prmJSon: [...selectedRows] }]      | Selected indent rows with internal id stripped |

**Response**

```
{
  "Table": [
    {
      "ItemID": 501,
      "ItemName": "Stainless Steel Pipe",
      "TranQty": 100,
      "Unit": "Kg",
      "IndentNo": "IND/2026/001",
      "IndentDate": "2026-05-20T00:00:00",
      "ChildFKey": 501
    }
  ]
}
```

| Field        | Type   | Used for                                                                             |
|--------------|--------|--------------------------------------------------------------------------------------|
| ItemID       | number | Parent row identifier; children matched via <code>ChildFKey === parent.ItemID</code> |
| (all fields) | any    | Spread onto parent item grid rows                                                    |

**Why:** Aggregates selected indent rows into summary parent rows for the item grid; also builds the collapsible child row mapping.

## API 4.14 — Fetch Supplier List (Supplier Modal)

**Endpoint:** `GET /FN_Fetch_Data`

**When called:** User clicks "Select Supplier" button

**Component:** `PurchaseInquiryPage.handleSelectSupplier()`

### Request

```
GET .../FN_Fetch_Data
?ObjType=2
&ObjName=Fn_tbl_FetchCustomerSupplierTranWs4Web
&JSon=[{
  "PrmDivisionId":3,
  "PrmLoginId":1,
  "PrmYearId":2,
  "PrmPartyType":"S"
}]
&p_ErrCode=-1
&p_ErrMsg=
```

| JSon Field                 | Type   | Value               | Notes                                                                    |
|----------------------------|--------|---------------------|--------------------------------------------------------------------------|
| <code>PrmDivisionId</code> | number | selected DivisionID | Guard: alert if <code>0</code>                                           |
| <code>PrmLoginId</code>    | number | <code>1</code>      | <code>DEFAULT_LOGIN_ID</code>                                            |
| <code>PrmYearId</code>     | number | <code>2</code>      | <code>PI_CONFIG.CONFIG_YEAR_ID</code>                                    |
| <code>PrmPartyType</code>  | string | <code>"S"</code>    | <code>PI_CONFIG.SUPPLIER_PARTY_TYPE</code> — <code>"S"</code> = Supplier |

### Response

```
{
  "Table": [
    {
      "SupplierID": 301,
      "SupplierName": "ABC Suppliers Ltd",
      "SuppAddress": "123 Industrial Area, Andheri",
      "City": "Mumbai",
      "ContactNo": "9876543210",
      "SrNo": 1
    }
  ]
}
```

| Field                     | Type   | Used for                                                             |
|---------------------------|--------|----------------------------------------------------------------------|
| <code>SupplierID</code>   | number | Row ID and supplier grid value                                       |
| <code>SupplierName</code> | string | Supplier grid "Supplier Name" column                                 |
| <code>SuppAddress</code>  | string | Supplier grid "Address" column (fallback: <code>Address</code> )     |
| <code>City</code>         | string | Supplier grid "City" column                                          |
| <code>ContactNo</code>    | string | Supplier grid "Mobile No." column (fallback: <code>MobileNo</code> ) |

**Why:** Provides the supplier list for the Supplier picker modal; selected suppliers are added to the Suppliers tab grid.

## API 4.15 — Save Purchase Inquiry (REST Gateway)

**Endpoint:** `POST /API/TranFormSave/Post_RB_PurInquiryMst_Save`

**When called:** User clicks Save (or Save & Print)

**Component:** `PurchaseInquiryPage.handleSave()`

### Request

```
POST http://122.179.135.100:8095/IMS_LIVE/API/TranFormSave/Post_RB_PurInquiryMst_Save
Content-Type: application/json
```

```
{
  "prmStrMstJSON": "[{"TranCode":"","TranDate":"2026-06-08","ConfigID":5,"ExpectedDate":null,"DivisionID":3,"D
  "prmStrDetJSON": "[{"ItemID":501,"ItemCode":"SS-PIPE-001","TranQty":100,"TranUnit":1,"LoginID":1}]",
  "prmStrIndtDetJSON": "[{"ItemID":501,"IndentNo":"IND/2026/001","IndentQty":100,"LoginID":1}]"
}
```

**Master row fields ( `prmStrMstJSON` ):**

| Field                     | Type          | Example                   | Notes                                                            |
|---------------------------|---------------|---------------------------|------------------------------------------------------------------|
| <code>TranCode</code>     | string        | <code>" "</code>          | Auto-generated by backend if empty                               |
| <code>TranDate</code>     | string        | <code>"2026-06-08"</code> | ISO date from header                                             |
| <code>ConfigID</code>     | number        | <code>5</code>            | Selected Inquiry Type ( <code>ConfigurationId</code> )           |
| <code>ExpectedDate</code> | string / null | <code>null</code>         | From header                                                      |
| <code>DeptID</code>       | number        | <code>1</code>            | Selected Department                                              |
| <code>BasedOnID</code>    | string        | <code>"0"</code>          | <code>"0"</code> = Direct, <code>"2"</code> = Indent wise        |
| <code>Remarks</code>      | string        | <code>" "</code>          | From header                                                      |
| <code>CompanyID</code>    | number        | <code>1</code>            | <code>DEFAULT_COMPANY_ID</code>                                  |
| <code>YearID</code>       | number        | <code>2</code>            | <code>PI_CONFIG.DIVISION_YEAR_ID</code>                          |
| <code>LoginID</code>      | number        | <code>1</code>            | <code>DEFAULT_LOGIN_ID</code>                                    |
| <code>IDNumber</code>     | number        | <code>0</code>            | <code>0</code> = new entry; route <code>:id</code> value = amend |

**Detail row fields ( `prmStrDetJSON` ):**

| Field                 | Type | Notes                                                                          |
|-----------------------|------|--------------------------------------------------------------------------------|
| All item grid columns | any  | Internal <code>id</code> field stripped; <code>LoginID</code> injected per row |



Indent detail fields ( `prmStrIndtDetJSON` ):

| Field                 | Type | Notes                                                                                             |
|-----------------------|------|---------------------------------------------------------------------------------------------------|
| All indent child rows | any  | From <code>childRowsMap</code> ; internal <code>id</code> stripped; <code>LoginID</code> injected |

## Response

```
{ "ok": true, "message": "Saved successfully." }
```

If `!res.ok`, error message from `result?.message` is thrown. Success triggers an alert dialog.

**Why:** Creates or amends a purchase inquiry on the server with all three data layers: master header, item detail rows, and indent detail children.

## Summary Table

| #    | Endpoint                                                  | Method | SP / Function                                             | Trigger                                                     |
|------|-----------------------------------------------------------|--------|-----------------------------------------------------------|-------------------------------------------------------------|
| 4.1  | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_Fetch_RBDetailByRBCode</code> (RB_PurInquiryMst) | Page mount                                                  |
| 4.2  | <code>/GetDetailColData</code>                            | GET    | —                                                         | After 4.1 resolves                                          |
| 4.3  | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_tbl_FetchUserWsDivision</code>                   | Page mount (parallel)                                       |
| 4.4  | <code>/FN_Fetch_Data</code>                               | GET    | <code>Pr_Fetch_DepartmentData_IMS</code>                  | Page mount (parallel)                                       |
| 4.5  | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_Fetch_RBDetailByRBCode</code> (RB_PurInquiryDet) | Page mount (parallel)                                       |
| 4.6  | <code>/GetDetailColData</code>                            | GET    | —                                                         | After 4.5 resolves                                          |
| 4.7  | <code>/GetFilterDetail</code>                             | GET    | —                                                         | On<br><code>fetchGridColumns()</code><br>— per dropdown col |
| 4.8  | <code>/FN_Fetch_Data</code>                               | GET    | <code>fn_tbl_ddl_Pur_Configuration</code>                 | Division dropdown change                                    |
| 4.9  | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_Tbl_FetchPurchaseItemDetailTransWs4Web</code>    | Division + ConfigID set                                     |
| 4.10 | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_Fetch_RBDetailByRBCode</code> (item picker RB)   | "Select Item" click                                         |
| 4.11 | <code>/GetDetailColData</code>                            | GET    | —                                                         | After 4.10 resolves                                         |
| 4.12 | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_Tbl_FetchPurchaseItemDetailTransWs4Web</code>    | After 4.11 resolves                                         |
| 4.13 | <code>/API/Values</code>                                  | POST   | <code>Fn_tbl_FetchIndentSummaryItem4Inquiry</code>        | Insert (indent-wise)                                        |
| 4.14 | <code>/FN_Fetch_Data</code>                               | GET    | <code>Fn_tbl_FetchCustomerSupplierTranWs4Web</code>       | "Select Supplier" click                                     |
| 4.15 | <code>/API/TranFormSave/Post_RB_PurInquiryMst_Save</code> | POST   | —                                                         | Save button click                                           |