

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code:	20211#005
Product name	LUMOROL 54/SPEZIAL-M
Chemical name and synonym	Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts (and) Sodium Laureth Sulfate (and) Amides, C8-18 (eben numbered) and C18 (unsatd.),N,N-bis(hydroxyethyl) (and) Aqua

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	Blend of anionic and non ionic surfactants, used in handwashing and detergency field, in industrial, building, leather and textile sectors.
--------------	---------------------------------------------------------------------------------------------------------------------------------------------

#### 1.3. Details of the supplier of the safety data sheet

Name	Zschimmer & Schwarz Italiana S.p.a.	
Full address	via A. Ariotto, 1/C	
District and Country	13038 Tricerro Italia	(VC)
	Tel. 0039 0161 808111	
	Fax 0039 0161 801002	
e-mail address of the competent person responsible for the Safety Data Sheet	e.merlo@zschimmer-schwarz.com	

#### 1.4. Emergency telephone number

For urgent inquiries refer to	0039 0161 808111 / 0039 3316593305
-------------------------------	------------------------------------

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Eye Dam. 1	H318
Skin Irrit. 2	H315
Aquatic Chronic 3	H412

##### 2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.

Danger Symbols:	Xi
-----------------	----

R phrases:	38-41
------------	-------

The classification of the compound, featuring an extreme pH value, is based on the results of an appropriate validated in-vitro test as set out in the 67/548/EEC directive, annex VI, paragraph 3.2.5, and following modifications.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

**LUMOROL 54/SPEZIAL-M****SECTION 2. Hazards identification. ... / >>****2.2. Label elements.**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

**H318** Causes serious eye damage.  
**H315** Causes skin irritation.  
**H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

**P264** Wash skin and eyes thoroughly after handling.  
**P273** Avoid release to the environment.  
**P280** Wear protective gloves / protective clothing / eye protection / face protection.  
**P302+P352** IF ON SKIN: Wash with plenty of soap and water.

**Contains:** Sodium Laureth Sulfate  
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts  
Methylisothiazolinone sol. 10%

The classification of the compound, featuring an extreme pH value, is based on the results of an appropriate validated in-vitro test as set out in the 67/548/EEC directive, annex VI, paragraph 3.2.5, and following modifications.

**2.3. Other hazards.**

Information not available.

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**3.2. Mixtures.**

**Contains:**

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).	
<b>Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts</b>				
CAS.	68411-30-3	25 - 50	Xi R38, Xi R41	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC.	270-115-0			
INDEX.	-			
Reg. no. 01-2119489428-22-0037				
<b>Sodium Laureth Sulfate</b>				
CAS.	9004-82-4	5 - 20	Xi R38, Xi R41	Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC.	-			
INDEX.	-			
Reg. no. absent, polymer				
<b>Methylisothiazolinone sol. 10%</b>				
CAS.	2682-20-4	1 - 5	Xn R21/22, Xi R36/38, Xi R43	Acute Tox. 4 H302, Acute Tox. 4 H312, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317
EC.	220-239-6			
INDEX.	-			
Reg. no. pre-registered				

**LUMOROL 54/SPEZIAL-M****SECTION 3. Composition/information on ingredients.** ... / >>**Amides, C8-18 (even numbered) and C18 (unsatd.),N,N-bis(hydroxyethyl)**

CAS. 68155-07-7 1 - 5

Xi R38, Xi R41

Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 2 H411

EC. 931-329-6

INDEX. -

Reg. no. 01-2119490100-53-0001

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

**SECTION 4. First aid measures.****4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

**4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

**SECTION 5. Firefighting measures.****5.1. Extinguishing media.****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture.****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters.****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures.****6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

**LUMOROL 54/SPEZIAL-M****SECTION 6. Accidental release measures.** ... / >>

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage.****7.1. Precautions for safe handling.**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities.**

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s).**

Information not available.

**SECTION 8. Exposure controls/personal protection.**

Respiratory protection: in case of formation of vapours/dusts: Particle filter P2 - Hand protection: gloves made of chloroprene (CR, e.g. Neoprene): Minimum break-through time of the glove: 480 min, Glove strength: 0.6 mm; gloves made of nitril (NBR): Minimum break-through time of the glove: 480 min, Glove strength: 0,4 mm; gloves made of butyl (IIR): Minimum break-through time of the glove: 480 min, Glove strength: 0,3 mm - Eye protection: goggles or face shield if necessary - Skin and body protection: light protective clothing

**8.1. Control parameters.**

## Regulatory References:

United Kingdom

Éire

OEL EU

TLV-ACGIH

EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended). Code of Practice Chemical Agent Regulations 2011. Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. ACGIH 2012

**Amides, C8-18 (even numbered) and C18 (unsatd.),N,N-bis(hydroxyethyl)****Predicted no-effect concentration - PNEC.**

Normal value for the terrestrial compartment	0,104	mg/kg/d
Normal value in fresh water	0,007	mg/l
Normal value for water, intermittent release	0,03	mg/l
Normal value in marine water	0,0007	mg/l
Normal value for fresh water sediment	NEA	
Normal value for marine water sediment	0,22	mg/kg/d
Normal value of STP microorganisms	0,83	g/l

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers.				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	NPI	NPI	NPI	6,25 mg/kg				
Inhalation.	NPI	NPI	NPI	21,7 mg/m3	NPI	NPI	NPI	73,4 mg/m3
Skin.	NPI	NPI	0,056 mg/kg	2,5 mg/kg	NPI	NPI	0,09 mg/kg	4,16 mg/kg

**LUMOROL 54/SPEZIAL-M****SECTION 8. Exposure controls/personal protection. ... / >>****Methylisothiazolinone sol. 10%****Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV		1,5		4,5	

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Appearance		paste
Colour		ivory
Odour		characteristic
Odour threshold.		characteristic
pH.		7.0 - 8.0 (sol. 10%, 20°C)
Melting point / freezing point.		Not available.
Initial boiling point.	>	100 °C.
Boiling range.		Not available.
Flash point.	>	100 °C.
Evaporation Rate		Not available.
Flammability of solids and gases		not flammable
Lower inflammability limit.		Not available.
Upper inflammability limit.		Not available.
Lower explosive limit.		Not available.
Upper explosive limit.		Not available.
Vapour pressure.		Not available.
Vapour density		Not available.
Relative density.		1.085 - 1.095 g/ml (20°C)
Solubility		miscible
Partition coefficient: n-octanol/water		Not available.
Auto-ignition temperature.		Not available.
Decomposition temperature.		Not available.
Viscosity		Not available.

**LUMOROL 54/SPEZIAL-M****SECTION 9. Physical and chemical properties. ... / >>**Explosive properties  
Oxidising propertiesNon explosive  
Non oxidant**9.2. Other information.**

Information not available.

**SECTION 10. Stability and reactivity.****10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid.**

None in particular. However the usual precautions used for chemical products should be respected.

It can reacts with strong oxidants.

**10.5. Incompatible materials.**

Information not available.

**10.6. Hazardous decomposition products.**

Information not available.

**SECTION 11. Toxicological information.****11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Irritant to eye and skin (rabbit); Sensitizer (guinea pig); Not mutagenic; Not cancerogenic, Not teratogenic.

Irritant to eyes and skin.

Methylisothiazolinone sol. 10%

LD50 (Oral).

2834 mg/kg Rat (male)

LD50 (Dermal).

&gt; 5000 mg/kg Rabbit

LC50 (Inhalation).

5,26 mg/l Calculation method

Amides,

C8-18

(even

numbered)

and

C18

(unsatd.),N,N-bis(hydroxyethyl)

LD50 (Oral).

&gt; 2000 mg/kg Rats (OECD 401)

LD50 (Dermal).

&gt; 2000 mg/kg Rabbits

Sodium Laureth Sulfate

LD50 (Oral).

&gt; 2000 mg/kg Rat

Benzenesulfonic

acid,

C10-13-alkyl

derivs.,

sodium

salts

LD50 (Oral).

&gt; 2000 mg/kg

Irritant to skin and eye (product as it is); Not mutagenic (Ames test); Not sensitizing.

**LUMOROL 54/SPEZIAL-M****SECTION 12. Ecological information.**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity.**

Methylisothiazolinone sol. 10%

LC50 - for Fish. > 0,07 mg/l/96h Oncorhynchus mykiss  
EC50 - for Crustacea. 0,158 mg/l/48h Algae (OECD TG 201)  
EC50 - for Algae / Aquatic Plants. 0,85 mg/l/72h Daphnia magna (48h)

Amides, C8-18 (even numbered) and C18 (unsatd.),N,N-bis(hydroxyethyl)  
LC50 - for Fish. > 3 mg/l/96h Oncorhynchus mykiss  
EC50 - for Crustacea. < 10 mg/l/48h Daphnia Magna (Reproduction Test, OECD 211)  
EC50 - for Algae / Aquatic Plants. > 3,9 mg/l/72h Scenedesmus subspicatus

Sodium Laureth Sulfate  
LC50 - for Fish. 7,1 mg/l/96h Brachydanio rerio  
EC50 - for Crustacea. 7,7 mg/l/48h Daphnia  
EC50 - for Algae / Aquatic Plants. 12 mg/l/72h Scenedesmus subspicatus

Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts  
LC50 - for Fish. > 1 mg/l/96h Fish  
EC50 - for Crustacea. > 1 mg/l/48h Daphnia and Algae

**12.2. Persistence and degradability.**

Not readily biodegradable.

This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Readily biodegradable (according to CE 648/2004).

Readily biodegradable according to CE 648/2004.

**12.3. Bioaccumulative potential.**

No bioaccumulo.

No bioaccumulo.

No bioaccumulo.

No biaccumulo.

**12.4. Mobility in soil.**

Log Pow: -0,486 (24°C).

Not mobile

**12.5. Results of PBT and vPvB assessment.**

No PBT/vPvB.

No PBT/vPvB.

No PBT/vPvB.

**12.6. Other adverse effects.**

Information not available.

**SECTION 13. Disposal considerations.****13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

CONTAMINATED PACKAGING

## SECTION 14. Transport information.

## SECTION 15. Regulatory information.

**SECTION 16. Other information.**





**LUMOROL 54/SPEZIAL-M****SECTION 16. Other information. ... / >>**

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
9. The Merck Index. - 10th Edition
10. Handling Chemical Safety
11. Niosh - Registry of Toxic Effects of Chemical Substances
12. INRS - Fiche Toxicologique (toxicological sheet)
13. Patty - Industrial Hygiene and Toxicology
14. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
15. ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**LUMOROL 54/SPEZIAL-M****SECTION 16. Other information. ... / >>**

Changes to previous review:  
The following sections were modified:  
13 / 14.