


VBCore DC motor Driver 15A v1.3



VBCore DC motor Driver v1.3

VIN: 9-50V
MAX CURRENT: 15A
MCU: VB32G4 (STM32G474RE)
DRIVER: ALLEGRO A4955
SPI interface
ABZ encoder interface
I2C interface
Current control
I2C EEPROM
CAN / CAN-FD
Dimensions: 51x56mm
Mount holes: 45x50mm D2.5 mm

NOTES:

1. The SPI1 and SPI3 connectors are connected to the controller via level shifters.
2. The Hall sensor connectors are connected to the controller via a filter.
3. The I2C4 SCL and SDA lines have external pull-ups — **do not use the internal pull-up.**
4. To supply power to the I2C4 bus (including the EEPROM), close the voltage selection solder jumper.
5. To use the SPI3 7-pin connector as an SPI bus, leave the INV solder pads open. Close the INV_1 solder jumper to configure the PA15 and PB4 pins as inputs. Close the INV_2 solder jumper to configure the PC10 and PC12 pins as inputs.
6. Carefully read datasheet for ALLEGRO A4955 driver futures



www.vbcores.com
Electronics for robotics
research and development

Driver

Allegro A4955, 50V
Full-Bridge PWM Gate Driver
designed for control of DC motors

Controll	PIN	Notes
SLEEPn	PB3	
IN1	PA8	TIM1_CH1
IN2	PA9	TIM1_CH2
AIOU	PC1	
VREF	PA4	1:2 divider
FAULT	PB5	
RC		$R_{RC} = 47K, C_{RC} = 1n$
ISET		$R_{ISET} = 47K$
SENSE		$R_{SENSE} = 0,01$

EEPROM

256K, AT24C256C
*For enable, one of I2C4 voltage select solder jumper must be closed

Controll	PIN	I2C
A0, A1, A2	GND	
Address		0x50
SCL	PC6	I2C4_SCL
SDA	PB7	I2C4_SDA

Voltage controll

Resistive voltage divider 16:1

Controll	PIN	ADC
V input	PC0	ADC12_IN6

Current shunt resistor

Connected to A4955 driver

Size	Default
1206	$R_{SENSE} 0.01 \text{ Ohm}$

