

# CIS Apache HTTP Server 2.4 Benchmark

v1.0.0

The CIS Security Benchmarks division provides consensus-oriented information security products, services, tools, metrics, suggestions, and recommendations (the “SB Products”) as a public service to Internet users worldwide. Downloading or using SB Products in any way signifies and confirms your acceptance of and your binding agreement to these CIS Security Benchmarks Terms of Use.

## ***CIS SECURITY BENCHMARKS TERMS OF USE***

### ***BOTH CIS SECURITY BENCHMARKS DIVISION MEMBERS AND NON-MEMBERS MAY:***

- Download, install, and use each of the SB Products on a single computer, and/or
- Print one or more copies of any SB Product that is in a .txt, .pdf, .doc, .mcw, or .rtf format, but only if each such copy is printed in its entirety and is kept intact, including without limitation the text of these CIS Security Benchmarks Terms of Use.

### ***UNDER THE FOLLOWING TERMS AND CONDITIONS:***

- **SB Products Provided As Is.** CIS is providing the SB Products “as is” and “as available” without: (1) any representations, warranties, or covenants of any kind whatsoever (including the absence of any warranty regarding: (a) the effect or lack of effect of any SB Product on the operation or the security of any network, system, software, hardware, or any component of any of them, and (b) the accuracy, utility, reliability, timeliness, or completeness of any SB Product); or (2) the responsibility to make or notify you of any corrections, updates, upgrades, or fixes.
- **Intellectual Property and Rights Reserved.** You are not acquiring any title or ownership rights in or to any SB Product, and full title and all ownership rights to the SB Products remain the exclusive property of CIS. All rights to the SB Products not expressly granted in these Terms of Use are hereby reserved.
- **Restrictions.** You acknowledge and agree that you may not: (1) decompile, dis-assemble, alter, reverse engineer, or otherwise attempt to derive the source code for any software SB Product that is not already in the form of source code; (2) distribute, redistribute, sell, rent, lease, sublicense or otherwise transfer or exploit any rights to any SB Product in any way or for any purpose; (3) post any SB Product on any website, bulletin board, ftp server, newsgroup, or other similar mechanism or device; (4) remove from or alter these CIS Security Benchmarks Terms of Use on any SB Product; (5) remove or alter any proprietary notices on any SB Product; (6) use any SB Product or any component of an SB Product with any derivative works based directly on an SB Product or any component of an SB Product; (7) use any SB Product or any component of an SB Product with other products or applications that are directly and specifically dependent on such SB Product or any component for any part of their functionality; (8) represent or claim a particular level of compliance or consistency with any SB Product; or (9) facilitate or otherwise aid other individuals or entities in violating these CIS Security Benchmarks Terms of Use.
- **Your Responsibility to Evaluate Risks.** You acknowledge and agree that: (1) no network, system, device, hardware, software, or component can be made fully secure; (2) you have the sole responsibility to evaluate the risks and benefits of the SB Products to your particular circumstances and requirements; and (3) CIS is not assuming any of the liabilities associated with your use of any or all of the SB Products.
- **CIS Liability.** You acknowledge and agree that neither CIS nor any of its employees, officers, directors, agents or other service providers has or will have any liability to you whatsoever (whether based in contract, tort, strict liability or otherwise) for any direct, indirect, incidental, consequential, or special damages that arise out of or are connected in any way with your use of any SB Product.
- **Indemnification.** You agree to indemnify, defend, and hold CIS and all of CIS’s employees, officers, directors, agents and other service providers harmless from and against any liabilities, costs and expenses incurred by any of them in connection with your violation of these CIS Security Benchmarks Terms of Use.
- **Jurisdiction.** You acknowledge and agree that: (1) these CIS Security Benchmarks Terms of Use will be governed by and construed in accordance with the laws of the State of Maryland; (2) any action at law or in equity arising out of or relating to these CIS Security Benchmarks Terms of Use shall be filed only in the courts located in the State of Maryland; and (3) you hereby consent and submit to the personal jurisdiction of such courts for the purposes of litigating any such action.
- **U.S. Export Control and Sanctions laws.** Regarding your use of the SB Products with any non-U.S. entity or country, you acknowledge that it is your responsibility to understand and abide by all U.S. sanctions and export control laws as set from time to time by the U.S. Bureau of Industry and Security (BIS) and the U.S. Office of Foreign Assets Control (OFAC).

***SPECIAL RULES FOR CIS MEMBER ORGANIZATIONS:*** CIS reserves the right to create special rules for: (1) CIS Members; and (2) Non-Member organizations and individuals with which CIS has a written contractual relationship. CIS hereby grants to each CIS Member Organization in good standing the right to distribute the SB Products within such Member’s own organization, whether by manual or electronic means. Each such Member Organization acknowledges and agrees that the foregoing grants in this paragraph are subject to the terms of such Member’s membership arrangement with CIS and may, therefore, be modified or terminated by CIS at any time.

# Table of Contents

1 Recommendations .....	9
1.1 Planning and Installation .....	9
1.1.1 Pre-Installation Planning Checklist (Not Scored) .....	9
1.1.2 Do Not Install a Multi-use System (Not Scored) .....	10
1.1.3 Installing Apache (Not Scored) .....	11
1.2 Minimize Apache Modules .....	12
1.2.1 Enable only necessary Authentication and Authorization Modules (Not Scored) .....	12
1.2.2 Enable the Log Config Module (Scored) .....	14
1.2.3 Disable WebDAV Modules (Scored) .....	15
1.2.4 Disable Status Module (Scored) .....	16
1.2.5 Disable Autoindex Module (Scored) .....	17
1.2.6 Disable Proxy Modules (Scored) .....	18
1.2.7 Disable User Directories Modules (Scored) .....	20
1.2.8 Disable Info Module (Scored) .....	21
1.3 Principals, Permissions, and Ownership .....	22
1.3.1 Run the Apache Web Server as a non-root user (Scored) .....	23
1.3.2 Give the Apache User Account an Invalid Shell (Scored) .....	24
1.3.3 Lock the Apache User Account (Scored) .....	25
1.3.4 Set Ownership on Apache Directories and Files (Scored) .....	26
1.3.5 Restrict Write Access on Apache Directories and Files (Scored) .....	27
1.3.6 Secure Core Dump Directory (Scored) .....	28
1.3.7 Secure the Lock File (Scored) .....	29
1.3.8 Secure the Pid File (Scored) .....	30
1.3.9 Secure the ScoreBoard File (Scored) .....	31
1.4 Apache Access Control .....	33
1.4.1 Deny Access to OS Root Directory (Scored) .....	33
1.4.2 Allow Appropriate Access to Web Content (Not Scored) .....	35
1.4.3 Restrict Override for the OS Root Directory (Scored) .....	37

1.4.4 Restrict Override for All Directories (Scored) .....	39
1.5 Minimize Features, Content and Options.....	40
1.5.1 Restrict Options for the OS Root Directory (Scored).....	40
1.5.2 Restrict Options for the Web Root Directory (Scored).....	41
1.5.3 Minimize Options for Other Directories (Scored) .....	42
1.5.4 Remove Default HTML Content (Scored).....	44
1.5.5 Remove Default CGI Content printenv (Scored) .....	47
1.5.6 Remove Default CGI Content test-cgi (Scored) .....	48
1.5.7 Limit HTTP Request Methods (Scored) .....	49
1.5.8 Disable HTTP TRACE Method (Scored) .....	51
1.5.9 Restrict HTTP Protocol Versions (Scored) .....	52
1.5.10 Restrict Access to .ht* files (Scored).....	53
1.5.11 Restrict File Extensions (Scored) .....	54
1.5.12 Deny IP Address Based Requests (Scored).....	56
1.5.13 Restrict Listen Directive (Scored) .....	58
1.5.14 Restrict Browser Frame Options (Scored) .....	59
1.6 Operations - Logging, Monitoring and Maintenance .....	60
1.6.1 Configure the Error Log (Scored).....	60
1.6.2 Configure the Access Log (Scored) .....	62
1.6.3 Establish Log Monitoring (Not Scored) .....	63
1.6.4 Log Storage and Rotation (Scored) .....	65
1.6.5 Monitor Vulnerability Lists (Not Scored) .....	67
1.6.6 Apply Applicable Patches (Scored) .....	68
1.7 SSL/TLS Configuration.....	69
1.7.1 Install mod_ssl and/or mod_nss (Scored) .....	69
1.7.2 Install a Valid Trusted Certificate (Not Scored) .....	71
1.7.3 Protect the Server's Private Key (Scored) .....	74
1.7.4 Restrict Weak SSL Ciphers (Scored) .....	76
1.7.5 Disable SSL Insecure Renegotiation (Scored) .....	77
1.7.6 Ensure SSL Compression is not Enabled (Scored) .....	78

1.8 Information Leakage .....	79
1.8.1 Set ServerToken to 'Prod' (Scored) .....	80
1.8.2 Set ServerSignature to 'Off' (Scored) .....	81
1.8.3 Information Leakage via Default Apache Content (Scored) .....	82
1.9 Denial of Service Mitigations .....	83
1.9.1 Set TimeOut to 10 or less (Scored) .....	83
1.9.2 Set the KeepAlive directive to On (Scored) .....	84
1.9.3 Set MaxKeepAliveRequests to 100 or greater (Scored) .....	85
1.9.4 Set KeepAliveTimeout Low to Mitigate Denial of Service (Scored) .....	86
1.9.5 Set Timeout Limits for Request Headers (Scored) .....	87
1.9.6 Set Timeout Limits for the Request Body (Scored) .....	88
1.10 Request Limits .....	89
1.10.1 Set the LimitRequestLine directive to 512 or less (Scored) .....	90
1.10.2 Set the LimitRequestFields directive to 100 or less (Scored) .....	91
1.10.3 Set the LimitRequestFieldsize directive to 1024 or less (Scored) .....	92
1.10.4 Set the LimitRequestBody directive to 102400 or less (Scored) .....	93

# Overview

This document, CIS Apache 2.4 Benchmark, provides prescriptive guidance for establishing a secure configuration posture for Apache Web Server versions 2.4 running on Linux. This guide was tested against Apache Web Server 2.4.3 as built from source <http://httpd.apache.org/> on Linux. To obtain the latest version of this guide, please visit <http://benchmarks.cisecurity.org>. If you have questions, comments, or have identified ways to improve this guide, please write us at [feedback@cisecurity.org](mailto:feedback@cisecurity.org).

## *Intended Audience*

This document is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate Apache HTTP Server 2.4 running on Linux.

## *Consensus Guidance*

This benchmark was created using a consensus review process comprised of volunteer and contract subject matter experts. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS benchmark undergoes two phases of consensus review. The first phase occurs during initial benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the benchmark. This discussion occurs until consensus has been reached on benchmark recommendations. The second phase begins after the benchmark has been released to the public Internet. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the benchmark. If you are interested in participating in the consensus review process, please send us a note to [feedback@cisecurity.org](mailto:feedback@cisecurity.org).

## Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
<code>Stylized Monospace font</code>	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
<code>Monospace font</code>	Used for inline code, commands, or examples. Text should be interpreted exactly as presented.
<i>&lt;italic font in brackets&gt;</i>	Italic texts set in angle brackets denote a variable requiring substitution for a real value.
<i>Italic font</i>	Used to denote the title of a book, article, or other publication.
<b>Note</b>	Additional information or caveats

## Scoring Information

A scoring status indicates whether compliance with the given recommendation impacts the assessed target's benchmark score. The following scoring statuses are used in this benchmark:

### Scored

Failure to comply with "Scored" recommendations will decrease the final benchmark score. Compliance with "Scored" recommendations will increase the final benchmark score.

### Not Scored

Failure to comply with "Not Scored" recommendations will not decrease the final benchmark score. Compliance with "Not Scored" recommendations will not increase the final benchmark score.

## ***Profile Definitions***

The following configuration profiles are defined by this Benchmark:

- **Level 1**

Items in this profile intend to:

- be practical and prudent;
- provide a clear security benefit; and
- not negatively inhibit the utility of the technology beyond acceptable means.

- **Level 2**

This profile extends the "Level 1" profile. Items in this profile exhibit one or more of the following characteristics:

- are intended for environments or use cases where security is paramount
- acts as defense in depth measure
- may negatively inhibit the utility or performance of the technology.



## ***Acknowledgements***

This benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of the CIS Apache Benchmarks:

### **Author**

Ralph Durkee CISSP, GSEC, GCIH, GSNA, GPEN, *Durkee Consulting, Inc.*

### **Contributors**

Ahmed Adel GSEC, GCIH, GCFW, GWAN

Ryan Barnett

Quan Bui

Lawrence Grim

Blake Frantz , *Center for Internet Security*

Peter Morin CISA, CGEIT, GCFA , *Bell Canada Enterprises*

Mihai Nitulescu

Eduardo Petazze

Vinoth Sivasubramanian

Art Stricek , *County of Berks, PA*

Eric Taylor , *Northrop Grumman Corporation*

Sven Vermeulen

Vytautas Vysniauskas PhD, *Consumer Direct*

Roger Kennedy Linux Systems Engineer

Christopher Sierra

Sam Sexton

# Recommendations

## 1 Recommendations

This benchmark is tested with a source code build of Apache on Linux and hence the defaults values reflect that configuration. Any paths to Apache files and directories are prefixed with a `$APACHE_PREFIX` variable which is expected to be the Server Root directory value where all of the Apache directories are located. Although having all of the Apache2 directories under one parent isn't compliant with the Filesystem Hierarchy Standard (FHS), many distributions which are compliant, place symbolic links in the Server Root directory (such as `/etc/httpd`) to provide a logical root directory that works well. The Server Root directory may be obtained from the `httpd` binary and from the configuration file with the following commands:

```
httpd -V | grep HTTPD_ROOT  
grep '^ServerRoot' conf/httpd.conf
```

Also a `find` command may be helpful in determining the correct Apache directory paths.

```
find / -type d -name apache2
```

### 1.1 Planning and Installation

This section contains recommendations for the planning and installation of an Apache HTTP Server.

#### 1.1.1 Pre-Installation Planning Checklist (Not Scored)

##### Profile Applicability:

- Level 1

##### Description:

Review and implement the following items as appropriate:

- Reviewed and implemented my company's security policies as they relate to web security.
- Implemented a secure network infrastructure by controlling access to/from your web server by using firewalls, routers and switches.

- Harden the Underlying Operating System of the web server, by minimizing listening network services, applying proper patches and hardening the configurations as recommended in the appropriate Center for Internet Security benchmark for the platform.
- Implement central log monitoring processes.
- Implemented a disk space monitoring process and log rotation mechanism.
- Educate developers, architects and testers about developing secure applications, and integrate security into the software development lifecycle. <http://www.owasp.org/> <http://www.webappsec.org/>
- Ensure the WHOIS Domain information registered for our web presence does not reveal sensitive personnel information, which may be leveraged for Social Engineering (Individual POC Names), War Dialing (Phone Numbers) and Brute Force Attacks (Email addresses matching actual system usernames).
- Ensure your Domain Name Service (DNS) servers have been properly secured to prevent attacks, as recommended in the CIS BIND DNS Benchmark.
- Implemented a Network Intrusion Detection System to monitor attacks against the web server.

## References:

1. Open Web Application Security Project - <http://www.OWASP.org>
2. Web Application Security Consortium - <http://www.webappsec.org/>

### *1.1.2 Do Not Install a Multi-use System (Not Scored)*

#### Profile Applicability:

- Level 1

#### Description:

Default server configurations often expose a wide variety of services unnecessarily increasing the risk to the system. Just because a server can perform many services doesn't mean it is wise to do so. The number of services and daemons executing on the Apache Web server should be limited to those necessary, with the Web server being the only primary function of the server.

#### Rationale:

Maintaining a server for a single purpose increases the security of your application and system. The more services which are exposed to an attacker, the more potential vectors an attacker has to exploit the system and therefore the higher the risk for the server. A Web server should function as only a web server and if possible should not be mixed with other primary functions such as mail, DNS, database or middleware.

#### Audit:

Leverage the package or services manager for your OS to list enabled services and review with document business needs of the server. On Red Hat systems, the following will produce the list of current services enabled:

```
chkconfig --list | grep ':on'
```

### Remediation:

Leverage the package or services manager for your OS to uninstall or disable unneeded services. On Red Hat systems, the following will disable a given service:

```
chkconfig <servicename> off
```

## 1.1.3 Installing Apache (Not Scored)

### Profile Applicability:

- Level 1

### Description:

The CIS Apache Benchmark recommends using the Apache binary provided by your vendor for most situations in order to reduce the effort and increase the effectiveness of maintenance and security patches. However to keep the benchmark as generic and applicable to all Unix/Linux platforms as possible, a default source build has been used for this benchmark.

**Important Note:** There is a major difference between source builds and most vendor packages that is very important to highlight. The default source build of Apache is fairly conservative and minimalist in the modules included and therefore starts off in a fairly strong security state, while most vendor binaries are typically very well loaded with most of the functionality that one may be looking for. ***Therefore it is important that you don't assume the default value shown in the benchmark will match default values in your installation.***

You should always test any new installation in your environment before putting it into production. Also keep in mind you can install and run a new version alongside the old one by using a different Apache prefix and a different IP address or port number in the `Listen` directive.

### Rationale:

The benefits of using the vendor supplied binaries include:

- Ease of installation as it will just work, straight out of the box.
- It is customized for your OS environment.

- It will be tested and have gone through QA procedures.
- Everything you need is likely to be included, probably including some third party modules. For example, many OS vendors ship Apache with `mod_ssl` and OpenSSL, PHP, `mod_perl`, and `mod_security`.
- Your vendor will tell you about security issues so you have to look in fewer places.
- Updates to fix security issues will be easy to apply. The vendor will have already verified the problem, checked the signature on the Apache download, worked out the impact and so on.
- You may be able to get the updates automatically, reducing the window of risk.

### Remediation:

Installation depends on the operating system platform. For a source build consult the Apache 2.4 documentation on compiling and installing <http://httpd.apache.org/docs/2.4/install.html> for a Red Hat Enterprise Linux 5 the following yum command could be used.

```
# yum install httpd
```

### References:

1. Apache Compiling and Installation <http://httpd.apache.org/docs/2.4/install.html>

## 1.2 Minimize Apache Modules

It's crucial to have a minimal and compact Apache installation based on documented business requirements. This section covers specific modules that should be reviewed and disabled if not required for business purposes. However it's very important that the review and analysis of which modules are required for business purposes not be limited to the modules explicitly listed.

### 1.2.1 Enable only necessary Authentication and Authorization Modules (Not Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache 2.4 modules for authentication and authorization are grouped and named to provide both granularity, and a consistent naming convention to simplify configuration. The `authn_*` modules provide authentication, while the `authz_*` modules provide authorization. Apache provides two types of authentication - basic and digest. Review the

Apache Authentication and Authorization how-to documentation

<http://httpd.apache.org/docs/2.4/howto/auth.html> and enable only the modules that are required.

### Rationale:

Authentication and authorization are the front doors to the protected information in your web site. Most installations only need a small subset of the modules available. By minimizing the enabled modules to those that are actually used, we reduce the number of "doors" and have therefore reduced the attack surface of the web site. Likewise, having fewer modules means less software that could have vulnerabilities.

### Audit:

1. Use the `httpd -M` option as root to check which `auth*` modules are loaded.

```
# httpd -M | egrep 'auth._'
```

2. Also use the `httpd -M` option as root to check for any LDAP modules which don't follow the same naming convention.

```
# httpd -M | egrep 'ldap'
```

The above commands should generate a "Syntax OK" message to `stderr`, in addition to a list of modules installed to `stdout`. If the "Syntax OK" message is missing, then there was most likely an error in parsing the configuration files.

### Remediation:

Consult Apache module documentation for descriptions of each module in order to determine the necessary modules for the specific installation.

<http://httpd.apache.org/docs/2.4/mod/> The unnecessary static compiled modules are disabled through compile time configuration options as documented in <http://httpd.apache.org/docs/2.4/programs/configure.html>. The dynamically loaded modules are disabled by commenting out or removing the `LoadModule` directive from the Apache configuration files (typically `httpd.conf`). Some modules may be separate packages, and may be removed.

### Default Value:

The following modules are loaded by a default source build:

```
authn_file_module (shared)
authn_core_module (shared)
authz_host_module (shared)
```

```
authz_groupfile_module (shared)
authz_user_module (shared)
authz_core_module (shared)
```

**References:**

1. Apache AAA how-to <http://httpd.apache.org/docs/2.4/howto/auth.html>
2. Apache Module Documentation <http://httpd.apache.org/docs/2.4/mod/>
3. Apache Source Configuration <http://httpd.apache.org/docs/2.4/programs/configure.html>

### 1.2.2 Enable the Log Config Module (Scored)

**Profile Applicability:**

- Level 1

**Description:**

The `log_config` module provides for flexible logging of client requests, and provides for the configuration of the information in each log.

**Rationale:**

Logging is critical for monitoring usage and potential abuse of your web server. This module is required to configure web server logging using the `log_format` directive.

**Audit:**

Perform the following to determine if the `log_config` has been loaded:

1. Use the `httpd -M` option as `root` to check that the module is loaded.

```
# httpd -M | grep log_config
```

**Note:** If the module is correctly enabled, the output will include the module name and whether it is loaded statically or as a shared module

**Remediation:**

Perform either one of the following:

- For source builds with static modules, run the Apache `./configure` script without including the `--disable-log-config` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

- For dynamically loaded modules, add or modify the `LoadModule` directive so that it is present in the apache configuration as below and not commented out :

```
LoadModule log_config_module modules/mod_log_config.so
```

### Default Value:

The `log_config` module is loaded by default.

### References:

1. Mod Log Config [http://httpd.apache.org/docs/2.4/mod/mod\\_log\\_config.html](http://httpd.apache.org/docs/2.4/mod/mod_log_config.html)

### 1.2.3 Disable WebDAV Modules (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache `mod_dav` and `mod_dav_fs` modules support WebDAV ('Web-based Distributed Authoring and Versioning') functionality for Apache. WebDAV is an extension to the HTTP protocol which allows clients to create, move, and delete files and resources on the web server.

#### Rationale:

Disabling WebDAV modules will improve the security posture of the web server by reducing the amount of potentially vulnerable code paths exposed to the network and reducing potential for unauthorized access to files via misconfigured WebDAV access controls.

#### Audit:

Perform the following to determine if the WebDAV modules are enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep 'dav_[[:print:]]+module'
```



Note: If the WebDav modules are correctly disabled, there will be no output when executing the above command.

## Remediation:

Perform either one of the following to disable WebDAV module:

1. For source builds with static modules run the Apache `./configure` script without including the `mod_dav`, and `mod_dav_fs` in the `--enable-modules=configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

2. For dynamically loaded modules comment out or remove the `LoadModule` directive for `mod_dav`, and `mod_dav_fs` modules the from the `httpd.conf` file.

```
##LoadModule dav_module modules/mod_dav.so
##LoadModule dav_fs_module modules/mod_dav_fs.so
```

## Default Value:

The WebDav modules are not enabled with a default source build.

## References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_dav.html](http://httpd.apache.org/docs/2.4/mod/mod_dav.html)

### 1.2.4 Disable Status Module (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache `mod_status` module provides current server performance statistics.

#### Rationale:

When `mod_status` is loaded into the server, its handler capability is available in all configuration files, including per-directory files (e.g., `.htaccess`). The `mod_status` module may provide an adversary with information that can be used to refine exploits that depend on measuring server load.

**Audit:**

Perform the following to determine if the Status module is enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | egrep 'status_module'
```

**Note:** If the modules are correctly disabled, there will be no output when executing the above command.

**Remediation:**

Perform either one of the following to disable the `mod_status` module:

1. For source builds with static modules, run the Apache `./configure` script with the `--disable-status` configure script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure --disable-status
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for the `mod_status` module from the `httpd.conf` file.

```
##LoadModule status_module modules/mod_status.so
```

**Default Value:**

The `mod_status` module IS enabled with a default source build.

**References:**

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_status.html](http://httpd.apache.org/docs/2.4/mod/mod_status.html)

### *1.2.5 Disable Autoindex Module (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

The Apache `autoindex` module automatically generates web page listing the contents of directories on the server, typically used so that an `index.html` does not have to be generated.

## Rationale:

Automated directory listings should not be enabled as it will also reveal information helpful to an attacker such as naming conventions and directory paths. Directory listings may also reveal files that were not intended to be revealed.

## Audit:

Perform the following to determine if the module is enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep autoindex_module
```

**Note:** If the module is correctly disabled, there will be no output when executing the above command.

## Remediation:

Perform either one of the following to disable the `mod_autoindex` module:

1. For source builds with static modules, run the Apache `./configure` script with the `--disable-autoindex` configure script options

```
$ cd $DOWNLOAD_HTTPD
$ ./configure --disable-autoindex
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for `mod_autoindex` from the `httpd.conf` file.

```
## LoadModule autoindex_module modules/mod_autoindex.so
```

## Default Value:

The `mod_autoindex` module IS enabled with a default source build.

## References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_autoindex.html](http://httpd.apache.org/docs/2.4/mod/mod_autoindex.html)

## 1.2.6 Disable Proxy Modules (Scored)

### Profile Applicability:

- Level 1

## Description:

The Apache proxy modules allow the server to act as a proxy (either forward or reverse proxy) of HTTP and other protocols with additional proxy modules loaded. If the Apache installation is not intended to proxy requests to or from another network then the proxy module should not be loaded.

## Rationale:

Proxy servers can act as an important security control when properly configured, however a secure proxy server is not within the scope of this benchmark. A web server should be primarily a web server or a proxy server but not both, for the same reasons that other multi-use servers are not recommended. Scanning for web servers that will also proxy requests is a very common attack, as proxy servers are useful for anonymizing attacks on other servers, or possibly proxying requests into an otherwise protected network.

## Audit:

Perform the following to determine if the modules are enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep proxy_
```

**Note:** If the modules are correctly disabled, there will be no output when executing the above command.

## Remediation:

Perform either one of the following to disable the proxy module:

1. For source builds with static modules, run the Apache `./configure` script without including the `mod_proxy` in the `--enable-modules=configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for `mod_proxy` module and all other proxy modules from the `httpd.conf` file.

```
##LoadModule proxy_module modules/mod_proxy.so
##LoadModule proxy_connect_module modules/mod_proxy_connect.so
##LoadModule proxy_ftp_module modules/mod_proxy_ftp.so
```

```
##LoadModule proxy_http_module modules/mod_proxy_http.so
##LoadModule proxy_fcgi_module modules/mod_proxy_fcgi.so
##LoadModule proxy_scgi_module modules/mod_proxy_scgi.so
##LoadModule proxy_ajp_module modules/mod_proxy_ajp.so
##LoadModule proxy_balancer_module modules/mod_proxy_balancer.so
##LoadModule proxy_express_module modules/mod_proxy_express.so
```

### Default Value:

The `mod_proxy` module and other proxy modules are NOT enabled with a default source build.

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_proxy.html](http://httpd.apache.org/docs/2.4/mod/mod_proxy.html)

## 1.2.7 Disable User Directories Modules (Scored)

### Profile Applicability:

- Level 1

### Description:

The `UserDir` directive must be disabled so that user home directories are not accessed via the web site with a tilde (~) preceding the username. The directive also sets the path name of the directory that will be accessed. For example:

- <http://example.com/~ralph/> might access a `public_html` sub-directory of `ralph` user's home directory.
- The directive `UserDir ./` might map `/~root` to the root directory (`/`).

### Rationale:

The user directories should not be globally enabled since it allows anonymous access to anything users may want to share with other users on the network. Also consider that every time a new account is created on the system, there is potentially new content available via the web site.

### Audit:

Perform the following to determine if the modules are enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | grep userdir_
```

**Note:** If the modules are correctly disabled, there will be no output when executing the above command.

### Remediation:

Perform either one of the following to disable the user directories module:

1. For source builds with static modules, run the Apache `./configure` script with the `--disable-userdir` configure script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure --disable-userdir
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for `mod_userdir` module from the `httpd.conf` file.

```
##LoadModule userdir_module modules/mod_userdir.so
```

### Default Value:

The `mod_userdir` module is not enabled with a default source build.

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_userdir.html](http://httpd.apache.org/docs/2.4/mod/mod_userdir.html)

## 1.2.8 Disable Info Module (Scored)

### Profile Applicability:

- Level 1

### Description:

The Apache `mod_info` module provides information on the server configuration via access to a `/server-info` URL location.

### Rationale:

While having server configuration information available as a web page may be convenient it's recommended that this module NOT be enabled:

- Once `mod_info` is loaded into the server, its handler capability is available in per-directory `.htaccess` files and can leak sensitive information from the

configuration directives of other Apache modules such as system paths, usernames/passwords, database names, etc.

### Audit:

Perform the following to determine if the Info module is enabled.

1. Run the `httpd` server with the `-M` option to list enabled modules:

```
# httpd -M | egrep 'info_module'
```

**Note:** If the module is correctly disabled, there will be no output when executing the above command.

### Remediation:

Perform either one of the following to disable the `mod_info` module:

1. For source builds with static modules, run the Apache `./configure` script without including the `mod_info` in the `--enable-modules=` `configure` script options.

```
$ cd $DOWNLOAD_HTTPD
$ ./configure
```

2. For dynamically loaded modules, comment out or remove the `LoadModule` directive for the `mod_info` module from the `httpd.conf` file.

```
##LoadModule info_module modules/mod_info.so
```

### Default Value:

The `mod_info` module is not enabled with a default source build.

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_info.html](http://httpd.apache.org/docs/2.4/mod/mod_info.html)

## 1.3 Principals, Permissions, and Ownership

This section provides recommendations for configuring identities (users and groups) that Apache leverages, permissions on Apache-related filesystem resources, and ownership of Apache-related filesystem resources.

### 1.3.1 Run the Apache Web Server as a non-root user (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Although Apache is typically started with `root` privileges in order to listen on port 80 and 443, it can and should run as another non-root user in order to perform the web services. The `Apache User` and `Group` directives are used to designate the user and group that the Apache worker processes will assume.

#### Rationale:

One of the best ways to reduce your exposure to attack when running a web server is to create a unique, unprivileged user and group for the server application. The "nobody" or "daemon" user and group that comes default on Unix variants should NOT be used to run the web server, since the account is commonly used for other separate daemon services. Instead, an account used only by the apache software so as to not give unnecessary access to other services. Also the user identifier used for the apache user should be a unique system account. System user accounts UID numbers have lower values which are reserved for the special system accounts not used by regular users, such as discussed in User Accounts section of the CIS Red Hat benchmark. Typically system accounts numbers ranges from 1-999, or 1-499 and are defined in the `/etc/login.defs` file.

As an even more secure alternative, if the Apache web server can be run on high unprivileged ports, then it is not necessary to start Apache as `root`, and all of the Apache processes may be run as the Apache specific user as described below.

#### Audit:

Ensure the `apache` account is unique and has been created with a UID less than the minimum normal user account with the `apache` group and configured in the `httpd.conf` file.

1. Ensure the previous lines are present in the Apache configuration and not commented out :

```
# grep -i '^User' $APACHE_PREFIX/conf/httpd.conf
# grep -i '^Group' $APACHE_PREFIX/conf/httpd.conf
```

2. Ensure the `apache` account UID is correct:



```
# grep '^UID_MIN' /etc/login.defs
# id apache
```

The uid must be less than the `UID_MIN` value in `/etc/login.defs`, and group of `apache` similar to the following entries:

```
UID_MIN          1000
uid=48(apache) gid=48(apache) groups=48(apache)
```

3. While the web server is running, check the user id for the `httpd` processes. The user name should match the configuration file.

```
# ps axu | grep httpd | grep -v '^root'
```

### Remediation:

Perform the following:

1. If the `apache` user and group do not already exist, create the account and group as a unique system account:

```
# groupadd -r apache
# useradd apache -r -g apache -d /var/www -s /sbin/nologin
```

2. Configure the Apache user and group in the Apache configuration file `httpd.conf`:

```
User apache
Group apache
```

### Default Value:

The default Apache User and Group is configured as `daemon`.

### 1.3.2 Give the Apache User Account an Invalid Shell (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The `apache` account must not be used as a regular login account, and should be assigned an invalid or `nologin` shell to ensure that the account cannot be used to login.

#### Rationale:

Service accounts such as the `apache` account represent a risk if they can be used to get a login shell to the system.

### **Audit:**

Check the `apache` login shell in the `/etc/passwd` file:

```
# grep apache /etc/passwd
```

The `apache` account shell must be `/sbin/nologin` or `/dev/null` similar to the following:

```
/etc/passwd:apache:x:48:48:Apache:/var/www:/sbin/nologin
```

### **Remediation:**

Change the `apache` account to use the `nologin` shell or an invalid shell such as `/dev/null`:

```
# chsh -s /sbin/nologin apache
```

### **Default Value:**

The default Apache user account is `daemon`. The `daemon` account may have a valid login shell or a shell of `/sbin/nologin` depending on the operating system distribution version.

## ***1.3.3 Lock the Apache User Account (Scored)***

### **Profile Applicability:**

- Level 1

### **Description:**

The user account under which Apache runs should not have a valid password, but should be locked.

### **Rationale:**

As a defense-in-depth measure the Apache user account should be locked to prevent logins, and to prevent a user from `su`-ing to `apache` using the password. In general there shouldn't be a need for anyone to have to `su` as `apache`, and when there is a need, then `sudo` should be used instead, which would not require the `apache` account password.

**Audit:**

Ensure the `apache` account is locked using the following:

```
# passwd -S apache
```

The results will be similar to the following:

```
apache LK 2010-01-28 0 99999 7 -1 (Password locked.)
```

- or -

```
apache L 07/02/2012 -1 -1 -1 -1
```

**Remediation:**

Use the `passwd` command to lock the `apache` account:

```
# passwd -l apache
```

**Default Value:**

The default user is `daemon` and the account is typically locked.

### *1.3.4 Set Ownership on Apache Directories and Files (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

The Apache directories and files should be owned by `root` with the `root` (or `root` equivalent) group. This applies to all of the Apache software directories and files installed. The only expected exception is that the Apache web document root (`$APACHE_PREFIX/htdocs`) are likely to need a designated group to allow web content to be updated (such as `webupdate`) through a change management process.

**Rationale:**

Securing Apache files and directories will reduce the probability of unauthorized modifications to those resources.

**Audit:**

1. Identify files in the Apache directory that are not owned by `root`:

```
# find $APACHE_PREFIX \! -user root -ls
```

2. Identify files in the Apache directories other than `htdocs` with a group other than `root`:

```
# find $APACHE_PREFIX -path $APACHE_PREFIX/htdocs -prune -o \! -group root -ls
```

**Remediation:**

Perform the following:

- Set ownership on the `$APACHE_PREFIX` directories such as `/usr/local/apache2`:

```
$ chown -R root:root $APACHE_PREFIX
```

**Default Value:**

Default ownership and group is a mixture of the `user:group` that built the software and `root:root`.

### *1.3.5 Restrict Write Access on Apache Directories and Files (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

Permissions on Apache directories should generally be `rwxr-xr-x` (755) and file permissions should be similar except not executable if executable is not appropriate. This applies to all of the Apache software directories and files installed with the possible exception of the web document root `$APACHE_PREFIX/htdocs`. The directories and files in the web document root may have a designated group with write access to allow web content to be updated. In summary, the minimum recommendation is to not allow write access by `other`.

**Rationale:**

Restricting write permissions on the Apache files and directories can help mitigate attacks that modify web content to provide unauthorized access, or to attack web clients.

**Audit:**

Identify files or directories in the Apache directory with other write access, excluding symbolic links:

```
# find -L $APACHE_PREFIX \! -type l \! -type s -perm /o=w -ls
```

**Remediation:**

Perform the following to remove other write access on the \$APACHE\_PREFIX directories.

```
# chmod -R o-w $APACHE_PREFIX
```

### 1.3.6 Secure Core Dump Directory (Scored)

**Profile Applicability:**

- Level 1

**Description:**

The `CoreDumpDirectory` directive is used to specify the directory Apache attempts to switch to before creating the core dump. Core dumps will be disabled if the directory is not writable by the Apache user. Also, core dumps will be disabled if the server is started as `root` and switches to a non-root user, as is typical. It is recommended that the `CoreDumpDirectory` directive be set to a directory that is owned by the `root` user, owned by the group the Apache HTTPD process executes as, and be inaccessible to other users.

**Rationale:**

Core dumps are snapshots of memory and may contain sensitive information that should not be accessible by other accounts on the system.

**Audit:**

Verify that either the `CoreDumpDirectory` directive is not enabled in any of the Apache configuration files or that the configured directory meets the following requirements:

1. `CoreDumpDirectory` is not within the Apache web document root (`$APACHE_PREFIX/htdocs`)
2. Must be owned by `root` and have a group ownership of the Apache group (as defined via the `Group` directive)
3. Must have no read-write-search access permission for other users. (e.g. `o=rwx`)

## Remediation:

Either remove the `CoreDumpDirectory` directive from the Apache configuration files or ensure that the configured directory meets the following requirements.

1. `CoreDumpDirectory` is not to be within the Apache web document root (`$APACHE_PREFIX/htdocs`)
2. Must be owned by root and have a group ownership of the Apache group (as defined via the `Group` directive)

```
# chown root:apache /var/log/httpd
```

3. Must have no read-write-search access permission for other users.

```
# chmod o-rwx /var/log/httpd
```

## Default Value:

The default core dump directory is the `ServerRoot` directory.

## References:

1. [http://httpd.apache.org/docs/2.4/mod/mpm\\_common.html#coredumpdirectory](http://httpd.apache.org/docs/2.4/mod/mpm_common.html#coredumpdirectory)

### 1.3.7 Secure the Lock File (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The `Mutex` directive sets the locking mechanism used to serialize access to resources. It may be used to specify that a lock file is to be used as a mutex mechanism and may provide the path to the lock file to be used with the `fcntl(2)` or `flock(2)` system calls. Most Linux systems will default to using semaphores instead, so the directive may not apply. However in the event a lock file is used, it is important for the lock file to be in local directory that is not writable by other users.

#### Rationale:

If the lock file to be used as a mutex is placed in a writable directory, other accounts could create a denial of service attack and prevent the server from starting by creating a lock file with the same name.

**Audit:**

Verify the configuration does not include a `Mutex` directive with the mechanism of `fcntl`, `flock` or `file`.

If one of the file locking mechanisms is configured, then find the directory in which the lock file would be created. The default value is the `ServerRoot/logs` directory.

1. Verify that the lock file directory is not a directory within the Apache `DocumentRoot`
2. Verify that the ownership and group of the directory is `root:root` (or the user under which Apache initially starts up if not root).
3. Verify the permissions on the directory are only writable by root (or the startup user if not root),
4. Check that the lock file directory is on a locally mounted hard drive rather than an NFS mounted file system

**Remediation:**

Find the directory path in which the lock file would be created. The default value is the `ServerRoot/logs` directory.

1. Modify the directory if the path is a directory within the Apache `DocumentRoot`
2. Change the ownership and group to be `root:root`, if not already.
3. Change the permissions so that the directory is only writable by root, or the user under which Apache initially starts up (default is root),
4. Check that the lock file directory is on a locally mounted hard drive rather than an NFS mounted file system.

**Default Value:**

The default mechanism for the `Mutex` directive is platform specific and may be determined by running `httpd -V`. The default path is the `ServerRoot/logs` directory.

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#mutex>

### *1.3.8 Secure the Pid File (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

The `PidFile` directive sets the file path to the process ID file to which the server records the process id of the server, which is useful for sending a signal to the server process or for checking on the health of the process.

**Rationale:**

If the `PidFile` is placed in a writable directory, other accounts could create a denial of service attack and prevent the server from starting by creating a pid file with the same name.

**Audit:**

1. Find the directory in which the `PidFile` would be created. The default value is the `ServerRoot/logs` directory.
2. Verify that the process ID file directory is not a directory within the Apache `DocumentRoot`
3. Verify that the ownership and group of the directory is `root:root` (or the user under which Apache initially starts up if not root).
4. Verify the permissions on the directory are only writable by root (or the startup user if not root).

**Remediation:**

1. Find the directory in which the `PidFile` would be created. The default value is the `ServerRoot/logs` directory.
2. Modify the directory if the `PidFile` is in a directory within the Apache `DocumentRoot`
3. Change the ownership and group to be `root:root`, if not already.
4. Change the permissions so that the directory is only writable by root, or the user under which Apache initially starts up (default is root).

**Default Value:**

The default process ID file is `logs/httpd.pid`.

**References:**

1. [http://httpd.apache.org/docs/2.4/mod/mpm\\_common.html#pidfile](http://httpd.apache.org/docs/2.4/mod/mpm_common.html#pidfile)

### *1.3.9 Secure the ScoreBoard File (Scored)*

**Profile Applicability:**

- Level 1



**Description:**

The `ScoreBoardFile` directive sets a file path which the server will use for inter-process communication (IPC) among the Apache processes. On most Linux platforms shared memory will be used instead of a file in the file system, so this directive is not generally needed and does not need to be specified. However, if the directive is specified, then Apache will use the configured file for the inter-process communication. Therefore if it is specified it needs to be located in a secure directory.

**Rationale:**

If the `ScoreBoardFile` is placed in a writable directory, other accounts could create a denial of service attack and prevent the server from starting by creating a file with the same name, and or users could monitor and disrupt the communication between the processes by reading and writing to the file.

**Audit:**

1. Check to see if the `ScoreBoardFile` is specified in any of the Apache configuration files. If it is not present, the configuration is compliant.
2. Find the directory in which the `ScoreBoardFile` would be created. The default value is the `ServerRoot/logs` directory.
3. Verify that the scoreboard file directory is not a directory within the Apache `DocumentRoot`.
4. Verify that the ownership and group of the directory is `root:root` (or the user under which Apache initially starts up if not root).
5. Change the permissions so that the directory is only writable by root (or the startup user if not root).
6. Check that the scoreboard file directory is on a locally mounted hard drive rather than an NFS mounted file system.

**Remediation:**

1. Check to see if the `ScoreBoardFile` is specified in any of the Apache configuration files. If it is not present no changes are required.
2. If the directive is present, find the directory in which the `ScoreBoardFile` would be created. The default value is the `ServerRoot/logs` directory.
3. Modify the directory if the `ScoreBoardFile` is in a directory within the Apache `DocumentRoot`.
4. Change the ownership and group to be `root:root`, if not already.
5. Change the permissions so that the directory is only writable by root, or the user under which apache initially starts up (default is root),
6. Check that the scoreboard file directory is on a locally mounted hard drive rather than an NFS mounted file system.

**Default Value:**

The default scoreboard file is `logs/apache_status`.

**References:**

1. [http://httpd.apache.org/docs/2.4/mod/mpm\\_common.html#scoreboardfile](http://httpd.apache.org/docs/2.4/mod/mpm_common.html#scoreboardfile)

## ***1.4 Apache Access Control***

Recommendations in this section pertain to configurable access control mechanisms that are available in Apache HTTP server.

### ***1.4.1 Deny Access to OS Root Directory (Scored)***

**Profile Applicability:**

- Level 1

**Description:**

The Apache `Directory` directive allows for directory specific configuration of access controls and many other features and options. One important usage is to create a default deny policy that does not allow access to Operating system directories and files, except for those specifically allowed. This is done, by denying access to the OS root directory.

**Rationale:**

One aspect of Apache, which is occasionally misunderstood, is the feature of default access. That is, unless you take steps to change it, if the server can find its way to a file through normal URL mapping rules, it can and will serve it to clients. Having a default deny is a predominate security principal, and then helps prevent the unintended access, and we do that in this case by denying access to the OS root directory using either of two methods but not both:

1. Using the Apache `Deny` directive along with an `Order` directive.
2. Using the Apache `Require` directive.

Either method is effective. The `Order/Deny/Allow` combination are now deprecated; they provide three passes where all the directives are processed in the specified order. In contrast, the `Require` directive works on the first match similar to firewall rules. The `Require` directive is the default for Apache 2.4 and is demonstrated in the remediation procedure as it may be less likely to be misunderstood.

**Audit:**

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Ensure that either one of the following two methods are configured:

**Using the deprecated Order/Deny/Allow method:**

1. Ensure there is a single `Order` directive with the value of `deny, allow`
2. Ensure there is a `Deny` directive, and with the value of `from all`.
3. Ensure there are no `Allow` or `Require` directives in the root `<Directory>` element.

**Using the Require method:**

1. Ensure there is a single `Require` directive with the value of `all denied`
2. Ensure there are no `Allow` or `Deny` directives in the root `<Directory>` element.

The following may be useful in extracting root directory elements from the Apache configuration for auditing.

```
$ perl -ne 'print if /^ *<Directory *\\//i .. /<\\Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

**Remediation:**

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Add a single `Require` directive and set the value to `all denied`
3. Remove any `Deny` and `Allow` directives from the root `<Directory>` element.

```
<Directory>
. . .
    Require all denied
. . .
</Directory>
```

**Default Value:**

The following is the default root directory configuration:

```
<Directory>
. . .
    Require all denied
```

```
. . .  
</Directory
```

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#directory>
2. [http://httpd.apache.org/docs/2.4/mod/mod\\_authz\\_host.html](http://httpd.apache.org/docs/2.4/mod/mod_authz_host.html)

### *1.4.2 Allow Appropriate Access to Web Content (Not Scored)*

**Profile Applicability:**

- Level 1

**Description:**

In order to serve Web content, either the Apache `Allow` directive or the `Require` directive will need to be used to allow for appropriate access to directories, locations and virtual hosts that contain web content.

**Rationale:**

Either the `Allow` or `Require` directives may be used within a directory, a location or other context to allow appropriate access. Access may be allowed to all, or to specific networks, or hosts, or users as appropriate. The `Allow/Deny/Order` directives are deprecated and should be replaced by the `Require` directive. It is also recommended that either the `Allow` directive or the `Require` directive be used, but not both in the same context.

**Audit:**

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find all `<Directory>` elements.
2. Ensure that either one of the following two methods are configured:

**Use the deprecated `Order/Deny/Allow` method:**

1. Ensure there is a single `Order` directive with the value of `Deny,Allow` for each.
2. Ensure the `Allow` and `Deny` directives, have values that are appropriate for the purposes of the directory.

**Use the `Require` method:**

1. Ensure that the Order/Deny/Allow directives are NOT used for the directory.
2. Ensure the Require directives have values that are appropriate for the purposes of the directory.

The following command may be useful to extract <Directory> and <Location> elements and Allow directives from the Apache configuration files.

```
# perl -ne 'print if /^ *<Directory */i .. //<\\Directory/i'
$APACHE_PREFIX/conf/httpd.conf $APACHE_PREFIX/conf.d/*.conf
# perl -ne 'print if /^ *<Location */i .. //<\\Location/i'
$APACHE_PREFIX/conf/httpd.conf $APACHE_PREFIX/conf.d/*.conf
# grep -i -C 6 -i 'Allow[[:space:]]from' $APACHE_PREFIX/conf/httpd.conf
$APACHE_PREFIX/conf.d/*.conf
```

### Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (httpd.conf and any included configuration files) to find all <Directory> and <Location> elements. There should be one for the document root and any special purpose directories or locations. There are likely to be other access control directives in other contexts, such as virtual hosts or special elements like <Proxy>.
2. Include the appropriate Require directives, with values that are appropriate for the purposes of the directory.

The configurations below are just a few possible examples.

```
<Directory "/var/www/html/">
    Require ip 192.169.
</Directory>
```

```
<Directory "/var/www/html/">
    Require all granted
</Directory>
```

```
<Location /usage>
    Require local
</Location>
<Location /portal>
    Require valid-user
</Location>
```

### Default Value:

The following is the default Web root directory configuration:

```
<Directory "/usr/local/apache2/htdocs">
    . . .
    Require all granted
    . . .
</Directory>
```

## References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#directory>
2. [http://httpd.apache.org/docs/2.4/mod/mod\\_authz\\_host.html](http://httpd.apache.org/docs/2.4/mod/mod_authz_host.html)
3. [http://httpd.apache.org/docs/2.4/mod/mod\\_authz\\_core.html](http://httpd.apache.org/docs/2.4/mod/mod_authz_core.html)
4. [http://httpd.apache.org/docs/2.4/mod/mod\\_access\\_compat.html](http://httpd.apache.org/docs/2.4/mod/mod_access_compat.html)

### 1.4.3 Restrict Override for the OS Root Directory (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache `AllowOverride` directive and the new `AllowOverrideList` directive allow for `.htaccess` files to be used to override much of the configuration, including authentication, handling of document types, auto generated indexes, access control, and options. When the server finds an `.htaccess` file (as specified by `AccessFileName`) it needs to know which directives declared in that file can override earlier access information. When this directive is set to `None`, then `.htaccess` files are completely ignored. In this case, the server will not even attempt to read `.htaccess` files in the filesystem. When this directive is set to `All`, then any directive which has the `.htaccess` Context is allowed in `.htaccess` files.

#### Rationale:

While the functionality of `htaccess` files is sometimes convenient, usage decentralizes the access controls and increases the risk of configurations being changed or viewed inappropriately by an unintended or rogue `.htaccess` file. Consider also that some of the more common vulnerabilities in web servers and web applications allow the web files to be viewed or to be modified, then it is wise to keep the configuration out of the web server from being placed in `.htaccess` files.

## Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (httpd.conf and any included configuration files) to find a root element.
2. Ensure there is a single AllowOverride directive with the value of None.
3. Ensure there are no AllowOverrideList directives present.

The following may be useful for extracting root directory elements from the Apache configuration for auditing.

```
$ perl -ne 'print if /^ *<Directory *\\/i .. /<\\/Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

## Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (httpd.conf and any included configuration files) to find a root <Directory> element.
2. Remove any AllowOverrideList directives found.
3. Add a single AllowOverride directive if there is none.
4. Set the value for AllowOverride to None.

```
<Directory />
. . .
    AllowOverride None
. . .
</Directory>
```

## Default Value:

The following is the default root directory configuration:

```
<Directory />
. . .
    AllowOverride None
. . .
</Directory>
```

## References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverride>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverridelist>

### 1.4.4 Restrict Override for All Directories (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache `AllowOverride` directive and the new `AllowOverrideList` directive allow for `.htaccess` files to be used to override much of the configuration, including authentication, handling of document types, auto generated indexes, access control, and options. When the server finds an `.htaccess` file (as specified by `AccessFileName`) it needs to know which directives declared in that file can override earlier access information. When this directive is set to `None`, then `.htaccess` files are completely ignored. In this case, the server will not even attempt to read `.htaccess` files in the filesystem. When this directive is set to `All`, then any directive which has the `.htaccess` context is allowed in `.htaccess` files.

#### Rationale:

`.htaccess` files decentralizes access control and increases the risk of server configuration being changed inappropriately.

#### Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find any `AllowOverride` directives.
2. Ensure there the value for `AllowOverride` is `None`.

```
grep -i AllowOverride $APACHE_PREFIX/conf/httpd.conf
```

3. Ensure there are no `AllowOverrideList` directives present.

#### Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find `AllowOverride` directives.
2. Set the value for all `AllowOverride` directives to `None`.



```
. . .  
AllowOverride None  
. . .
```

3. Remove any `AllowOverrideList` directives found.

## References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverride>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#allowoverridelist>

## 1.5 Minimize Features, Content and Options

Recommendations in this section intend to reduce the effective attack surface of Apache HTTP server.

### 1.5.1 Restrict Options for the OS Root Directory (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache `Options` directive allows for specific configuration of options, including execution of CGI, following symbolic links, server side includes, and content negotiation.

#### Rationale:

The `Options` directive for the root OS level is used to create a default minimal options policy that allows only the minimal options at the root directory level. Then for specific web sites or portions of the web site, options may be enabled as needed and appropriate. No options should be enabled and the value for the `Options` directive should be `None`.

#### Audit:

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Ensure there is a single `Options` directive with the value of `None`.

The following may be useful for extracting root directory elements from the Apache configuration for auditing.

```
perl -ne 'print if /^ *<Directory */i .. /<\/Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

## Remediation:

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find a root `<Directory>` element.
2. Add a single `Options` directive if there is none.
3. Set the value for `Options` to `None`.

```
<Directory>
. . .
Options None
. . .
</Directory>
```

## Default Value:

The default value for the root directory's `Options` directive is `Indexes FollowSymLinks`.

## References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#options>

## 1.5.2 Restrict Options for the Web Root Directory (Scored)

### Profile Applicability:

- Level 1

### Description:

The Apache `Options` directive allows for specific configuration of options, including:

- Execution of CGI
- Following symbolic links
- Server side includes
- Content negotiation

### Rationale:

The `Options` directive at the web root or document root level also needs to be restricted to the minimal options required. A setting of `None` is highly recommended, however it is

recognized that at this level content negotiation may be needed if multiple languages are supported. No other options should be enabled.

### **Audit:**

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find the document root `<Directory>` elements.
2. Ensure there is a single `Options` directive with the value of `None` or `Multiviews`.

The following may be useful in extracting directory elements from the Apache configuration for auditing.

```
perl -ne 'print if /^ *<Directory */i .. /<\/Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

### **Remediation:**

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find the document root `<Directory>` element.
2. Add or modify any existing `Options` directive to have a value of `None` or `Multiviews`, if multiviews are needed.

```
<Directory "/usr/local/apache2/htdocs">
    . . .
    Options None
    . . .
</Directory>
```

### **Default Value:**

The default value for the web root directory's `Options` directive is `FollowSymLinks`.

### **References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#options>

## **1.5.3 Minimize Options for Other Directories (Scored)**

### **Profile Applicability:**

- Level 1

### **Description:**

The Apache `Options` directive allows for specific configuration of options, including execution of CGI, following symbolic links, server side includes, and content negotiation.

### **Rationale:**

Likewise the options for other directories and hosts needs to be restricted to the minimal options required. A setting of `None` is recommended, however it is recognized that other options may be needed in some cases:

- `Multiviews` - Is appropriate if content negotiation is required, such as when multiple language are supported.
- `ExecCGI` - Is only appropriate for special directories dedicated to executable content such as a `cgi-bin/` directory. That way you will know what is executed on the server. It is possible to enable CGI script execution based on file extension or permission settings, however this makes script control and management almost impossible as developers may install scripts without your knowledge. This may become a factor in a hosting environment.
- `FollowSymLinks` & `SymLinksIfOwnerMatch` - The following of symbolic links is not recommended and should be disabled if possible. The usage of symbolic links opens up additional risk for possible attacks that may use inappropriate symbolic links to access content outside of the document root of the web server. Also consider that it could be combined with a vulnerability that allowed an attacker or insider to create an inappropriate link. The option `SymLinksIfOwnerMatch` is much safer in that the ownership must match in order for the link to be used, however keep in mind there is additional overhead created by requiring Apache to check the ownership.
- `Includes` & `IncludesNOEXEC` - The `IncludesNOEXEC` option should only be needed when server side includes are required. The full `Includes` option should not be used as it also allows execution of arbitrary shell commands. See Apache Mod Include for details [http://httpd.apache.org/docs/2.4/mod/mod\\_include.html](http://httpd.apache.org/docs/2.4/mod/mod_include.html)
- `Indexes` - The `Indexes` option causes automatic generation of indexes, if the default index page is missing, and should be disabled unless required.

### **Audit:**

Perform the following to determine if the recommended state is implemented:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find the all `Directory` elements.
2. Ensure that the `Options` directives do not enable `Includes`.

The following may be useful for extracting `Directory` elements from the Apache configuration for auditing.

```
perl -ne 'print if /^ *<Directory */i .. /<\Directory/i'
$APACHE_PREFIX/conf/httpd.conf
```

or

```
grep -i -A 12 '<Directory[[:space:]]' $APACHE_PREFIX/conf/httpd.conf
```

### **Remediation:**

Perform the following to implement the recommended state:

1. Search the Apache configuration files (`httpd.conf` and any included configuration files) to find all `<Directory>` elements.
2. Add or modify any existing `Options` directive to NOT have a value of `Includes`. Other options may be set if necessary and appropriate as described above.

### **References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#options>

## ***1.5.4 Remove Default HTML Content (Scored)***

### **Profile Applicability:**

- Level 1

### **Description:**

Apache installations have default content that is not needed or appropriate for production use. The primary function for these sample content is to provide a default web site, provide user manuals or to demonstrate special features of the web server. All content that is not needed should be removed.

### **Rationale:**

Historically these sample content and features have been remotely exploited and can provide different levels of access to the server. In the Microsoft arena, Code Red exploited a problem with the index service provided by the Internet Information Service. Usually these routines are not written for production use and consequently little thought was given to security in their development.

### **Audit:**

Perform the following to determine if the recommended state is implemented:

1. Verify the document root directory and the configuration files do not provide for default index.html or welcome page,
2. Ensure the Apache User Manual content is not installed by checking the configuration files for manual location directives.
3. Verify the Apache configuration files do not have the Server Status handler configured.
4. Verify that the Server Information handler is not configured.
5. Verify that any other handler configurations such as `perl-status` is not enabled.

## Remediation:

Review all pre-installed content and remove content which is not required. In particular look for the unnecessary content which may be found in the document root directory, a configuration directory such as `conf/extra` directory, or as a Unix/Linux package

1. Remove the default index.html or welcome page, if it is a separate package or comment out the configuration if it is part of main Apache `httpd` package such as it is on Red Hat Linux. Removing a file such as the `welcome.conf` shown below is not recommended as it may get replaced if the package is updated.

```
#
# This configuration file enables the default "Welcome"
# page if there is no default index page present for
# the root URL. To disable the Welcome page, comment
# out all the lines below.
#
##<LocationMatch "^/+$">
##     Options -Indexes
##     ErrorDocument 403 /error/noindex.html
##</LocationMatch>
```

2. Remove the Apache user manual content or comment out configurations referencing the manual

```
# yum erase httpd-manual
```

3. Remove or comment out any Server Status handler configuration.

```
#
# Allow server status reports generated by mod_status,
# with the URL of http://servername/server-status
# Change the ".example.com" to match your domain to enable.
#
##<Location /server-status>
##     SetHandler server-status
##     Order deny,allow
##     Deny from all
##     Allow from .example.com
##</Location>
```

4. Remove or comment out any Server Information handler configuration.

```
#
# Allow remote server configuration reports, with the URL of
# http://servername/server-info (requires that mod_info.c be loaded).
# Change the ".example.com" to match your domain to enable.
#
##<Location /server-info>
##     SetHandler server-info
##     Order deny,allow
##     Deny from all
##     Allow from .example.com
##</Location>
```

5. Remove or comment out any other handler configuration such as perl-status.

```
# This will allow remote server configuration reports, with the URL of
# http://servername/perl-status
# Change the ".example.com" to match your domain to enable.
#
##<Location /perl-status>
##     SetHandler perl-script
##     PerlResponseHandler Apache2::Status
##     Order deny,allow
##     Deny from all
##     Allow from .example.com
##</Location>
```

### Default Value:

The default source build provides extra content available in the `/usr/local/apache2/conf/extra/` directory, but the configuration of most of the extra content is commented out by default. **In particular, the include of `conf/extra/proxy-html.conf` is not commented out in the `httpd.conf`.**

```
# Server-pool management (MPM specific)
#Include conf/extra/httpd-mpm.conf
# Multi-language error messages
#Include conf/extra/httpd-multilang-errordoc.conf
# Fancy directory listings
#Include conf/extra/httpd-autoindex.conf
# Language settings
#Include conf/extra/httpd-languages.conf
# User home directories
#Include conf/extra/httpd-userdir.conf
# Real-time info on requests and configuration
#Include conf/extra/httpd-info.conf
# Virtual hosts
#Include conf/extra/httpd-vhosts.conf
# Local access to the Apache HTTP Server Manual
#Include conf/extra/httpd-manual.conf
# Distributed authoring and versioning (WebDAV)
#Include conf/extra/httpd-dav.conf
# Various default settings
#Include conf/extra/httpd-default.conf
# Configure mod_proxy_html to understand HTML4/XHTML1
```

```
<IfModule proxy_html_module>
Include conf/extra/proxy-html.conf
</IfModule>
# Secure (SSL/TLS) connections
#Include conf/extra/httpd-ssl.conf
```

Also the only other default content is a minimal barebones `index.html` in the document root which contains.

```
<html><body><h1>It works!</h1></body></html>
```

### 1.5.5 Remove Default CGI Content `printenv` (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Most Web Servers, including Apache installations have default CGI content which is not needed or appropriate for production use. The primary function for these sample programs is to demonstrate the capabilities of the web server. One common default CGI content for Apache installations is the script `printenv`. This script will print back to the requester all of the CGI environment variables which includes many server configuration details and system paths.

#### Rationale:

CGI programs have a long history of security bugs and problems associated with improperly accepting user-input. Since these programs are often targets of attackers, we need to make sure that there are no unnecessary CGI programs that could potentially be used for malicious purposes. Usually these programs are not written for production use and consequently little thought was given to security in their development. The `printenv` script in particular will disclose inappropriate information about the web server including directory paths and detailed version and configuration information.

#### Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate `cgi-bin` files and directories enabled in the Apache configuration via `Script`, `ScriptAlias` or `ScriptAliasMatch` or `ScriptInterpreterSource` directives.
2. Ensure the `printenv` CGI is not installed in any configured `cgi-bin` directory.

#### Remediation:



Perform the following to implement the recommended state:

1. Locate cgi-bin files and directories enabled in the Apache configuration via `Script`, `ScriptAlias`, `ScriptAliasMatch`, or `ScriptInterpreterSource` directives.
2. Remove the `printenv` default CGI in cgi-bin directory if it is installed.

```
# rm $APACHE_PREFIX/cgi-bin/printenv
```

### Default Value:

The default source installation includes the `printenv` script. However, this script is not executable by default.

### 1.5.6 Remove Default CGI Content *test-cgi* (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Most Web Servers, including Apache installations have default CGI content which is not needed or appropriate for production use. The primary function for these sample programs is to demonstrate the capabilities of the web server. A common default CGI content for Apache installations is the script `test-cgi`. This script will print back to the requester CGI environment variables which includes many server configuration details.

#### Rationale:

CGI programs have a long history of security bugs and problems associated with improperly accepting user-input. Since these programs are often targets of attackers, we need to make sure that there are no unnecessary CGI programs that could potentially be used for malicious purposes. Usually these programs are not written for production use and consequently little thought was given to security in their development. The `test-cgi` script in particular will disclose inappropriate information about the web server including directory paths and detailed version and configuration information.

#### Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate cgi-bin files and directories enabled in the Apache configuration via `Script`, `ScriptAlias` or `ScriptAliasMatch` other `ScriptInterpreterSource` directives.

2. Ensure the `test-cgi` script is not installed in any configured `cgi-bin` directory.

**Remediation:**

Perform the following to implement the recommended state:

1. Locate `cgi-bin` files and directories enabled in the Apache configuration via `Script`, `ScriptAlias`, `ScriptAliasMatch`, or `ScriptInterpreterSource` directives.
2. Remove the `test-cgi` default CGI in `cgi-bin` directory if it is installed.

```
# rm $APACHE_PREFIX/cgi-bin/test-cgi
```

**Default Value:**

The default source installation includes the `test-cgi` script. However, this script is not executable by default.

### *1.5.7 Limit HTTP Request Methods (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

Use the Apache `<LimitExcept>` directive to restrict unnecessary HTTP request methods of the web server to only accept and process the `GET`, `HEAD`, `POST` and `OPTIONS` HTTP request methods.

**Rationale:**

The HTTP 1.1 protocol supports several request methods which are rarely used and potentially high risk. For example, methods such as `PUT` and `DELETE` are rarely used and should be disabled in keeping with the primary security principal of minimize features and options. Also since the usage of these methods is typically to modify resources on the web server, they should be explicitly disallowed. For normal web server operation, you will typically need to allow only the `GET`, `HEAD` and `POST` request methods. This will allow for downloading of web pages and submitting information to web forms. The `OPTIONS` request method will also be allowed as it used to request which HTTP request methods are allowed. Unfortunately the Apache `<LimitExcept>` directive does not deny the `TRACE` request method. The `TRACE` request method will be disallowed in another benchmark recommendation with the `TraceEnable` directive.

**Audit:**

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Search for all `<Directory>` directives other than the one on the OS root directory.
3. Ensure that either one of the following two methods are configured:

**Using the deprecated Order/Deny/Allow method:**

1. Ensure that group contains a single `Order` directive within the `<Directory>` directive with a value of `deny, allow`
2. Verify the `<LimitExcept>` directive does not include any HTTP methods other than GET, POST, and OPTIONS. (It may contain fewer methods.)

**Using the Require method:**

1. Ensure there is a single `Require` directive with the value of `all denied`
2. Ensure there are no `Allow` or `Deny` directives in the root element.

**Remediation:**

Perform the following to implement the recommended state:

1. Locate the Apache configuration files and included configuration files.
2. Search for the directive on the document root directory such as:

```
<Directory "/usr/local/apache2/htdocs">
    . . .
</Directory>
```

3. Add a directive as shown below within the group of document root directives.

```
# Limit HTTP methods to standard methods. Note: Does not limit TRACE
<LimitExcept GET POST OPTIONS>
    Require all denied
</LimitExcept>
```

4. Search for other directives in the Apache configuration files other than the OS root directory, and add the same directives to each. It is very important to understand that the directives are based on the OS file system hierarchy as accessed by Apache and not the hierarchy of the locations within web site URLs.

```
<Directory "/usr/local/apache2/cgi-bin">
    . . .
    # Limit HTTP methods
    <LimitExcept GET POST OPTIONS>
        Require all denied
```

```
</LimitExcept>  
</Directory>
```

**Default Value:**

No Limits on HTTP methods.

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitexcept>
2. <http://www.ietf.org/rfc/rfc2616.txt>

### *1.5.8 Disable HTTP TRACE Method (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

Use the Apache `TraceEnable` directive to disable the HTTP `TRACE` request method.

**Rationale:**

The HTTP 1.1 protocol requires support for the `TRACE` request method which reflects the request back as a response and was intended for diagnostics purposes. The `TRACE` method is not needed and is easily subjected to abuse and should be disabled.

**Audit:**

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Verify there is a single `TraceEnable` directive configured with a value of `off`.

**Remediation:**

Perform the following to implement the recommended state:

1. Locate the main Apache configuration file such as `httpd.conf`.
2. Add a `TraceEnable` directive to the server level configuration with a value of `off`. Server level configuration is the top level configuration, not nested within any other directives like `<Directory>` or `<Location>`.

**Default Value:**

The TRACE method is enabled.

#### References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#traceenable>
2. <http://www.ietf.org/rfc/rfc2616.txt>

### 1.5.9 Restrict HTTP Protocol Versions (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The Apache modules `mod_rewrite` or `mod_security` can be used to disallow old and invalid HTTP protocols versions. The HTTP version 1.1 RFC is dated June 1999, and has been supported by Apache since version 1.2. It should no longer be necessary to allow ancient versions of HTTP such as 1.0 and prior.

#### Rationale:

Many malicious automated programs, vulnerability scanners and fingerprinting tools will send abnormal HTTP protocol versions to see how the web server responds. These requests are usually part of the attacker's enumeration process and therefore it is important that we respond by denying these requests.

#### Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Verify there is a rewrite condition within the global server context that disallows requests that do not include the HTTP/1.1 header as shown below .

```
RewriteEngine On
RewriteCond %{THE_REQUEST} !HTTP/1\..1$
RewriteRule .* - [F]
```

3. Verify the following directives are included in each section so that the main server settings will be inherited.

```
RewriteEngine On
RewriteOptions Inherit
```

#### Remediation:

Perform the following to implement the recommended state:

1. Load the `mod_rewrite` module for Apache by doing either one of the following:
  1. Build Apache with `mod_rewrite` statically loaded during the build, by adding the `--enable-rewrite` option to the `./configure` script.

```
./configure --enable-rewrite
```

2. Or dynamically loading the module with the `LoadModule` directive in the `httpd.conf` configuration file.

```
LoadModule rewrite_module modules/mod_rewrite.so
```

2. Locate the main Apache configuration file such as `httpd.conf` and add the following rewrite condition to match HTTP/1.1 and the rewrite rule to the global server level configuration to disallow other protocol versions.

```
RewriteEngine On
RewriteCond %{THE_REQUEST} !HTTP/1\..1$
RewriteRule .* - [F]
```

3. By default, `mod_rewrite` configuration settings from the main server context are not inherited by virtual hosts. Therefore it is also necessary to add the following directives in each section to inherit the main server settings.

```
RewriteEngine On
RewriteOptions Inherit
```

### Default Value:

The default value for the `RewriteEngine` directive is `off`.

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_rewrite.html](http://httpd.apache.org/docs/2.4/mod/mod_rewrite.html)

## 1.5.10 Restrict Access to `.ht*` files (Scored)

### Profile Applicability:

- Level 1

### Description:

Restrict access to any files beginning with `.ht` using the `FilesMatch` directive.

**Rationale:**

The default name for access filename which allows files in web directories to override the Apache configuration is `.htaccess`. The usage of access files should not be allowed, but as a defense in depth a `FilesMatch` directive is recommended to prevent web clients from viewing those files in case they are created. Also a common name for web password and group files is `.htpasswd` and `.htgroup`. Neither of these files should be placed in the document root, but in the event they are, the `FilesMatch` directive can be used to prevent them from being viewed by web clients.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify that a `FilesMatch` directive similar to the one below is present in the apache configuration and not commented out, The deprecated `Deny from All` directive may be used instead of the `Require` directive.

```
<FilesMatch "^\.ht">  
    Require all denied  
</FilesMatch>
```

**Remediation:**

Perform the following to implement the recommended state:

1. Add or modify the following lines in the apache configuration at the server configuration level.

```
<FilesMatch "^\.ht">  
    Require all denied  
</FilesMatch>
```

**Default Value:**

`.ht*` files are not accessible.

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#filesmatch>

### *1.5.11 Restrict File Extensions (Scored)*

**Profile Applicability:**

- Level 2

## Description:

Restrict access to inappropriate file extensions that are not expected to be a legitimate part of web sites using the `FilesMatch` directive.

## Rationale:

There are many files that are often left within the web server document root that could provide an attacker with sensitive information. Most often these files are mistakenly left behind after installation, trouble-shooting, or backing up files before editing. Regardless of the reason for their creation, these files can still be served by Apache even when there is no hyperlink pointing to them. The web administrators should use the `FilesMatch` directive to restrict access to only those file extensions that are appropriate for the web server. Rather than create a list of potentially inappropriate file extensions such as `.bak`, `.config`, `.old`, etc, it is recommended instead that a white list of the appropriate and expected file extensions for the web server be created, reviewed and restricted with a `FilesMatch` directive.

## Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify that the `FilesMatch` directive that denies access to all files is present as shown in step 3 of the remediation.
2. Verify that there is another `FilesMatch` directive similar to the one in step 4 of the remediation, with an expression that matches the approved file extensions.

## Remediation:

Perform the following to implement the recommended state:

1. Compile a list of existing file extension on the web server. The following `find/awk` command may be useful, but is likely to need some customization according to the appropriate webroot directories for your web server. Please note that the `find` command skips over any files without a dot (.) in the file name, as these are not expected to be appropriate web content.

```
find */htdocs -type f -name '*.*' | awk -F. '{print $NF }' | sort -u
```

2. Review the list of existing file extensions, for appropriate content for the web server, remove those that are inappropriate and add any additional file extensions expected to be added to the web server in the near future.
3. Add the `FilesMatch` directive below which denies access to all files by default.



```
# Block all files by default, unless specifically allowed.
<FilesMatch "^.*$">
    Require all denied
</FilesMatch>
```

4. Add another a `FilesMatch` directive that allows access to those file extensions specifically allowed from the review process in step 2. An example `FilesMatch` directive is below. The file extensions in the regular expression should match your approved list, and not necessarily the expression below.

```
# Allow files with specifically approved file extensions
# Such as (css, htm; html; js; pdf; txt; xml; xsl; ...),
# images (gif; ico; jpeg; jpg; png; ...), multimedia
<FilesMatch "^.*\.(css|html?|js|pdf|txt|xml|xsl|gif|ico|jpe?g|png)$">
    Require all granted
</FilesMatch>
```

### Default Value:

There are no restrictions on file extensions in the default configuration.

### References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#filesmatch>

## 1.5.12 Deny IP Address Based Requests (Scored)

### Profile Applicability:

- Level 2

### Description:

The Apache module `mod_rewrite` can be used to disallow access for requests that use an IP address instead of a host name for the URL. Most normal access to the website from browsers and automated software will use a host name, and will therefore include the host name in the HTTP HOST header.

### Rationale:

A common malware propagation and automated network scanning technique is to use IP addresses rather than host names for web requests, since it's much simpler to automate. By denying IP based web requests, these automated techniques will be denied access to the website. Of course malicious web scanning techniques continue to evolve, and many are now using hostnames, however denying access to the IP based requests is still a worthwhile defense.

## Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Verify there is a rewrite condition within the global server context that disallows IP based requests by requiring a HTTP HOST header similar to the example shown below.

```
RewriteCond %{HTTP_HOST} !^www\.example\.com [NC]
RewriteCond %{REQUEST_URI} !^/error [NC]
RewriteRule ^.(.*) - [L,F]
```

## Remediation:

Perform the following to implement the recommended state:

1. Load the `mod_rewrite` module for Apache by doing either one of the following:
  1. Build Apache with `mod_rewrite` statically loaded during the build, by adding the `--enable-rewrite` option to the `./configure` script.

```
./configure --enable-rewrite
```

2. Or dynamically loading the module with the `LoadModule` directive in the `httpd.conf` configuration file.

```
LoadModule rewrite_module modules/mod_rewrite.so
```

2. Add the `RewriteEngine` directive to the configuration within the global server context with the value of `on` so that the rewrite engine is enabled.

```
RewriteEngine On
```

3. Locate the Apache configuration file such as `httpd.conf` and add the following rewrite condition to match the expected host name of the top server level configuration.

```
RewriteCond %{HTTP_HOST} !^www\.example\.com [NC]
RewriteCond %{REQUEST_URI} !^/error [NC]
RewriteRule ^.(.*) - [L,F]
```

## Default Value:

`RewriteEngine off`

**References:**

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_rewrite.html](http://httpd.apache.org/docs/2.4/mod/mod_rewrite.html)

### 1.5.13 Restrict Listen Directive (Scored)

**Profile Applicability:**

- Level 2

**Description:**

The Apache `Listen` directive specifies the IP addresses and port numbers the Apache web server will listen for requests. Rather than be unrestricted to listen on all IP addresses available to the system, the specific IP address or addresses intended should be explicitly specified. Specifically a `Listen` directive with no IP address specified, or with an IP address of zeros should not be used.

**Rationale:**

Having multiple interfaces on web servers is fairly common, and without explicit `Listen` directives, the web server is likely to be listening on an inappropriate IP address / interface that was not intended for the web server. Single homed system with a single IP addressed are also required to have an explicit IP address in the `Listen` directive, in case additional interfaces are added to the system at a later date.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify that no `Listen` directives are in the Apache configuration file with no IP address specified, or with an IP address of all zero's.

**Remediation:**

Perform the following to implement the recommended state:

1. Find any `Listen` directives in the Apache configuration file with no IP address specified, or with an IP address of all zeros similar to the examples below. Keep in mind there may be both IPv4 and IPv6 addresses on the system.

```
Listen 80
Listen 0.0.0.0:80
Listen [::ffff:0.0.0.0]:80
```

2. Modify the `Listen` directives in the Apache configuration file to have explicit IP addresses according to the intended usage. Multiple `Listen` directives may be specified for each IP address & Port.

```
Listen 10.1.2.3:80
Listen 192.168.4.5:80
Listen [2001:db8::a00:20ff:fea7:ccea]:80
```

**Default Value:**

`Listen 80`

**References:**

1. [http://httpd.apache.org/docs/2.4/mod/mpm\\_common.html#listen](http://httpd.apache.org/docs/2.4/mod/mpm_common.html#listen)

### *1.5.14 Restrict Browser Frame Options (Scored)*

**Profile Applicability:**

- Level 2

**Description:**

The `Header` directive allows server HTTP response headers to be added, replaced or merged. We will use the directive to add an server HTTP response header to tell browsers to restrict all of the web pages from being framed by other web sites.

**Rationale:**

Using iframes and regular web frames to embed malicious content along with expected web content has been a favored attack vector for attacking web clients for a long time. This can happen when the attacker lures the victim to a malicious web site, which using frames to include the expected content from the legitimate site. The attack can also be performed via XSS (either reflected, DOM or stored XSS) to add the malicious content to the legitimate web site.

To combat this vector, an HTTP Response header, `X-Frame-Options`, has been introduced that allows a server to specify whether a web page may be loaded in any frame (`DENY`) or those frames that share the pages origin (`SAMEORIGIN`).

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Ensure the previous line is present in the Apache configuration and not commented out :

```
# grep -i X-Frame-Options $APACHE_PREFIX/conf/httpd.conf
```

### Remediation:

Perform the following to implement the recommended state:

1. Add or modify the Header directive for the X-Frame-Options header in the Apache configuration to have the condition always, an action of append and a value of SAMEORIGIN or DENY, as shown below.

```
Header always append X-Frame-Options SAMEORIGIN
```

### Default Value:

The X-Frame-Options HTTP response header is not generated by default.

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_headers.html#header](http://httpd.apache.org/docs/2.4/mod/mod_headers.html#header)
2. [https://developer.mozilla.org/en/The\\_X-FRAME-OPTIONS\\_response\\_header](https://developer.mozilla.org/en/The_X-FRAME-OPTIONS_response_header)
3. <http://blogs.msdn.com/b/ie/archive/2009/01/27/ie8-security-part-vii-clickjacking-defenses.aspx>

## 1.6 Operations - Logging, Monitoring and Maintenance

Operational procedures of logging, monitoring and maintenance are vital to protecting your web servers as well as the rest of the infrastructure.

### 1.6.1 Configure the Error Log (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The LogLevel directive is used to configure the severity level for the error logs. While the ErrorLog directive configures the error log file name. The log level values are the standard syslog levels of emerg, alert, crit, error, warn, notice, info and debug. The recommended level is notice, so that all errors from the emerg level through notice level will be logged.

#### Rationale:

The server error logs are invaluable because they can also be used to spot any potential problems before they become serious. Most importantly, they can be used to watch for anomalous behavior such as a lot of "not found" or "unauthorized" errors may be an indication that an attack is pending or has occurred.

### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `LogLevel` in the Apache server configuration has a value of `notice` or lower. Note that it is also compliant to have a value of `info` or `debug` if there is a need for a more verbose log and the storage and monitoring processes are capable of handling the extra load. The recommended value is `notice`.
2. Verify the `ErrorLog` directive is configured to an appropriate log file or syslog facility.
3. Verify there is a similar `ErrorLog` directive for each virtual host configured if the virtual host will have different people responsible for the web site.

### **Remediation:**

Perform the following to implement the recommended state:

1. Add or modify the `LogLevel` in the Apache configuration to have a value of `notice` or lower. Note that it is compliant to have a value of `info` or `debug` if there is a need for a more verbose log and the storage and monitoring processes are capable of handling the extra load. The recommended value is `notice`.

```
LogLevel notice
```

2. Add an `ErrorLog` directive if not already configured. The file path may be relative or absolute, or the logs may be configured to be sent to a syslog server.

```
ErrorLog "logs/error_log"
```

3. Add a similar `ErrorLog` directive for each virtual host configured if the virtual host will have different people responsible for the web site. Each responsible individual or organization needs access to their own web logs, and needs the skills/training/tools for monitoring the logs.

### **Default Value:**

The following is the default configuration:

```
LogLevel warn
ErrorLog "logs/error_log"
```

**References:**

1. <http://httpd.apache.org/docs/2.4/logs.html>
2. <http://httpd.apache.org/docs/2.4/mod/core.html#loglevel>
3. <http://httpd.apache.org/docs/2.4/mod/core.html#errorlog>

### *1.6.2 Configure the Access Log (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

The `LogFormat` directive defines the format and information to be included in the access log entries. The `CustomLog` directive specifies the log file, syslog facility or piped logging utility.

**Rationale:**

The server access logs are also invaluable for a variety of reasons. They can be used to determine what resources are being used most. Most importantly, they can be used to investigate anomalous behavior that may be an indication that an attack is pending or has occurred. If the server only logs errors, and does not log successful access, then it is very difficult to investigate incidents. You may see that the errors stop, and wonder if the attacker gave up, or was the attack successful.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `LogFormat` directive in the Apache server configuration has the recommended information parameters.
2. Verify the `CustomLog` directive is configured to an appropriate log file, syslog facility, or piped logging utility and uses the combined format.
3. Verify there is a similar `CustomLog` directives for each virtual host configured if the virtual host will have different people responsible for the web site.

**Remediation:**

Perform the following to implement the recommended state:

1. Add or modify the `LogFormat` directives in the Apache configuration to use the standard and recommended combined format show as shown below.

```
LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-agent}i\""
combined
```

2. Add or modify the `CustomLog` directives in the Apache configuration to use the combined format with an appropriate log file, syslog facility or piped logging utility.

```
CustomLog log/access_log combined
```

3. Add a similar `CustomLog` directives for each virtual host configured if the virtual host will have different people responsible for the web site. Each responsible individual or organization needs access to their own web logs, and needs the skills/training/tools for monitor the logs.

### Default Value:

The following are the default log configuration:

```
LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-Agent}i\"" combined
LogFormat "%h %l %u %t \"%r\" %>s %b" common
CustomLog "logs/access_log" common
```

## 1.6.3 Establish Log Monitoring (Not Scored)

### Profile Applicability:

- Level 1

### Description:

Collecting the Apache logs is an important start, but there must be a monitoring process that will review the logs for indications of potential attack or abuse. The monitoring process should be at least on a daily process, and more frequently for high risk environment or large installations. Log collection and analysis tools are important to making the monitoring process effective. Some of the most popular and recommended log monitoring tools include:

- LogWatch provides host based log monitoring and is installed by default on many Linux systems,
- Syslog and syslog-ng provides central collection is very popular and recommended for medium and larger installations and would feed into a centralized log monitoring process,



- OSSEC is an open source HIDS which optionally includes log collection and monitoring and is useful for all size organizations.

At a minimum, a processed summary of the web request that resulted in errors (Status codes 400's - 599) should be reviewed daily. Detection of other anomalies like spikes in traffic to specific URL's and/or from individual IP addresses are also desirable, as common attack patterns such as password guessing or attempted blind sql-injection may be detected.

### **Rationale:**

Even with sophisticated tools, log monitoring when done correctly is necessarily one of the more expensive security controls, as it requires human effort in the review process as well as investigating of anomalies and handling of incidents. It is a way too common mistake to underestimate the tremendous value to the organization in proper monitoring, and hence resources for monitoring are not sufficient and/or the log filtering and anomaly detection is turned up to the point where attacks and abuse are not detected. Increases in web application attacks has been one of the primary security trends on this past decade and is expected to continue for the foreseeable future.

### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify that a log collection and monitoring process is implemented and configured to send appropriate reports and alerts to an individual or a team monitoring the logs.
2. All of the Apache logs are configure to be included in the implemented log collection and monitoring process.
3. If possible review the log monitoring and incident response process, to ensure they are assigned to appropriate staff with sufficient training and resources.

### **Remediation:**

Perform the following to implement the recommended state:

1. Decide on host based log monitoring and/or central log collection, and perform either or both of the following:
  1. Install suitable host based log monitoring tools such as LogWatch or OSSEC and configure to send appropriate reports and alerts to an individual or a team monitoring the logs.
  2. Configure Apache to send logs to the syslog daemon and configure syslog to send to a central collection and monitoring system(s).
2. Develop a log monitoring and incident response process and assign appropriate staff with the training and system resources to implement.

**Default Value:**

LogWatch is installed by default and it is configured by default to send email to the local root. However, logwatch will not monitor the log files of the default source build, (`/usr/local/apache2/logs`) unless it is configured. Likewise, OSSEC needs to be configured to know where the Apache logs are found. Syslog is installed by default, but is not configured to send logs to another host.

**References:**

1. <http://www.logwatch.org/>
2. <http://www.ossec.net/>
3. <http://www.balabit.com/network-security/syslog-ng/>

### *1.6.4 Log Storage and Rotation (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

It is important that there is adequate disk space on the partition that will hold all the log files, and that log rotation is configured to retain at least 3 months or 13 weeks if central logging is not used for storage.

**Rationale:**

Keep in mind that the generation of logs is under a potential attacker's control. So do not hold any Apache log files on the root partition of the OS. This could result in a denial of service against your web server host by filling up the root partition and causing the system to crash. For this reason it is recommended that the log files should be stored on a dedicated partition. Likewise consider that attackers sometimes put information into your logs which is intended to attack your log collection or log analysis processing software. So it is important that they are not vulnerable. Investigation of incidents often require access to several months or more of logs, which is why it is important to keep at least 3 months available. Two common log rotation utilities include `rotatelogs(8)` which is bundled with Apache, and `logrotate(8)` commonly bundled on Linux distributions are described in the remediation section.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify the web log rotation configuration matches the Apache configured log files.

2. Verify the rotation period and number of logs to retain is at least 13 weeks or 3 months.
3. For each virtual host configured with its own log files ensure that those log files are also included in a similar log rotation.

## Remediation:

To implement the recommended state do either option a) if using the Linux `logrotate` utility or option b) if using a piped logging utility such as the Apache `rotatelog`s:

### 1. File Logging with Logrotate:

1. Add or modify the web log rotation configuration to match your configured log files in `/etc/logrotate.d/httpd` to be similar to the following.

```
/var/log/httpd/*log {
    missingok
    notifempty
    sharedscripts
    postrotate
        /bin/kill -HUP `cat /var/run/httpd.pid 2>/dev/null` 2> /dev/null ||
    true
    endscript
}
```

2. Modify the rotation period and number of logs to keep so that at least 13 weeks or 3 months of logs are retained. This may be done as the default value for all logs in `/etc/logrotate.conf` or in the web specific log rotation configuration in `/etc/logrotate.d/httpd` to be similar to the following.

```
# rotate log files weekly
weekly
# keep 13 weeks of backlogs
rotate 13
```

3. For each virtual host configured with its own log files ensure that those log files are also included in a similar log rotation.

### 2. Piped Logging:

1. Configure the log rotation interval and log file names to a suitable interval such as daily.

```
CustomLog "|bin/rotatelog -l /var/logs/logfile.%Y.%m.%d 86400" combined
```

2. Ensure the log file naming and any rotation scripts provide for retaining at least 3 months or 13 weeks of log files.
3. For each virtual host configured with its own log files ensure that those log files are also included in a similar log rotation.

**Default Value:**

The following is the default httpd log rotation configuration in `/etc/logrotate.d/httpd`:

```
/var/log/httpd/*log {  
    missingok  
    notifempty  
    sharedscripts  
    postrotate  
        /bin/kill -HUP `cat /var/run/httpd.pid 2>/dev/null` 2> /dev/null || true  
    endscript  
}
```

The default log retention configured in `/etc/logrotate.conf`:

```
# rotate log files weekly  
weekly  
# keep 4 weeks worth of backlogs  
rotate 4
```

### *1.6.5 Monitor Vulnerability Lists (Not Scored)*

**Profile Applicability:**

- Level 1

**Description:**

Subscribe to an appropriate security advisory list.

**Rationale:**

To keep abreast of issues specific to Apache software and the operating system platform, the individuals responsible for security and/or administration of the server should subscribe to a notification service such as those listed below that will alert them to newly discovered security issues.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Identify personnel responsible updating the Apache software.
2. Interview responsible personnel with regard to how they find out about vulnerabilities and security patches available.

**Remediation:**

Subscribe to one or more of the following to stay abreast of new vulnerabilities.

1. Apache httpd mailing list - <http://httpd.apache.org/lists.html> The main announcement mailing list is going to tell you whenever a new release of Apache comes out and about security fixes but doesn't usually contain much information about the actual issues. Serious vulnerabilities tend to get their own advisories written up, which also get posted to the announce list.
2. OS Vendor security lists such as Red Hat  
<https://www.redhat.com/mailman/listinfo/enterprise-watch-list>
3. CERT CC <http://www.cert.org/> The Computer Emergency Response Team Co-ordination Centre monitors security incidents - mostly focused on those that have a significant impact. CERT advisories are well researched and a good source of information, especially when CERT was notified of an issue in advance. Not all issues are notified to CERT so it cannot be relied upon as a sole source of information, and since CERT deal with issues across all products and operating systems they are not always able to give immediate updates. Even so, it is well worth subscribing to their alert lists.
4. Security service provider lists - Many security service providers now provide security notifications which can be customized to report only on software and systems that you actual deploy. If you already subscribe to one of these, then be sure Apache is included in the customization.

### *1.6.6 Apply Applicable Patches (Scored)*

#### **Profile Applicability:**

- Level 1

#### **Description:**

Apply available Apache patches within 1 month of availability.

#### **Rationale:**

Obviously knowing about newly discovered vulnerabilities is only part of the solution; there needs to be a process in place where patches are tested and installed. These patches fix diverse problems, including security issues. It is recommended to use the Apache packages and updates provide by the your Linux platform vendor rather than building from source when possible, in order to minimize the disruption and the work of keeping the software up-to-date.

#### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. When Apache was built from source:

1. Check the Apache web site for latest versions, date of releases and any security patches.  
[http://httpd.apache.org/security/vulnerabilities\\_24.html](http://httpd.apache.org/security/vulnerabilities_24.html) Apache patches are available <http://www.apache.org/dist/httpd/patches>
2. If newer versions with security patches more than 1 month old and are not installed, then the installation is not sufficiently up-to-date.
2. When using platform packages
3. Check for vendor supplied updates from the vendor web site.
4. If newer versions with security patches more than 1 month old are not installed, then the installation is not sufficiently up-to-date.

### **Remediation:**

Update to the latest Apache release available according to either of the following:

1. When building from source:
  1. Read release notes and related security patch information
  2. Download latest source and any dependent modules such as `mod_security`.
  3. Build new Apache software according to your build process with the same configuration options.
  4. Install and Test the new software according to your organizations testing process.
  5. Move to production according to your organizations deployment process.
2. When using platform packages
  1. Read release notes and related security patch information
  2. Download and install latest available Apache package and any dependent software.
  3. Test the new software according to your organizations testing process.
  4. Move to production according to your organizations deployment process.

### **References:**

1. [http://httpd.apache.org/security/vulnerabilities\\_24.html](http://httpd.apache.org/security/vulnerabilities_24.html)

## ***1.7 SSL/TLS Configuration***

Recommendations in this section pertain to the configuration of SSL/TLS-related aspects of Apache HTTP server.

### ***1.7.1 Install `mod_ssl` and/or `mod_nss` (Scored)***

#### **Profile Applicability:**

- Level 1

## Description:

Secure Sockets Layer (SSL) was developed by Netscape and turned into an open standard, and was renamed Transport Layer Security (TLS) as part of the process. TLS is important for protecting communication and can provide authentication of the server and even the client. However contrary to vendor claims, implementing SSL does NOT directly make your web server more secure! SSL is used to encrypt traffic and therefore does provide confidentiality of private information and users credentials. Keep in mind, however that just because you have encrypted the data in transit does not mean that the data provided by the client is secure while it is on the server. Also SSL does not protect the web server, as attackers will easily target SSL-Enabled web servers, and the attack will be hidden in the encrypted channel. The `mod_ssl` module is the standard, most used module that implements SSL/TLS for Apache. A newer module found on Red Hat systems can be a compliment or replacement for `mod_ssl`, and provides the same functionality plus additional security services. The `mod_nss` is an Apache module implementation of the Network Security Services (NSS) software from Mozilla, which implements a wide range of cryptographic functions in addition to TLS.

## Rationale:

It is best to plan for SSL/TLS implementation from the beginning of any new web server. As most web servers have some need for SSL/TLS due to:

- Non-public information submitted that should be protected as it's transmitted to the web server.
- Non-public information that is downloaded from the web server.
- Users are going to be authenticated to some portion of the web server
- There is a need to authenticate the web server to ensure users that they have reached the real web server, and have not been phished or redirected to a bogus site.

## Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Ensure the `mod_ssl` and/or `mod_nss` is loaded in the Apache configuration:

```
# httpd -M | egrep 'ssl_module|nss_module'
```

Results should show "Syntax OK" along with either or both of the modules.

## Remediation:

Perform either of the following to implement the recommended state:

1. For Apache installations built from the source, use the option `--with-ssl=` to specify the openssl path, and the `--enable-ssl` configure option to add the SSL modules to the build. The `--with-included-apr` configure option may be necessary if there are conflicts with the platform version. If a new version of Openssl is needed it may be downloaded from <http://www.openssl.org/> See the Apache documentation on building from source <http://httpd.apache.org/docs/2.4/install.html> for details.

```
# ./configure --with-included-apr --with-ssl=$OPENSSL_DIR --enable-ssl
```

2. For installations using OS packages, it is typically just a matter of ensuring the `mod_ssl` package is installed. The `mod_nss` package might also be installed. The following yum commands are suitable for Red Hat Linux.

```
# yum install mod_ssl
```

### Default Value:

SSL is not enabled by default.

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_ssl.html](http://httpd.apache.org/docs/2.4/mod/mod_ssl.html)
2. [http://directory.fedoraproject.org/wiki/Mod\\_nss](http://directory.fedoraproject.org/wiki/Mod_nss)

## 1.7.2 Install a Valid Trusted Certificate (Not Scored)

### Profile Applicability:

- Level 1

### Description:

The default SSL certificate is self-signed and is not trusted. Install a valid certificate signed by a commonly trusted certificate authority. To be valid, the certificate must be:

- Signed by a trusted certificate authority
- Not be expired, and
- Have a common name that matches the host name of the web server, such as `www.example.com`.

### Rationale:

A digital certificate on your server automatically communicates your site's authenticity to visitors' web browsers. If a trusted authority signs your certificate, it confirms for the



visitor they are actually communicating with you, and not with a fraudulent site stealing credit card numbers or personal information.

### Audit:

Perform either or both of the following steps to determine if the recommended state is implemented:

1. OpenSSL can also be used to validate a certificate as a valid trusted certificate, using a trusted bundle of CA certificate. It is important that the CA bundle of certificates be an already validated and trusted file in order for the test to be valid.

```
$ openssl verify -CAfile /etc/pki/tls/certs/ca-bundle.crt -purpose sslserver  
/etc/pki/tls/certs/example.com.crt  
/etc/pki/tls/certs/example.com.crt: OK
```

A specific error message and code will be reported in addition to the OK if the certificate is not valid, For example:

```
error 10 at 0 depth lookup:certificate has expired  
OK
```

2. Testing can also be done by connecting to a running web server. This may be done with your favorite browser, a command line web client or with `openssl s_client`. Of course it is important here as well to be sure of the integrity of the trusted certificate authorities used by the web client. Visit the OWASP testing SSL web page for additional suggestions:  
[http://www.owasp.org/index.php/Testing for SSL-TLS %28OWASP-CM-001%29](http://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29)

### Remediation:

Perform the following to implement the recommended state:

1. Decide on the host name to be used for the certificate. It is important to remember that the browser will compare the host name in the URL to the common name in the certificate, so that it is important that all https: URL's match the correct host name. Specifically the host name `www.example.com` is not the same as `example.com` nor the same as `ssl.example.com`.
2. Generate a private key using openssl. Although certificate key lengths of 1024 have been common in the past, a key length of 2048 is now recommended for strong authentication. The key must be kept confidential and will be encrypted with a passphrase by default. Follow the steps below and respond to the prompts for a passphrase. See the Apache or OpenSSL documentation for details:

[http://httpd.apache.org/docs/2.4/ssl/ssl\\_faq.html#realcert](http://httpd.apache.org/docs/2.4/ssl/ssl_faq.html#realcert)  
<http://www.openssl.org/docs/HOWTO/certificates.txt>

```
# cd /etc/pki/tls/certs
# umask 077
# openssl genrsa -aes128 2048 > example.com.key
Generating RSA private key, 2048 bit long modulus
...+++
.....+++
e is 65537 (0x10001)
Enter pass phrase:
Verifying - Enter pass phrase:
```

3. Generate the certificate signing request (CSR) to be signed by a certificate authority. It is important that common name exactly make the web host name.

```
# openssl req -utf8 -new -key www.example.com.key -out www.example.com.csr
Enter pass phrase for example.com.key:
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [GB]:US
State or Province Name (full name) [Berkshire]:New York
Locality Name (eg, city) [Newbury]:Lima
Organization Name (eg, company) [My Company Ltd]:Durkee Consulting
Organizational Unit Name (eg, section) []:
Common Name (eg, your name or your server's hostname) []:www.example.com
Email Address []:ralph@example.com
Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:
An optional company name []:
# mv www.example.com.key /etc/pki/tls/private/
```

4. Send the certificate signing request (CSR) to a certificate signing authority to be signed, and follow their instructions for submission and validation. The CSR and the final signed certificate are just encoded text, and need to be protected for integrity, but not confidentiality. This certificate will be given out for every SSL connection made.
5. The resulting signed certificate may be named `www.example.com.crt` and placed in `/etc/pki/tls/certs/` as readable by all (mode `0444`). Please note that the certificate authority does not need the private key (`example.com.key`) and this file must be carefully protected. With a decrypted copy of the private key, it would be possible to decrypt all conversations with the server.
6. Do not forget the passphrase used to encrypt the private key. It will be required every time the server is started in https mode. If it is necessary to avoid requiring an

administrator having to type the passphrase every time the `httpd` service is started, the private key may be stored in clear text. Storing the private key in clear text increases the convenience while increasing the risk of disclosure of the key, but may be appropriate for the sake of being able to restart, if the risks are well managed. Be sure that the key file is only readable by root. To decrypt the private key and store it in clear text file the following `openssl` command may be used. You can tell by the private key headers whether it is encrypted or clear text.

```
# cd /etc/pki/tls/private/  
# umask 077  
# openssl rsa -in www.example.com.key -out www.example.com.key.clear
```

7. Locate the Apache configuration file for `mod_ssl` and add or modify the `SSLCertificateFile` and `SSLCertificateKeyFile` directives to have the correct path for the private key and signed certificate files. If a clear text key is referenced then a passphrase will not be required. You can use the CA's certificate that signed your certificate instead of the CA bundle, to speed up the initial SSL connection as fewer certificates will need to be transmitted.

```
SSLCertificateFile /etc/pki/tls/certs/example.com.crt  
SSLCertificateKeyFile /etc/pki/tls/private/example.com.key  
# Default CA file, can be replaced with your CA's certificate.  
SSLCACertificateFile /etc/pki/tls/certs/ca-bundle.crt
```

8. Lastly, start or restart the `httpd` service and verify correct functioning with your favorite browser.

## References:

1. [http://www.owasp.org/index.php/Testing\\_for\\_SSL-TLS\\_%28OWASP-CM-001%29](http://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29)
2. [http://httpd.apache.org/docs/2.4/ssl/ssl\\_faq.html#realcert](http://httpd.apache.org/docs/2.4/ssl/ssl_faq.html#realcert)
3. <http://www.openssl.org/docs/HOWTO/certificates.txt>

### 1.7.3 Protect the Server's Private Key (Scored)

#### Profile Applicability:

- Level 1

#### Description:

It is critical to protect the server's private key. The server private key is encrypted by default as a means of protecting it. However, having it encrypted means that the passphrase is required each time the server is started up, and now it is necessary to protect the passphrase as well. The passphrase may be typed in when it is manually started up, or provided by an automated program.

To summarize, the options are:

1. Use `SSLPassPhraseDialog builtin`, - requires a passphrase to be manually entered.
2. Use `SSLPassPhraseDialog |/path/to/program` to provide the passphrase.
3. Use `SSLPassPhraseDialog exec:/path/to/program` to provide the passphrase,
4. Store the private key in clear text so that a passphrase is not required.

Any of the above options 1-4 are acceptable as long as the key and passphrase are protected as described below. Option 1 has the additional security benefit of not storing the passphrase, but is not generally acceptable for most production web servers, since it requires the web server to be manually started. Options 2 and 3 can provide additional security if the programs providing them are secure. Option 4 is the simplest, is widely used and is acceptable as long as the private key is appropriately protected.

### **Rationale:**

If the private key were to be disclosed, it could be used to decrypt all of the SSL communications with the web server, and could also be used to impersonate the web server.

### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. For each certificate file referenced in the Apache configuration files with the `SSLCertificateFile` directive, examine the file for a private key, clearly identified by the string "PRIVATE KEY---"
2. For each file referenced in the Apache configuration files with the `SSLCertificateKeyFile` directive, verify the ownership is `root:root` and the permission 0400.

### **Remediation:**

Perform the following to implement the recommended state:

1. All private keys must be stored separately from the public certificates. Find all `SSLCertificateFile` directives in the Apache configuration files. For any `SSLCertificateFile` directives that do not have a corresponding separate `SSLCertificateKeyFile` directive, move the key to a separate file from the certificate, and add the `SSLCertificateKeyFile` directive for the key file.
2. For each the `SSLCertificateKeyFile` directive , change the ownership and permissions on the server private key to owned by `root:root` with permission 0400.

**References:**

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_ssl.html](http://httpd.apache.org/docs/2.4/mod/mod_ssl.html)
2. [http://httpd.apache.org/docs/2.4/mod/mod\\_ssl.html#sslpassphrasedialog](http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslpassphrasedialog)

### *1.7.4 Restrict Weak SSL Ciphers (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

Disable weak SSL ciphers using the `SSLCipherSuite`, and `SSLHonorCipherOrder` directives. The `SSLCipherSuite` directive specifies which ciphers are allowed in the negotiation with the client. While the `SSLHonorCipherOrder` causes the servers preferred ciphers to be used instead of the clients specified preferences.

**Rationale:**

In October 2011, a new TLS attack, known as BEAST, was widely disclosed against the SSL/TLS CBC based ciphers. The attack affected all SSLv3 and TLS1.0 block ciphers that used CBC mode. Since RC4 is a stream cipher it does not use CBC mode. To mitigate this vulnerability it is recommended to enable the `SSLHonorCipherOrder` and then prefer a few of the TLS1.2 ciphers, followed by the RC4 ciphers, and then to allow the SSLv3 ciphers which had previously been considered strong. It is important to note that the cipher preference is only a mitigation, and will not prevent a client from connecting with ciphers that are vulnerable.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `SSLCipherSuite` directive disables weak ciphers in the Apache server level configuration and every virtual host that is SSL enabled.
2. Alternately the SSL protocols and ciphers supported can be easily tested by connecting to a running web server with `openssl s_client` such as shown in [http://www.owasp.org/index.php/Testing\\_for\\_SSL-TLS\\_%28OWASP-CM-001%29](http://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29)

**Remediation:**

Perform the following to implement the recommended state:

Add or modify the following line in the Apache server level configuration and every virtual host that is SSL enabled (The second line is long and has been wrapped):

```
SSLHonorCipherOrder On
SSLCipherSuite ECDHE-RSA-AES256-SHA384:AES256-SHA256:RC4:HIGH:!MD5:!aNULL:!EDH:!AESGCM
```

**FIPS Compliance:** For servers that fall under FIPS 140-2 compliance requirements, SP800-52 provides guidelines for the TLS ciphers. To eliminate usage of the RC4 cipher and MD5 hash which are not deemed FIPS compliant, therefore the cipher suite should disallow MD5 and RC4. Such as:

```
# enable only FIPS 140-2 compliant cyphers
SSLCipherSuite ALL:!EXP:!NULL:!ADH:!LOW:!SSLv2:!MD5:!RC4
```

### Default Value:

The following are the default values:

SSLCipherSuite default depends on OpenSSL version.

SSLHonorCipherOrder Off

### References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_ssl.html#sslprotocol](http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslprotocol)
2. [http://httpd.apache.org/docs/2.4/mod/mod\\_ssl.html#sslcipher suite](http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcipher suite)
3. <http://www.openssl.org/>
4. [http://www.owasp.org/index.php/Testing\\_for\\_SSL-TLS\\_%28OWASP-CM-001%29](http://www.owasp.org/index.php/Testing_for_SSL-TLS_%28OWASP-CM-001%29)
5. <http://www.phonefactor.com/resources/CipherSuiteMitigationForBeast.pdf>
6. <http://blog.ivanristic.com/2011/10/mitigating-the-beast-attack-on-tls>

## 1.7.5 Disable SSL Insecure Renegotiation (Scored)

### Profile Applicability:

- Level 1

### Description:

A man-in-the-middle renegotiation attack was discovered in SSLv3 and TLSv1 in November, 2009 ([CVE-2009-3555](#)). First, a work around and then a fix was approved as an Internet Standard as RFC 574, Feb 2010. The work around, which removes the renegotiation, is available from OpenSSL as of version 0.9.8l and newer versions. For details: [http://www.openssl.org/news/secadv\\_20091111.txt](http://www.openssl.org/news/secadv_20091111.txt)

The `SSLInsecureRenegotiation` directive was added in Apache 2.2.15, for web servers linked with OpenSSL version 0.9.8m or later, to provide backward compatibility to clients with the older, unpatched SSL implementations.

### **Rationale:**

Enabling the `SSLInsecureRenegotiation` directive leaves the server vulnerable to man-in-the-middle renegotiation attack. Therefore, the `SSLInsecureRenegotiation` directive should not be enabled.

### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Search the Apache configuration files for the `SSLInsecureRenegotiation` directive and verify that the directive is either not present or has a value of `off`.

### **Remediation:**

Perform the following to implement the recommended state:

1. Search the Apache configuration files for the `SSLInsecureRenegotiation` directive. If the directive is present modify the value to be `off`. If the directive is not present then no action is required.

```
SSLInsecureRenegotiation off
```

### **Default Value:**

```
SSLInsecureRenegotiation off
```

### **References:**

1. [http://httpd.apache.org/docs/2.2/mod/mod\\_ssl.html#sslinsecurerenegotiation](http://httpd.apache.org/docs/2.2/mod/mod_ssl.html#sslinsecurerenegotiation)
2. <http://cve.mitre.org/cgi-bin/cvename.cgi?name=CAN-2009-3555>
3. <http://www.phonefactor.com/sslgap/ssl-tls-authentication-patches>

## ***1.7.6 Ensure SSL Compression is not Enabled (Scored)***

### **Profile Applicability:**

- Level 1

### **Description:**

The `SSLCompression` directive controls whether SSL compression is used by Apache when serving content over HTTPS. It is recommended that the `SSLCompression` directive be set to `off`.

### **Rationale:**

If SSL compression is enabled, HTTPS communication between the client and the server may be at increased risk to the CRIME attack. The CRIME attack increases a malicious actor's ability to derive the value of a session cookie, which commonly contains an authenticator. If the authenticator in a session cookie is derived, it can be used to impersonate the account associated with the authenticator.

### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

1. Search the Apache configuration files for the `SSLCompression` directive.
2. Verify that the directive either does not exist or exists and is set to `off`.

### **Remediation:**

Perform the following to implement the recommended state:

1. Search the Apache configuration files for the `SSLCompression` directive.
2. If the directive is present, set it `off`.

### **Default Value:**

In Apache  $\geq 2.4.3$ , the `SSLCompression` directive is available and SSL compression is implicitly disabled. In Apache 2.4 - 2.4.2, the `SSLCompression` directive is not available and SSL compression is implicitly enabled.

### **References:**

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_ssl.html#sslcompression](http://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcompression)
2. [http://en.wikipedia.org/wiki/CRIME\\_\(security\\_exploit\)](http://en.wikipedia.org/wiki/CRIME_(security_exploit))

## ***1.8 Information Leakage***

Recommendations in this section intend to limit the disclosure of potentially sensitive information.



### 1.8.1 Set ServerToken to 'Prod' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Configure the Apache `ServerTokens` directive to provide minimal information. By setting the value to `Prod` or `ProductOnly`. The only version information given in the server HTTP response header will be "Apache" rather than providing detailed on modules and versions installed.

#### Rationale:

Information is power, and identifying web server details greatly increases the efficiency of any attack, as security vulnerabilities are extremely dependent upon specific software versions and configurations. Excessive probing and requests may cause too much "noise" being generated and may tip off an administrator. If an attacker can accurately target their exploits, the chances of successful compromise prior to detection increase dramatically. Script Kiddies are constantly scanning the Internet and documenting the version information openly provided by web servers. The purpose of this scanning is to accumulate a database of software installed on those hosts, which can then be used when new vulnerabilities are released.

#### Audit:

Perform the following steps to determine if the recommended state is implemented:

1. Verify the `ServerTokens` directive is present in the Apache configuration and has a value of `Prod` or `ProductOnly`.

#### Remediation:

Perform the following to implement the recommended state:

1. Add or modify the `ServerTokens` directive as shown below to have the value of `Prod` or `ProductOnly`:

```
ServerTokens Prod
```

#### Default Value:

The default value is `Full` which provides the most detailed information.

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#servertokens>

### *1.8.2 Set ServerSignature to 'Off' (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

Disable the server signatures which generates a signature line as a trailing footer at the bottom of server generated documents such as error pages.

**Rationale:**

Server signatures are helpful when the server is acting as a proxy, since it helps the user distinguish errors from the proxy rather than the destination server, however in this context there is no need for the additional information and we want to limit leakage of unnecessary information.

**Audit:**

Verify the `ServerSignature` directive is either NOT present in the Apache configuration or has a value of `Off`.

**Remediation:**

Perform the following to implement the recommended state:

1. Add or modify the `ServerSignature` directive as shown below to have the value of `Off`:

```
ServerSignature Off
```

**Default Value:**

The default value is `Off` for `ServerSignature`.

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#serversignature>

### 1.8.3 Information Leakage via Default Apache Content (Scored)

#### Profile Applicability:

- Level 2

#### Description:

In previous recommendations, we have removed default content such as the Apache manuals and default CGI programs. However, if you want to further restrict information leakage about the web server, it is important that default content such as icons are not left on the web server.

#### Rationale:

To identify the type of web servers and versions software installed it is common for attackers to scan for icons or special content specific to the server type and version. A simple request like [http://example.com/icons/apache\\_pb2.png](http://example.com/icons/apache_pb2.png) may tell the attacker that the server is Apache 2.2 as shown below. The many icons are used primarily for auto indexing, which is also recommended to be disabled.

#### Audit:

Perform the following step to determine if the recommended state is implemented:

1. Verify that there is no alias or directory access to the Apache icons directory in any of the Apache configuration files.

#### Remediation:

Perform either of the following to implement the recommended state:

1. The default source build places the auto-index and icon configurations in the `extra/httpd-autoindex.conf` file, so it can be disabled by leaving the include line commented out in the main `httpd.conf` file as shown below.

```
# Fancy directory listings
#Include conf/extra/httpd-autoindex.conf
```

2. Alternatively the icon `alias` directive and the directory access control configuration can be commented out as shown if present:

```
# We include the /icons/ alias for FancyIndexed directory listings. If
# you do not use FancyIndexing, you may comment this out.
#
#Alias /icons/ "/var/www/icons/"
```

```
#<Directory "/var/www/icons">
#   Options Indexes MultiViews FollowSymLinks
#   AllowOverride None
#   Order allow,deny
#   Allow from all
#</Directory>
```

**Default Value:**

The default source build does not enable access to the Apache icons

## ***1.9 Denial of Service Mitigations***

Denial of Service (DoS) attacks intend to degrade a service's ability to process and respond to service requests. Typically, DoS attacks attempt to exhaust the service's network-, CPU-, disk-, and/or memory- related resources. Configuration states in this section may increase a server's resiliency to DoS attacks.

### ***1.9.1 Set Timeout to 10 or less (Scored)***

**Profile Applicability:**

- Level 1

**Description:**

Denial of Service (DoS) is an attack technique with the intent of preventing a web site from serving normal user activity. DoS attacks, which are normally applied to the network layer, are also possible at the application layer. These malicious attacks can succeed by starving a system of critical resources, vulnerability exploit, or abuse of functionality. Although there is no 100% solution for preventing DoS attacks, the following recommendation uses the `Timeout` directive to mitigate some of the risk, by requiring more effort for a successful DoS attack. Of course DoS attacks can happen in rather unintentional ways as well as intentional and these directives will help in many of those situations as well.

**Rationale:**

One common technique for DoS is to initiate many connections to the server. By decreasing the timeout for old connections and we allow the server to free up resources more quickly and be more responsive. By making the server more efficient, it will be more resilient to DoS conditions. The `Timeout` directive affects several timeout values for Apache, so review the Apache document carefully.

<http://httpd.apache.org/docs/2.4/mod/core.html#timeout>

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

Verify that the `Timeout` directive is specified in the Apache configuration files to have a value of 10 seconds or shorter.

### **Remediation:**

Perform the following to implement the recommended state:

Add or modify the `Timeout` directive in the Apache configuration to have a value of 10 seconds or shorter.

```
Timeout 10
```

### **Default Value:**

```
Timeout 60
```

### **References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#timeout>

## *1.9.2 Set the KeepAlive directive to On (Scored)*

### **Profile Applicability:**

- Level 1

### **Description:**

The `KeepAlive` directive controls whether Apache will reuse the same TCP connection per client to process subsequent HTTP requests from that client. It is recommended that the `KeepAlive` directive be set to `On`.

### **Rationale:**

Allowing per-client reuse of TCP sockets reduces the amount of system and network resources required to serve requests. This efficiency gain may improve a server's resiliency to DoS attacks.

### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

Verify that the `KeepAlive` directive in the Apache configuration to have a value of `On`, or is not present. If the directive is not present the default value is `On`.

### Remediation:

Perform the following to implement the recommended state:

Add or modify the `KeepAlive` directive in the Apache configuration to have a value of `On`, so that Keepalive connections are enabled.

```
KeepAlive On
```

### Default Value:

```
KeepAlive On
```

### References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#keepalive>

### 1.9.3 Set `MaxKeepAliveRequests` to 100 or greater (Scored)

#### Profile Applicability:

- Level 1

#### Description:

The `MaxKeepAliveRequests` directive limits the number of requests allowed per connection when `KeepAlive` is on. If it is set to 0, unlimited requests will be allowed.

#### Rationale:

The `MaxKeepAliveRequests` directive is important to be used to mitigate the risk of Denial of Service (DoS) attack technique by reducing the overhead imposed on the server. The `KeepAlive` directive must be enabled before it is effective. Enabling `KeepAlives` allows for multiple HTTP requests to be sent while keeping the same TCP connection alive. This reduces the overhead of having to setup and tear down TCP connections for each request. By making the server more efficient, it will be more resilient to DoS conditions.

#### Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `MaxKeepAliveRequests` directive in the Apache configuration to have a value of 100 or more. If the directive is not present the default value is 100.

### Remediation:

Perform the following to implement the recommended state:

Add or modify the `MaxKeepAliveRequests` directive in the Apache configuration to have a value of 100 or more.

```
MaxKeepAliveRequests 100
```

### Default Value:

```
MaxKeepAliveRequests 100
```

### References:

1. <http://httpd.apache.org/docs/2.4/mod/core.html#maxkeepaliverequests>

## 1.9.4 Set `KeepAliveTimeout` Low to Mitigate Denial of Service (Scored)

### Profile Applicability:

- Level 1

### Description:

The `KeepAliveTimeout` directive specifies the number of seconds Apache will wait for a subsequent request before closing a connection that is being kept alive.

### Rationale:

The `KeepAliveTimeout` directive is used mitigate some of the risk, by requiring more effort for a successful DoS attack. By enabling `KeepAlive` and keeping the timeout relatively low for old connections and we allow the server to free up resources more quickly and be more responsive.

### Audit:

Perform the following steps to determine if the recommended state is implemented:

Verify that the `KeepAliveTimeout` directive in the Apache configuration to have a value of 15 or less. If the directive is not present the default value is 5 seconds.

**Remediation:**

Perform the following to implement the recommended state:

Add or modify the `KeepAliveTimeout` directive in the Apache configuration to have a value of 15 or less.

```
KeepAliveTimeout 15
```

**Default Value:**

```
KeepAliveTimeout 5
```

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#keepalivetimeout>

### *1.9.5 Set Timeout Limits for Request Headers (Scored)*

**Profile Applicability:**

- Level 1

**Description:**

The `RequestReadTimeout` directive allows configuration of timeout limits for client requests. The header portion of the directive provides for an initial timeout value, a maximum timeout and a minimum rate. The minimum rate specifies that after the initial timeout, the server will wait an additional 1 second for each N bytes received. The recommended setting is to have a maximum timeout of 40 seconds or less. Keep in mind that for SSL/TLS virtual hosts the time for the TLS handshake must fit within the timeout.

**Rationale:**

Setting a request header timeout is vital for mitigating Denial of Service attacks based on slow requests. The slow request attacks are particularly lethal and relative easy to perform, because they require very little bandwidth and can easily be done through anonymous proxies. Starting in June 2009 with the Slow Loris DoS attack, which used a slow GET request, was published by Robert Hansen (RSnake) on his blog <http://h.ckers.org/slowloris/>. Later in November 2010 at the OWASP App Sec DC conference Wong Onn Chee demonstrated a slow POST request attack which was even more effective. See <http://code.google.com/p/owasp-dos-http-post/> for details.

**Audit:**

Perform the following to determine if the recommended state is implemented:



1. Locate the Apache configuration files and included configuration files.
2. Locate any `RequestReadTimeout` directives and verify that they have a maximum header request timeout of 40 seconds or less.
3. If the configuration does not contain any `RequestReadTimeout` directives, and the `mod_reqtimeout` module is being loaded, then the default value of 40 seconds is compliant with the benchmark recommendation.

```
RequestReadTimeout header=XXX-40,MinRate=XXX body=XXXXXXXXXX
```

### Remediation:

Load the `mod_reqtimeout` module in the Apache configuration with the following configuration.

```
LoadModule reqtimeout_module modules/mod_reqtimeout.so
```

Add a `RequestReadTimeout` directive similar to the one below with the maximum request header timeout value of 40 seconds or less.

```
RequestReadTimeout header=20-40,MinRate=500 body=20,MinRate=500
```

### Default Value:

```
header=20-40,MinRate=500
```

### References:

1. <http://ha.ckers.org/slowloris/>
2. <http://code.google.com/p/owasp-dos-http-post/>
3. [http://httpd.apache.org/docs/2.4/mod/mod\\_reqtimeout.html](http://httpd.apache.org/docs/2.4/mod/mod_reqtimeout.html)

## 1.9.6 Set Timeout Limits for the Request Body (Scored)

### Profile Applicability:

- Level 1

### Description:

The `RequestReadTimeout` directive also allows setting timeout values for the body portion of a request. The directive provides for an initial timeout value, and a maximum timeout and minimum rate. The minimum rate specifies that after the initial timeout, the server will wait an additional 1 second for each N bytes are received. The recommended setting is to have a maximum timeout of 20 seconds or less. The default value is `body=20,MinRate=500`.

## Rationale:

It is not sufficient to timeout only on the header portion of the request, as the server will still be vulnerable to attacks like the OWASP Slow POST attack, which provide the body of the request very slowly. Therefore the body portion of the request must have a timeout as well. A timeout of 20 seconds or less is recommended.

## Audit:

Perform the following to determine if the recommended state is implemented:

1. Locate the Apache configuration files and included configuration files.
2. Locate any `RequestReadTimeout` directives and verify the configuration has a maximum body request timeout of 20 seconds or less.
3. If the configuration does not contain any `RequestReadTimeout` directives, and the `mod_reqtimeout` module is being loaded, then the default value of 20 seconds is compliant with the benchmark recommendation.

```
RequestReadTimeout header=XXXXXX body=20,MinRate=XXXXXXXXXX
```

## Remediation:

Load the `mod_reqtimeout` module in the Apache configuration with the following configuration.

```
LoadModule reqtimeout_module modules/mod_reqtimeout.so
```

Add a `RequestReadTimeout` directive similar to the one below with the maximum request body timeout value of 20 seconds or less.

```
RequestReadTimeout header=20-40,MinRate=500 body=20,MinRate=500
```

## Default Value:

```
body=20,MinRate=500
```

## References:

1. [http://httpd.apache.org/docs/2.4/mod/mod\\_reqtimeout.html](http://httpd.apache.org/docs/2.4/mod/mod_reqtimeout.html)

## 1.10 Request Limits

Recommendations in this section reduce the maximum allowed size of request parameters. Doing so increases the likelihood of negatively impacting application and/or site

functionality. It is highly recommended that the configuration states described in this section be tested on test servers prior deploying them to production servers.

### *1.10.1 Set the LimitRequestLine directive to 512 or less (Scored)*

#### **Profile Applicability:**

- Level 2

#### **Description:**

Buffer Overflow attacks attempt to exploit an application by providing more data than the application buffer can contain. If the application allows copying data to the buffer to overflow the boundaries of the buffer, then the application is vulnerable to a buffer overflow. The results of Buffer overflow vulnerabilities varies, and may result in the application crashing, or may allow the attacker to execute instructions provided in the data. The Apache `LimitRequest*` directives allow the Apache web server to limit the sizes of requests and request fields and can be used to help protect programs and applications processing those requests.

Specifically the `LimitRequestLine` directive limits the allowed size of a client's HTTP request-line, which consists of the HTTP method, URI, and protocol version.

#### **Rationale:**

The limiting of the size of request line is helpful so that the web server can prevent an unexpectedly long or large requests from being passed to a potentially vulnerable CGI program, module or application that would have attempted to process the request. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. Since the configuration directive is available only at the server configuration level, it is not possible to tune the value for different portions of the same web server. Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

#### **Audit:**

Perform the following steps to determine if the recommended state is implemented:

Verify that the `LimitRequestline` directive is in the Apache configuration and has a value of 512 or less.

#### **Remediation:**

Perform the following to implement the recommended state:

Add or modify the `LimitRequestline` directive in the Apache configuration to have a value of 512 or shorter.

```
LimitRequestline 512
```

**Default Value:**

```
LimitRequestline 8190
```

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestline>

*1.10.2 Set the `LimitRequestFields` directive to 100 or less (Scored)*

**Profile Applicability:**

- Level 2

**Description:**

The `LimitRequestFields` directive limits the number of fields allowed in an HTTP request.

**Rationale:**

The limiting of the number of fields is helpful so that the web server can prevent an unexpectedly high number of fields from being passed to a potentially vulnerable CGI program, module or application that would have attempted to process the request. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. Since the configuration directives are available only at the server configuration level, it is not possible to tune the value for different portions of the same web server. Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

**Audit:**

Verify that the `LimitRequestFields` directive is in the Apache configuration and has a value of 100 or less.

**Remediation:**

Perform the following to implement the recommended state:

Add or modify the `LimitRequestFields` directive in the Apache configuration to have a value of 100 or less. If the directive is not present the default depends on a compile time configuration, but defaults to a value of 100.

```
LimitRequestFields 100
```

**Default Value:**

```
LimitRequestFields 100
```

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestfields>

### *1.10.3 Set the `LimitRequestFieldSize` directive to 1024 or less (Scored)*

**Profile Applicability:**

- Level 2

**Description:**

The `LimitRequestFieldSize` limits the number of bytes that will be allowed in an HTTP request header. It is recommended that the `LimitRequestFieldSize` directive be set to 1024 or less.

**Rationale:**

By limiting of the size of request headers is helpful so that the web server can prevent an unexpectedly long or large values from being passed to exploit a potentially vulnerable program. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. Since the configuration directives are available only at the server configuration level, it is not possible to tune the value for different portions of the same web server. Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

**Audit:**

Perform the following steps to determine if the recommended state is implemented:

Verify that the `LimitRequestFieldSize` directive is in the Apache configuration and has a value of 1024 or less.

**Remediation:**

Perform the following to implement the recommended state:

Add or modify the `LimitRequestFieldsize` directive in the Apache configuration to have a value of 1024 or less.

```
LimitRequestFieldsize 1024
```

**Default Value:**

```
LimitRequestFieldsize 8190
```

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestfieldsize>

*1.10.4 Set the `LimitRequestBody` directive to 102400 or less (Scored)*

**Profile Applicability:**

- Level 2

**Description:**

The `LimitRequestBody` directive limits the number of bytes that are allowed in a request body. Size of requests may vary greatly; for example during a file upload the size of the file must fit within this limit.

**Rationale:**

The limiting of the size of the request body is helpful so that the web server can prevent an unexpectedly long or large requests from being passed to a potentially vulnerable program. Of course the underlying dependency is that we need to set the limits high enough to not interfere with any one application on the server, while setting them low enough to be of value in protecting the applications. The `LimitRequestBody` may be configured on a per directory, or per location context.

Please read the Apache documentation carefully, as these requests may interfere with the expected functionality of some web applications.

**Audit:**

Verify that the `LimitRequestBody` directive in the Apache configuration to have a value of 102400 (100K) or less.

**Remediation:**

Perform the following to implement the recommended state:

Add or modify the `LimitRequestBody` directive in the Apache configuration to have a value of 102400 (100K) or less. Please read the Apache documentation so that it is understood that this directive will limit the size of file up-loads to the web server.

```
LimitRequestBody 102400
```

**Default Value:**

```
LimitRequestBody 0 (unlimited)
```

**References:**

1. <http://httpd.apache.org/docs/2.4/mod/core.html#limitrequestbody>

# Appendix: Change History

Date	Version	Changes for this version
12-30-2012	1.0.0	Initial Release