



# Learning to Program With Python – Part 4



## Logic and Control Flow

*Based on the book:*

Snake Wrangling for Kids, Learning to Program with Python  
by Jason R. Briggs

*(Version 0.7.7-python2.7, modified by SJL)*

*Presented by*

*Steve Arnold\*, Principal Scientist VCT Labs*

*Stephanie Lockwood-Childs\*, President VCT Labs*

*Nick Lockwood, Senior Engineer, VCT Labs*

*(\* also open source Gentoo Linux / Yocto developers)*



# Decisions, Decisions



In the programs we have seen till now, there has always been a series of statements faithfully executed by Python in exact top-down order. What if you wanted to change the flow of how it works? For example, what if you want the program to take some decisions and do different things depending on different situations, such as printing Good Morning or Good Evening depending on the time of the day?

As you might have guessed, this is achieved using control flow statements. There are three control flow statements in Python - **if**, **for**, and **while**. - *A Byte of Python*

==	Equal to
!=	Not equal to
>	Greater than
<	Less than
>=	Greater than or equal to
<=	Less than or equal to

CS Terminology:  
*Control Flow*  
*Relational*  
*Operators*



Note assignment “=” is not the same as the conditional “==” above.



# If This, Then That



In programming terms, a question usually means we want to do either one thing, or another, depending on the answer to the question. This usually involves an **if** statement.

An **if** statement is made up of an 'if' followed by what is called a 'condition', followed by a colon (:). Note the condition will often include one or more of the relational operators.

Making a choice:

"If you're hungry, let's eat lunch. Or else we can eat in an hour."

"If there's mint ice cream, I'll have a scoop. Or else I'll take vanilla."

Making a choice in our code  
with the *else clause*:

```
>>> if name == "Katie":  
        print "Hi Katie!"  
    else:  
        print "Impostor!"
```



# But What If... ?



Making many choices:

"If there's mint ice cream, I'll have a scoop.

Or else if we have vanilla, I'll have 2!

Or else if there's chocolate, give me 3!

Or I'll just have a donut."

Making more choices  
in our code with the  
*elif* clause:

```
>>> if name == "Katie":  
        print "Hi Katie!"  
    elif name == "Barbara":  
        print "Hi Barbara!"  
    else:  
        print "Who are you?"
```



# Loopty-Loop



*Loops* are sections of code that repeat a task over and over again.

A “*for*” loop usually repeats a certain number of times

A “*while*” loop usually keeps going until a certain thing happens (or as long as some condition is True).





# Loops that Count



- A *for* loop repeats a certain number of times – it will keep going until it gets to the end of a count.
  - Can you think of a way this could go wrong?

```
>>> for mynum in [1, 2, 3, 4, 5]:  
        print "Hello", mynum
```

```
Hello 1  
Hello 2  
Hello 3  
Hello 4  
Hello 5
```



# Loops That Wait for a Condition



- A *while* loop will repeat until something happens (or as long as some condition is True).

```
>>> count = 0
>>> while (count < 4):
    print 'The count is:', count
    count = count + 1
```

```
The count is: 0
The count is: 1
The count is: 2
The count is: 3
```



This work is an original work by Stephen Arnold  
<stephen.arnold@acm.org>

<<http://www.vctlabs.org>>

Portions copyright 2014 Stephen L Arnold. Some rights reserved.

The Gentoo Linux logo is Copyright 2006 Gentoo Foundation, used with permission.



This work is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike License. To view a copy of this license, visit <<http://creativecommons.org/licenses/by-nc-sa/1.0>> or send a letter to Creative Commons, 559 Nathan Abbott Way, Stanford, California 94305, USA.

Please contact Stephen Arnold <stephen.arnold@acm.org> for commercial uses of this work.