



E80-xxxM2213S User Manual

Sub-GHz/2.4GHz LoRa Dual-band Wireless Module



Table of contents

Chapter 1 Product Overview	2
1.1 Product Introduction	2
1.2 Features	2
1.3 Application Scenario	3
Chapter 2 Specifications	3
2.1 RF parameters	3
2.2 Electrical parameters	4
2.3 Hardware Parameters	4
Chapter 3 Mechanical Dimensions and Pin Definition	5
Chapter 4 Software development and use	6
Chapter 5 Hardware Design	11
Chapter 6 Reference Circuit	12
Chapter 7 Frequently Asked Questions	13
7.1 The transmission distance is not ideal	13
7.2 Modules are vulnerable to damage	13
7.3 The bit error rate is too high	13
Chapter 8 Welding Operation Instructions	13
8.1 Reflow temperature	13
8.2 Reflow soldering curve	14
Chapter 9 Bulk Packaging Methods	15
Revision history	15
About Us	15


Chapter 1 Product Overview

1.1 Product Introduction


E80 -xxxM2213S is a dual-frequency SMD LoRa hardware SPI wireless module independently developed based on SEMTECH LoRa Connect™ LR1121 chip for multi-band global connectivity, with a transmit power of 22 dBm and 13 dBm respectively . The module integrates an industrial-grade 48MHz high-precision low-temperature drift crystal oscillator.

LR1121 is SEMTECH third generation ultra-low power LoRa transceiver. It provides multi-band LoRa and long-range frequency hopping spread spectrum (LR-FHSS) communications based on the Sub -GHz and 2.4 GHz ISM bands, as well as satellite S-band connectivity. LR1121 is designed to comply with LoRa Alliance® published the physical layer requirements of the LoRaWAN® specification while remaining configurable to meet different application needs and proprietary protocols .

** Since this module is a pure hardware RF module, it needs to be programmed by the user before use.*



E80-400 M2213S



E80 - 900M2213S

1.2 Features

- Low power consumption and high sensitivity LoRa/(G)FSK half-duplex RF transceiver;
- Global ISM band support ranges from 150-960MHz (Sub- GHz) and 2.4 GHz, as well as 2.1 GHz S-band;
- Built-in low noise figure RX front end, enhanced LoRa / (G) FSK sensitivity;
- Maximum transmit power 22 dBm @ Sub - GHz/ 13 dBm @ 2.4GHz, software-adjustable in multiple levels;
- Under ideal conditions, the communication distance can reach 5.6 km @ 433MHz / 5.6km@ 868 MHz / 2.6km @2.4G Hz ;
- The chip has a built-in LR-FHSS modulator , which supports remote frequency hopping spread spectrum in the 2.4 GHz band ;
- Integrated PA regulator power selector simplifies dual power supply design, achieving a maximum RF output power of +15/+22dBm (Sub- GHz only) on a single board ;
- Built-in DC-DC power supply circuit, lower power consumption and more stable system;
- Capable of supporting multi-regional BOMs worldwide, with circuits that adapt matching networks to meet regulatory restrictions ;
- with SX126x devices under Sub-GHz communication and compliant with LoRa The LoRaWAN ® standard defined by the Alliance® ;
- with SX12 8x devices (except FLRC modulation) at 2.4GHz communication and compliant with LoRa The LoRa standard defined by Alliance® ;

- Hardware supports AES-128 encryption/decryption algorithms ;
- The module includes 48M high-speed crystal oscillator/32.768k low-speed crystal oscillator ;
- Industrial-grade standard design, supports long-term use at -40~+85°C;
- Dual antennas are optional (IPEX/stamp hole), users can choose to use according to their needs ;

1.3 Application Scenario

- Smart Meter
- Building Automation
- Agricultural Sensors
- Smart City
- Retail Store Sensors
- Asset Tracking
- Street lighting
- Reversing radar
- Environmental Sensors
- Safety Sensors
- Remote control application
- Smart Home
- Radio-controlled toys and drones

Chapter 2 Specifications

2.1 RF parameters

RF parameters	Parameter Value		Remark
	E80-400M2213 S	E80-900M2213 S	
Operating frequency band (MHz)	410-493	850-930	@Sub-GHz, users can program the module to work at different frequencies
	2400-2500		@2.4GHz, users can program the module to work at different frequencies
Blocking power (dBm)	10		The probability of burning is lower when used at close range
Maximum transmit power (dBm)	21.5	22.0	@Sub-GHz, users can adjust the output power through programming
	13		@2.4GHz, users can adjust the output power through programming
Receive sensitivity (dBm)	-136		@Sub-GHz, BWL=125kHz, SF=9
	-129		@2.4GHz, BWL=406kHz, SF=7
Reference communication distance (km)	≤5.6		@Sub-GHz, clear and open environment, antenna gain 3.5dBi , antenna height 2.5 meters , air rate 2.4 kbps
	≤2.6		@2.4GHz, clear and open environment, antenna gain 5dBi , antenna height 2.5 meters, air rate 2.4k bps



2.2 Electrical parameters

Electrical parameters	Minimum	Typical Value	Maximum	Remark
Operating voltage (V)	1.8	3.3	3.7	≥3.3V can guarantee output power , more than 3.8V may cause burnout risk
Communication level (V)	-	3.3	-	Using 5V TTL may cause burnout , please use the conversion circuit reasonably
Emission current (mA)	-	120	-	@433/470MHz, instantaneous power consumption
	-	125	-	@868/915MHz, instantaneous power consumption
	-	35	-	@2.4GHz, instantaneous power consumption
Receive current (mA)	-	9.5	-	@Sub-GHz
	-	9.0	-	@2.4GHz
Sleep current (μA)	-	10	-	Software shutdown , all radio frequencies are not working
Operating temperature (°C)	-40	-	+85	Industrial-grade design
Operating humidity (%rh)	10	-	90	-
Storage temperature (°C)	- 50	-	+150	-

2.3 Hardware Parameters

Hardware Parameters	Parameter Value	Preparation	Note
IC full name	LR11211MLTRT	SEMTECH official website lead-free product number	
Crystal frequency (MHz)	32	The module has built-in active temperature compensated crystal oscillator	
Module size (mm)	26.0*16.0*3.0	Length*Width*Height	
Antenna type	IPEX-1/Stamp Hole	IPEX 1st generation socket, Sub-GHz/2.4GHz dual antenna interface design	
Communication Interface	SPI	Communication level 1.8-3.7V, 3.3V is recommended to ensure data reliability	
Packaging	Patch/Stamp Hole	Pin spacing 1.27mm, please see Chapter 3 for detailed dimension information	
Weight (g)	1.85	-	

Chapter 3 Mechanical Dimensions and Pin Definition



Pin number	Pin Name	Pin Direction	Function
1	GND	power supply	-
2	NC	--	-
3	MISO	Output	SPI interface pin, connected to "DIO4" of LR1121, please refer to the chip manual or Ebyte custom SDK information for details
4	MOSI	Input	SPI interface pin, connected to "DIO3" of LR1121, please refer to the chip manual or Ebyte custom SDK information for details
5	SCK	Input	SPI interface pin, connected to "DIO2" of LR1121, please refer to the chip manual or Ebyte custom SDK information for details
6	NSS	Input	SPI interface pin, connected to "DIO1" of LR1121, please refer to the chip manual or Ebyte custom SDK information for details
7	BUSY	Output	Module "busy" indication, connected to LR1121's "BUSY", for details, please refer to the chip manual or Ebyte custom SDK information
8	GND	power supply	-
9	none	none	Reserve space for future expansion
10	none	none	Reserve space for future expansion
11	GND	power supply	-
12	ANT	Input/Output	2.4GHz antenna interface
13	GND	power supply	-
14	GND	power supply	-
15	ANT	Input/Output	Sub-GHz Antenna Interface
16	GND	power supply	-
17	none	none	Reserve space for future expansion
18	none	none	Reserve space for future expansion
19	GND	power supply	-
20	NC	--	-
21	LR_NRESET	Input	Module reset pin, low level is effective, connected to "NRESET" of LR1121, please refer to the chip manual for details
22	DIO9	Input/Output	Available to connect to LR1121 . Leave it unconnected if not in use. Please refer to the chip manual for details.
23	DIO8	Input/Output	Available to connect to LR1121 , leave it unconnected if not in use. For details, please refer to the chip manual
24	DIO7	Input/Output	Available to connect to LR1121 . If not in use, please leave it vacant. For details, please refer to the chip manual.
25	VCC	power input	-
26	GND	power supply	-

Note:

1. The "32k_P/DIO11" and "32k_N/DIO10" pins of the LR1121 RF chip inside the module have been connected to a 32.768k crystal oscillator;
2. The "XTA", "XTB" and "VTCXO" pins of the LR1121 RF chip inside the module have been connected to a 32M active crystal oscillator;
3. The "DIO5/RFSW0" and "DIO6/RFSW1" pins of the LR1121 RF chip inside the module have been connected to the RF switch to control the "Sub-1GHz" and "2.4GHz" RF transceivers. Since the control state of the RF switch is different from the default control state of the SEMTECH official SDK, please pay attention to the difference. For details, please refer to the SEMTECH official original SDK or Ebyte custom SDK.


DIO5/RFSW0	DIO6/RFSW1	RF Status
0	0	RX
0	1	TX (Sub-1GHz low power mode)
1	0	TX (Sub-1GHz high power mode)
1	1	TX (2.4GHz)

Chapter 4 Software development and use


Software development is divided into two parts: one is the SEMTECH official original SDK usage tutorial, and the other is the Ebyte custom SDK example usage tutorial

● LR1121 Official SDK

①Download link: <https://github.com/Lora-net/SWSD003>



②SDK structure description



The sample code provided by the official website can be used as a reference for users to develop


③Use keil to open the official website project;

Download the SDK package "SWSD003" from the official website, open it and select the "lr11xx" folder, and select the required sample project under the internal app file.


For our demonstration example, temporarily select "ping-pong" > "MDK-ARM"



④ Select a workspace;




⑤ main function entry analysis;




LR1221 Initial configuration

⑥ Key parameter configuration-RF switch;



⑦ Key RF parameter configuration-LoRa modulation related parameters;



Select Lora for data type

Frequency configuration

Power configuration

RF parameter configuration


Modulation parameter configuration

Data packet format configuration


Sync word configuration

- E80 - xxxM2213S Ebyte Custom SDK (Since the DEMO code has detailed comments, the software operation process will not be explained in detail)

- ①Download "E80_DEMO.zip" from Ebyte official website and unzip it to the English path;
- ②Use Keil to open the project;



- ③E80_DEMO SDK structure description;



Application layer

HAL hardware abstraction layer

LR1121 underlying driver library layer

main function entry

④ E80_DEMO main function entry ;

```


97 //
98 int main(void)
99 {
100     hal_mcu_disable_irq();
101     HAL_Init();
102     SystemClock_Config();
103     /* Initialize all configured peripherals */
104     MX_GPIO_Init();
105     MX_SPI1_Init();
106     MX_UART1_UART_Init();
107     /* 清除串口接收中断标志 */
108     __HAL_UART_CLEAR_FLAG(&huart1, UART_FLAG_RXNE);
109     /* 开启串口接收中断 */
110     __HAL_UART_ENABLE_IT(&huart1, UART_IT_RXNE);
111     /* 串口中断使能 */
112     HAL_NVIC_EnableIRQ(USART1_IRQn);
113     /* 串口fifo初始化 */
114     uart_fifo_init();
115     /* USER CODE BEGIN 2 */
116     hal_mcu_enable_irq();
117     /* 射频初始化 */
118     radio_init(LR11XX_WITH_LF_HP_PA, 32, frequency);
119     /* 射频进入接收状态 */
120     radio_rx();
121     /* 系统启动打印信息 */
122     HAL_UART_Transmit(&huart1, (const uint8_t *) "Radio enter receive\r\n", sizeof("Radio enter receive\r\n"), 100);
123     HAL_UART_Transmit(&huart1, (const uint8_t *) "FW:7468-0-10\r\n", sizeof("FW:7468-0-10\r\n"), 100);
124     HAL_UART_Transmit(&huart1, (const uint8_t *) "Enter the main program\r\n", sizeof("Enter the main program\r\n"), 100);
125     /* USER CODE END 2 */
126     /* USER CODE BEGIN WHILE */
127     while (1)
128     {
129         /* USER CODE END WHILE */
130         /* USER CODE BEGIN 3 */
131         /* 串口接收数据完成 */
132         if(event_check( EVENT_UART_RX_DONE ))
133         {
134             /* 射频接收数据完成 */
135             if(event_check( EVENT_RADIO_RX_DONE ))
136             {
137                 //
138             }
139         }
140     }
141 }

```

系统主要轮询事件

System main polling events

⑤ E80_DEMO key RF parameter configuration;



```

1 //
2 #define SYS_CLOCK_RADIO 0x12
3 #define WIFI_CLOCK_RADIO 0x11
4 extern UART_HandleTypeDef huart1;
5
6 /* 射频开关配置 */
7 lr11xx_system_rfswitch_cfg_t system_rf_switch_cfg =
8 {
9     .enable = LR11XX_SYSTEM_RFSW0_HIGH | LR11XX_SYSTEM_RFSW1_HIGH | LR11XX_SYSTEM_RFSW2_HIGH,
10     .standby = 0,
11     .tx = LR11XX_SYSTEM_RFSW1_HIGH,
12     .tx_hp = LR11XX_SYSTEM_RFSW0_HIGH | LR11XX_SYSTEM_RFSW1_HIGH,
13     .tx_rf = 0,
14     .gnss = LR11XX_SYSTEM_RFSW2_HIGH,
15     .wifi = 0,
16 };
17
18 /* 射频参数配置 */
19 lr11xx_radio_pkt_params_loara_t radio_pkt_params =
20 {
21     .preamble_len_in_symb = 1,
22     .header_type = LR11XX_RADIO_LOARA_PKT_EXPLICIT,
23     .pid_len_in_bytes = 255,
24     .crc = false,
25     .iq = false
26 };
27
28 /* LoRa 参数配置 */
29 lr11xx_radio_mod_params_loara_t mod_params =
30 {
31     .ldro = 0,
32     .bw = LR11XX_RADIO_LOARA_BW_125,
33     .cr = LR11XX_RADIO_LOARA_CR_4_5,
34     .sf = LR11XX_RADIO_LOARA_SF5
35 };
36
37 /* 低功耗配置 Supply current in power down mode */
38 lr11xx_system_sleep_cfg_t sleep_cfgs =
39 {
40     .is_rtc_timeout = false,
41     .is_wake_start = false
42 };
43
44 /* 用于存储射频参数 (Pa, 功率等) */
45 lr11xx_radio_tx_cfg_output_params_t output_params = {};
46
47 /* 自定义数据格式 */
48 uint8_t tx_buffer[] = {0,1,2,3,4,5,6,7,8,9,0,1,2,3,4,5,6,7,8,9};
49
50

```


Chapter 5 Hardware Design

- It is recommended to use a DC regulated power supply to power the module. The power supply ripple coefficient should be as small as possible and the module should be reliably grounded.
- Please pay attention to the correct connection of the positive and negative poles of the power supply. Reverse connection may cause permanent damage to the module.
- Please check the power supply to ensure that it is within the recommended power supply voltage. If it exceeds the maximum value, the module will be permanently damaged.
- Please check the stability of the power supply. The voltage should not fluctuate greatly or frequently.
- When designing the power supply circuit for the module, it is often recommended to retain more than 30% margin, which is

conductive to long-term stable operation of the whole machine;

- The module should be kept as far away as possible from power supplies, transformers, high-frequency wiring and other parts with large electromagnetic interference;
- High-frequency digital routing, high-frequency analog routing, and power routing must avoid the bottom of the module. If it is necessary to pass under the module, assuming that the module is soldered on the Top Layer, ground copper should be laid on the Top Layer of the module contact part (all copper should be laid and well grounded), and it must be close to the digital part of the module and routed on the Bottom Layer ;
- Assuming the module is soldered or placed on the Top Layer, it is also wrong to randomly route the wires on the Bottom Layer or other layers, which will affect the module's spurious signal and receiving sensitivity to varying degrees ;
- If there are devices with large electromagnetic interference around the module, it will also greatly affect the performance of the module. It is recommended to keep away from the module according to the intensity of the interference. If possible, appropriate isolation and shielding can be performed.
- If there are traces with large electromagnetic interference around the module (high-frequency digital, high-frequency analog, power traces), it will also greatly affect the performance of the module. It is recommended to keep them away from the module according to the intensity of the interference. If possible, appropriate isolation and shielding can be performed.
- Try to stay away from some TTL protocols whose physical layer is also 2.4GHz, such as USB3.0;
- The antenna installation structure has a great impact on the performance of the module. Make sure the antenna is exposed and preferably vertically upward. When the module is installed inside the housing, use a high-quality antenna extension cable to extend the antenna to the outside of the housing;
- The antenna must not be installed inside a metal shell, as this will greatly reduce the transmission distance.

Chapter 6 Reference Circuit



※ The reference circuits of E80-400M2213S and E80-900M2213S are the same ※

Chapter 7 Frequently Asked Questions

7.1 The transmission distance is not ideal

- When there is a straight-line communication obstacle, the communication distance will be attenuated accordingly ;
- Temperature, humidity, and co-channel interference can increase the communication packet loss rate ;
- The ground absorbs and reflects radio waves, so the test results are poor when close to the ground ;
- Seawater has a strong ability to absorb radio waves, so the test effect at the seaside is poor ;
- If there are metal objects near the antenna, or the antenna is placed in a metal shell, the signal attenuation will be very serious ;
- The power register is set incorrectly, or the air rate is set too high (the higher the air rate, the closer the distance) ;
- The power supply voltage is lower than the recommended value at room temperature. The lower the voltage, the lower the power output .
- The antenna used does not match the module well or the antenna itself has quality issues.

7.2 Modules are vulnerable to damage

- Please check the power supply to ensure that it is within the recommended power supply voltage. If it exceeds the maximum value, the module will be permanently damaged .
- Please check the stability of the power supply. The voltage should not fluctuate greatly or frequently .
- Please ensure anti-static operation during installation and use, as high-frequency components are sensitive to static electricity ;
- Please ensure that the humidity is not too high during installation and use, as some components are humidity sensitive devices ;
- If there is no special requirement, it is not recommended to use it at too high or too low temperature.

7.3 The bit error rate is too high

- There is interference from the same frequency signal nearby. Stay away from the interference source or change the frequency or channel to avoid interference.
- An unsatisfactory power supply may also cause garbled characters, so the reliability of the power supply must be ensured;
- Extension cables or feeder cables that are of poor quality or are too long can also cause a high bit error rate.


Chapter 8 Welding Operation Instructions

8.1 Reflow temperature


Profile Feature	Curve characteristics	Sn-Pb Assembly	Pb-Free Assembly
Solder Paste	Solder Paste	Sn63/Pb37	Sn96.5/Ag3/Cu0.5
Preheat Temperature min (T _{min})	Minimum preheating temperature	100°C	150°C

Preheat temperature max (T _{smax})	Maximum preheating temperature	150°C	200°C
Preheat Time (T _{smin} to T _{smax})(t _s)	Preheat time	60-120 sec	60-120 sec
Average ramp-up rate (T _{smax} to T _p)	Average ascent rate	3°C/second max	3°C/second max
Liquid Temperature (T _L)	Liquidus temperature	183°C	217°C
Time (t _L) Maintained Above (T _L)	Time above liquidus	60-90 sec	30-90 sec
Peak temperature (T _p)	Peak temperature	220-235°C	230-250°C
Average ramp-down rate (T _p to T _{smax})	Average descent rate	6°C/second max	6°C/second max
Time 25°C to peak temperature	Time from 25°C to peak temperature	6 minutes max	8 minutes max

8.2 Reflow soldering curve



Chapter 9 Bulk Packaging Methods



Revision history

Version	Revision Date	Revision Notes	Maintenance man
1.0	2024-6-25	First edition	Ning

About Us



Sales hotline: 4000-330-990

Company phone: 028 -61399028

Technical support : support@cdebyte.com

Official website: www.ru-ebyte.com

Company Address: 2nd Floor, Building B2, No. 199, Xiqu Avenue, High-tech Zone, Chengdu, Sichuan

 **成都亿佰特电子科技有限公司**
Chengdu Ebyte Electronic Technology Co.,Ltd.