



Panchip Microelectronics Co., Ltd.

PAN3029/3060 Series RSSI Application Reference

Current version: 1.3

Release date: 2024.04

**Shanghai Panqi Microelectronics Co.,
Ltd.**

Address: Room 302, Building D, No. 666, Shengxia Road, Zhangjiang

Hi-Tech Park, Shanghai Contact number: 021-50802371

Website: <http://www.panchip.com>



PAN3029/3060 Series RSSI Application Reference

Documentation

Due to version upgrades or other reasons, the content of this document will be updated from time to time. Unless otherwise agreed, the content of this document is only for guidance, and all statements, information and suggestions in this document do not constitute any express or implied warranty.

Trademark

Panqi is a trademark of Panqi Microelectronics Co., Ltd. Other names mentioned in this document are trademarks/registered trademarks of their respective owners.

Disclaimer

All or part of the products, services or features described in this document may not be within the scope of your purchase or use. Unless otherwise agreed in the contract, Panqi Microelectronics Co., Ltd. does not make any express or implied statements or warranties regarding the contents of this document.

Revision History

Version	Revision Date	Description
V1.0	2023.06	Initial version
V1.1	2023.11	Modify RSSI related description
V1.2	2024.04	Modify function interface and chip description

Table of contents

1	Function Introduction	1
2	Software Design Reference	2
2.1	Software	2
2.2	Software Design Verification.....	2
2.2.1	SDK Examples	2
2.2.2	Verification Results	3
3	Notes	4
3.1	About	4

1 Function Introduction

The PAN3029/3060 series chips support the RSSI reading function. The RSSI reading function refers to the function of reading the signal strength value of the current data packet when the chip receives data. After receiving the RX_IRQ signal, directly read the register to obtain the RSSI value.

2 Software Design Reference

2.1 Software Design Process

1. Initialize the chip.
2. Configure related parameters.
3. Enter receiving mode.
4. The chip receives data and reads the RSSI value.

2.2 Software Design Verification

Refer to SDK Rx Demo.

2.2.1 SDK Examples

Reference code:

```
ret = rf_init();                                     //initialization
if(ret != OK)
{
    printf("  RF Init Fail");
    while(1);
}

rf_set_default_para();                               //Configuration
rf_enter_continuous_rx();                             //continuous receive mode
while (1)
{

    key_scan();
    key_event_process();
    process_rf_events();    //Event Handling
}
```

The sample code configures the continuous receiving mode and prints out the received data content and SNR and RSSI values after receiving the data.

```
if(irq & REG_IRQ_RX_DONE)
{
    RxDoneParams.Snr = rf_get_snr();
    RxDoneParams.Rssi = rf_get_rssi();
    RxDoneParams.Size = rf_recv_packet(RxDoneParams.Payload);
    irq &= ~REG_IRQ_RX_DONE;
    rf_clr_irq(REG_IRQ_RX_DONE);
    rf_set_recv_flag(RADIO_FLAG_RXDONE);
}
```

In the interrupt processing function, when the chip receives data and generates a REG_IRQ_RX_DONE (RX_IRQ) interrupt, the signal strength value of the current data packet is read through the rf_get_rssi interface function.

2.2.2 Verification Results

The serial port assistant displays the result as follows:

```
[17:03:49.516]收←◆RF RX:1
Rx : SNR: 11.243670 , RSSI: -12.000000
0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x07 0x08 0x09
1
[17:03:51.366]收←◆RF RX:2
[17:03:51.391]收←◆Rx : SNR: 11.236878 , RSSI: -12.000000
0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x07 0x08 0x09
2
```

Figure 2-1 Serial Port Assistant Display Results

3 Notes

3.1 About RSSI

The RSSI function needs to read the signal strength value when receiving a data packet and before clearing the rxdone interrupt. If the interrupt is cleared, the value will be invalid.

The RSSI measurement range is -10 to -125, and the measurement range is slightly different in different parameter (SF, BW) modes.