

# Using Web services

## Disclaimer about downloading genomic or protein sequences

If you need the genomic, transcript, protein sequences for many IDs (genes, transcripts, genomic sequence/chromosomes), instead of using webservices please check the ready files at each website, eg: [https://plasmodb.org/common/downloads/Current\\_Release](https://plasmodb.org/common/downloads/Current_Release).

E.g. [https://plasmodb.org/common/downloads/Current\\_Release/Pfalciparum3D7/fasta/data/PlasmoDB-65\\_Pfalciparum3D7\\_AnnotatedProteins.fasta](https://plasmodb.org/common/downloads/Current_Release/Pfalciparum3D7/fasta/data/PlasmoDB-65_Pfalciparum3D7_AnnotatedProteins.fasta)

## Record types and searches

Our websites data are organized around :

1. A small set of **record types** (e.g. genes, transcripts, datasets, organisms, etc).
  - a. eg: <https://plasmodb.org/plasmo/service/record-types>
2. A record type defines:
  - a. **attributes** (univalue)
  - b. **tables** (multivalue)
  - c. **reporters** which allow for different output formats in a search result
  - d. **searches**
  - e. eg: <https://plasmodb.org/plasmo/service/record-types/genomic-sequence>
3. There is a containment relationship between some record types:
  - a. **Organism > Genomic-Sequences > Genes > Transcripts.**
4. The **searches** for each record type:
  - a. define input **parameters**, whose values are needed to run.
  - b. return **IDs** ( `primary_key` ) of a record type, and for each ID you may request any of the **attributes** and **tables**.
  - c. sometimes they define "**dynamic attributes**" whose value for each ID is calculate on the fly. These attributes are not in the record definition; they show in the search definition.
  - d. eg: <https://plasmodb.org/plasmo/service/record-types/transcript/searches/GenesByGoTerm> (find the dynamic attribute "evidence\_code")
5. **Reporters** to choose from, are:
  - a. JSON : you may request any number of attributes and tables
  - b. AttributeTabular : tab delimited; any number of attributes
  - c. TableTabular : tab delimited; one table
  - d. FASTA
  - e. GFF3

## API

The full API of WDK REST service is at: <https://veupathdb.org/service-api.html> .

Below are the basic ones you need, to get search results the same way you run searches in the website and obtain results.

## Record types definitions

<https://plasmodb.org/plasmo/service/record-types>

<https://plasmodb.org/plasmo/service/record-types/gene>

Be aware that searches may define ID attributes calculated on the fly. These would be described under the search definition. These are not included in the ontology.

## Searches definitions

<https://plasmodb.org/plasmo/service/record-types/transcript/searches>

<https://plasmodb.org/plasmo/service/record-types/transcript/searches/GeneByLocusTag>

## Ontology of records and searches

A file contains the ontology we use to categorize searches, records, attributes and tables. It lists all searches, attributes and tables used by the WDK client and sets scopes for the website client to determine where to show what.

<https://github.com/VEuPathDB/ApiCommonModel/blob/master/Model/lib/wdk/ontology/individuals.txt>

A subset is uploaded to:  [Sep 2023 - individuals project\\_home - genes/transcripts/organisms](#)

It is useful to know these if you use the website to check on record types and their attributes and tables. But take into account the ontology is not an exhaustive list of defined searches, records, attributes or tables.

## Genes and Transcripts searches

Genes and Transcripts are closely related. In the website we offer “gene searches” that return transcripts records; they are really transcript searches under the hood. But when using web services you need to understand the difference.

1. In **gene search** results: genes `primary_key` is composed of 2 strings:
  - a. `source_id` , `project_id` . E.g. PF3D7\_1133400, PlasmoDB;
  - b. `source_id` is the gene ID;
  - c. `project_id` is the component website that contains these data.
2. In **transcript search** results: transcripts `primary_key` is composed of 3 strings:
  - a. `gene_source_id` , `source_id` , `project_id` . E.g. PF3D7\_1133400, PF3D7\_1133400.1, PlasmoDB;
  - b. `source_id` is the transcript ID.
3. The **transcript record** defines most attributes, while the **gene record** defines all tables and some attributes. The attributes offered by genes and transcripts records may overlap.
4. To get just **one table for all IDs in a result**, you may use a **transcript search**: the transcript record offers a `TableTabular` reporter which will convert to genes and will allow you to download a gene table, one at a time.
5. **Use a gene search returning genes** if you want any number of **both attributes and tables in a result** (using the json reporter). There are only 2 gene searches:
  - a. `single_record_question_GeneRecordClasses_GeneRecordClass` : takes a gene ID and a project ID as input
  - b. `GenesByTaxonGene` : takes organisms as input

Check each search help page described in next section to find the correct syntax in your GET or POST. Eg: :

<https://plasmodb.org/plasmo/app/web-services-help?>

`searchName=single_record_question_GeneRecordClasses_GeneRecordClass&weight=10&primaryKeys=PF3D7_1133400%2CPlasmoDB`  
.

## Web service request syntax for a search: GET and POST

In a website, each search page (e.g. <https://plasmodb.org/plasmo/app/search/transcript/GenesByTaxon>) has a link (under the “Get Answer” button) to a web services help page to build a **GET** and a **POST**. You can use either one. This is explained in this help page:

<https://plasmodb.org/plasmo/app/static-content/content/PlasmoDB/webServices.html>.

For example, the search <https://plasmodb.org/plasmo/app/search/transcript/GenesByTaxon>, after selecting an organism (eg: *Plasmodium falciparum* 3D7) the link takes you to <https://plasmodb.org/plasmo/app/web-services-help?searchName=GenesByTaxon&weight=10&organism=%5B%22Plasmodium%20falciparum%203D7%22%5D> where you can define your output and copy the proposed GET or POST.

Next we show you some GET examples using different reporters (standard == json).

## Get all organisms in a site, and for each: the URLs to the organism fasta files, its component website and its gene count

[https://plasmodb.org/plasmo/service/record-types/organism/searches/GenomeDataTypes/reports/standard?reportConfig={\"attributes\":\[\"primary\\_key\",\"species\",\"URLGenomeFasta\",\"URLproteinFasta\",\"project\\_id\",\"genecount\"\],\"tables\": \[\],\"attributeFormat\":\"text\"}](https://plasmodb.org/plasmo/service/record-types/organism/searches/GenomeDataTypes/reports/standard?reportConfig={\)

## For each organism, get all the gene IDs and transcript IDs with the specified attributes

[https://plasmodb.org/plasmo/service/record-types/transcript/searches/GenesByTaxon/reports/standard?organism=\[\"Plasmodium falciparum 3D7\"\]&reportConfig={\"attributes\":\[\"primary\\_key\",\"organism\",\"gene\\_product\",\"transcript\\_product\"\],\"tables\": \[\],\"attributeFormat\":\"text\"}](https://plasmodb.org/plasmo/service/record-types/transcript/searches/GenesByTaxon/reports/standard?organism=[\)

## For each transcript ID, get the specified attributes

[https://plasmodb.org/plasmo/service/record-types/transcript/searches/single\\_record\\_question\\_TranscriptRecordClasses\\_TranscriptRecordClass/reports/attributesTabular?primaryKeys=PF3D7\\_1133400%2CPF3D7\\_1133400.1%2CPlasmoDB&reportConfig={\"attributes\": \[\"primary\\_key\",\"source\\_id\",\"gene\\_transcript\\_count\",\"strand\",\"gene\\_type\",\"transcript\\_length\",\"genomic\\_sequence\\_length\",\"chromosome\",\"sequence\\_id\",\"organism\",\"gene\\_ortholog\\_number\",\"gene\\_paralog\\_number\",\"protein\\_length\",\"cds\\_length\",\"interpro\\_id\",\"pfam\\_id\",\"pirsf\\_id\",\"smart\\_id\",\"ec\\_numbers\",\"predicted\\_go\\_id\\_function\",\"annotated\\_go\\_id\\_function\"\],\"includeHeader\":true,\"attachmentType\":\"plain\"}](https://plasmodb.org/plasmo/service/record-types/transcript/searches/single_record_question_TranscriptRecordClasses_TranscriptRecordClass/reports/attributesTabular?primaryKeys=PF3D7_1133400%2CPF3D7_1133400.1%2CPlasmoDB&reportConfig={\)

## For each gene ID, get the specified tables

[https://plasmodb.org/plasmo/service/record-types/gene/searches/single\\_record\\_question\\_GeneRecordClasses\\_GeneRecordClass/reports/standard?primaryKeys=PF3D7\\_1133400%2CPlasmoDB&reportConfig={\"attributes\":\[\"primary\\_key\"\],\"tables\": \[\"GeneTranscripts\",\"GeneModelDump\",\"PreferredProducts\",\"GeneLinkouts\",\"GeneLocation\",\"OrthologsLite\",\"InterPro\",\"GOTerms\"\],\"attributeFormat\":\"text\"}](https://plasmodb.org/plasmo/service/record-types/gene/searches/single_record_question_GeneRecordClasses_GeneRecordClass/reports/standard?primaryKeys=PF3D7_1133400%2CPlasmoDB&reportConfig={\)

## For each organism, get all genes with the specified tables

[https://plasmodb.org/plasmo/service/record-types/gene/searches/GenesByTaxonGene/reports/standard?organism=\[\"Plasmodium falciparum 3D7\"\]&reportConfig={\"attributes\":\[\"primary\\_key\",\"organism\",\"product\"\],\"tables\": \[\"GeneTranscripts\",\"GeneModelDump\",\"PreferredProducts\",\"GeneLinkouts\",\"GeneLocation\",\"OrthologsLite\",\"InterPro\",\"GOTerms\"\],\"attributeFormat\":\"text\"}](https://plasmodb.org/plasmo/service/record-types/gene/searches/GenesByTaxonGene/reports/standard?organism=[\)

## Using the portal vs a component site

There are 12 component sites and one portal: [VEuPathDB.org](http://VEuPathDB.org). The component sites are: AmoebaDB, CryptoDB, FungiDB, GiardiaDB, HostDB, MicrosporidiaDB, PiroplasmaDB, PlasmoDB, ToxoDB, TrichDB, TriTrypDB and VectorBase. For most record types (all but dataset and organism), when running a search, the portal reaches out to component sites to get the search results. That means **it will be faster to use a component site directly when you can**. For a given ID (a gene, a sequence, a pathway), the portal has access to most attributes (univalue) information locally but does not have access to tables (multivalue) information; **if you need table information for an ID, use a**

**component site.** If you have an ID in your hand and you want to know to which component site it belongs, you may query the portal and get back a `project_id` as part of the IDs in the result; this will tell you which component site to query next.

The best use of the portal is to get a table with **all organisms in our sites, and for each organism: the component site, and the urls to access their fasta and gff files.**

[https://veupathdb.org/veupathdb/service/record-types/organism/searches/GenomeDataTypes/reports/standard?reportConfig={"attributes":\["primary\\_key","species","URLGenomeFasta","URLproteinFasta","project\\_id","genecount"\],"tables":\[\],"attributeFormat":"text"}](https://veupathdb.org/veupathdb/service/record-types/organism/searches/GenomeDataTypes/reports/standard?reportConfig={)

# Appendices

## Url encoding

 [HTML URL Encoding Reference](#)

## Gene and Transcript basic attributes and tables

1	GENE ATTR
2	
3	source_id
4	name
5	
6	organism:           italics: <i>P. falciparum</i> 3D7
7	organism_text
8	organism_full
9	
10	chromosome
11	sequence_id
12	strand_plus_minus
13	start_min
14	end_max
15	location_text           Pf3D7_11_v3:1,292,966..1,296,696(+)
16	
17	transcript_count
18	exon_count
19	
20	gene_type, type_with_pseudo
21	product
22	
23	ortholog_number
24	paralog_number
25	
26	gene_gff_link
27	
28	TRANSCR ATTR
29	
30	source_id
31	gene_source_id
32	
33	organism           italics: <i>Plasmodium falciparum</i> 3D7
34	organism_full
35	
36	chromosome
37	sequence_id
38	strand
39	gene_start_min

```

40 gene_end_max
41 gene_location_text, location_text Pf3D7_11_v3:1,292,966..1,296,696(+) (transcript no commas)
42
43 genomic_sequence_length
44 cds_length
45 five_prime_utr_length
46 transcript_length
47 protein_length
48
49 gene_transcript_count
50 exon_count
51 gene_exon_count
52
53 gene_type
54 gene_product
55 transcript_product
56
57 gene_ortholog_number
58 gene_paralog_number
59
60 interpro_description
61 interpro_id
62 pfam_description
63 pfam_id
64 smart_description
65 smart_id
66 uniprot_ids
67 uniprot_links
68
69 annotated_go_function
70 predicted_go_function
71 ec_numbers
72
73 transcript_sequence
74 protein_sequence
75
76
77 GENE TABLES
78
79 GeneId
80 GeneName
81
82 GeneTranscripts
83
84 GeneLocation
85 GeneModelDump
86
87 PreferredProducts
88 Product (dumper?)
89 AlternateProducts
90
91 GeneLinkouts
92
93 EcNumber
94 ECNumbers
95 GOTerms
96 GeneGffGoTerms
97

```

```

98 InterPro
99
100 Orthologs
101 OrthologsLite
102
103 ProteinProperties
104
105 ProteinSequence
106
107 Sequences
108

```

## Example of a single search POST request and response

\*\*\*\*\* SINGLE RECORD QUESTION REQUEST \*\*\*\*\*

POST [https://veupathdb.org/veupathdb/service/record-types/dataset/searches/single\\_record\\_question\\_DatasetRecordClasses\\_DatasetRecordClass/reports/standard](https://veupathdb.org/veupathdb/service/record-types/dataset/searches/single_record_question_DatasetRecordClasses_DatasetRecordClass/reports/standard)

```

1 {
2   "searchConfig": {
3     "parameters": {
4       "primaryKeys": "DS_09e81bd198"
5     }
6   },
7   "reportConfig": {
8     "attributes": [
9       "version", "contact", "institution", "description", "eupath_release",
10      "acknowledgement", "annotation_version", "newcategory", "caveat",
11      "email", "functional_annotation_version", "genome_version",
12      "megabase_pairs", "organism_prefix", "release_policy", "summary", "genecount"
13    ],
14    "tables": [
15      "Publications", "Contacts", "GenomeHistory", "DatasetHistory", "Version",
16      "References", "HyperLinks", "GeneTypeCounts", "TranscriptTypeCounts"
17    ]
18  }
19 }

```

\*\*\*\*\* SINGLE RECORD QUESTION RESPONSE \*\*\*\*\*

```

1 {
2   "records": [{
3     "id": [{
4       "name": "dataset_id",
5       "value": "DS_09e81bd198"
6     }],
7     "displayName": "EC mappings",
8     "recordClassName": "DatasetRecordClasses.DatasetRecordClass",
9     "attributes": {
10      "megabase_pairs": null,
11      "summary": "Enzyme classification (EC) mappings to <i>P. falciparum</i> genes supplied by Hagai Ginsburg (",
12      "acknowledgement": null,
13      "annotation_version": null,
14      "genome_version": null,
15      "description": "Enzyme classification (EC) mappings to <i>P. falciparum</i> genes supplied by Hagai Ginsbu",
16      "organism_prefix": "<i>Plasmodium falciparum</i> 3D7<br>",
17      "version": "03-2019",

```

```

18     "release_policy": null,
19     "newcategory": "Function prediction",
20     "institution": "Malaria Parasite Metabolic Pathways",
21     "contact": "Hagai Ginsburg",
22     "genecount": null,
23     "eupath_release": "EuPathDB rel. 1.0, 01-JAN-05",
24     "caveat": null,
25     "email": "hagai@vms.huji.ac.il",
26     "functional_annotation_version": null
27 },
28 "tables": {
29     "GenomeHistory": [],
30     "Publications": [1],
31     "Contacts": [1],
32     "Version": [1],
33     "GeneTypeCounts": [],
34     "References": [3],
35     "DatasetHistory": [],
36     "HyperLinks": [],
37     "TranscriptTypeCounts": []
38 },
39 "tableErrors": []
40 }],
41 "meta": {
42     "responseCount": 1,
43     "totalCount": 1,
44     "viewTotalCount": 1,
45     "displayTotalCount": 1,
46     "displayViewTotalCount": 1,
47     "cachePreviouslyExisted": false,
48     "sorting": [],
49     "recordClassName": "dataset",
50     "pagination": {
51         "offset": 0,
52         "numRecords": -1
53     },
54     "attributes": [
55         "version",
56         "contact",
57         "institution",
58         "description",
59         "eupath_release",
60         "acknowledgement",
61         "annotation_version",
62         "newcategory",
63         "caveat",
64         "email",
65         "functional_annotation_version",
66         "genome_version",
67         "megabase_pairs",
68         "organism_prefix",
69         "release_policy",
70         "summary",
71         "genecount"
72     ],
73     "tables": [
74         "Publications",
75         "Contacts",

```

```

76     "GenomeHistory",
77     "DatasetHistory",
78     "Version",
79     "References",
80     "HyperLinks",
81     "GeneTypeCounts",
82     "TranscriptTypeCounts"
83 ]
84 }
85 }

```

## Example of a single record POST

\*\*\*\*\* RECORD'S ENDPOINT REQUEST \*\*\*\*\*

POST <https://veupathdb.org/veupathdb/service/record-types/dataset/records>

```

1  {
2    "primaryKey": [{
3      "name": "dataset_id",
4      "value": "DS_09e81bd198"
5    }],
6    "attributes": [
7      "version", "contact", "institution", "description", "eupath_release",
8      "acknowledgement", "annotation_version", "newcategory", "caveat",
9      "email", "functional_annotation_version", "genome_version",
10     "megabase_pairs", "organism_prefix", "release_policy", "summary", "genecount"
11   ],
12   "tables": [
13     "Publications", "Contacts", "GenomeHistory", "DatasetHistory", "Version",
14     "References", "HyperLinks", "GeneTypeCounts", "TranscriptTypeCounts"
15   ]
16 }

```

\*\*\*\*\* RECORD'S ENDPOINT RESPONSE \*\*\*\*\*

```

1  {
2    "id": [{
3      "name": "dataset_id",
4      "value": "DS_09e81bd198"
5    }],
6    "displayName": "EC mappings",
7    "recordClassName": "DatasetRecordClasses.DatasetRecordClass",
8    "attributes": {
9      "megabase_pairs": null,
10     "summary": "Enzyme classification (EC) mappings to <i>P. falciparum</i> genes supplied by Hagai Ginsburg (MP
11     "acknowledgement": null,
12     "annotation_version": null,
13     "genome_version": null,
14     "description": "Enzyme classification (EC) mappings to <i>P. falciparum</i> genes supplied by Hagai Ginsburg
15     "organism_prefix": "<i>Plasmodium falciparum</i> 3D7<br>",
16     "version": "03-2019",
17     "release_policy": null,
18     "newcategory": "Function prediction",
19     "institution": "Malaria Parasite Metabolic Pathways",
20     "contact": "Hagai Ginsburg",
21     "genecount": null,
22     "eupath_release": "EuPathDB rel. 1.0, 01-JAN-05",

```



```

23     "caveat": null,
24     "email": "hagai@vms.huji.ac.il",
25     "functional_annotation_version": null
26 },
27 "tables": {
28     "GenomeHistory": [0],
29     "Publications": [1],
30     "Contacts": [1],
31     "Version": [1],
32     "GeneTypeCounts": [],
33     "References": [3],
34     "DatasetHistory": [],
35     "HyperLinks": [],
36     "TranscriptTypeCounts": []
37 },
38 "tableErrors": []
39 }

```

## wget, curl examples

Curl and wget are both command-line tools used to retrieve data from internet. They use different protocols to perform this task, with curl supporting a variety of protocols, including HTTP, HTTPS, FTP, FTPS, SCP, SFTP, and more. Wget, on other hand, primarily supports HTTP and FTP protocols, and in general more limited in options, but faster.

```

1  wget --debug --header 'content-type: application/json' --post-data '{"searchConfig": {"parameters": {"organism":
1  curl -d '{"attributes": [], "primaryKey": [{"name": "source_id", "value": "ACON2_034749"}, {"name": "project_id", "va

```