

# hrosailing-Module Documentation

## Dependencies

The hrosailing-module has the following third-party dependencies

- [numpy](#)
- [matplotlib](#)
- [tabulate](#)
- [scipy](#)

## How To Use This Module

After installing/downloading one can easily use the hrosailing-module via

```
>>> import hrosailing
```

or

```
>>> from hrosailing import something
```

## Contents Of This Module

The hrosailing-module defines the following functions:

`hrosailing.to_csv(csv_path, obj)`

**Parameters :**

`csv_path : string`

Path where a .csv-file is located or where a new .csv-file will be created

`obj : PolarDiagram`

An hrosailing.**PolarDiagram**-object which will be written to the .csv-file

Calls the `.to_csv`-function of the hrosailing.**PolarDiagram**-object.

`hrosailing.from_csv(csv_path)`

**Parameters :**

`csv_path : string`

Path to an existing .csv file which you want to be read

Creates an hrosailing.**PolarDiagram**-object from the data that is written in the given .csv file via the `csv.reader`-class, see [reader](#).

The .csv file needs to be in the right format which is found in the documentation of the corresponding `.to_csv`-function or in the source code. Note that this function doesn't work for the hrosailing.**PolarDiagramCurve** class.

`hrosailing.pickling(pkl_path, obj)`

**Parameters :**

`pkl_path : string`

Path to an existing .pkl file or where the created .pkl file will be located

`obj : PolarDiagram`

An `hrosailing.PolarDiagram`-object which will be written to the .pkl file

Calls the `.pickling`-function of the `hrosailing.PolarDiagram`-object.

`hrosailing.depickling(pkl_path)`

**Parameters :**

`pkl_path: string`

Path to an existing .pkl file which is to be read

Creates an `hrosailing.PolarDiagram`-object from the data that is written in the given .pkl file, via the `pickle.load`-function, see [load](#).

`hrosailing.convert(obj, convert_type)`

**Parameters :**

`obj: PolarDiagram`

An `hrosailing.PolarDiagram`-object that is to be converted to another `hrosailing.PolarDiagram`-type

`convert_type: PolarDiagram`

A subclass of `hrosailing.PolarDiagram`

For a given instance a `hrosailing.PolarDiagram`-subclass, the function converts it into an instance of a given `hrosailing.PolarDiagram`-subclass.

Currently only works for the classes **PolarDiagramTable** and **PolarDiagramPointcloud**

The `hrosailing`-module defines the following classes:

`hrosailing.PolarDiagram()`

An abstract base class for most classes in the `hrosailing`-module

The **PolarDiagram** class defines the following public methods:

`PolarDiagram.pickling(self, pkl_path)`

**Parameters :**

`pkl_path: string`

Path to an existing .pkl file or where the created .pkl file will be located

Creates or overwrites a .pkl file via with the class data of the object which called the function via the `pickle.dump`-function, see [dump](#).

The **PolarDiagram** class also defines the following abstract methods:

`PolarDiagram.__str__()`

`PolarDiagram.__repr__()`

`PolarDiagram.wind_speeds`

`PolarDiagram.wind_angles`

`PolarDiagram.boat_speeds`

`PolarDiagram.to_csv(csv_path)`

`PolarDiagram.polar_plot_slice(wind_speed, **kwargs)`

`PolarDiagram.flat_plot_slice(wind_speed, **kwargs)`

`PolarDiagram.plot_convex_hull_slice(wind_speed, **kwargs)`

`hrosailing.PolarDiagramTable(true_wind_speed=True, true_wind_angle=True, **kwargs)`

A class to represent, visualize and work with a polar performance diagram in form of a table.

```
>>> wind_angle_resolution = [52,60,75,90,110,120,135,150]
>>> wind_speed_resolution = [6,8,10,12,14,16,20]
>>> data = [[4.06,4.82,5.42,5.83,6.04,6.13,6.16],
...         [4.31,5.11,5.69,6.01,6.2,6.31,6.36],
...         [4.5,5.35,5.89,6.16,6.36,6.52,6.72],
...         [4.45,5.31,5.91,6.21,6.44,6.66,6.99],
...         [4.11,4.98,5.71,6.13,6.39,6.62,7.12],
...         [3.85,4.72,5.49,6.6,6.29,6.53,7.03],
...         [3.39,4.27,5.5,5.64,6.06,6.32,6.78],
...         [2.91,3.78,4.5,5.15,5.72,6.09,6.55]]
>>> polar_table = hrosailing.PolarDiagramTable(data=data,
                                                wind_speed_resolution=wind_speed_resolution,
                                                wind_angle_resolution=wind_angle_resolution)
```

Once initiated one can present the table in a nice way

```
>>> print(polar_table)
TWA \ TWS      6      8     10     12     14     ...      10      12      14      16      20
-----
52  4.06  4.82  5.42  5.83  6.04  ...      5.42  5.83  6.04  6.13  6.16
60  4.31  5.11  5.69  6.01  6.2   ...      5.69  6.01  6.2   6.31  6.36
75  4.5   5.35  5.89  6.16  6.36  ...      5.89  6.16  6.36  6.52  6.72
90  4.45  5.31  5.91  6.21  6.44  ...      5.91  6.21  6.44  6.66  6.99
110 4.11  4.98  5.71  6.13  6.39  ...      5.71  6.13  6.39  6.62  7.12
120 3.85  4.72  5.49  6     6.29  ...      5.49  6     6.29  6.53  7.03
135 3.39  4.27  5     5.64  6.06  ...      5     5.64  6.06  6.32  6.78
150 2.91  3.78  4.5   5.15  5.72  ...      4.5   5.15  5.72  6.09  6.55
```

The `PolarDiagramTable` class defines the following public methods:

Returns a tabulate of the `PolarDiagramTable` object via the `tabulate` function, see [tabulate](#)

If `self._resolution_wind_speed` has more than 15 elements, only the first 15 are used to create the table.

`PolarDiagramTable.__repr__()`

`PolarDiagramTable.wind_speeds`

Returns a read only version of `self._resolution_wind_speed`

`PolarDiagramTable.wind_angles`

Returns a read only version of `self._resolution_wind_angle`

`PolarDiagramTable.boat_speeds`

Returns a read only version of `self._data`

`PolarDiagramTable.to_csv(csv_path)`

**Parameters :**

`csv_path: string`

Path to an existing .csv file or where the created .csv file will be located

Creates or overwrites a .csv file with the class data of object which called the function via the `csv.writer`-class, see [writer](#).

The format of the .csv file will be as follows:

```
PolarDiagramTable
Wind speed resolution:
self.wind_speeds
```

Wind angle resolution:  
self.wind\_angles  
Boat speeds:  
self.boat\_speeds

with the delimiter ','.

PolarDiagramTable.**change\_entry**(data, true\_wind\_speed=True, true\_wind\_angle=True, \*\*kwargs)

**Parameters :**

data : int, float or array\_like of matching shape

true\_wind\_speed : bool

true\_wind\_angle : bool

kwargs : Keywords containing the entries in the "table" that are to be changed and the new data.

- wind\_speed : int, float or Iterable
- wind\_angle : int, float or Iterable

Updates self.\_data on the specified entries with the given new data.

```
>>> polar_table.change_entry(data=4,
...                           true_wind_angle=52,
...                           true_wind_speed=6)
>>> print(polar_table)
```

TWA \ TWS	6	8	10	12	14	16	20
52	4	4.82	5.42	5.83	6.04	6.13	6.16
60	4.31	5.11	5.69	6.01	6.2	6.31	6.36
75	4.5	5.35	5.89	6.16	6.36	6.52	6.72
90	4.45	5.31	5.91	6.21	6.44	6.66	6.99
110	4.11	4.98	5.71	6.13	6.39	6.62	7.12
120	3.85	4.72	5.49	6	6.29	6.53	7.03
135	3.39	4.27	5	5.64	6.06	6.32	6.78
150	2.91	3.78	4.5	5.15	5.72	6.09	6.55

Can be used to change a whole row/column in one go:

```
>>> data = [6, 6.16, 6.3, 6.4, 6.35, 6.26, 6.01, 6.03]
>>> polar_table.change_entry(data=data,
...                           true_wind_angle=14)
>>> print(polar_table)
```

TWA \ TWS	6	8	10	12	14	16	20
52	4	4.82	5.42	5.83	6	6.13	6.16
60	4.31	5.11	5.69	6.01	6.16	6.31	6.36
75	4.5	5.35	5.89	6.16	6.3	6.52	6.72
90	4.45	5.31	5.91	6.21	6.4	6.66	6.99
110	4.11	4.98	5.71	6.13	6.35	6.62	7.12
120	3.85	4.72	5.49	6	6.26	6.53	7.03
135	3.39	4.27	5	5.64	6.01	6.32	6.78
150	2.91	3.78	4.5	5.15	6.03	6.09	6.55

PolarDiagramTable.**polar\_plot\_slice**(wind\_speed, \*\*kwargs)

**Parameters :**

`wind_speed`: int *or* float

Element in `self._resolution_wind_speed`

`kwargs` : Keyword arguments to change the appearance of the created plot.  
Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

For a given column in the table corresponding to the input `wind_speed` , the function returns a polar plot of the column entries together with corresponding wind angles via the `matplotlib.pyplot.plot`-function, see [plot](#)

The function supports the same appearance-keyword arguments as the `matplotlib.pyplot.plot`-function. However, if no `linestyle` or `marker` was specified in the keywords, the function automatically adds the keywords `linestyle = ''` and `marker = 'o'`.

```
>>> polar_table.polar_plot_slice(6)
```

`PolarDiagramTable.flat_plot_slice(wind_speed, **kwargs)`

**Parameters :**

`wind_speed`: int *or* float

Element in `self._resolution_wind_speed`

`kwargs` : Keyword arguments to change the appearance of the created plot.  
Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

For a given column in the table corresponding to the input `wind_speed` , the function returns a kartsian plot of column entries as y-coordinates together with corresponding wind angles as x-coordinates via the `matplotlib.pyplot.plot`-function, see [plot](#)

The function supports the same appearance-keyword arguments as the `matplotlib.pyplot.plot`-function. However, if no `linestyle` or `marker` was specified in the keywords, the function automatically adds the keywords `linestyle = ''` and `marker = 'o'`.

```
>>> polar_table.flat_plot_slice(6)
```

`PolarDiagramTable.plot_convex_hull_slice(wind_speed, **kwargs)`

**Parameters :**

`wind_speed`: int *or* float

Element in `self._resolution_wind_speed`

`kwargs` : Keyword arguments to change the appearance of the created plot.  
Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

For a given column in the table corresponding to the input `wind_speed` , the function computes the convex hull of the column entries together with corresponding wind angles and returns a polar plot of the computed convex hull via the `matplotlib.pyplot.plot`-function, see [plot](#)

```
>>> polar_table.plot_convex_hull_slice(6)
```

`hrosailing.PolarDiagramCurve(f, *params)`

A class to represent, visualize and work with a polar performance diagram given as a fitted curve with a list of optimal parameters

The **PolarDiagramCurve** class defines the following public methods:

PolarDiagramCurve.\_\_str\_\_()

PolarDiagramCurve.\_\_repr\_\_()

PolarDiagramCurve.curve

Returns a read only version of `self._f`

PolarDiagramCurve.parameters

Returns a read only version of `self._params`

PolarDiagramCurve.to\_csv(csv\_path)

**Parameters :**

csv\_path: string

Path to an existing .csv file or where the created .csv file will be located

Creates or overwrites a .csv file with the class data of object which called the function via the `csv.writer`-class, see [writer](#).

The format of the .csv file will be as follows:

PolarDiagramCurve

Function:

self.curve

Parameters:

self.parameters

with the delimiter ','

PolarDiagramCurve.polar\_plot\_slice(wind\_speed, \*\*kwargs)

**Parameters :**

wind\_speed: int or float

kwargs : Keyword arguments to change the appearance of the created plot. Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

PolarDiagramCurve.flat\_plot\_slice(wind\_speed, \*\*kwargs)

**Parameters :**

wind\_speed: int or float

kwargs : Keyword arguments to change the appearance of the created plot. Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

PolarDiagramCurve.plot\_convex\_hull\_slice(wind\_speed, \*\*kwargs)

**Parameters :**

wind\_speed: int or float

kwargs : Keyword arguments to change the appearance of the created plot. Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

`hrosailing.PolarDiagramPointcloud(points=None, true_wind_speed=True, true_wind_angle=True)`

A class to present, visualize and work with a polar performance diagram in form of a point cloud.

The **PolarDiagramPointcloud** class defines the following public methods:

PolarDiagramPointcloud.\_\_str\_\_()

PolarDiagramPointcloud.\_\_repr\_\_()

PolarDiagramPointcloud.**wind\_speeds**

Returns a list of all occurring wind speeds

PolarDiagramPointcloud.**wind\_angles**

Returns a list of all occurring wind angles

PolarDiagramPointcloud.**points**

Returns a read only version of `self._data`

PolarDiagramPointcloud.**to\_csv**(csv\_path)

**Parameters :**

csv\_path: string

Path to an existing .csv file or where the created .csv file will be located

Creates or overwrites a .csv file with the class data of object which called the function via the `csv.writer`-class, see [writer](#).

The format of the .csv file will be as follows:

```
PolarDiagramPointcloud
True Wind Speed: ,True Wind Angle: ,Boat Speed:
self.points
```

with the delimiter ','

PolarDiagramPointcloud.**add\_points**(new\_points, true\_wind\_speed=True, true\_wind\_angle=True)

**Parameters :**

new\_points: array\_like of shape (x, 3)

true\_wind\_speed: bool

true\_wind\_angle: bool

PolarDiagramPointcloud.**change\_points**()

**Parameters :**

PolarDiagramPointcloud.**polar\_plot\_slice**(wind\_speed, \*\*kwargs)

**Parameters :**

wind\_speed: int or float

kwargs : Keyword arguments to change the appearance of the created plot. Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

```
>>> polar_pointcloud.polar_plot_slice(8)
```

PolarDiagramPointcloud.**flat\_plot\_slice**(wind\_speed, \*\*kwargs)

**Parameters :**

wind\_speed: int or float

kwargs : Keyword arguments to change the appearance of the created plot. Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

```
>>> polar_pointcloud.flat_plot_slice(8)
```

PolarDiagramPointcloud.**plot\_convex\_hull\_slice**(wind\_speed, \*\*kwargs)

**Parameters :**

`wind_speed: int or float`

`kwargs` : Keyword arguments to change the appearance of the created plot.  
Supports the same keyword arguments as the `matplotlib.pyplot.plot`-function

```
>>> polar_point_cloud.plot_convex_hull_slice(8)
```