



MUST USE DUMB COIL SETUP IN IGNITION SHEET!!!!!!





rusefi.com

Sheet: /Ignition/
File: IGN6.kicad_sch

Title: UAEFI Ignition

Size: A4


Date: 2023-11-01

Rev:

KiCad E.D.A. 8.0.8

Id: 2/7

$F_{in(max)} = 1/(1.346 \times R28 \times C4)$
 Designing for ~15k max RPM to account for badly money shifting
 f_{max} of cam signal is ~1.4khz at 15000 RPM
 $C = 1.23 \times 10^{-9}$, JLCPCB has 1.2nf caps in stock



Sheet: /LM1815-Cam/
 File: LM1815-Cam.kicad_sch

Title:


Size: A4

Date:

KiCad E.D.A. 8.0.8


Rev:

Id: 3/7





$F_{in(max)} = 1 / (1.346 \times R28 \times C4)$
 Designing for ~15k max RPM to account for badly money shifting
 24 pulse per crankshaft rotation, $F_{in(Max)} = 6000\text{hz}$
 $C = 1.23 \times 10^{-9}$, JLCPCB has 1.2nf caps in stock



Sheet: /LM1815-Crank/
 File: LM1815.kicad_sch

Title:

Size: A4

Date:

KiCad E.D.A. 8.0.8

Rev:

Id: 6/7



rusefi.com

Sheet: /Injector/
File: INJ6.kicad_sch

Title: UAEFI Injector

Size: A4 Date: 2023-11-01

KiCad E.D.A. 8.0.8

Rev:
Id: 9/7