

COMP 2401 B

Test #1 (version 3)

1. [4 marks]

a. [3 marks]

Answer: $0x2e + 151 = 2 \times 16 + 14 + 151 = 46 + 151 = 197$
 $= 2^7 + 2^6 + 2^2 + 2^0 = 1100\ 0101$

Marking:

- 1 mark for correct approach
- 1 mark for correct addition result, given correct approach
- 1 mark for correct answer in binary, given correct approach

b. [1 mark]

Answer: 197

Marking:

- 1 mark for correct answer

2. [8 marks]

a. [2 marks]

Answer: $2^7 + 2^5 + 2^1 + 2^0 + 49 = 128 + 32 + 3 + 49 = 212$
 $212 = 2^7 + 2^6 + 2^4 + 2^2 = 1101\ 0100$

Marking:

- 1 mark for correct approach
- 1 mark for correct answer, given correct approach

b. [4 marks]

Answer: Because it's a signed char and the binary value begins with a 1, the value will be interpreted as a negative number; to get the decimal value, apply two's complement to the binary value:

1101 0100

invert: 0010 1011

add 1: 0010 1100

convert to decimal: $2^5 + 2^3 + 2^2 = 44$

negative value that is printed: -44

Marking:

- 2 marks for correctly applying two's complement
- 2 marks for correct negative decimal value (alt: 1 mark for positive decimal value)

c. [2 marks]

Answer: $2^7 + 2^6 + 2^4 + 2^2 = 212$

Marking:

-- 1 mark for correct approach

-- 1 mark for correct answer, given correct approach

3. [8 marks]

Answer: 0100 0010 1011 0010 0100 0000 0000 0000

-- sign bit: 0

-- fixed point: $89.125 = 2^6 + 2^4 + 2^3 + 2^0 + 2^{-3}$
 $= 1011001.001 = 1.011001001 * 2^6$

-- exponent: $6 + 127 = 133 = 1000\ 0101$

-- fraction: 011001001

Marking:

-- 1 mark for correct sign bit

-- 2 marks for correct fixed point representation

-- 2 marks for correct exponent in binary

-- 2 marks for correct fraction

-- 1 mark for correct final answer, padded with zeros to make 32 bits

4. [30 marks]

a. [6 marks]

```
typedef struct {                                // 1 mark for typedef struct
    char species[MAX_STR_SIZE];                 // 1 mark for species
    char name[MAX_STR_SIZE];                    // 1 mark for name
    int age;                                     // 1 mark for age
    char gender;                                // 1 mark for gender
} AnimalType;                                   // 1 mark AnimalType
```

b. [8 marks]

i. [2 marks] Answer: output

ii. [2 marks] Answer: input

iii. [2 marks] Answer: input

iv. [2 marks] Answer: input-output

c. [16 marks]

```
// 1 mark for looping over correct collection
for (int i=0; i<org->size; ++i) {

// 8 marks for correct condition
// -- 4 marks for correctly comparing species
// -- 2 marks for correctly comparing gender
// -- 2 marks for correctly comparing age
    if ( strcmp(org->animals[i].species, species) == 0
        && org->animals[i].gender == gender
        && org->animals[i].age <= age ) {

// OPTION #1:
// 5 marks for correctly adding to sel
// -- 2 marks for assigning from org current element
// -- 2 marks for assigning to sel
// -- 1 mark for assigning to end of sel
        sel->animals[sel->size] = org->animals[i];
// 2 marks for incrementing sel size
        sel->size++;

// OPTION #2:
// 3 marks for calling addAnimal
// 2 marks for using sel as param
// 2 marks for using org current element
        addAnimal(sel, &(org->animals[i]));
    }
}
```