

Computer Science 3005
2019 Winter
Midterm Examination

TIME: 75 minutes
INSTRUCTOR: Dr. M. Liu

STUDENT NUMBER: _____

NAME: _____
First Name Last Name

Instructions:

1. This is a closed book exam, with no additional material permitted.
2. Verify that your examination consists of 5 pages including this one.
3. Answer all questions in the spaces provided.
4. Please write as legibly as possible. Anything that cannot be read will be marked 0.
5. Total marks for the exam is **74** and you have **75** minutes. Allocate your time wisely.

Part 1 (24 marks)

Explain the following terms as complete as possible. Simply give full name is not acceptable. Each question is 3 marks.

1. Database System:

The database and the applications developed for the users on top of DBMS

2. Relation:

A relation consists of a schema and an instance that is a set of tuples.

3. Database designer:

Responsible to defining the content, the structure, the constraints, and functions or transactions against the database.

4. SQL:

Official language for relational databases that consists DDL, DML, DQL (or QL).

5. Three-Tier Client-Server architecture:

Consists of database server, client and application/web server (to provide more secure database access)

6. Referential Integrity Rule:

The value in the foreign key column (or columns) of the the **referencing relation** can be either a value of an existing primary key value of a corresponding primary key in the **referenced relation**, or just a **null**.

7. Program-data independence:

The capacity to change **data structure** without having to change the associated application programs.

8. Physical data independence:

The capacity to change the internal schema without having to change the conceptual schema.

Part 2 (50 marks)

Consider the following Supplier-Part database with three tables Supplier, Part, and SP. The primary keys are underlined and foreign keys are obvious. Use both relational algebra (ALG) and tuple calculus (TRC) to express the following queries. Each query is 10 marks: Each ALG/TRC is 4 marks and the result is 2 marks.

Supplier

| <u>S#</u> | NAME | STATUS | CITY |
|-----------|-------|--------|--------|
| S1 | Smith | 20 | London |
| S2 | Jones | 30 | Paris |
| S3 | Blake | 30 | Paris |
| S4 | Clark | 20 | London |
| S5 | Adams | 30 | Athens |

Part

| <u>P#</u> | NAME | COLOR | WEIGHT | CITY |
|-----------|-------|-------|--------|--------|
| P1 | Nut | Red | 12.0 | London |
| P2 | Bolt | Green | 17.0 | Paris |
| P3 | Screw | Blue | 17.0 | Oslo |
| P4 | Screw | Red | 14.0 | London |
| P5 | Cam | Blue | 12.0 | Paris |
| P6 | Cog | Red | 19.0 | London |

SP

| <u>S#</u> | <u>P#</u> | QTY |
|-----------|-----------|-----|
| S1 | P1 | 300 |
| S1 | P2 | 200 |
| S1 | P3 | 400 |
| S1 | P4 | 200 |
| S1 | P5 | 100 |
| S1 | P6 | 100 |
| S2 | P1 | 300 |
| S2 | P2 | 400 |
| S3 | P2 | 200 |
| S4 | P2 | 200 |
| S4 | P3 | 300 |
| S4 | P4 | 400 |
| S4 | P5 | 500 |
| S4 | P6 | 600 |

1. Get the names of suppliers who supply P1.

ALG> Project name Select P# = 'P1' (Supplier njoin SP)

TRC> {S.name | S in Supplier and (exists R in SP)(R.S# = S.S# and R.P# = 'P1')};

Result>

Name

Smith

Jones

2. Get the names of suppliers who do not supply any part.

ALG> T1 = Project S# (Supplier) – Project S# (SP)

Project name (T1 njoin Supplier)

TRC> {S.name | S in Supplier and (not exists R in SP)(S.S# = R.S#)};

Other solutions:

{S.name | S in Supplier and (forall R in SP)(S.S# != R.S#)};

Result>

Name

Adams

3. Get names of suppliers who supply all parts.

ALG> T1 = Project S#, P#(SP) / Project P#(Part)
project name (T1 njoin Supplier)

TRC> {S.name | S in Supplier and (forall P in Part)((exists R in SP)(R.S# = S.S# and R.P# = P.P#))};

Other solutions:

{S.name | S in Supplier and not (exists P in Part)(
not (exists R in SP)(R.S# = S.S# and R.P# = P.P#))};

Result>

Name

Smith

4. Get the names of suppliers who supply all parts except P1.

ALG> T1 = Project S#,P#(SP) / (Project P# Select P# != 'P1' (Part))
T2 = T1 – (Project S# (Select P# = 'P1' (Supplier njoin SP)))
Project name (T2 njoin Supplier)

TRC> {S.name | S in Supplier and (forall P in Part)(
P.P# = 'P1' AND not (exists R in SP)(R.P# = P.P# and S.S# = R.S#)
OR
P.P# != 'P1' AND (exists R in SP)(R.P# = P.P# and S.S# = R.S#))};

Other solutions:

{S.name | S in Supplier and (not exists P in Part)(
(P.P# != 'P1' OR (exists R in SP)(R.P# = P.P# and S.S# = R.S#))
AND
(P.P# = 'P1' OR not (exists R in SP)(R.P# = P.P# and S.S# = R.S#))
)};

{S.name | S in Supplier and (not exists P in Part)(
P.P# = 'P1' AND (exists R in SP)(R.P# = P.P# and S.S# = R.S#)
OR
P.P# != 'P1' AND not (exists R in SP)(R.P# = P.P# and S.S# = R.S#)
)};

Result>

Name

Clark

5. Get the names of suppliers who supply more than two parts using aggregate operations.

Both >2 and >=2 are acceptable.

ALG> T1(S#, count) = Aggregate S#, count(P#) (Supplier njoin SP);
Project name Select count > 2 (T1 njoin Supplier)

TRC> T(name, count) = {S.name, count(R.P#) | S in Supplier and R in SP and R.S# = S.S#};
{T.name | T in T and T.count > 2};

Result>
Name
Smith
Clark