

# SMART DISPLAY MODULE SPECIFICATION

1.75 Inch AI Smart Display with Touch	
<b>Model:</b>	SmartRing
<b>Version:</b>	V1.0
<b>Date:</b>	2025-04-20

## Customer Confirmation

Approved by	Notes

## REVISION HISTORY

Revision	Date	Contents of Revision Change	Remark
V1.0	20250420	Preliminary release	

## TABLE of CONTENTS

<b>1. INTRODUCTION .....</b>	<b>4</b>
<b>2. PRODUCT INFORMATION .....</b>	<b>6</b>
2.1 Display Information .....	6
2.2 PIN Information .....	7
2.3 Voltage & Current .....	8
2.4 Reliability Test .....	8
<b>3. MECHANICAL DRAWING .....</b>	<b>9</b>

## 1. Introduction



### Brief Info:

- 1) Outline Dimension:  $\phi$  55 Round
- 2) Thickness: 9mm
- 3) Interaction Method: Rotate and Press
- 4) Shell Color: Black/Silver/Customized
- 5) Power: DC 5V, 100mA

### System

- 1) OS: RTOS
- 2) CPU: ESP32-S3 240Mhz
- 3) RAM: 8MB
- 4) Flash: 16MB
- 5) Interface: UART/USB
- 6) Support 2.4GHz Wi-Fi、BLE 5、BLE Mesh

For more information on ESP32-S3-R8, please refer to the following link:[datasheet\\_en.pdf](#)(English)  
or [datasheet\\_cn.pdf](#)(Chinese)

### Display

- 1) Size: 1.75 Inch
- 2) Resolution: 466\*466
- 3) Mode: AMOLED
- 4) Driver IC: CO5300

- 5) Interface type: QSPI/MIPI ( This product uses a QSPI interface )
- 6) Brightness: 700 cd/m<sup>2</sup>
- 7) Touch IC: CST9217

#### **PCM**

- 1) Model: PCM5100APWR
- 2) For more information: [datasheet](#)

#### **MIC**

- 1) Model: MSM261D4030H1CPM
- 2) For more information: [datasheet](#)

#### **IMU**

- 1) Model: QMI8658C
- 2) For more information: [datasheet](#)

#### **Other**

- 1) Operation Temperature: -20~60°C
- 2) Storage Temperature: -30~70°C

## 2. Product information

### 2.1 Display Information

Item	Specification	Unit	Remark
Display type	AMOLED	-	-
Screen Size	1.75	Inch	Diagonal
Resolution	466*466	Dots	-
Module Power Consumption	-	Watt	
Active Area	Φ43.76	mm	-
Pixel pitch (W*H)	82.2	mm	-
Module Size (W*H*D)	45.93(W)*46.35(H)*0.8(D)	mm	
Driver IC	CO5300	-	
Interface Mode	MIPI/QSPI	-	
Display mode	Normal Black	-	
Luminance	700	cd/m <sup>2</sup>	Typ.
Viewing Direction	ALL	O'clock	-
Display Color	16.7M	Colors	24bits
PPI	273	-	
TP IC	CST9217	-	
TP Outline(assembly)	48.16(H) × 48.16(V) × 1.1(T)	mm	
TP Viewing Area	Φ44.16	mm	

## 2.2 PIN Information

ESP Pin NO.	FUNCTION
GPIO0	BOOT
GPIO1	SDMMC_D1
GPIO2	SDMMC_D0
GPIO3	SDMMC_SCK
GPIO4	SDMMC_CMD
GPIO5	SDMMC_D3
GPIO6	SDMMC_D2
GPIO7	LCD_QSPI_CS
GPIO8	LCD_QSPI_D1
GPIO9	LCD_QSPI_D3
GPIO10	LCD_TE
GPIO11	LCD_RST
GPIO12	LCD_QSPI_D0
GPIO13	LCD_QSPI_SCL
GPIO14	LCD_QSPI_D2
GPIO15	XSMT
GPIO16	I2S_DAC_LRCK/WS
GPIO17	I2S_DAC_DIN
GPIO18	I2S_DAC_BCK
GPIO19	USB_N
GPIO20	USB_P
GPIO21	IMU_INT1
GPIO38	IMU_INT2
GPIO39	RGB_DIN
GPIO40	LCD_VCIEN
GPIO41	TP_SDA
GPIO42	TP_INT
GPIO43	UART0_RX
GPIO44	UART0_TX
GPIO45	TP_SCL
GPIO46	TP_RST

## 2.3 Voltage & Current

Item	Conditions	Min	Typ	Max	Unit
Power Voltage	DC	4.0	5.0	5.5	V
Operation	VCC= +5V, Maximum backlight current	-	200	-	mA
Recommended power supply:5V 1A DC					

## 2.4 Reliability Test

Item	Conditions	Min	Typ	Max	Unit
Working Temperature	60%RH at 5V voltage	-20	25	60	C
Storage Temperature	---	-30	25	70	C
Working Humidity	25°C	10%	60%	90%	RH
ESD	---	Contact: ±4KV Air: ±8KV			KV



## 3. MECHANICAL DRAWING

