



We are on a mission to address the digital skills gap for 10 Million+ young professionals, train and empower them to forge a career path into future tech

Handling Browser - Navigation

APRIL, 2026



Contents

- Browser Commands
- Navigation Commands
- Web Elements Commands

Browser Commands



Browser Commands

Browser Commands

- Listed below are the basic and most commonly used Browser Commands in Selenium Webdriver:
 1. Get command
 2. Title command
 3. Current URL command
 4. Page Source Command
 5. Close command
 6. Quit command

Browser Commands

Browser Commands

1. Get command

- The get() method takes a string URL as a parameter and returns nothing.
- This method opens the specified URL in the current browser window.
- URL must be in the form of <https://www.google.com>.
- If the HTTPS is not included then it will throw a message “Cannot navigate to invalid URL”.
- The general syntax to use get command is as follows:

get (String arg) : void

- Example

driver.get(“https://www.google.com”) OR URL = “https://www.google.com”
driver.get(URL)

Browser Commands

Browser Commands

2. Title command

- The **title method** takes nothing as a parameter and returns the page title of the currently loaded web page. If the web page has no title, it will return a null String.
- The general syntax to use title command is as follows:

driver.title

OR

Title = driver.title

Browser Commands

Browser Commands

3. Current URL command

- The **current_url method** takes nothing as a parameter and returns URL of the web page currently loaded in the browser.
- This method is used to get string URL of the current web page loaded in the opened browser.
- The general syntax to use current_url command is as follows:

driver.current_url

OR

CurrentUrl = driver.current_url

Browser Commands

Browser Commands

4. Page Source command

- The **page_source method** accepts nothing as a parameter and returns the source code of the current web page.
- This method is used to get the page source code of the currently loaded web page.
- The general syntax to use **page_source** command is as follows:

driver.page_source

OR

pageSource = driver.page_source

Browser Commands

Browser Commands

5. Close command

- The close method takes nothing as a parameter and returns nothing.
- This method is used to close only the browser window that web driver is currently controlling.
- The general syntax to use close command is as follows:

driver.close()

Browser Commands

Browser Commands

6. Quit command

- The quit() method accepts nothing as a parameter and returns nothing.
- This method is used to close all the browser window that web driver opened.
- The general syntax to use quit command is as follows:

driver.quit()

Browser Commands

Browser Commands – Practice

Practice Exercise - 1

- 1. Launch a new Chrome browser.*
- 2. Open Flipkart Web Application*
- 3. Get Page Title name and Title length*
- 4. Print Page Title and Title length on the Eclipse Console.*
- 5. Get Page URL and verify if it is a correct page opened*
- 6. Get Page Source (HTML Source code) and Page Source length*
- 7. Print Page Length in Console.*
- 8. Close the Browser.*

Navigation Commands



Navigation Commands

Navigation Commands

- Listed below are the most commonly used Navigation Commands in Selenium WebDriver:

1. Back command
2. Forward command
3. Refresh commands



Navigation Commands

Navigate using commands

Command used for navigation with the help of command

- **driver.forward()** -Takes you forward by one page on the browser's history.
- **driver.back()** -Takes you back by one page on the browser's history.
- **driver.refresh()** -Takes you back the refreshed current URL in the browser.

Note : return type is void and these commands will not accept any parameter.

Sample Java Selenium Program

```
import time
from selenium import webdriver
from selenium.webdriver.common.by import By

driver = webdriver.Chrome()

driver.maximize_window()
driver.get("https://www.google.co.in")

time.sleep(3)

driver.get("https://www.flipkart.com")

driver.back()
time.sleep(3)
driver.forward()
time.sleep(3)
#driver.refresh()
```

Navigation Commands

navigation Commands – Practice

Practice Exercise – 1

- 1. Launch new Browser*
- 2. Open **<https://www.toolsqa.com/selenium-training/>** website*
- 3. Click on Registration link using "driver.find_element(By.XPATH, value=" ").click()*
- 4. Come back to Home page (Use 'Back' command)*
- 5. Again go back to Registration page (This time use 'Forward' command)*
- 6. Again come back to Home page (This time use 'To' command)*
- 7. Refresh the Browser (Use 'Refresh' command)*
- 8. Close the Browser*

Web Element Commands



Web Elements Commands

Web Elements Commands

- Web element refers to an HTML element, which contains a start tag, an end tag and the content in between.
- Listed below are the basic and most commonly used Web Elements Commands in Selenium Webdriver:

1. clear Command

2. click Command

3. text Command

4. is_selected Command

5. is_enabled Command

6. is_displayed Command

7. size Command

8. value_of_css_property Command

9. location Command

10. submit Command

11. get_attribute Command

12. tag_name Command

13. send_keys Command

14. save_screenshot Command

Web Elements Commands

Web Elements Commands

1. Clear command

- The Clear() method has no effect on other elements.
- If this element is a text entry element, this will clear the value.
- This method accepts nothing as a parameter and returns nothing.
- Text entry elements are INPUT and TEXTAREA elements.
- Example

```
element = driver.find_element(By.id, value="UserName")  
  
element.clear()
```

OR

```
driver.find_element(By.id, value="UserName").clear()
```

Web Elements Commands

Web Elements Commands

2. Click command

- This command helps to interact with web elements like text elements, links, radio boxes and many more.
- This method accepts nothing as a parameter and returns nothing.
- Example

```
element = driver.find_element(By.LINK_TEXT, value="ToolsQA")  
element.click()
```

OR

```
driver.find_element(By.LINK_TEXT, value="ToolsQA").click();
```

Web Elements Commands

Web Elements Commands

3. Text command

- This command retrieves the visible inner-Text of the element. This accepts nothing as a parameter but returns a String value.
- Command : Element.text
- This returns an innerText of the element, including sub-elements, without any leading or trailing whitespace.
- Example

```
element = driver.find_element(By.xpath, value="anyLink").text
```

Web Elements Commands

Web Elements Commands

4. is_enabled command

- is_enabled() method is used to check if the web element is enabled or disabled within the web page.
- This method returns “true” value if the specified web element is enabled on the web page otherwise returns “false” value if the web element is disabled on the web page.
- Example

```
element = driver.find_element(By.id, value="UserName")
```

```
status = element.is_enabled()
```

//Or can be written as

```
status = driver.find_element(By.id, value="UserName").is_enabled()
```

Web Elements Commands

Web Elements Commands

4. is_enabled command

- Example :

```
element = driver.find_element(By.id, value="userName")  
status = element.is_enabled()  
  
// Check that if the Text field is enabled, if yes enter value  
  
if(status)  
{  
    element.send_keys("ToolsQA")  
}
```

Web Elements Commands

Web Elements Commands

5. is_displayed command

- The is_displayed() method is used to check whether an element is displayed on a web page or not.
- It returns a boolean value (true) if the target element is displayed otherwise returns false.
- Example

```
element = driver.find_element(By.id, value="UserName")
```

```
status = element.is_displayed()
```

//Or can be written as

```
status = driver.find_element(By.id, value="UserName").is_displayed()
```

Web Elements Commands

Web Elements Commands

6. is_selected command

- The is_selected() method checks that if an element is selected on the web page or not.
- It returns a boolean value (true) if selected, else false for deselected.
- It can be executed only on a radio button, checkbox, and select options.
- Example

```
element = driver.find_element(By.id, value="Sex-Male")
```

```
status = element.is_selected()
```

//Or can be written as

```
status = driver.find_element(By.id, value="Sex-Male").is_selected()
```

Web Elements Commands

Web Elements Commands

7. submit command

- This method works well/better than the click() if the current element is a form, or an element within a form.
- This accepts nothing as a parameter and returns nothing.
- Example

```
element = driver.find_element(By.id, value="SubmitButton")
```

```
element.submit()
```

//Or can be written as

```
driver.find_element(By.id, value="SubmitButton").submit()
```

Web Elements Commands

8. `get_attribute` command

- This method gets the value of the given attribute of the element.
- This accepts the String as a parameter and returns a String value.
- Attributes are Ids, Name, Class extra and using this method you can get the value of the attributes of any given element.
- Example

```
element = driver.find_element(By.id, value="SubmitButton")
```

```
attValue = element.get_attribute("id") //This will return "SubmitButton"
```

Web Elements Commands

Web Elements Commands

9. tag_name command

- This method gets the tag name of this element.
- This accepts nothing as a parameter and returns a String value.
- This does not return the value of the name attribute but return the tag for e.g. "input" for the element `<input name="foo"/>`.
- Example

```
element = driver.find_element(By.id, value="SubmitButton")
```

```
tagName = element.tag_name
```

//Or can be written as

```
tagName = driver.find_element(By.id, value="SubmitButton").tag_name
```

Web Elements Commands

Web Elements Commands

10. size command

- This method fetch the width and height of the rendered element.
- This accepts nothing as a parameter but returns dictionary with the height and width of the element.
- This method returns the size of the element on the page.
- Example

```
element_size = driver.find_element(By.id, value="SubmitButton").size  
  
print(element.size)
```

Web Elements Commands

Web Elements Commands

11.value_of_css_property command

- This method fetch CSS property value of the give element.
- This accepts nothing as a parameter and returns a String value.
- Example

```
element = driver.find_element(By.id, value="SubmitButton")  
  
print(elementcss_property.value_of_css_property('height'))
```

Web Elements Commands

Web Elements Commands

12. location command

- This method locate the location of the element on the page.
- This accepts nothing as a parameter but returns the Point object.
- This returns the dictionary object, from which we can get **X and Y coordinates of specific element.**
- Example

```
element = driver.find_element(By.id, value="SubmitButton")  
  
print(element.location)
```

Web Elements Commands

Web Elements Commands

13. send_keys command

- This command simulates typing into an element, which may set its value.
- This method accepts CharSequence as a parameter and returns nothing.
- This method works fine with text entry elements like **INPUT** and **TEXTAREA** elements.
- Example

```
element = driver.find_element(By.id, value="UserName")
```

```
element.send_keys("ToolsQA")
```

//Or can be written as

```
driver.find_element(By.id, value="UserName").send_keys("ToolsQA")
```

Web Elements Commands

Web Elements Commands

14. save_screenshot command

- save_screenshot method allows user to save the webpage as a png file.
- **Argument :**
filename or the full path you wish to save your screenshot to.
- **Action performed :**
The screenshot will be saved in the same directory as the program, if path is provided screenshot will be saved at that location only.
- Example

```
driver.save_screenshot("homepage.png")
```

or

```
driver.save_screenshot("homepage.png")
```

WebElements Commands

Web Elements Commands – Practice

Practice Exercise – 1

1. Launch the web browser and open the application under test – <https://www.google.com>
2. Verify the web page title.
3. Verify that “Google Search Box” is enabled or not.
4. Enter the text **Selenium** in the “Google Search” box.
5. Verify that the “Google Search button” is enabled or not.
6. Click the Search Button

WebElements Commands

Web Elements Commands – Practice

Practice Exercise – 2

1. Launch the web browser and open the application under test – <https://www.google.com>
2. Verify the web page title.
3. Verify that “Google Search Box” is displayed or not.
4. Enter the text in the “Google Search” box.
5. Verify that the “Google Search button” is displayed or not.

WebElements Commands

Web Elements Commands – Practice

Practice Exercise – 3

1. Launch web browser and open the application under test –
<https://selenium08.blogspot.com/2019/07/check-box-and-radio-buttons.html>
2. Verify that “Red checkbox” is enabled or not.
3. Check that “Red checkbox” is selected or not.
4. Check that “Opera radio button” is selected or not.

THANK YOU