

VIKAMI

PRODUCT SAFETY & REGULATORY DOCUMENT

PRIMA - CRYSTAL PINK POWDER

PRODUCT CODE	PHYSICAL FORM	SIGNAL WORD	PRIMARY HAZARDS
4021123BK	Powder	Warning	Combustible dust; skin sensitization Category 1

1

IDENTIFICATION

GHS product identifier	PRIMA - CRYSTAL PINK POWDER
Product code	4021123BK
Other means of identification	Not available.
Product type	Powder.
Relevant identified uses and uses advised against	Not applicable.
Supplier details	VIKAMI #15, 1011 57 Avenue NE Calgary, AB T2E 8X9, Canada +1 403-207-0208 info@vikami.com www.vikami.com
Emergency telephone number	(800) 535-5053

2

HAZARDS IDENTIFICATION

OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	COMBUSTIBLE DUSTS SKIN SENSITIZATION - Category 1

GHS label elements

	Signal word Warning	Hazard statements May cause an allergic skin reaction. May form combustible dust concentrations in air.
---	-------------------------------	--

Prevention	Wear protective gloves. Avoid breathing dust or mist. Contaminated work clothing must not be allowed out of the workplace.
Response	Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation.
Hazards not otherwise classified	None known.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Substance / mixture	Mixture
Other means of identification	Not available.

Ingredient name	%	CAS number
dibenzoyl peroxide	≤3	94-36-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4 FIRST AID MEASURES

Description of necessary first aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, keep the head low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms / effects, acute and delayed

Eye contact	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes. Adverse symptoms may include irritation and redness.
Inhalation	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. Adverse symptoms may include respiratory tract irritation and coughing.
Skin contact	May cause an allergic skin reaction. Adverse symptoms may include irritation and redness.
Ingestion	No known significant effects or critical hazards. No specific data.

Indication of immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11).

5 FIRE-FIGHTING MEASURES

Suitable extinguishing media	Use dry chemical powder.
Unsuitable extinguishing media	Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	Decomposition products may include carbon dioxide and carbon monoxide.
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
--------------------	--

Large spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. See Section 1 for emergency contact information and Section 13 for waste disposal.
--------------------	--

7 HANDLING AND STORAGE

Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See Section 8 for additional information on hygiene measures.
Conditions for safe storage, including incompatibilities	Do not store above 240°C (464°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters - occupational exposure limits

Ingredient	Exposure limits
dibenzoyl peroxide	ACGIH TLV (United States, 1/2022): TWA 5 mg/m ³ , 8 hours. OSHA PEL 1989 (United States, 3/1989): TWA 5 mg/m ³ , 8 hours. NIOSH REL (United States, 10/2020): TWA 5 mg/m ³ , 10 hours. OSHA PEL (United States, 5/2018): TWA 5 mg/m ³ , 8 hours.

Biological exposure indices: No exposure indices known.

Appropriate engineering controls	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Use appropriate techniques to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation.
Eye / face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, wear safety glasses with side-shields unless a higher degree of protection is indicated. If operating conditions cause high dust concentrations, use dust goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn whenever a risk assessment indicates this is necessary. Check during use that gloves retain their protective properties. Breakthrough time varies among glove materials and manufacturers. For mixtures, protection time cannot be accurately estimated.
Body protection	Personal protective equipment for the body should be selected based on the task and risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection should be selected based on the task and risks involved and approved by a specialist.

Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training and other important aspects of use.
-------------------------------	---

9

PHYSICAL AND CHEMICAL PROPERTIES AND SAFETY CHARACTERISTICS

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Physical state	Solid. [Powder.]
Color	Pink [Light]
Odor	Faint odor. [Slight]
Odor threshold	Not available.
pH	Not available.
Melting point / freezing point	Not available.
Boiling point, initial boiling point and range	Not available.
Flash point	Closed cup: >93.3°C (>199.9°F) [Tagliabue] [Product does not sustain combustion.]
Flammability	Not available.
Lower and upper explosion / flammability limit	Not applicable.
Vapor pressure	Not applicable.
Relative vapor density	Not applicable.
Relative density	Not available.
Solubility in water	Not available.
Partition coefficient: n-octanol/water	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Median particle size	Not available.

Solubility(ies)

Media	Result
Cold water	Not soluble
Hot water	Not soluble

10 STABILITY AND REACTIVITY

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	Reactive or incompatible with oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Product / ingredient	Result	Species	Dose	Exposure
dibenzoyl peroxide	LD50 Oral	Rat	6400 mg/kg	-

Irritation / corrosion

Product / ingredient	Result	Species	Score	Exposure	Observation
dibenzoyl peroxide	Skin - Moderate irritant	Woman	-	1%	-
dibenzoyl peroxide	Skin - Severe irritant	Human	-	1344 hours; 5%	-

Sensitization	Not available.
Mutagenicity	Not available.
Carcinogenicity	Not available.
Reproductive toxicity	Not available.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	Not available.
Specific target organ toxicity - repeated exposure	Not available.
Aspiration hazard	Not available.
Information on likely routes of exposure	Not available.

Carcinogenicity classification

Product / ingredient	OSHA	IARC	NTP
dibenzoyl peroxide	-	3	-

Potential acute health effects and related symptoms

Eye contact	Exposure above statutory or recommended limits may cause irritation of the eyes. Adverse symptoms may include irritation and redness.
Inhalation	Exposure above statutory or recommended limits may cause irritation of the nose, throat and lungs. Adverse symptoms may include respiratory tract irritation and coughing.
Skin contact	May cause an allergic skin reaction. Adverse symptoms may include irritation and redness.
Ingestion	No known significant effects or critical hazards. No specific data.

Delayed and immediate effects; chronic effects from short- and long-term exposure

Short-term exposure - potential immediate effects	Not available.
Short-term exposure - potential delayed effects	Not available.
Long-term exposure - potential immediate effects	Not available.
Long-term exposure - potential delayed effects	Not available.
Potential chronic health effects	Not available.
General	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Reproductive toxicity	No known significant effects or critical hazards.

Numerical measures of toxicity - acute toxicity estimates

Product / ingredient	Oral (mg/kg)	Dermal (mg/kg)	Inhalation gases (ppm)	Inhalation vapors (mg/L)	Inhalation dusts and mists (mg/L)
dibenzoyl peroxide	6400	N/A	N/A	N/A	N/A

12 ECOLOGICAL INFORMATION

Toxicity

Product / ingredient	Result	Species	Exposure
dibenzoyl peroxide	EC50 0.83 mg/L	Algae	72 hours
dibenzoyl peroxide	EC50 0.07 mg/L	Daphnia	48 hours
dibenzoyl peroxide	LC50 2 mg/L	Fish	96 hours

Persistence and degradability

Product / ingredient	Test	Result	Dose	Inoculum
dibenzoyl peroxide	-	60% - 28 days	-	-

Product / ingredient	Aquatic half-life	Photolysis	Biodegradability
dibenzoyl peroxide	-	-	Inherent

Bioaccumulative potential

Product / ingredient	LogPow	BCF	Potential
dibenzoyl peroxide	3.2	-	Low

Soil / water partition coefficient (Koc)	Not available.
Other adverse effects	No known significant effects or critical hazards.

13 DISPOSAL CONSIDERATIONS

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with environmental protection and waste disposal legislation and regional local authority requirements. Dispose of surplus and non-recyclable products through a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with all authorities having jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of safely. Take care when handling emptied containers that have not been cleaned or rinsed. Empty containers or liners may retain product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14 TRANSPORT INFORMATION

Item	DOT	TDG	Mexico	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments

Not available.

15 REGULATORY INFORMATION

U.S. Federal regulations

TSCA 8(a) CDR Exempt / Partial exemption	Not determined.
Clean Air Act Section 112(b) Hazardous Air Pollutants	Not listed.
Clean Air Act Section 602 Class I Substances	Not listed.
Clean Air Act Section 602 Class II Substances	Not listed.
DEA List I Chemicals (Precursor Chemicals)	Not listed.
DEA List II Chemicals (Essential Chemicals)	Not listed.
SARA 302 / 304	No products were found.
SARA 304 RQ	Not applicable.
SARA 311 / 312 classification	COMBUSTIBLE DUSTS SKIN SENSITIZATION - Category 1

SARA 311 / 312 - composition / information on ingredients

Name	%	Classification
dibenzoyl peroxide	≤3	ORGANIC PEROXIDES - Type B SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

SARA 313

Requirement	Product name	CAS number	%
Form R - Reporting requirements	dibenzoyl peroxide	94-36-0	≤3
Supplier notification	dibenzoyl peroxide	94-36-0	≤3

SARA 313 notifications must not be detached from the SDS. Any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies subsequently redistributed.

State regulations

Massachusetts	The following components are listed: BENZOYL PEROXIDE.
New York	None of the components are listed.
New Jersey	The following components are listed: BENZOYL PEROXIDE.
Pennsylvania	The following components are listed: PEROXIDE, DIBENZOYL.
California Proposition 65	This product does not require a Safe Harbor warning under California Prop. 65.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals	Not listed.
Montreal Protocol	Not listed.
Stockholm Convention on Persistent Organic Pollutants	Not listed.
Rotterdam Convention on Prior Informed Consent (PIC)	Not listed.
UNECE Aarhus Protocol on POPs and Heavy Metals	Not listed.

Inventory list

Australia	All components are listed or exempted.
Canada	All components are listed or exempted.
China	All components are listed or exempted.
Eurasian Economic Union	Russian Federation inventory: All components are listed or exempted.
Japan	Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
New Zealand	All components are listed or exempted.
Philippines	All components are listed or exempted.
Republic of Korea	All components are listed or exempted.
Taiwan	All components are listed or exempted.
Thailand	Not determined.
Turkey	Not determined.
United States	Not determined.
Viet Nam	Not determined.

16 OTHER INFORMATION

Hazardous Material Information System (U.S.A.)

Health	Flammability	Physical hazards
1	1	1

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc. The customer is responsible for determining the PPE code for this material. For more information, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health	Flammability	Instability	Special hazards
1	1	1	-

Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS	On basis of test data
SKIN SENSITIZATION - Category 1	Calculation method

HISTORY

Item	Value
Date of printing	2026-08-05
Date of issue / revision	2026-08-05
Previous technical issue	2022-11-16
Version	1.0
References	Not available.

KEY TO ABBREVIATIONS

ATE = Acute Toxicity Estimate; BCF = Bioconcentration Factor; GHS = Globally Harmonized System of Classification and Labelling of Chemicals; IATA = International Air Transport Association; IBC = Intermediate Bulk Container; IMDG = International Maritime Dangerous Goods; LogPow = logarithm of the octanol/water partition coefficient; MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978; N/A = Not available; SGG = Segregation Group; UN = United Nations.

Notice to reader

VIKAMI NOTICE

To the best of VIKAMI's knowledge, the information contained herein is accurate. VIKAMI assumes no liability for the accuracy or completeness of this information. Final determination of suitability is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described, VIKAMI cannot guarantee that these are the only hazards that exist. This SDS is only to be distributed as required by law.