



SYT Series

30KW to 40KW

The SYT Series infuses capacity with higher efficiency in a lightweight compact design. The option ranges from 30KW to 40KW that yields high performance for longer generation.

- ✓ Best Compatible with Bifacial PV and N-Type TOPCON Modules
- ✓ PV String Current Monitoring
- ✓ AFCI Function
- ✓ IP66 and C5 Protection
- ✓ 40A Input Current



PV String Current Monitoring



PID Recovery



IP66 Rating



LED, Wi-Fi + App

- ✓ Smart Air Cooling
- ✓ Surge Protection Type II (DC & AC)

- ✓ Max. Efficiency 98.3%
- ✓ Insulation Monitoring

THREE PHASE INVERTERS

MODEL SYT	30KW	33KW	35KW	40KW
INPUT (DC)				
Max. Input Voltage [V]			1100	
Start-up Input Voltage [V]			200	
MPPT Operating Voltage Range [V]			200 ~ 1000	
MPPT Operating Voltage Range (Full load) [V]	330-850	370-850	300-850	350-850
Max. Input Current [A]	3*40	3*40	3*40	3*40
Max. Short-circuit Current [A]	3*52	3*52	3*52	3*52
No. of Independent MPP Trackers			3	
No. of Strings per MPP Tracker			2	
OUTPUT (AC)				
Rated Output Power [W]	30000	33000	35000	40000
Rated Grid Voltage [V]		3/N/PE, 220/380, 230/400, 240/415		
Rated Grid Frequency [Hz]		50/60		
Rated Output Current [A]	43.5	47.8	52.2	58.0
Power Factor			1 (Adjustable from 0.8 leading to 0.8 lagging)	
Total Harmonic Distortion (THDi) [%]			<3	
EFFICIENCY				
Euro-Efficiency [%]			98.1	
Max MPPT Efficiency [%]			99.8	
Max. Efficiency [%]			98.3	
PROTECTION				
Insulation Monitoring			YES	
Residual Current Monitoring			YES	
PV String Current Monitoring			YES	
DC Reverse Polarity Protection			YES	
Anti-islanding Protection			YES	
AC Short-circuit Protection			YES	
AC Overcurrent Protection			YES	
AC Overvoltage Protection			YES	
Surge Protection			DC/AC: Type II	
DC Switch			YES	
PID			YES	
AFCI			YES	
GENERAL DATA				
Dimensions (W x H x D) [mm]		580*430*263		
Weight [kg]		33		
Cooling Method		FAN		
Topology		Non-isolated		
Noise Emission (typical) [dB]		<55		
Max. Operating Altitude [m]		3000		
Operating Temperature Range		-25 ~ 60 (Derating at +45°C)		
Humidity [%]		0 ~ 100 (No Condensation)		
Protection Degree		IP66		
Internal Consumption at Night [W]		<1		
Monitoring Module		WLAN / 4G (Optional)		
Communication		RS485, Meter		
Display		LED, App, Website		