

# SYS Series

## 2KW-4.6KW

The SYS series of our company consists of single-phase inverters that infuse the best technology with an integrated streamlined case design. With 20A DC Current, it is robust for residential and commercial spaces.

Best compatible with Bifacial PV and N-Type TOPCON modules



DC Input 200% with a higher MPPT Range with inbuilt global MPP scan for higher yield efficiency



AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported.



10s level interval of data update (Optional) and multiple interfaces for presenting data.



IP 65 rated, engineered to last with maximum flexibility, making it suitable for outdoor installation.

# Single Phase Inverters

| Model                                       | 2KW                                                                                                             | 2.3KW | 2.5KW | 3KW  | 3.3KW | 3.6KW | 4KW   | 4.2KW | 4.6KW |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------|-------|-------|------|-------|-------|-------|-------|-------|
| DC INPUT                                    |                                                                                                                 |       |       |      |       |       |       |       |       |
| MAX DC Voltage [V]                          | 500                                                                                                             |       |       |      |       |       |       |       |       |
| MPPT voltage range [V]                      | 40-500                                                                                                          |       |       |      |       |       |       |       |       |
| Rated Voltage DC [V]                        | 360                                                                                                             |       |       |      |       |       |       |       |       |
| Start-up Voltage [V]                        | 60                                                                                                              |       |       |      |       |       |       |       |       |
| 60 Max DC current /MPPT [A]                 | 20                                                                                                              |       |       |      |       |       |       |       |       |
| No of MPPT                                  | 1                                                                                                               |       |       |      |       |       |       |       |       |
| No of Strings per MPPT 1                    | 1                                                                                                               |       |       |      |       |       |       |       |       |
| Short Circuit Current Isc. [A]              | 26                                                                                                              |       |       |      |       |       |       |       |       |
| OUTPUT (AC)                                 |                                                                                                                 |       |       |      |       |       |       |       |       |
| Nominal AC Output power [W]                 | 2000                                                                                                            | 2300  | 2500  | 3000 | 3300  | 3600  | 4000  | 4200  | 4600  |
| Rated AC Current [A]                        | 8.7                                                                                                             | 10    | 10.9  | 13.1 | 14.4  | 15.65 | 17.40 | 18.26 | 21.39 |
| Rated Voltage                               | 220-230V -240V/ 50 Hz as Per the Indian Grid Standards                                                          |       |       |      |       |       |       |       |       |
| voltage Range                               | 160-290V Variable                                                                                               |       |       |      |       |       |       |       |       |
| Frequency Range [Hz]                        | 50/60; ±5                                                                                                       |       |       |      |       |       |       |       |       |
| AC connection Configuration                 | P+N+E                                                                                                           |       |       |      |       |       |       |       |       |
| Power Factor                                | >0.99%, 0.8 leading - 0.8 lagging                                                                               |       |       |      |       |       |       |       |       |
| THD                                         | <3%                                                                                                             |       |       |      |       |       |       |       |       |
| Self-consumption [W]                        | <0.2                                                                                                            |       |       |      |       |       |       |       |       |
| DC Current Injection                        | <0.25%                                                                                                          |       |       |      |       |       |       |       |       |
| EFFICIENCY                                  |                                                                                                                 |       |       |      |       |       |       |       |       |
| MPPT efficiency                             | 98.00%                                                                                                          |       |       |      |       |       |       |       |       |
| FEATURES/PROTECTIONS                        |                                                                                                                 |       |       |      |       |       |       |       |       |
| Display type (LED/LCD)                      | 2 * 16-character LCD Display with LED Indicators                                                                |       |       |      |       |       |       |       |       |
| Communication Port                          | GPRS/ WIFI / RS-485/USB/Ethernet                                                                                |       |       |      |       |       |       |       |       |
| GFM/OT/ RCD/DC Rev Pol /Anti-Islanding /OCP | INTEGRATED                                                                                                      |       |       |      |       |       |       |       |       |
| DC Switch /Anti-PID feature                 | OPTIONAL                                                                                                        |       |       |      |       |       |       |       |       |
| Built-in AC/ DCSPD type                     | TYPE III SPD (GDT)                                                                                              |       |       |      |       |       |       |       |       |
| AMBIENT CONDITIONS                          |                                                                                                                 |       |       |      |       |       |       |       |       |
| Protection level (IP)                       | IP-66                                                                                                           |       |       |      |       |       |       |       |       |
| OT-Range                                    | - 20 °C + 60 °C (>50 °C Derating)                                                                               |       |       |      |       |       |       |       |       |
| Dimensions (W x H x D) mm / Weight          | 290×226×116 /5.4kg                                                                                              |       |       |      |       |       |       |       |       |
| Warranty                                    | As per the company standard policy (inverters + accessories)                                                    |       |       |      |       |       |       |       |       |
| IEC/BIS                                     | BIS16169, BIS16221, IEC61727, IEC62116, IEC61000-1-2-3-4, IEC 62109-1/-2, IEC61683:1999, IEC 60068-2(1,2,14,30) |       |       |      |       |       |       |       |       |