



## SYS Series

4.6KW to 6KW

The SYS series of our company consists of single-phase inverters that infuse the best technology with an integrated streamlined case design. It is robust for residential and commercial spaces.

Best compatible with Bifacial PV and N-Type TOPCON modules



DC Input 200% with a higher MPPT Range with inbuilt global MPP scan for higher yield efficiency



AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported.



10s level interval of data update (Optional) and multiple interfaces for presenting data.



IP 65 rated, engineered to last with maximum flexibility, making it suitable for outdoor installation.

# Single Phase Inverters

| Model SYS                                   | 4.6KW                                                                                                             | 5KW    | 5.3KW  | 5.5KW  | 6KW    |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------|--------|--------|--------|
| DC INPUT                                    |                                                                                                                   |        |        |        |        |
| MAX DC Voltage [V]                          | 600                                                                                                               |        |        |        |        |
| Start-Up Voltage [V]                        | 120                                                                                                               |        |        |        |        |
| Rated Voltage DC [V]                        | 360                                                                                                               |        |        |        |        |
| MPPT operating Range [V]                    | 80-550                                                                                                            |        |        |        |        |
| Max. permissible DC current / MPPT [A]      | 16                                                                                                                |        |        |        |        |
| No of MPPT                                  | 2                                                                                                                 |        |        |        |        |
| No of Strings per MPPT                      | 1+1                                                                                                               |        |        |        |        |
| Short Circuit Current [A]                   | 22                                                                                                                |        |        |        |        |
| OUTPUT (AC)                                 |                                                                                                                   |        |        |        |        |
| Nominal AC Output power [W]                 | 4600                                                                                                              | 5000   | 5300   | 5500   | 6000   |
| Max AC Current [A]                          | 20                                                                                                                | 21.73  | 23     | 25.46  | 26.1   |
| Rated Voltage                               | 220-230V -240V/ 50 Hz as Per the Indian Grid Standards.                                                           |        |        |        |        |
| Operating voltage Range                     | 160-290V Variable                                                                                                 |        |        |        |        |
| Operating Frequency Range                   | 45-55Hz Variable                                                                                                  |        |        |        |        |
| AC connection configuration                 | P+N+E                                                                                                             |        |        |        |        |
| Power Factor                                | >0.99%, 0.8 leading - 0.8 lagging                                                                                 |        |        |        |        |
| THD                                         | <3%                                                                                                               |        |        |        |        |
| Self-consumption (Night) [W]                | <0.2                                                                                                              |        |        |        |        |
| DC Current Injection                        | <0.25%                                                                                                            |        |        |        |        |
| EFFICIENCY                                  |                                                                                                                   |        |        |        |        |
| MPPT efficiency                             | 99.00%                                                                                                            | 98.00% | 99.00% | 99.90% | 98.00% |
| FEATURES/PROTECTIONS                        |                                                                                                                   |        |        |        |        |
| Display type (LED/LCD)                      | 2 * 16-character LCD Display with LED Indicators                                                                  |        |        |        |        |
| Communication Port                          | GPRS/ WIFI / RS-485/USB/Ethernet                                                                                  |        |        |        |        |
| GFM/OT/ RCD/DC Rev Pol /Anti-Islanding /OCP | INTEGRATED                                                                                                        |        |        |        |        |
| DC Switch /Anti-PID feature                 | OPTIONAL                                                                                                          |        |        |        |        |
| Built-in AC/ DCSPD type                     | TYPE III SPD (GDT)                                                                                                |        |        |        |        |
| AMBIENT CONDITIONS                          |                                                                                                                   |        |        |        |        |
| Operating Temperature Range                 | - 20 °C + 60 °C (>50 °C Derating                                                                                  |        |        |        |        |
| Protection level (IP)                       | IP65                                                                                                              |        |        |        |        |
| Cooling                                     | Self-cooling                                                                                                      |        |        |        |        |
| Dimensions (W x H x D) mm /Weight           | 402×476.5×148 mm / 15.5kg                                                                                         |        |        |        |        |
| Warranty                                    | As per the company standard policy (inverters + accessories)                                                      |        |        |        |        |
| IEC/BIS                                     | BIS 16169, BIS16221, IEC61727, IEC62116, IEC61000-1-2-3-4, IEC 62109-1/-2, IEC61683:1999, IEC 60068-2 (1,2,14,30) |        |        |        |        |